



HAL
open science

A new framework for shallow approximations of incompressible flows

Nathan Shourick, Ibrahim Cheddadi, Pierre Saramito

► **To cite this version:**

Nathan Shourick, Ibrahim Cheddadi, Pierre Saramito. A new framework for shallow approximations of incompressible flows. 2023. hal-04062098v1

HAL Id: hal-04062098

<https://hal.science/hal-04062098v1>

Preprint submitted on 7 Apr 2023 (v1), last revised 4 Sep 2023 (v2)

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution - NonCommercial - ShareAlike 4.0 International License



A new framework for shallow approximations of incompressible flows

Nathan Shourick^{a, b}, Ibrahim Cheddadi^b and Pierre Saramito^a

^a Lab. Jean Kuntzmann – CNRS and Université Grenoble-Alpes, F-38041 Grenoble, France

^b Univ. Grenoble Alpes, CNRS, UMR 5525, VetAgro Sup, Grenoble INP, TIMC, 38000 Grenoble, France

E-mails: nathan.shourick@univ-grenoble-alpes.fr,
ibrahim.cheddadi@univ-grenoble-alpes.fr, pierre.saramito@imag.fr

Abstract. A new framework for the asymptotic analysis of incompressible flows of complex non-Newtonian materials is presented in this paper. It allows both to avoid redundant mathematical hypotheses and to dramatically reduce the amount of tedious formal calculations. The starting point of the proposed framework is a generic equation, easily adaptable to most problems of continuum mechanics, for which a thin-layer approximation is developed. We then show how to treat the so-called Gordon-Schowalter derivative, a general objective time derivative involved in non-Newtonian viscoelastic fluids. As a proof of concept of our framework, we apply it to the Maxwell viscoelastic model.

2020 Mathematics Subject Classification. 35Q35.

1. Introduction

The scientific literature addresses a wide range of thin-layer flow problems, suitable for geophysical, biological and industrial applications. The corresponding approximation leads to reduce a tridimensional time-dependent and free-surface flow problem to a bidimensional one with an explicit description of the elevation of the free-surface. The problem is then much simpler, from both theoretical and numerical points of view.

This approach was first introduced in 1871 by Saint-Venant [12] for the so-called shallow-water equations that approximate the Euler's fluid equations. Since then, significant progress has been made in obtaining reduced equations. Especially, asymptotic analysis allows a rigorous formal development, up to an arbitrary order, of quantities with respect to ϵ , the small aspect ratio of the thin geometry (see Fig. 1). Among others, it has allowed to obtain thin-layer approximations of Navier-Stokes model [8, 10], of the Bingham viscoplastic fluid model [1, 2, 7, 9], and more recently of the Maxwell viscoelastic model [4]. See *e.g.* [6] for a recent review, including slowly varying topography effects. Note that the reduced equations obtained after asymptotic analysis strongly

depend upon the boundary conditions imposed on the substrate on which the fluid is moving. In the literature, two main cases are considered: a slip-friction together with a no-penetration condition [4, 6–8, 10] and a no-slip condition [1, 9].

Our aim is to propose a general framework for facilitating the formal derivation of the thin-layer approximation of incompressible fluids, either Newtonian or non-Newtonian, with slip-friction and no-penetration boundary condition on a flat substrate. It allows both to avoid redundant mathematical hypotheses and to dramatically reduce most tedious formal calculations. While we focus on fluid mechanics applications, the present framework could be suitable to a wider class of partial differential equations from mathematical physics. The idea to provide some kind of generalization has already been suggested in the literature. In 2004, Bouchut and Westdickenberg [5] studied general varying topographies and, in 2016, Bouchut and Boyaval [6] proposed for the first time a unified framework for deriving thin-layer models for shallow free-surface flows driven by gravity, with slip-friction and no-penetration boundary condition, and under the motion by slices hypothesis. The present framework requires a minimal number of assumptions. In particular, we neither assume that the system is driven by gravity nor that the motion by slices hypothesis is satisfied.

The viscoelastic Maxwell model is studied as a proof of concept for the proposed framework. It writes [11]:

$$\left\{ \begin{array}{l} \lambda \left(\frac{\partial \boldsymbol{\tau}}{\partial t} + (\mathbf{v} \cdot \nabla) \boldsymbol{\tau} - \nabla \mathbf{v} \cdot \boldsymbol{\tau} - \boldsymbol{\tau} \cdot \nabla \mathbf{v}^\top \right) + \boldsymbol{\tau} = 2\eta D(\mathbf{v}), \\ \rho \left(\frac{\partial \mathbf{v}}{\partial t} + (\mathbf{v} \cdot \nabla) \mathbf{v} \right) - \operatorname{div} \boldsymbol{\sigma} = \rho \mathbf{g}, \\ \operatorname{div} \mathbf{v} = 0, \end{array} \right. \quad \begin{array}{l} (1a) \\ (1b) \\ (1c) \end{array}$$

where the total stress tensor is $\boldsymbol{\sigma} = \boldsymbol{\tau} - p\mathbf{I}$, and the three unknowns are $\boldsymbol{\tau}$, the elastic stress tensor, \mathbf{v} , the velocity field and p , the pressure. Here, ρ is the density of the fluid, assumed to be constant, and \mathbf{g} is the constant gravity vector. The parameter η is a viscosity and λ is a relaxation time. The notation $D(\mathbf{v})$ stands for the rate of deformation tensor, that is the symmetric part of the velocity gradient, defined by $D(\mathbf{v}) := (\nabla \mathbf{v} + \mathbf{v}^\top)/2$. Note that when $\lambda = 0$, the Maxwell model reduces to the Navier-Stokes one. Rather than directly performing the asymptotic analysis of the system (1), we propose in this paper to treat the following general equation:

$$\mathcal{A}(u) - \operatorname{div} \mathbf{j} = 0, \quad (2)$$

where \mathcal{A} is a given scalar operator depending on the scalar unknown u and \mathbf{j} is the equivalent of a flux. This equation is scalar but it can correspond component by component to vectorial conservation equations such as (1b), and tensorial evolution equations such as (1a), and, in general, to a large class of equations from mathematical physics.

After a presentation of the general mathematical setting in section 2, the asymptotic analysis of (2) will be presented along with sufficient conditions for the motion by slices. This section ends with the asymptotic analysis of the general objective Gordon-Schwalter derivatives of both vector and tensor fields. Finally, section 4 turns to applications to Navier-Stokes and Maxwell systems. To the best of our knowledge, the tools presented here are new and we hope that they will (i) help to clarify the mathematical hypothesis required for asymptotic analysis, and (ii) make formal calculations easier for future applications in the study of complex materials.

2. Mathematical setting

2.1. Geometry

We consider here a thin-layer fluid domain $\mathcal{B} \subset \mathbb{R}^3$ moving at velocity $\mathbf{v} : \mathcal{B} \times \mathbb{R}_+ \rightarrow \mathbb{R}^3$, with a free surface characterized by its height $h : \mathcal{B} \times \mathbb{R}_+ \rightarrow \mathbb{R}_+$, assumed small compared to the flow length. Let Σ_s be the three-dimensional rigid substrate on which the fluid flows. It is defined as the set of points \mathbf{x} with $x_3 = 0$, and $\Omega \subset \mathbb{R}^2$ its two-dimensional counterpart such that $\Sigma_s := \Omega \times \{0\}$, see Fig. 1. The free surface is defined as the set $\Sigma_f(t) := \Omega \times \{h(t)\}$. The thin-layer approximation aims at obtaining a two-dimensional problem defined over Ω .




Figure 1. Asymptotic analysis of a free-surface flow of a shallow fluid.

2.2. Evolution equations

A large part of the equations derived from mechanics can be written as one of the following equations:

$$\lambda \frac{D\varphi}{Dt} + b(\varphi) - \operatorname{div} \mathbf{j} = f, \quad (3a)$$

$$\lambda \frac{\mathcal{D}_a \mathbf{u}}{\mathcal{D}t} + \mathbf{b}(\mathbf{u}) - \operatorname{div} \boldsymbol{\sigma} = \mathbf{f}, \quad (3b)$$

$$\text{or } \lambda \frac{\mathcal{D}_a \boldsymbol{\tau}}{\mathcal{D}t} + \boldsymbol{\beta}(\boldsymbol{\tau}) - \operatorname{div} \mathbf{J} = \boldsymbol{\phi}, \quad (3c)$$

where λ is a time relaxation, b (resp. \mathbf{b} and $\boldsymbol{\beta}$) is a generic scalar-valued (resp. vector and symmetric tensor) source term, \mathbf{j} (resp. $\boldsymbol{\sigma}$ and \mathbf{J}) is a vector-valued (resp. tensor-valued and order 3 tensor-valued) flux and f (resp. \mathbf{f} and $\boldsymbol{\phi}$) is a scalar-valued (resp. vector and symmetric tensor) source term independent of the scalar (resp. vector and symmetric tensor) unknown φ (resp. \mathbf{u} and $\boldsymbol{\tau}$). Three time derivatives have also been introduced. The first one is the Lagrangian derivative $D\varphi/Dt := \partial\varphi/\partial t + (\mathbf{v} \cdot \nabla)\varphi$. The two others are the vector and the tensor Gordon-Schwalter derivatives, parameterized by $a \in \mathbb{R}$ and defined by

$$\begin{aligned} \frac{\mathcal{D}_a \mathbf{u}}{\mathcal{D}t} &:= \frac{D\mathbf{u}}{Dt} - (W(\mathbf{v}) + aD(\mathbf{v})) \cdot \mathbf{u}, \\ \frac{\mathcal{D}_a \boldsymbol{\tau}}{\mathcal{D}t} &:= \frac{D\boldsymbol{\tau}}{Dt} - 2 \operatorname{sym}((W(\mathbf{v}) + aD(\mathbf{v})) \cdot \boldsymbol{\tau}), \end{aligned}$$

where $\operatorname{sym}(\cdot)$ is the tensor symmetric part operator and $W(\mathbf{v}) := (\nabla \mathbf{v} - \nabla \mathbf{v}^\top)/2$ is the vorticity tensor, *i.e.* the skew-symmetric part of the velocity gradient. Note that these time derivatives are defined for a general velocity field \mathbf{v} , not necessarily divergence-free.

Note that all the three variants of (3) reduce component-by-component to the general case (2) for a suitable choice of the \mathcal{A} that includes both the time derivative, the source and the right-hand-side terms. This approach leads to split the difficulties for the asymptotic analysis of the next section 3: we first study (2) with a general operator \mathcal{A} before we deal with the complicated terms involved by Gordon-Schowalter derivatives.

2.3. Boundary conditions

Only the boundary conditions satisfied on the free surface and on the substrate are involved by the asymptotic analysis. Indeed, conditions on vertical boundary walls have no effects on the reduced models.

2.3.1. On the free surface

For fluid flow systems such as Navier-Stokes or Maxwell (1), the boundary conditions on the free surface $\Sigma_f(t)$ write [6, 10]:

$$\boldsymbol{\sigma} \cdot \mathbf{n} - \gamma \kappa \mathbf{n} = \mathbf{0}, \quad (4a)$$

$$\text{and } \frac{\partial h}{\partial t} + v_1 \frac{\partial h}{\partial x_1} + v_2 \frac{\partial h}{\partial x_2} = v_3 \quad (4b)$$

where \mathbf{n} is the unit outward normal vector, along the direction $(-\partial h/\partial x_1, -\partial h/\partial x_2, 1)$. Eqn. (4a) expresses the normal-stress continuity condition where γ is the surface tension at the air/fluid interface and $\kappa := -\text{div } \mathbf{n}$ is the local mean curvature while (4b) is the usual free surface kinematic equation. Note that (4a) is a non-homogeneous Neumann boundary condition. By extension, for our general scalar equation (2), we consider the general condition on free surface $\Sigma_f(t)$:

$$\mathbf{j} \cdot \mathbf{n} = q. \quad (5)$$

2.3.2. On the substrate

On the substrate Σ_s , we consider:

$$\mathbf{v} \cdot \mathbf{n} = 0, \quad (6a)$$

$$\boldsymbol{\sigma}_{nt} = k \mathbf{v}_t, \quad (6b)$$

where $\boldsymbol{\sigma}_{nt} := \boldsymbol{\sigma} \cdot \mathbf{n} - (\mathbf{n} \cdot \boldsymbol{\sigma} \cdot \mathbf{n}) \mathbf{n}$ is the tangential part of the normal stress, $\mathbf{v}_t := \mathbf{v} - (\mathbf{v} \cdot \mathbf{n}) \mathbf{n}$ is the tangential part of the velocity. Relation (6a) expresses the *no-penetration* of the flow material across the substrate surface while (6b) is the tangential *slip-friction* condition, where k is the friction coefficient, which is constant for laminar flows.

Condition (6) is the usual starting point of most *motion by slices* approximate models. Note that a popular alternative is the *no-slip* condition $\mathbf{v} = \mathbf{0}$, which is the starting point of the so-called *lubrication* approximate models [1, 2, 9]. For simplicity, the later will not be considered and we assume (6) all along this paper.

3. The framework

3.1. Notations

3.1.1. Asymptotic analysis

Let H , L and U be the characteristic height, length and velocity, respectively. For instance L is the substrate length. The asymptotic analysis consists in exploiting the small, yet fixed, aspect ratio

$$\epsilon := H/L$$

in order to reduce the three-dimensional problem to a bidimensional one. The approximation being of order say one, meaning the obtained problem will solve the original one with an error of about ϵ . For this purpose, we are going to scale the spatial coordinates with this parameter, distinguishing the contribution from planar and horizontal dimensions. We then assume each *dimensionless* unknown admits a Taylor expansion with respect to ϵ at second order, which, to fix ideas, writes

$$\varphi = \varphi^{(0)} + \varphi^{(1)}\epsilon + \varphi^{(2)}\epsilon^2 + O(\epsilon^3). \quad (7)$$

At the end of the next paragraph, we will assume that every field, parameter and differential operator is dimensionless, for convenience. By convention, we consider that both the height and the x_3 -coordinate are exactly of order one while both the x_1 -coordinate and x_2 -coordinate do not depend on ϵ :

$$\mathbf{x}_s = L\mathbf{x}_s^{(0)}, \quad x_3 = Lx_3^{(1)}\epsilon, \quad h = Lh^{(1)}\epsilon, \quad t = \frac{L}{U}t^{(0)}, \quad (8)$$

where the s index refers to the planar components of a given variable, e.g. $\mathbf{x}_s := (x_1, x_2)$. We deduce the following scaling for differential operators:

$$\nabla_s = \frac{1}{L}\nabla_s^{(0)}, \quad \frac{\partial}{\partial x_3} = \frac{1}{\epsilon L}\frac{\partial}{\partial x_3^{(1)}}, \quad \frac{\partial}{\partial t} = \frac{U}{L}\frac{\partial}{\partial t^{(0)}}, \quad (9)$$

where $\nabla_s := (\partial/\partial x_1, \partial/\partial x_2)^\top$ is the planar gradient. We also define the planar divergence operator $\text{div}_s \square := \partial \square_{i_1 \dots i_{p-1} 1} / \partial x_1 + \partial \square_{i_1 \dots i_{p-1} 2} / \partial x_2$, where p is the order of the given tensor, and the planar Laplacian $\Delta_s := \nabla_s \cdot \nabla_s$. Similarly, we assume that the dimensionless velocity field satisfies an expansion of the form (7) except for the vertical velocity that starts at order one: $v_3^{(0)} = 0$. Observe that the notation $\varphi^{(k)}$ makes it possible to immediately recognise the order with respect to ϵ of the considered term. For instance, the product $\varphi^{(k)}\psi^{(l)}$ will be associated to a term of order $O(\epsilon^{k+l})$, while the quotient $\varphi^{(k)}/\psi^{(l)}$ will be associated to a term of order $O(\epsilon^{k-l})$.

3.1.2. Depth averaging

Depth averaging is the final stage of the reduction of equations. It is defined through the following operator:

Definition 1 (depth average). Let $\varphi : \mathcal{B} \times \mathbb{R}_+ \rightarrow \mathbb{R}$ a continuous scalar field with respect to x_3 . Its depth average is defined by the quantity

$$\langle \varphi \rangle_h(\mathbf{x}_s, t) := \begin{cases} \frac{1}{h} \int_0^h \varphi(\mathbf{x}_s, x_3, t) dx_3, & \forall (\mathbf{x}_s, t) \in \Omega \times \mathbb{R}_+ \quad \text{when } h(\mathbf{x}_s, t) \neq 0, \\ \varphi(\mathbf{x}_s, 0, t) & \text{otherwise.} \end{cases}$$

This linear operator extends componentwise to any vector or tensor field. We also define the depth variance and covariance:

Definition 2 (depth variance and covariance). Let φ and ψ be two scalar fields defined in $\mathcal{B} \times \mathbb{R}_+$, continuous with respect to x_3 .

- The depth variance of φ is defined by the quantity

$$\text{var}_h(\varphi) := \langle (\varphi - \langle \varphi \rangle_h)^2 \rangle_h.$$

- The depth covariance of φ and ψ is defined by the quantity

$$\text{cov}_h(\varphi, \psi) := \langle (\varphi - \langle \varphi \rangle_h)(\psi - \langle \psi \rangle_h) \rangle_h.$$

In particular, $\text{cov}_h(\varphi, \varphi) = \text{var}_h(\varphi)$.

Those operators satisfy the Cauchy-Schwartz inequality

$$|\text{cov}_h(\varphi, \psi)|^2 \leq \text{var}_h(\varphi)\text{var}_h(\psi), \quad (10a)$$

and the König-Huygens theorem-like

$$\text{var}_h(\varphi) = \langle \varphi^2 \rangle_h - \langle \varphi \rangle_h^2, \quad (10b)$$

$$\text{cov}_h(\varphi, \psi) = \langle \varphi\psi \rangle_h - \langle \varphi \rangle_h \langle \psi \rangle_h. \quad (10c)$$

Note the following useful identities:

$$\langle x_3 \rangle_h = h/2 \quad \text{and} \quad \text{var}_h x_3 = h^2/12. \quad (11)$$

3.2. Analysis of the general scalar problem

Considering equation (2) together with the Neumann condition (5), let us perform the asymptotic analysis of the following general scalar problem:

Problem 3 (general scalar). Find u , defined in $\mathcal{B} \times \mathbb{R}_+$, such that for any time $t \in \mathbb{R}_+$

$$\begin{cases} \mathcal{A}(u(t)) - \text{div } \mathbf{j}(t) = \mathbf{0} & \text{in } \mathcal{B}(t), \\ \mathbf{j}(t) \cdot \mathbf{n} = q & \text{on } \Sigma_f(t). \end{cases} \quad (12a)$$

$$\quad (12b)$$

Recall that this scalar problem extends componentwise to a vector or a tensor one. Assume that u is a solution of (12) and that the following expansions hold:

$$\mathcal{A} = \mathcal{A}^{(-1)} \frac{1}{\epsilon} + \mathcal{A}^{(0)} + \mathcal{A}^{(1)} \epsilon + O(\epsilon^2), \quad (13a)$$

$$\mathbf{j} = \mathbf{j}^{(-1)} \frac{1}{\epsilon} + \mathbf{j}^{(0)} + \mathbf{j}^{(1)} \epsilon + \mathbf{j}^{(2)} \epsilon^2 + O(\epsilon^3), \quad (13b)$$

$$q = q^{(-1)} \frac{1}{\epsilon} + q^{(0)} + q^{(1)} \epsilon + q^{(2)} \epsilon^2 + O(\epsilon^3) \quad (13c)$$

Then (12a) leads to

$$-\frac{\partial j_3^{(-1)}}{\partial x_3^{(1)}} \frac{1}{\epsilon^2} + \sum_{k=-1}^1 \left(\mathcal{A}^{(k)} - \text{div}_s \mathbf{j}_s^{(k)} - \frac{\partial j_3^{(k+1)}}{\partial x_3^{(1)}} \right) \epsilon^k + O(\epsilon^2) = 0,$$

while the boundary condition (12b) becomes

$$\left(j_3^{(-1)} - q^{(-1)} \right) \frac{1}{\epsilon} + \sum_{k=-1}^1 \left(j_3^{(k+1)} - \mathbf{j}_s^{(k)} \cdot \nabla_s h^{(1)} - q^{(k+1)} \right) \epsilon^{k+1} + O(\epsilon^2) = 0 \quad \text{on } \Sigma_f(t).$$

By identification, we get, for any $k \in \{-1, 0, 1\}$

$$\frac{\partial j_3^{(k)}}{\partial x_3^{(1)}} = 0, \quad (15a)$$

$$\mathcal{A}^{(k)} - \operatorname{div}_s \mathbf{j}_s^{(k)} = \frac{\partial j_3^{(k+1)}}{\partial x_3^{(1)}}, \quad (15b)$$

$$j_3^{(-1)} = q^{(-1)} \quad \text{on } \Sigma_f(t), \quad (15c)$$

$$j_3^{(k+1)} = \nabla_s h^{(1)} \cdot \mathbf{j}_s^{(k)} + q^{(k+1)} \quad \text{on } \Sigma_f(t). \quad (15d)$$

From (15a) and (15c), we also deduce $j_3^{(-1)} = q^{(-1)}$ in $\Omega \times \mathbb{R}_+$.

Lemma 4 (vertical flux and Neumann BC).

• First, the term of order -1 of the vertical flux is given by

$$j_3^{(-1)} = q^{(-1)}, \quad \text{in } \Omega \times \mathbb{R}_+. \quad (16a)$$

• Second, for any $k \in \{-1, 0, 1\}$, we define the hypothesis $\mathcal{H}^{(k)}$: it holds if and only if $\mathcal{A}^{(k)} = 0$ and $\mathbf{j}_s^{(k)} = \mathbf{0}$. Then, (15b) reduces to

$$\frac{\partial j_3^{(k+1)}}{\partial x_3^{(1)}} = 0, \quad \text{whence } j_3^{(k+1)} = q^{(k+1)} \quad \text{in } \Omega \times \mathbb{R}_+, \quad (16b)$$

from the boundary condition (15d).

It remains to average in depth the problem defined by equations (15a)–(15b) together with boundary conditions (15c)–(15d). This can be performed thanks to **Corollary 22** in appendix A.

Problem 5 (reduced general scalar). Find $\langle u^{(0)} \rangle_h$, defined in $\Omega \times \mathbb{R}_+$, such that for any time $t \in \mathbb{R}_+$ and any index $k \in \{-1, 0, 1\}$

$$h^{(1)} \langle \mathcal{A}^{(k)} \rangle_h - \operatorname{div}_s \left(h^{(1)} \langle \mathbf{j}_s^{(k)} \rangle_h \right) = q^{(k+1)} - j_3^{(k+1)}(x_3 = 0). \quad (17)$$

Theorem 1 (asymptotic analysis of the general problem). Any problem of the form (12) satisfying the expansion (13) can be approximated by problem (17), and this approximation is of order $O(\varepsilon^2)$.

Corollary 6 (motion by slices). Under the same assumptions than the above **Theorem 1**, let us assume in addition that $\mathbf{j} = v \nabla u + \mathbf{m}$, where $v > 0$ and \mathbf{m} is a vector field that does not depend on ∇u . If \mathbf{m} expands as $\mathbf{m} = \mathbf{m}^{(0)} + \mathbf{m}^{(1)} \varepsilon + \mathbf{O}(\varepsilon^2)$, $q^{(-1)} = 0$ and $v = O(1)$, then

$$\frac{\partial u^{(0)}}{\partial x_3^{(1)}} = 0.$$

Proof: By construction, $j_3^{(-1)} = v \partial u^{(0)} / \partial x_3^{(1)}$. The result follows then from (16a). ■

Remark 7 (no-slip condition).

More generally, if \mathbf{m} expands as $\mathbf{m} = \mathbf{m}^{(-1)} \varepsilon + \mathbf{m}^{(0)} + \mathbf{m}^{(1)} \varepsilon + \mathbf{m}^{(2)} \varepsilon^2 + \mathbf{O}(\varepsilon^3)$ and $v = O(\varepsilon^n)$, with $n \in \{0, \dots, 3\}$, then

$$\frac{\partial u^{(0)}}{\partial x_3^{(1)}} = \frac{1}{v} \left(q^{(n-1)} - m_3^{(n-1)} \right), \quad \text{that is } \langle u^{(0)} \rangle_h = u^{(0)}(x_3 = 0) + \frac{h^{(1)}}{2v} q^{(n-1)} - \left\langle \int_0^{x_3} \frac{1}{v} m_3^{(n-1)} dx_3 \right\rangle_h. \quad (18)$$

Instead of the Neumann boundary condition (12b), we could consider a Dirichlet condition on u . In that case, we do no more have information on the normal flux $\mathbf{j} \cdot \mathbf{n}$ on the substrate. This could be a difficulty since this term is involved in the right-hand-side of (17). Note that a popular case of such Dirichlet condition is the no-slip condition on the substrate, which the starting point of lubrication

shallow models. In that case, there is no more motion by slices, but this asymptotic expansion still allows to obtain an explicit expression of the zeroth order depth average of u . Moreover, from (16b) and under assumption $\mathcal{H}^{(k)}$ (see **Lemma 4**), it is possible to extend the result to any $k \in \{-1, 0, 1\}$ as

$$\langle u^{(k+1)} \rangle_h = u^{(k+1)}(x_3 = 0) + \frac{h^{(1)}}{2\nu} q^{(n+k)} - \left\langle \int_0^{x_3} \frac{1}{\nu} m_3^{(n+k)} dx_3 \right\rangle_h, \quad (19)$$

See e.g. [1, section 3.1] or [2] for practical examples of lubrication problems.

Corollary 8 (asymptotic analysis of the pressure). For any $i \in \{1, 2, 3\}$, assume the i -th component of a vector field \mathbf{u} is solution of a problem of the form (12) with vector flux $(\boldsymbol{\sigma}_{ij})_{1 \leq j \leq 3}$ and operator \mathcal{A}_i . Assume in addition that these three problems satisfy the expansion (13). Assume also that the tensor flux writes $\boldsymbol{\sigma} = \boldsymbol{\tau} - p\mathbf{I}$, where $\boldsymbol{\tau}$ is a tensor field and p is a scalar field, called the pressure, both of them being of order at most $O(1/\epsilon)$. Then the depth average of the pressure p is given by

$$\begin{aligned} \langle p^{(-1)} \rangle_h &= \langle \tau_{33}^{(-1)} \rangle_h - q^{(-1)}, \\ \langle p^{(k+1)} \rangle_h &= \langle \tau_{33}^{(k+1)} \rangle_h - q^{(k+1)} - \left\langle \int_{x_3}^h \left(\operatorname{div}_s \boldsymbol{\tau}_{3s}^{(k)} - \mathcal{A}_3^{(k)} \right) dx_3 \right\rangle_h - \boldsymbol{\tau}_{3s}^{(k)}(x_3 = h) \cdot \nabla_s h^{(1)}, \end{aligned}$$

for any $k \in \{-1, 0, 1\}$.

Proof: The first result is immediate from (16a). From (15b), we get

$$\frac{\partial p^{(k+1)}}{\partial x_3} = \frac{\partial \tau_{33}^{(k+1)}}{\partial x_3} + \operatorname{div}_s \boldsymbol{\tau}_{3s}^{(k)} - \mathcal{A}_3^{(k)},$$

and then, by integrating between x_3 and h

$$p^{(k+1)}(x_3 = h) - p^{(k+1)} = \tau_{33}^{(k+1)}(x_3 = h) - \tau_{33}^{(k+1)} + \int_{x_3}^h \left(\operatorname{div}_s \boldsymbol{\tau}_{3s}^{(k)} - \mathcal{A}_3^{(k)} \right) dx_3.$$

From the Neumann boundary condition (15d), we obtain the relation

$$\tau_{33}^{(k+1)}(x_3 = h) - p^{(k+1)}(x_3 = h) = \boldsymbol{\tau}_{3s}^{(k)}(x_3 = h) \cdot \nabla_s h^{(1)} + q^{(k+1)}.$$

A depth integration allows then to conclude. ■

Remark 9 (simplifications). If $\boldsymbol{\tau}_{3s}^{(k)}$ is independent upon x_3 , we have the much simpler result

$$\langle p^{(k+1)} \rangle_h = \langle \tau_{33}^{(k+1)} \rangle_h - q^{(k+1)} - \operatorname{div}_s \left(h^{(1)} \boldsymbol{\tau}_{3s}^{(k)} \right) + \frac{h^{(1)}}{2} \operatorname{div}_s \boldsymbol{\tau}_{3s}^{(k)} + \left\langle \int_{x_3}^h \mathcal{A}_3^{(k)} dx_3 \right\rangle_h.$$

Similarly, if $\mathcal{A}_3^{(k)}$ is also independent of x_3 , we have the even simpler result

$$\langle p^{(k+1)} \rangle_h = \langle \tau_{33}^{(k+1)} \rangle_h - q^{(k+1)} - \operatorname{div}_s \left(h^{(1)} \boldsymbol{\tau}_{3s}^{(k)} \right) + \frac{h^{(1)}}{2} \operatorname{div}_s \boldsymbol{\tau}_{3s}^{(k)} + \frac{h^{(1)}}{2} \mathcal{A}_3^{(k)}.$$

3.3. Time derivatives

The aim of this section is to derive the depth average of the time derivatives that we introduced in Section 2.2, namely the material derivative D/Dt and the vector and tensor Gordon-Schowalter derivatives $\mathcal{D}_a/\mathcal{D}t$, and express them as functions of their equivalents in the plane Ω . We will do so under the assumptions that lead to motion by slices (see **Corollary 6**):

$$\frac{\partial \mathbf{v}_s^{(0)}}{\partial x_3^{(1)}} = \mathbf{0}, \quad (21)$$

and the fact that the velocity field \mathbf{v} is divergence-free (incompressibility) and satisfies to the no-penetration constraint on the substrate. To exploit this, we will first need to perform the asymptotic analysis of the divergence-free condition.

3.3.1. Divergence-free condition

Let us start by the asymptotic analysis of the divergence-free condition

$$\operatorname{div} \mathbf{v} = 0, \quad (22)$$

under the boundary conditions

$$\mathbf{v} \cdot \mathbf{n} = 0 \iff v_3 = 0 \quad \text{on } \Sigma_s, \quad (23a)$$

$$\frac{D_s h}{Dt} = v_3 \quad \text{on } \Sigma_f(t), \quad (23b)$$

where we noted $\frac{D_s}{Dt} := \frac{\partial}{\partial t} + (\mathbf{v}_s \cdot \nabla_s)$ the material derivative advected by the velocity \mathbf{v}_s .

Proposition 10 (divergence-free velocity). *Assume that \mathbf{v} is divergence-free and that the property of motion by slices (21) and the boundary conditions (23) are satisfied. Then the vertical velocity v_3 is given by:*

$$v_3 = -\operatorname{div}_s(\mathbf{v}_s^{(0)})x_3 - \langle \operatorname{div}_s(\mathbf{v}_s^{(1)}) \rangle_{x_3} \epsilon + O(\epsilon^3), \quad \text{that is } v_3^{(1)} = -\operatorname{div}_s(\mathbf{v}_s^{(0)})x_3^{(1)}. \quad (24)$$

Proof: Note that $\operatorname{div} \mathbf{v} = \operatorname{div}_s \mathbf{v}_s + \partial v_3 / \partial x_3 = 0$. Therefore, the result follows directly from an integration of the equation (22) using the hypothesis of motion by slices and the boundary condition (23a). ■

Corollary 11 (divergence-free velocity). *Under the same conditions as in the above proposition, the height h is solution of the equation*

$$\frac{\partial h}{\partial t} + \operatorname{div}_s(h \mathbf{v}_s^{(0)}) + \operatorname{div}_s(h \langle \mathbf{v}_s^{(1)} \rangle_h) \epsilon = O(\epsilon^3). \quad (25)$$

Proof: Immediate from **Proposition 10**, **Corollary 22** (see appendix A) and boundary condition (23b). ■

3.3.2. Lagrangian derivative

The depth average of the Lagrangian derivative is expressed as a function of the planar material derivative, advected by the velocity $\mathbf{v}_s^{(0)}$, noted

$$\frac{D_s^{(0)} \varphi}{Dt} := \frac{\partial \varphi}{\partial t} + (\mathbf{v}_s^{(0)} \cdot \nabla_s) \varphi,$$

for any scalar field φ defined in $\Omega \times \mathbb{R}_+$. It extends componentwise to any vector or tensor field. Thanks to the new mass conservation law (25), we deduce the

Proposition 12 (averaged Lagrangian derivative). *Assume that \mathbf{v} is divergence-free and that the property of motion by slices (21) and the boundary conditions (23) are satisfied. Then, any scalar field u defined in $\mathcal{B} \times \mathbb{R}_+$ satisfies the relation*

$$\left\langle \frac{Du}{Dt} \right\rangle_h = \frac{D_s^{(0)} \langle u \rangle_h}{Dt} + O(\epsilon), \quad (26)$$

Moreover, if we assume $\operatorname{cov}_h(\nabla_s u, \mathbf{v}_s^{(1)}) = O(\epsilon)$, then we have a better approximation:

$$\left\langle \frac{Du}{Dt} \right\rangle_h = \frac{D_s^{(0)} \langle u \rangle_h}{Dt} + (\langle \mathbf{v}_s^{(1)} \rangle_h \cdot \nabla_s) \langle u \rangle_h \epsilon + O(\epsilon^2), \quad (27)$$

Proof: We show this property in the second case, the first result being independent of the assumption $\operatorname{cov}_h(\nabla_s u, \mathbf{v}_s^{(1)}) = O(\epsilon)$. The calculation is performed in two steps, by noting that $D/Dt = D_s/Dt + v_3 \partial / \partial x_3 = D_s/Dt + v_3^{(1)} \partial / \partial x_3^{(1)} + O(\epsilon)$ and by using the linearity of the operator $\langle \cdot \rangle_h$.

- (1) Two direct applications of the Leibniz formula (**Corollary 21** in appendix A) and one of the formula (10c) gives

$$\begin{aligned} h \left\langle \frac{D_s u}{Dt} \right\rangle_h &= \frac{D_s^{(0)}}{Dt} (h \langle u \rangle_h) - u(x_3 = h) \frac{D_s^{(0)} h}{Dt} + h \langle (\mathbf{v}_s^{(1)} \cdot \nabla_s) u \rangle_h \epsilon + O(\epsilon^3) \\ &= h \left(\frac{D_s^{(0)} \langle u \rangle_h}{Dt} + \langle \mathbf{v}_s^{(1)} \rangle_h \cdot \nabla_s \langle u \rangle_h \epsilon \right) + h \text{cov}_h(\nabla_s u, \mathbf{v}_s^{(1)}) \epsilon \\ &\quad + (\langle u \rangle_h - u(x_3 = h)) \left(\frac{D_s^{(0)} h}{Dt} + \langle \mathbf{v}_s^{(1)} \rangle_h \cdot \nabla_s h \epsilon \right) + O(\epsilon^3). \end{aligned}$$

- (2) A direct application of the appendix formula (49e), after expansion of the vertical velocity using the **Proposition 10** and use of the hypothesis of motion by slices, gives

$$\begin{aligned} h \left\langle v_3 \frac{\partial u}{\partial x_3} \right\rangle_h &= -(h \text{div}_s \mathbf{v}_s^{(0)} + h \langle \text{div}_s \mathbf{v}_s^{(1)} \rangle_h \epsilon) \left\langle x_3 \frac{\partial u}{\partial x_3} \right\rangle_h + O(\epsilon^3) \\ &= (h \text{div}_s \mathbf{v}_s^{(0)} + h \langle \text{div}_s \mathbf{v}_s^{(1)} \rangle_h \epsilon) (\langle u \rangle_h - u(x_3 = h)) + O(\epsilon^3). \end{aligned}$$

The sum of the two above results and the application of equality (25) allow to conclude. \blacksquare
This result still holds true when replacing u with a vector or a tensor field, in particular with the velocity field \mathbf{v} .

3.3.3. Gordon-Schwalter derivative of a vector

First, the depth average of the Gordon-Schwalter derivative of a vector is expressed as a function of its plane equivalent, with respect to the zeroth-order planar velocity $\mathbf{v}_s^{(0)}$:

$$\frac{\mathcal{D}_a^{(0)} \mathbf{w}_s}{\mathcal{D}t} := \frac{D_s^{(0)} \mathbf{w}_s}{Dt} - W_s(\mathbf{v}_s^{(0)}) \cdot \mathbf{w}_s - a D_s(\mathbf{v}_s^{(0)}) \cdot \mathbf{w}_s, \quad (28)$$

for any planar vector \mathbf{w}_s defined in $\Omega \times \mathbb{R}_+$.

Theorem 2 (Gordon-Schwalter derivative of a vector). *Let \mathbf{u} be a vector field defined in $\mathcal{B} \times \mathbb{R}_+$ such that $\text{var}_h(\mathbf{u}) = O(\epsilon)$ (closure assumption). Assume that \mathbf{v} is divergence-free and that the property of motion by slices (21) and the boundary conditions (23) are satisfied. Then the depth-average of the Gordon-Schwalter derivative of \mathbf{u} is given by*

$$\begin{aligned} \left\langle \frac{\mathcal{D}_a \mathbf{u}}{\mathcal{D}t} \right\rangle_{h,s} &= \frac{\mathcal{D}_a^{(0)} \langle \mathbf{u}_s \rangle_h}{\mathcal{D}t} - \frac{1+a}{2} \left\langle \frac{\partial \mathbf{v}_s^{(1)}}{\partial x_3^{(1)}} u_3 \right\rangle_h - \left\langle [W_s(\mathbf{v}_s^{(1)}) + a D_s(\mathbf{v}_s^{(1)})] \cdot \mathbf{u}_s \right\rangle_h \\ &\quad + \frac{1+a}{2} \left\langle \frac{\partial \mathbf{v}_s^{(2)}}{\partial x_3^{(1)}} u_3 \right\rangle_h + \frac{(1-a)h^{(1)}}{4} \langle u_3 \rangle_h \nabla_s \text{div}_s \mathbf{v}_s^{(0)} \epsilon + O(\epsilon^2), \quad (29a) \end{aligned}$$

$$\begin{aligned} \left\langle \frac{\mathcal{D}_a \mathbf{u}}{\mathcal{D}t} \right\rangle_{h,3} &= \frac{D_s^{(0)} \langle u_3 \rangle_h}{Dt} + \frac{1-a}{2} \left\langle \frac{\partial \mathbf{v}_s^{(1)}}{\partial x_3^{(1)}} \cdot \mathbf{u}_s \right\rangle_h + a \text{div}_s(\mathbf{v}_s^{(0)}) \langle u_3 \rangle_h \\ &\quad + \left(\frac{1-a}{2} \left\langle \frac{\partial \mathbf{v}_s^{(2)}}{\partial x_3^{(1)}} \cdot \mathbf{u}_s \right\rangle_h + \frac{(1+a)h^{(1)}}{4} \nabla_s \text{div}_s \mathbf{v}_s^{(0)} \cdot \langle \mathbf{u}_s \rangle_h + a \langle \text{div}_s(\mathbf{v}_s^{(1)}) u_3 \rangle_h \right) \epsilon + O(\epsilon^2). \quad (29b) \end{aligned}$$

Proof: Recall that

$$\frac{\mathcal{D}_a \mathbf{u}}{\mathcal{D}t} := \frac{D \mathbf{u}}{Dt} - W(\mathbf{v}) \cdot \mathbf{u} - a D(\mathbf{v}) \cdot \mathbf{u}.$$

As in the previous demonstration, we will treat each of the terms separately, and we use the previous result for the first term. The expansions (7), (8) and 9 applied to the velocity field, and the motion by slices assumption lead to

$$2W(\mathbf{v}) = \begin{pmatrix} 2W_s(\mathbf{v}_s^{(0)}) + 2W_s(\mathbf{v}_s^{(1)})\epsilon & \frac{1}{\epsilon} \frac{\partial \mathbf{v}_s^{(0)}}{\partial x_3} + \frac{\partial \mathbf{v}_s^{(1)}}{\partial x_3} + \left(\frac{\partial \mathbf{v}_s^{(2)}}{\partial x_3} - \nabla_s v_3^{(1)} \right) \epsilon \\ \left(\nabla_s v_3^{(1)} - \frac{\partial \mathbf{v}_s^{(2)}}{\partial x_3} \right) \epsilon - \frac{1}{\epsilon} \frac{\partial \mathbf{v}_s^{(0)}}{\partial x_3} - \frac{\partial \mathbf{v}_s^{(1)}}{\partial x_3} & 0 \end{pmatrix} + \mathbf{O}(\epsilon^2),$$

$$2D(\mathbf{v}) = \begin{pmatrix} 2D_s(\mathbf{v}_s^{(0)}) + 2D_s(\mathbf{v}_s^{(1)})\epsilon & \frac{1}{\epsilon} \frac{\partial \mathbf{v}_s^{(0)}}{\partial x_3} + \frac{\partial \mathbf{v}_s^{(1)}}{\partial x_3} + \left(\frac{\partial \mathbf{v}_s^{(2)}}{\partial x_3} + \nabla_s v_3^{(1)} \right) \epsilon \\ \left(\nabla_s v_3^{(1)} + \frac{\partial \mathbf{v}_s^{(2)}}{\partial x_3} \right) \epsilon + \frac{1}{\epsilon} \frac{\partial \mathbf{v}_s^{(0)}}{\partial x_3} + \frac{\partial \mathbf{v}_s^{(1)}}{\partial x_3} & 2 \frac{\partial v_3^{(1)}}{\partial x_3} + 2 \frac{\partial v_3^{(2)}}{\partial x_3} \epsilon \end{pmatrix} + \mathbf{O}(\epsilon^2).$$

Therefore, the second and third terms in the definition of the Gordon-Schowalter derivative are

$$W(\mathbf{v}) \cdot \mathbf{u} = \begin{pmatrix} W_s(\mathbf{v}_s^{(0)}) \cdot \mathbf{u}_s + \frac{1}{2} \frac{\partial \mathbf{v}_s^{(1)}}{\partial x_3} u_3 + \left(W_s(\mathbf{v}_s^{(1)}) \cdot \mathbf{u}_s + \frac{\partial \mathbf{v}_s^{(2)}}{\partial x_3} \frac{u_3}{2} - \nabla_s v_3^{(1)} \frac{u_3}{2} \right) \epsilon + \mathbf{O}(\epsilon^2) \\ - \frac{1}{2} \frac{\partial \mathbf{v}_s^{(1)}}{\partial x_3} \cdot \mathbf{u}_s + \frac{\epsilon}{2} \left(\nabla_s v_3^{(1)} - \frac{\partial \mathbf{v}_s^{(2)}}{\partial x_3} \right) \cdot \mathbf{u}_s + \mathbf{O}(\epsilon^2) \end{pmatrix},$$

$$D(\mathbf{v}) \cdot \mathbf{u} = \begin{pmatrix} D_s(\mathbf{v}_s^{(0)}) \cdot \mathbf{u}_s + \frac{1}{2} \frac{\partial \mathbf{v}_s^{(1)}}{\partial x_3} u_3 + \left(D_s(\mathbf{v}_s^{(1)}) \cdot \mathbf{u}_s + \frac{\partial \mathbf{v}_s^{(2)}}{\partial x_3} \frac{u_3}{2} + \nabla_s v_3^{(1)} \frac{u_3}{2} \right) \epsilon + \mathbf{O}(\epsilon^2) \\ \frac{1}{2} \frac{\partial \mathbf{v}_s^{(1)}}{\partial x_3} \cdot \mathbf{u}_s + \frac{\partial v_3^{(1)}}{\partial x_3} u_3 + \left(\frac{1}{2} \left[\nabla_s v_3^{(1)} + \frac{\partial \mathbf{v}_s^{(2)}}{\partial x_3} \right] \cdot \mathbf{u}_s + \frac{\partial v_3^{(2)}}{\partial x_3} u_3 \right) \epsilon + \mathbf{O}(\epsilon^2) \end{pmatrix},$$

where we used the **Proposition 10**. Depth averaging is easily done using the motion by slices assumption. However, it is necessary to treat the terms consisting in a product of two terms, a priori dependent on the coordinate x_3 , carefully. We deal with the term $u_3 \nabla_s v_3^{(1)} = -x_3^{(1)} \nabla_s \text{div}_s(\mathbf{v}_s^{(0)}) u_3$ for the example, whose average can be calculated through $\langle x_3^{(1)} u_3 \rangle_h$. By successively applying the formulas (10c) and (11), we get

$$\langle x_3^{(1)} u_3 \rangle_h = \frac{h^{(1)}}{2} \langle u_3 \rangle_h + \text{cov}_h(x_3^{(1)}, u_3) \approx \frac{h^{(1)}}{2} \langle u_3 \rangle_h.$$

The closure assumption allows then to prove the approximation since, from the result (10a) and the formula (11),

$$\left| \text{cov}_h(x_3^{(1)}, u_3) \right|^2 \leq \text{var}_h(x_3^{(1)}) \text{var}_h(u_3) = \frac{h^{(1)^2}}{12} \text{var}_h(u_3) = \mathbf{O}(\epsilon).$$

The linearity of $\langle \cdot \rangle_h$ and the **Proposition 12** on the asymptotic analysis of the Lagrangian derivative finally lead to the conclusion. \blacksquare

Remark 13 (average of a product). *The expression of the depth-average of the Gordon-Schowalter derivative involves averages of products, which is not desirable for closing the reduced problem: we would prefer instead a product of averaged quantities. The simplification of those products is actually case-dependent: one at least of the two quantities involved by the product should be independent upon x_3 . For instance, either the first-order planar velocity $\mathbf{v}_s^{(1)}$ or the vector field \mathbf{u} involved by the Gordon-Schowalter derivative should be independent upon x_3 .*

3.3.4. Gordon-Schwalter derivative of a tensor

Then, the depth average of the Gordon-Schwalter derivative of a tensor is expressed as a function of its plane equivalent, with respect to the zeroth-order planar velocity $\mathbf{v}_s^{(0)}$:

$$\frac{\mathcal{D}_a^{(0)} \boldsymbol{\sigma}_{ss}}{\mathcal{D}t} := \frac{D_s^{(0)} \boldsymbol{\sigma}_{ss}}{Dt} - 2 \text{sym} [W_s(\mathbf{v}_s^{(0)}) \cdot \boldsymbol{\sigma}_{ss} - a D_s(\mathbf{v}_s^{(0)}) \cdot \boldsymbol{\sigma}_{ss}], \quad (32)$$

for any planar tensor $\boldsymbol{\sigma}_{ss}$ in $\Omega \times \mathbb{R}_+$.

Theorem 3 (Gordon-Schwalter derivative of a tensor). *Let $\boldsymbol{\tau}$ be a symmetric tensor field defined in $\mathcal{B} \times \mathbb{R}_+$, whose zeroth order vertical variation with respect to ϵ is negligible, that is $\text{var}_h(\boldsymbol{\tau}^{(0)}) = O(\epsilon)$ (closure assumption). Assume that \mathbf{v} is divergence-free and that the property of motion by slices (21) and the boundary conditions (23) are satisfied. Then the depth-average of the Gordon-Schwalter derivative of $\boldsymbol{\tau}$ is given by*

$$\begin{aligned} \left\langle \frac{\mathcal{D}_a \boldsymbol{\tau}}{\mathcal{D}t} \right\rangle_{h,ss} &= \frac{\mathcal{D}_a^{(0)} \langle \boldsymbol{\tau}_{ss} \rangle_h}{\mathcal{D}t} - (1+a) \text{sym} \left(\left\langle \frac{\partial \mathbf{v}_s^{(1)}}{\partial x_3^{(1)}} \otimes \boldsymbol{\tau}_{3s} \right\rangle_h \right) \\ &\quad - \left[\text{sym} \left(\langle \{W_s(\mathbf{v}_s^{(1)}) + a D_s(\mathbf{v}_s^{(1)})\} \cdot \boldsymbol{\tau}_{ss} \rangle_h + (1+a) \left\langle \frac{\partial \mathbf{v}_s^{(2)}}{\partial x_3^{(1)}} \otimes \boldsymbol{\tau}_{3s} \right\rangle_h \right. \right. \\ &\quad \left. \left. + \frac{(1-a)h^{(1)}}{2} \nabla_s \text{div}_s \mathbf{v}_s^{(0)} \otimes \langle \boldsymbol{\tau}_{3s} \rangle_h \right) \right] \boldsymbol{\epsilon} + \mathbf{O}(\epsilon^2), \quad (33a) \end{aligned}$$

$$\begin{aligned} \left\langle \frac{\mathcal{D}_a \boldsymbol{\tau}}{\mathcal{D}t} \right\rangle_{h,s3} &= \frac{\mathcal{D}_a^{(0)} \langle \boldsymbol{\tau}_{s3} \rangle_h}{\mathcal{D}t} + \frac{1-a}{2} \left\langle \frac{\partial \mathbf{v}_s^{(1)}}{\partial x_3^{(1)}} \cdot \boldsymbol{\tau}_{ss} \right\rangle_h - \frac{1+a}{2} \left\langle \frac{\partial \mathbf{v}_s^{(1)}}{\partial x_3^{(1)}} \boldsymbol{\tau}_{33} \right\rangle_h + a \text{div}_s(\mathbf{v}_s^{(0)}) \langle \boldsymbol{\tau}_{s3} \rangle_h \\ &\quad + \left\{ - \langle [W_s(\mathbf{v}_s^{(1)}) + a D_s(\mathbf{v}_s^{(1)})] \cdot \boldsymbol{\tau}_{s3} \rangle_h + \frac{h^{(1)}}{4} [(1+a) \langle \boldsymbol{\tau}_{ss} \rangle_h - (1-a) \langle \boldsymbol{\tau}_{33} \rangle_h I_{ss}] \cdot \nabla_s \text{div}_s \mathbf{v}_s^{(0)} \right. \\ &\quad \left. + \frac{1-a}{2} \left\langle \boldsymbol{\tau}_{ss} \cdot \frac{\partial \mathbf{v}_s^{(2)}}{\partial x_3^{(1)}} \right\rangle_h - \frac{1+a}{2} \left\langle \frac{\partial \mathbf{v}_s^{(2)}}{\partial x_3^{(1)}} \boldsymbol{\tau}_{33} \right\rangle_h + a \langle \text{div}_s(\mathbf{v}_s^{(1)}) \boldsymbol{\tau}_{3s} \rangle_h \right\} \boldsymbol{\epsilon} + \mathbf{O}(\epsilon^2), \quad (33b) \end{aligned}$$

$$\begin{aligned} \left\langle \frac{\mathcal{D}_a \boldsymbol{\tau}}{\mathcal{D}t} \right\rangle_{h,33} &= \frac{D_s^{(0)} \langle \boldsymbol{\tau}_{33} \rangle_h}{Dt} + (1-a) \left\langle \frac{\partial \mathbf{v}_s^{(1)}}{\partial x_3^{(1)}} \cdot \boldsymbol{\tau}_{s3} \right\rangle_h + 2a \text{div}_s(\mathbf{v}_s^{(0)}) \langle \boldsymbol{\tau}_{33} \rangle_h \\ &\quad + \left[\left\langle \left(\frac{(1+a)h^{(1)}}{2} \nabla_s \text{div}_s \mathbf{v}_s^{(0)} + (1-a) \frac{\partial \mathbf{v}_s^{(2)}}{\partial x_3^{(1)}} \right) \cdot \boldsymbol{\tau}_{s3} \right\rangle_h + 2a \langle \text{div}_s(\mathbf{v}_s^{(1)}) \boldsymbol{\tau}_{33} \rangle_h \right] \boldsymbol{\epsilon} + \mathbf{O}(\epsilon^2), \quad (33c) \end{aligned}$$

Proof: By noticing that we just need to develop the expression of the tensor product $(W(\mathbf{v}) + aD(\mathbf{v})) \cdot \boldsymbol{\tau}$ and to use the decomposition

$$2 \text{sym}(\boldsymbol{\xi} \cdot \boldsymbol{\zeta}) = \begin{pmatrix} 2 \text{sym}(\boldsymbol{\xi}_{ss} \cdot \boldsymbol{\zeta}_{ss} + \boldsymbol{\xi}_{s3} \otimes \boldsymbol{\zeta}_{3s}) & \boldsymbol{\xi}_{ss} \cdot \boldsymbol{\zeta}_{s3} + \boldsymbol{\xi}_{3s} \cdot \boldsymbol{\zeta}_{ss} + \boldsymbol{\xi}_{s3} \boldsymbol{\zeta}_{33} + \boldsymbol{\xi}_{33} \boldsymbol{\zeta}_{3s} \\ & 2(\boldsymbol{\xi}_{3s} \cdot \boldsymbol{\zeta}_{s3} + \boldsymbol{\xi}_{33} \boldsymbol{\zeta}_{33}) \end{pmatrix},$$

we can return to the proof of the previous theorem and conclude. ■

4. Examples

4.1. From Navier-Stokes equations to viscous shallow water equations

4.1.1. Problem statement

The constitutive equation of an incompressible Newtonian fluid write:

$$\boldsymbol{\sigma} = 2\eta D(\mathbf{v}) - p\mathbf{I}, \quad (34)$$

where $\boldsymbol{\sigma}$ is the symmetric Cauchy stress tensor and p a contribution to the pressure. The constant material parameter is the viscosity $\eta > 0$. These constitutive equations are coupled with standard conservation of mass (35a) and momentum (35b) equations. Assuming that the density ρ is constant, *i.e.* the fluid is incompressible, the conservation equations write:

$$\operatorname{div} \mathbf{v} = 0, \quad (35a)$$

$$\rho \frac{D\mathbf{v}}{Dt} - \operatorname{div} \boldsymbol{\sigma} = \rho \mathbf{g}, \quad (35b)$$

where $\mathbf{g} = -g\hat{\mathbf{u}}$ is the constant gravity vector, with $\hat{\mathbf{u}}$ some given unit vector. The previous set of equations is closed by initial and boundary conditions. For the latter, we use, on the free surface, the conditions (4) with no surface tension ($\gamma = 0$), and, on the substrate, the conditions (6) with no friction ($k = 0$).

4.1.2. Asymptotic analysis

With $\Sigma := \eta U/L$ as characteristic stress, the dimensionless problem writes:

Problem 14. Find \mathbf{v} defined in Ω such that

$$Re \frac{D\mathbf{v}}{Dt} - \operatorname{div} \boldsymbol{\sigma} = -\frac{Re}{Fr^2} \hat{\mathbf{u}}, \quad (36a)$$

$$\operatorname{div} \mathbf{v} = 0, \quad (36b)$$

with $\boldsymbol{\sigma} = 2D(\mathbf{v}) - p\mathbf{I}$, where $Re := \rho UL/\eta$ is the Reynolds number and $Fr := U/\sqrt{gL}$ is the Froude number.

The same notation is used for dimensioned and dimensionless field for convenience.

We would like to use the framework developed in section 3.2 to get a shallow formulation of the above Navier-Stokes problem. To do so, $\mathcal{A}(u)$ is identified with $Re Dv_i/Dt + (Re/Fr^2)\hat{u}_i$ and \mathbf{j} with $(\boldsymbol{\sigma}_{ij})_{1 \leq j \leq 3}$, for i successively taken in $\{1, 2, 3\}$. Then, the condition of motion by slices is satisfied, up to order 1 at least, for each component of the velocity, thanks to **Corollary 6**. As a consequence, the rate of deformation expands with respect to ϵ as

$$2D(\mathbf{v}) = \begin{pmatrix} 2D_s(\mathbf{v}_s^{(0)}) & \mathbf{0} \\ \mathbf{0} & -2\operatorname{div}_s \mathbf{v}_s^{(0)} \end{pmatrix} + \begin{pmatrix} 2D_s(\mathbf{v}_s^{(1)}) & \frac{\partial \mathbf{v}_s^{(2)}}{\partial x_3^{(1)}} - \nabla_s \operatorname{div}_s \mathbf{v}_s^{(0)} x_3^{(1)} \\ \frac{\partial \mathbf{v}_s^{(2)}}{\partial x_3^{(1)}} - \nabla_s \operatorname{div}_s \mathbf{v}_s^{(0)\top} x_3^{(1)} & -2\operatorname{div}_s \mathbf{v}_s^{(1)} \end{pmatrix} \epsilon + \mathbf{O}(\epsilon^2), \quad (37)$$

where we used **Proposition 10**.

Following the literature, we make the fundamental assumption that $Re/Fr^2 = O(1/\epsilon)$. Therefore, due to the form of the deformation rate tensor (37), applying the **Corollary 8** leads to

$$p^{(-1)} = 0, \quad \langle p^{(0)} \rangle_h = -2\operatorname{div}_s(\mathbf{v}_s^{(0)}) + \frac{\hat{u}_3}{2} \frac{\epsilon Re}{Fr^2} h^{(1)}. \quad (38)$$

We can now apply **Theorem 1**, **Proposition 12** and **Corollary 11** to get a shallow formulation of the above Navier-Stokes problem.

Problem 15. Find $\mathbf{v}_s^{(0)}$ and $h^{(1)}$ defined in Ω such that

$$\frac{\partial h^{(1)}}{\partial t} + \operatorname{div}_s(h^{(1)} \mathbf{v}^{(0)}) = 0, \quad (39a)$$

$$\operatorname{Re} h^{(1)} \frac{D_s^{(0)} \mathbf{v}_s^{(0)}}{Dt} - \operatorname{div}_s(h^{(1)} \langle \boldsymbol{\sigma}_{ss}^{(0)} \rangle_h) = -\frac{\epsilon \operatorname{Re}}{Fr^2} h^{(1)} \hat{\mathbf{u}}_s, \quad (39b)$$

$$\langle \boldsymbol{\sigma}_{ss}^{(0)} \rangle_h = 2D_s(\mathbf{v}_s^{(0)}) + 2\operatorname{div}_s(\mathbf{v}_s^{(0)}) \mathbf{I}_{ss} - \frac{\dot{u}_3}{2} \frac{\epsilon \operatorname{Re}}{Fr^2} h^{(1)} \mathbf{I}_{ss}. \quad (39c)$$

This reduced model was first obtained in 2006 by Marche [10] after substantial formal calculations. In comparison, our approach requires less than one page.

4.2. Maxwell viscoelastic model

We use the constitutive equations of a Maxwell viscoelastic fluid (1) along with initial and boundary conditions. For the latter, we use, on the free surface, the conditions (4) with no surface tension ($\gamma = 0$), and, on the substrate, the conditions (6) with no friction ($k = 0$).

With $\Sigma := \eta U/L$ again as characteristic stress, the dimensionless problem writes:

Problem 16. Find \mathbf{v} and $\boldsymbol{\tau}$ defined in Ω such that

$$\operatorname{Re} \frac{D\mathbf{v}}{Dt} - \operatorname{div} \boldsymbol{\sigma} = -\frac{\operatorname{Re}}{Fr^2} \hat{\mathbf{u}}, \quad (40a)$$

$$\operatorname{div} \mathbf{v} = 0, \quad (40b)$$

$$\operatorname{We} \frac{\mathcal{D}_1 \boldsymbol{\tau}}{\mathcal{D}t} + \boldsymbol{\tau} = 2D(\mathbf{v}), \quad (40c)$$

with $\boldsymbol{\sigma} = \boldsymbol{\tau} - p\mathbf{I}$, where $\operatorname{We} := \lambda V/L$ is the Weissenberg number.

The same notation is used for dimensioned and dimensionless field for convenience.

4.2.1. Sufficient conditions for the motion by slices

With the help of our formalism, we can derive a new sufficient condition for the motion by slices in the context of the Maxwell model:

Corollary 17 (motion by slices for the Maxwell model). Let $\boldsymbol{\tau}$ be the elastic stress defined in the Maxwell model (1), and assume that it expands as $\boldsymbol{\tau} = \boldsymbol{\tau}^{(0)} + \boldsymbol{\tau}^{(1)}\epsilon + \mathbf{O}(\epsilon^2)$ and that the Weissenberg number We is of order $O(1)$, then

$$\frac{\partial \mathbf{u}_s^{(0)}}{\partial x_3^{(1)}} = \frac{\partial \mathbf{u}_s^{(1)}}{\partial x_3^{(1)}} = \mathbf{0}.$$

Proof: Let us write the components $s3$ and 33 of the equation (40c):

$$\operatorname{We} \left(\frac{D\tau_{s3}}{Dt} - \tau_{33} \frac{\partial v_s}{\partial x_3} - \left(\nabla_s v_s + \frac{\partial v_3}{\partial x_3} \mathbf{I} \right) \cdot \boldsymbol{\tau}_{s3} - \boldsymbol{\tau}_{ss} \cdot \nabla_s v_3 \right) + \tau_{s3} = \frac{\partial v_s}{\partial x_3} + \nabla_s v_3, \quad (41a)$$

$$\operatorname{We} \left(\frac{D\tau_{33}}{Dt} - 2\nabla_s v_3 \cdot \boldsymbol{\tau}_{s3} - 2 \frac{\partial v_3}{\partial x_3} \tau_{33} \right) + \tau_{33} = 2 \frac{\partial v_3}{\partial x_3}. \quad (41b)$$

By assumption, we know the only term of order $O(1/\epsilon)$ in (41a) satisfies

$$-\operatorname{We} \tau_{33}^{(0)} \frac{\partial v_s^{(0)}}{\partial x_3^{(1)}} = \frac{\partial v_s^{(0)}}{\partial x_3^{(1)}}. \quad (41c)$$

Now, $We = 0$ leads to the result. Assume the opposite and that $\tau_{33}^{(0)} = -1/We$. Then, from equation (41b), we have

$$\tau_{33}^{(0)} = -\frac{1}{We} = 0 \quad (42)$$

since $-2We\tau_{33}^{(0)} = 2$ and $2\nabla_s \nu_3 \cdot \boldsymbol{\tau}_{s3}$ is at most of order $O(\epsilon)$. This leads to a contradiction: $\tau_{33}^{(0)}$ cannot be uniformly constant equal to $-1/We$. We finally conclude from (41c) that $\partial \mathbf{v}_s^{(0)} / \partial x_3^{(1)} = \mathbf{0}$. Note that if $\tau_{33}^{(0)} = 0$ is assumed, then the proof is still valid.

Hypothesis $\mathcal{H}^{(-1)}$ is satisfied then, from **Lemma 4**, there holds $\boldsymbol{\sigma}_{s3}^{(0)} = \mathbf{0}$, which leads to $\boldsymbol{\tau}_{s3}^{(0)} = \mathbf{0}$, and then, from (41a)

$$\left(We\tau_{33}^{(0)} + 1 \right) \frac{\partial \mathbf{v}_s^{(1)}}{\partial x_3^{(1)}} = \mathbf{0}, \quad (43)$$

which leads to the second result, since $\tau_{33}^{(0)}$ cannot be uniformly constant equal to $-1/We$. ■

4.2.2. Asymptotic analysis

In what follows, we assume that $\boldsymbol{\tau}$ asymptotic expansion is of the form $\boldsymbol{\tau} = \boldsymbol{\tau}^{(0)} + \boldsymbol{\tau}^{(1)}\epsilon + \boldsymbol{\tau}^{(2)}\epsilon^2 + \mathbf{O}(\epsilon^3)$, whereas Re/Fr^2 is of order $O(1/\epsilon)$, as in the previous example. Corollary 17 ensures that the property of motion by slices is satisfied.

Momentum equation – Asymptotic. The asymptotic analysis of the momentum equation has already been done in the previous example. Similar to what was done to deduce the pressure in the previous example, the zeroth order of the averaged pressure is given by $\langle p^{(0)} \rangle_h = \langle \tau_{33}^{(0)} \rangle_h + \hat{u}_3 \epsilon Re / (2Fr^2) h^{(1)}$, whence

$$\langle \boldsymbol{\sigma}_{ss}^{(0)} \rangle_h = \langle \boldsymbol{\tau}_{ss}^{(0)} \rangle_h - \langle \tau_{33}^{(0)} \rangle_h \mathbf{I}_{ss} - \frac{\hat{u}_3 \epsilon Re}{2 Fr^2} h^{(1)} \mathbf{I}_{ss}. \quad (44)$$

In addition, assumption $\mathcal{H}^{(-1)}$ (see **Lemma 4**) is satisfied for both planar velocity components, then

$$\boldsymbol{\sigma}_{s3}^{(0)} = \boldsymbol{\tau}_{s3}^{(0)} = \mathbf{0}. \quad (45)$$

Maxwell equation – Asymptotic. Taking into account the very last result (45) and applying **Theorem 3** and **Proposition 10** lead to the shallow formulation of the Maxwell equation (1):

$$We \frac{\mathcal{D}_1^{(0)} \langle \boldsymbol{\tau}_{ss}^{(0)} \rangle_h}{\mathcal{D}t} + \langle \boldsymbol{\tau}_{ss}^{(0)} \rangle_h = 2D_s(\mathbf{v}_s^{(0)}), \quad (46a)$$

$$We \left(\frac{D_s^{(0)} \langle \tau_{33}^{(0)} \rangle_h}{Dt} + 2\text{div}_s(\mathbf{v}_s^{(0)}) \langle \tau_{33}^{(0)} \rangle_h \right) + \langle \tau_{33}^{(0)} \rangle_h = -2\text{div}_s(\mathbf{v}_s^{(0)}). \quad (46b)$$

Remark 18. From a microscopic perspective, it is known [3, p. 90] that the elastic stress can be expressed in terms of the conformation tensor $\mathbf{c} \propto \langle \boldsymbol{\ell} \otimes \boldsymbol{\ell} \rangle$ defined as an average over all possible directions $\boldsymbol{\ell}$ of molecules constituting the considered fluid:

$$\boldsymbol{\tau} = \frac{\eta}{\lambda} (\mathbf{c} - \mathbf{I}). \quad (47)$$

On the reasonable assumption that $\boldsymbol{\ell}$ expands with respect to ϵ as $\boldsymbol{\ell} = \begin{pmatrix} \mathbf{O}(1) \\ \mathbf{O}(\epsilon) \end{pmatrix}$, we deduce a possible expansion for the conformation tensor as $\mathbf{c} = \begin{pmatrix} \mathbf{O}(1) & \mathbf{O}(\epsilon) \\ \mathbf{O}(\epsilon) & \mathbf{O}(\epsilon^2) \end{pmatrix}$. Thus, at zeroth order, the component 33 of the elastic stress reads $\tau_{33}^{(0)} = -1/We$, but it would lead to the contradiction $-1/We = 0$, according to equation (46b). If this expansion does not work for \mathbf{c} , does it at least work for $\boldsymbol{\tau}$? Assume $\tau_{33}^{(0)} = 0$, then $\text{div}_s(\mathbf{v}_s^{(0)}) = 0$ from equation (46b). If this does not lead to a contradiction, it implies a strong

physical constraint, which does not hold in most situations. We therefore understand that the order with respect to ϵ of a given quantity (here $\boldsymbol{\tau}$) must be componentwise at least of the order of the second member (here $D(\mathbf{v})$).

Summary. The shallow formulation of the Maxwell problem writes

Problem 19. Find $\mathbf{v}_s^{(0)}$, $h^{(1)}$, $\langle \boldsymbol{\tau}_{ss}^{(0)} \rangle_h$ and $\langle \boldsymbol{\tau}_{33}^{(0)} \rangle_h$ defined in Ω such that

$$\frac{\partial h^{(1)}}{\partial t} + \operatorname{div}_s(h^{(1)} \mathbf{v}^{(0)}) = 0, \quad (48a)$$

$$\operatorname{Re} h^{(1)} \frac{D_s^{(0)} \mathbf{v}_s^{(0)}}{Dt} - \operatorname{div}_s(h^{(1)} \langle \boldsymbol{\sigma}_{ss}^{(0)} \rangle_h) = -\frac{\epsilon \operatorname{Re}}{Fr^2} h^{(1)} \hat{\mathbf{u}}_s, \quad (48b)$$

$$\langle \boldsymbol{\sigma}_{ss}^{(0)} \rangle_h = \langle \boldsymbol{\tau}_{ss}^{(0)} \rangle_h - \langle \boldsymbol{\tau}_{33}^{(0)} \rangle_h \mathbf{I}_{ss} - \frac{\hat{u}_3}{2} \frac{\epsilon \operatorname{Re}}{Fr^2} h^{(1)} \mathbf{I}_{ss}, \quad (48c)$$

$$\operatorname{We} \frac{\mathcal{D}_1^{(0)} \langle \boldsymbol{\tau}_{ss}^{(0)} \rangle_h}{\mathcal{D}t} + \langle \boldsymbol{\tau}_{ss}^{(0)} \rangle_h = 2D_s(\mathbf{v}_s^{(0)}), \quad (48d)$$

$$\operatorname{We} \left(\frac{D_s^{(0)} \langle \boldsymbol{\tau}_{33}^{(0)} \rangle_h}{Dt} + 2\operatorname{div}_s(\mathbf{v}_s^{(0)}) \langle \boldsymbol{\tau}_{33}^{(0)} \rangle_h \right) + \langle \boldsymbol{\tau}_{33}^{(0)} \rangle_h = -2\operatorname{div}_s(\mathbf{v}_s^{(0)}). \quad (48e)$$

It is consistent with what has been derived in [4]. With $\operatorname{We} = 0$, it reduces to the same asymptotic (39) as the Navier-Stokes equation.

5. Conclusion

A new framework for asymptotic analysis has been presented in this paper. We have proposed a set of tools for performing thin-layer approximations of free-surface fluid models with flat topography and no-penetration boundary condition. The motion by slices is no more an arbitrary assumption, and minimal assumptions for obtaining it have been pointed out. Moreover, for first time, to the best of our knowledge, the first-order expansion of the Gordon-Schwalter derivatives has been developed. The proposed framework makes it possible to clarify the necessary assumptions and to simplify the asymptotic analysis of a wide variety of partial differential equations from continuum physics, whether they are scalar, vector or tensor, with objective derivative and/or diffusive, reactive or advective terms. This framework has been illustrated by two applications: the Navier-Stokes and the Maxwell models. In perspective, a generalisation of this work would be to consider here an arbitrary topography, following the work made in [5] for the Saint-Venant system.

Acknowledgements.

This work has taken place in the context of an interdisciplinary collaboration with two physicists, H el ene Delano e-Ayari (Institut Lumi ere Mati ere, Univ. Lyon 1) and Fran ois Graner (Laboratoire Mati ere et Syst emes Complexes, Univ. Paris 7), on the modelling of biological tissues. We warmly thank them for fruitful discussions. This work is supported by the CNRS interdisciplinary mission (MITI).

Appendix A. Leibniz formulas

Proposition 20 (Leibniz's Integral Rule). Let \mathcal{X} and I be two intervals of \mathbb{R} and $f: (x, t) \in \mathcal{X} \times I \mapsto f(x, t) \in \mathbb{R}^N$, $N \in \mathbb{N} \setminus \{0\}$, a sufficiently smooth function. Let also a and b two

differentiable functions defined from \mathcal{X} to I . Then the parameterized integral function F , defined in \mathcal{X} by

$$F(x) = \int_{a(x)}^{b(x)} f(x, t) dt,$$

is differentiable and

$$F'(x) = \int_{a(x)}^{b(x)} \frac{\partial f}{\partial x} dt + f(x, b(x))b'(x) - f(x, a(x))a'(x).$$

Corollary 21 (Leibniz's Integral Rule for depth average). *Let \mathcal{L} be a first order differential linear operator, depending only on partial derivatives ∂_t , ∂_{x_1} and ∂_{x_2} . For any sufficiently smooth scalar field φ , the following formula is satisfied:*

$$\mathcal{L}(h\langle\varphi\rangle_h) = h\langle\mathcal{L}\varphi\rangle_h + \varphi(x_3 = h)\mathcal{L}h. \quad (49a)$$

Corollary 22. *For any sufficiently smooth vector field \mathbf{u} , the following formulas are satisfied:*

$$\operatorname{div}_s(h\langle\mathbf{u}\rangle_h) = h\langle\operatorname{div}_s\mathbf{u}\rangle_h + \mathbf{u}_s(x_3 = h) \cdot \nabla_s h, \quad (49b)$$

$$\Delta_s(h\langle\mathbf{u}\rangle_h) = h\langle\Delta_s\mathbf{u}\rangle_h + 2\nabla_s\mathbf{u}_s(x_3 = h) \cdot \nabla_s h + \mathbf{u}_s(x_3 = h)\Delta_s h, \quad (49c)$$

$$h\langle\Delta_s\mathbf{u}\rangle_h = \operatorname{div}_s(h\langle\nabla_s\mathbf{u}\rangle_h) - \nabla_s\mathbf{u}_s(x_3 = h) \cdot \nabla_s h. \quad (49d)$$

We close this section by giving a last relation that will be useful:

$$\langle x_3 \partial_{x_3} \varphi \rangle_h + \langle \varphi \rangle_h = \varphi(x_3 = h). \quad (49e)$$

References

- [1] N. Balmforth, R. Craster, "A consistent thin-layer theory for Bingham plastics", *Journal of Non-Newtonian Fluid Mechanics* **84** (1999), no. 1, p. 65-81, <https://www.sciencedirect.com/science/article/pii/S0377025798001335>.
- [2] N. Bernabeu, P. Saramito, C. Smutek, "Numerical modeling of shallow non-Newtonian flows: Part II. Viscoplastic fluids and general tridimensional topographies", *Int. J. Numer. Anal. Model.* **11** (2014), no. 1, p. 213-228, <http://www.math.ualberta.ca/ijnam/Volume-11-2014/No-1-14/2014-01-12.pdf>.
- [3] R. B. Bird, C. F. Curtiss, R. C. Armstrong, O. Hassager, *Dynamics of polymeric liquids: Kinetic Theory*, seconde édition ed., vol. 2, Wiley-Interscience, 1987.
- [4] F. Bouchut, S. Boyaval, "A new model for shallow viscoelastic fluids", *Math. Models Meth. Appl. Sci.* **23** (2013), no. 8, p. 1479-1526, <https://www.worldscientific.com/doi/abs/10.1142/S0218202513500140>.
- [5] F. Bouchut, M. Westdickenberg, "Gravity driven shallow water models for arbitrary topography", *Communications in Mathematical Sciences* **2** (2004), no. 3, p. 359 - 389, <https://projecteuclid.org/journals/communications-in-mathematical-sciences/volume-2/issue-3/Gravity-driven-shallow-water-models-for-arbitrary-topography/cms/1109868726.full>.
- [6] F. Bouchut, S. Boyaval, "Unified derivation of thin-layer reduced models for shallow free-surface gravity flows of viscous fluids", *European Journal of Mechanics - B/Fluids* **55** (2016), p. 116-131, <https://www.sciencedirect.com/science/article/pii/S0997754615001120>.
- [7] E. D. Fernández-Nieto, P. Noble, J.-P. Vila, "Shallow water equations for non-Newtonian fluids", *J. Non-Newt. Fluid Mech.* **165** (2010), no. 13, p. 712-732, <https://www.sciencedirect.com/science/article/abs/pii/S0377025710000947>.
- [8] J.-E. Gerbeau, B. Perthame, "Derivation of Viscous Saint-Venant System for Laminar Shallow Water; Numerical Validation", Research Report RR-4084, INRIA, 2000, <https://hal.inria.fr/inria-00072549>, Projet M3N.
- [9] K. F. Liu, C. C. Mei, "Approximate equations for the slow spreading of a thin sheet of Bingham plastic fluid", *Physics of Fluids A: Fluid Dynamics* **2** (1990), no. 1, p. 30-36, <https://doi.org/10.1063/1.857821>, <https://arxiv.org/abs/https://doi.org/10.1063/1.857821>.
- [10] F. Marche, "Derivation of a new two-dimensional viscous shallow water model with varying topography, bottom friction and capillary effects", *European Journal of Mechanics - B/Fluids* **26** (2007), no. 1, p. 49-63, <https://www.sciencedirect.com/science/article/pii/S0997754606000719>.
- [11] J. G. Oldroyd, "On the formulation of rheological equations of states", *Proc. R. Soc. Lond. A* **200** (1950), p. 523-541, <http://rspa.royalsocietypublishing.org/content/200/1063/523.full.pdf>.
- [12] A. B. de Saint-Venant, "Théorie et équations générales du mouvement non permanent des eaux courantes", *Comptes Rendus des séances de l'Académie des Sciences, Paris, France, Séance* **17** (1871), no. 73, p. 147-154, <https://gallica.bnf.fr/ark:/12148/bpt6k3030d/f147.item#>.