



HAL
open science

Spotting fake news in Arabic with Machine and Deep Learning Techniques

Maysoon Alkhair, Abdelouahab Hocini, Kamel Smaïli

► **To cite this version:**

Maysoon Alkhair, Abdelouahab Hocini, Kamel Smaïli. Spotting fake news in Arabic with Machine and Deep Learning Techniques. INTERNATIONAL JOURNAL OF SCIENTIFIC DEVELOPMENT AND RESEARCH, 2023, 8 (2), pp.605-611. hal-04064548

HAL Id: hal-04064548

<https://hal.science/hal-04064548>

Submitted on 11 Apr 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Spotting fake news in Arabic with Machine and Deep Learning Techniques

Maysoon Alkhair¹, Abdelouahab Hocini² and Kamel Smaili²

¹ Sudan University of Science and Technology

² LORIA, Université Lorraine, F-54600, France

mayssoonalkhier111@gmail.com, abdelouahab.hocini@loria.fr, smaili@loria.fr

Abstract. The rapid spread of rumors due to the growth of the internet and social media has prompted researchers to search for solutions to detect fake news, which is treated as a text classification problem. In this study, we examine the content of fake news in the Arabic-speaking world through YouTube comments. To start, we have updated our Arabic corpus for fake news analysis, incorporating the most frequently discussed topics in rumors. Next, we conducted experiments to determine the best combination of preprocessing, classical machine learning, and neural networks in classifying comments as either rumors or non-rumors. The models we used include Support Vector Machine (SVM), Decision Tree (DT), Multinomial Naïve Bayes (MNB) for machine learning, and LSTM, BiLSTM, and CNN for deep learning. Finally, we compare the results of previous machine learning models and deep learning techniques to determine which one is more effective in detecting fake news. Both models showed high accuracy in the results.

Keywords: Rumors, classifiers, Arabic Fake news corpus, Machine learning, Deep learning

1 Introduction

Internet has changed the whole planet, it introduced new means of communication between people all around the globe mainly for two reasons: its inexpensiveness and lack of restrictions. This wide network opened new doors for fast and easy information transmission and it became the user's favourite source of news replacing the classic media. This fast growth, has led to new concerns and challenges: the spread of false stories (fake news)[1, 2]. To make things worse, the fact that internet users can freely express their own opinion on any given topic and share it on many networks, platforms and with different people, generates a huge amount of unverified information[3]. In order to mitigate the problem of the fast and wild spread of false information, research works proposed automated or semi-automated techniques for the evaluation of the veracity of these fake stories. The first step to these processes of evaluation is usually the extraction of data from multiple social networks such as Twitter, Facebook, Youtube and other[4, 5]. These last networks are considered as the main source of fake news that spread throughout the web. These news could take multiple forms: junk news, bogus and hoaxes are examples of the many other forms of fake news on Internet and on classical media [6]. Fake news could be characterised and differentiated from real news. According to [7], fake news has a spreading pace that is much faster than of the real news'. In

addition to that, in [8] the authors describe fake news as false news that are made to be believed true for a specific purpose. A very widely known example for this last point is the US presidential elections in 2016 [9].

In this work, we investigate the content of fake news in the Arabic world through the information posted on YouTube. We selected fake news concerning the death of three known Arab personalities: the dancer Fifi Abdou, the ex Algerian president Bouteflika Abdelaziz and the comedian Adel Imam. The two main objectives of this work are: first, to crawl Arabic rumors in order to build a corpus that we will share with the international community. Then, present a comparative analysis on the performances of existing machine learning and deep learning classification methods for fake news detection on the built corpus.

The rest of this article is structured as follows: in Section 2, we discuss research works related to the current study. Then we give an overview of the datasets to build corpus rumors analysis and extraction. Thereafter, we give details about the machine and deep learning approaches that are described in section3. In Section 4, we present comparative results of the machine and deep learning classification algorithms and finally, “Conclusion and future work” presents the conclusion and future work on the problem.

2 Related Works

In this section, we provide recent research into social media rumors with a focus on comparability methods that were widely used to identify similar data related to the same rumors when the dataset was collected. Fake news detection research is limited, mostly centered around the 2016 US presidential elections, and lacks consistent features. It mainly employs machine and deep learning techniques based on the defined features.

2.1 Machine learning

Hadeer et al. in [10] proposed a four-step pipeline for fake news detection: preprocessing the dataset, extracting n-gram features to represent the document, training the classifier, and performing classification. In this work six machine learning algorithms have been investigated, the best performing was LSVM. In [11], hand-crafted features are employed, extracted from the news content, source, and context. Then a variety of machine learning models have been tested against a dataset consisting of 2282 BuzzFeed news articles related to the 2016 U.S. election with a split of 73% - 27% true-false. The best results were achieved with Random Forest and XGBoost using a threshold-based decision. In [12], two datasets were gathered: one crowdsourced and the other obtained from public figures’ websites. An SVM was trained with a five-fold cross-validation, where one dataset was used for training and the other for testing, yielding an accuracy of 67%. In [13], the authors introduced 163 features across 5 categories (ngrams count, tf-idf, word embedding, sentiment polarity, and Linguistics). They then tested 7 ML algorithms and found XGBoost to be the best performer.

2.2 Deep learning

Fake news detection is a challenging problem that can be tackled using deep learning techniques. One approach is to use neural networks to analyze the text of an article or news item and identify patterns that are indicative of fake news, such as the use of certain words or phrases, the sentiment of the text, or the credibility of the source. Another approach is to use deep learning to analyze images and videos that accompany a news item, in order to detect signs of manipulation or forgery.

In [14] researchers presented a new benchmark dataset collected from fact-checked news claims, the dataset is composed of 12.8k instances and use 6 labels (Pants-fire, False, Barely-true, Half-true, Mostly-true, True). A hybrid Convolutional Neural Networks framework that integrates text and metadata has also been proposed. In this work, CNNs and Bi-LSTM are utilized to extract features from both news text and metadata. However, the main challenge is overfitting, with validation and test accuracy around 27%. Similarly, [15] employed automatic feature extraction. The authors utilized a combination of Kaggle’s and GorgeMcIntire’s instances as the new dataset. Features were extracted using DOC2Vec and Word Embedding, followed by classification using a Deep CNN and an LSTM. The CNN demonstrated the best performance with an accuracy of 94.22%.

[16] addresses the fake news challenge (FNC-1) by utilizing a deep learning model on a dataset. The article body and headline are utilized as prediction features and an accuracy of 71.2% was achieved.

3 Methods and Techniques

The following section outlines the details of the dataset collected for this study, including its updated version, the fake news features in the dataset, and the various Machine Learning and Deep Learning algorithms utilized for classification.

3.1 Overview on the dataset

In a previous study [17], we explored the nature of fake news in the Arabic world by analyzing the content posted on YouTube. The data was collected using the YouTube API, which enabled us to search for videos about the death of personalities. This focus was chosen as rumors about the death of celebrities are often associated with fake news. The study selected three prominent figures in the Arab world who are frequently subject to such rumors: Fifi Abdu (Egyptian dancer), Abdelaziz Bouteflika (former Algerian president), and Adel Imam (Egyptian comedian).

Table 3.1 in the previous study shows the cleaned dataset, with $|C|$ representing the number of comments for each topic. In this new contribution, we expand the dataset by gathering more comments for each topic, increasing its size by 44% with the addition of 1509 new comments, as shown in table 3.1.


The figure [1] illustrates the distribution of the collected comments across the three topics. The dataset is imbalanced, with comments about Fifi Abdu’s death accounting for 55

Table 1. The collected stories related to Fifi abdo, Bouteflika and Adel Imam

Topics	c
Fifi Abdo	2,145
Bouteflika	964
Adel Imam	326

Table 2. The collected stories related to Fifi abdo, Bouteflika and Adel Imam (update datasets)

Topics	c
Fifi Abdo	2,725
Bouteflika	1,511
Adel Imam	708

Fig. 1. Distribution of the vocabulary after combination datasets

The data collected on rumors reveals that the President and the comedian's death garnered less attention than the death of Fifi Abdo, despite the President being a head of state. This highlights the greater interest of internet users in Fifi Abdo, both in terms of rumors and non-rumors. The tables (3 and 4) show the statistics and updated totals of rumors, and (5 and 6) show the same for non-rumors.

Table 3. Statistics corresponding to the rumors datasets

Topic	C	W
Fifi Abdo	187	1605
President Bouteflika	106	3507
Adel Imam	50	508

Table 4. Statistics corresponding to the rumors update datasets

Topic	C	W
Fifi Abdo	360	2767
President Bouteflika	347	6228
Adel Imam	187	1744

Table 5. Statistics corresponding to the Non-rumors datasets

Topic	C	W
Fifi Abdo	1958	22708
President Bouteflika	858	11917
Adel Imam	276	3085

Table 6. Statistics corresponding to the Non-rumors update datasets

Topic	C	W
Fifi Abdo	2300	13045
President Bouteflika	1180	22209
Adel Imam	521	5816

The chart in Figure 2 illustrates the distribution of the sample datasets, real or fake. As there is a lack of sufficient samples in the dataset for a Deep Learning model to be built from scratch, one approach tested was evaluating the ability of a Deep Learning model trained on the Arabic Algerian corpus to detect fake Arabic.


4 Classification task

4.1 Machine Learning

This work tested the ability to differentiate between rumor and non-rumor comments using three data classification methods: Decision Tree (DT), Multinomial Naive Bayes (MNB), and Support Vector Machine (SVM).

SVM [18] aims to find the best linear separating hyperplane that separates the data into two classes. This is done by maximizing the distance between the classes. Classification of new data is based on which side of the hyperplane it falls on. We used a linear kernel for separation.

Naive Bayes classifiers are popular in NLP, especially for text classification [19][20] due to their efficiency and good predictive performance. MNB estimates the conditional probability of a particular term given a class. To train the MNB classifier, we used 1-gram, 2-gram and 3-gram of words as features supported by a TFIDF vector scores

Fig. 2. Sample distribution for the resulting datasets in fake news and real news

[21].

We conducted experiments and evaluated classifiers using common Information Retrieval metrics: Accuracy, Recall, and Precision.

4.2 Deep Learning

Deep learning is a branch of machine learning that surpasses traditional machine learning in its ability to automatically identify patterns in raw data without the need for manual feature extraction, in contrast to traditional machine learning, which still requires human aid in feature extraction [22]. In this study, we delved deeper into the classification of rumors and non-rumors using three advanced deep learning techniques: Long Short-Term Memory (LSTM), Bidirectional Long Short-Term Memory (BiLSTM), and Convolution Neural Network (CNN).

LSTM (Long Short-Term Memory) is a popular type of Recurrent Neural Network (RNN) that is widely used for pattern recognition and improved performance in text classification and sequential data prediction tasks [23]. LSTM comprises of layers that allow it to selectively retain relevant information, making it more effective for text classification and solving sequential data prediction problems.

The Bidirectional LSTM (BiLSTM) model architecture consists of two Long Short-Term Memory (LSTM) cells that are on both side to carry the information and run in parallel. So this method is called The forward and backward hidden states of the Bidirectional LSTM. Which provides context information from the past and future in order to increase the memory capabilities of LSTMs.[24].

The Convolutional Neural Network (CNN) operates on n-grams and employs convolutional layers to identify features in the input data using various filter sizes. The layers are arranged in multiple feature mappings, allowing the CNN to learn and understand the details of the input data [25]. The initial layers extract high-level features with lower abstraction, while deeper layers extract low-level features with higher abstraction [25, 26].

5 The experiments and results

5.1 The experiments

we work the execution of experiments, used three methods were defined in combination with the datasets. firstly,was established a baseline, training and validating the three Machine learning models listed in subsection 4.1, using the dataset in Arbic. For Machine language models, the texts were represented using tf-idf techniques; this step was carried out to have a reference point for comparison purposes with the Deep learning approaches and varying the datasets used for training and validation. secondly, uses the dataset in arbic both to train and validate three vanilla Deep learning models based on LSTM,BILSTM and CNN layers, Concerning the experiments, we tried with different values for the number of epochs, and also applied the early stopping strategy considering different values of the hyperparameters tolerance and patience. For its part,we conducted some experiments where samples from the translated dataset were progressively mixed with all the dataset in arbic during the training phase; then, the remaining portion of the tested dataset was used for validation, i.e.,some a learning curve.

5.2 Hyper-parameters

The importance of adjusting the model cannot be overstated in predictive modeling. To ensure optimal results, we carried out experiments and fine-tuned various hyperparameters for the selected machine learning approaches. This was done to evaluate the performance of the classifiers using common evaluation metrics.

The batch size used in this experiment was 50-60, which represents the number of windows of data passed at once. Dropout, a regularization technique in neural networks, was applied with a value of 0.5 to reduce interdependent learning among neurons. The model was trained for 50 epochs, which refers to the number of iterations of forward and backward propagation. The Dense class was used to specify the number of neurons or nodes in the layer and the activation function, with 1 neuron being selected. The loss argument was used to specify the loss function used to evaluate a set of weights, and the accuracy metric was used to evaluate the model's performance.

5.3 Results and discussion

We evaluated the performance of our model on test datasets after fine-tuning the hyperparameters. The classification accuracy was used as the evaluation metric to accurately determine the proximity of the predicted results to the actual values. The tables in the study present the predicted accuracy of the models discussed in sections 4.

We presented the results of three machine learning classifiers and compared them to previous results. These findings are displayed in tables 7 and 8. The training was conducted using 70% of the data and the testing was done on the remaining 30% of the corpus. Additionally, two types of tests were performed. The first test was conducted on each individual rumor topic and the second test was performed on a mixture of all rumor topics. We observed that the performance results in 7 vary depending on the ru-

Table 7. Performance on detecting rumors of datasets

Topic	SVM			D. Tree			MNB		
	Acc	Prec	Rec	Acc	Prec	Rec	Acc	Prec	Rec
Fifi Abdo	95.35	87.72	82.16	93.59	79.94	82.8	92.63	78.01	73.42
Bouteflika	94.2	92.69	78.18	95.56	94.09	83.9	93.86	90.7	77.99
Adel Imam	93.68	85.2	78.82	89.47	73.15	80.88	90.53	74.87	72.65
Combi	95.35	92.77	83.12	93.47	84.07	83.56	92.38	82.76	76.94

mor topic and the classifier used. The best accuracy and precision for the Fifi Abdo topic were achieved by the SVM classifier, while the best recall was produced by the Decision Tree classifier. For the rumors related to President Bouteflika, the best results were produced by the D.Tree. In the case of the third rumor topic, the best accuracy and precision were achieved by the SVM classifier, and the best recall was produced by the D.Tree. When all the rumor topics were combined, the best results in terms of accuracy and precision were obtained by the SVM classifier, while the best recall was produced by the Decision Tree. Overall, the SVM classifier performed the best among the three classifiers, while the D.Tree. and Multinomial Naive Bayes (MNB) were not able to outperform the other classifiers in this dataset. We evaluated the updated datasets in table

Table 8. Performance on detecting rumors of update datasets

Topic	SVM			D. Tree			MNB		
	Acc	Prec	Rec	Acc	Prec	Rec	Acc	Prec	Rec
Fifi Abdo	92.73	85.96	80.63	89.35	76.80	78.28	91.60	84.07	76.39
Bouteflika	91.03	85.92	88.73	83.15	75.50	80.37	88.62	84.27	80.52
Adel Imam	85.92	81.62	77.98	80.28	73.73	77.63	89.20	86.03	83.50
Combi	92.09	89.47	84.13	90.87	85.43	85.24	90.52	88.65	79.27

10. The results showed slight variations in performance. The SVM classifier achieved the best accuracy and recall for the topic of Fifi Abdo, while the best precision was obtained by the Decision Tree. For rumors about President Bouteflika, the SVM classifier produced the best results. For the third rumor topic, the MNB classifier produced the best accuracy, precision, and recall. When all rumor topics were combined, the SVM classifier had the best accuracy and precision and the Decision Tree had the best recall. Overall, the SVM classifier performed the best in this dataset, while the other classifiers, despite their effectiveness in other classification tasks, were not able to outperform it for any of the topics.

In the second set of experiments, we utilized deep learning classifiers, such as LSTM, BILSTM, and CNN, as described in section 4. The models were trained on 70% of the Algerian corpus, and validated using the rest of the dataset. Due to the large size requirement of deep learning models, the results were shown in tables 9, and 10

which compared the predicted accuracy to the previous results. The experiments were run twice, once on individual rumor topics and once on a mixture of all the rumors.

Table 9. Performance on detecting rumors of datasets

Topic	LSTM	BiLSTM	CNN
	Accuracy	Accuracy	Accuracy
Fifi Abdo	0.92	0.95	0.95
Bouteflika	0.90	0.91	0.94
Adel Imam	0.85	0.85	0.85
Combi	0.90	0.93	0.93

The results displayed in table 9 indicate that the highest accuracy for rumors related to Fifi Abdo was achieved by the BiLSTM and CNN models. The CNN model had the highest accuracy for the second rumor topic. Results for the third topic revealed that all classifiers had equal accuracy. In terms of accuracy, the best results were obtained by the BiLSTM and CNN models when all the rumors were combined. Overall, the BiLSTM classifier performed the best followed by CNN, while the LSTM classifier failed to surpass the other models.



The experimental results in table 10 showed that the best accuracy for the rumors about

Table 10. Performance on detecting rumors of update datasets


Topic	LSTM	BiLSTM	CNN
	Accuracy	Accuracy	Accuracy
Fifi Abdo	0.86	0.92	0.92
Bouteflika	0.79	0.88	0.85
Adel Imam	0.79	0.82	0.80
Combi	0.80	0.90	0.85

Fifi Abdo were obtained by the BLSTM and CNN classifiers. The best results for the rumors about President Bouteflika were produced by the BiLSTM. The best accuracy for the third rumor topic was achieved by the BiLSTM as well. When all the rumors were combined, the best accuracy was still produced by the BiLSTM. Thus, overall, the BiLSTM classifier was the best performer, while the LSTM did not outperform the other classifiers.

To further evaluate the performance of these models, we implemented a learning curve by incorporating the Arabic dataset. The models evaluated were the LSTM, BiLSTM, and CNN layers, along with trainable embeddings. The results of the learning curve indicated an improvement in performance with different ratios. The figures in 3,4, and 5 show the cross-validation results of these models.

Fig. 3. Model train and test vs Validation loss (LSTM)**Fig. 4.** Model train and test vs Validation loss (BILSTM)

We noted that the learning curve in Figure [5] displayed an unusual pattern, with both the training and validation losses remaining constant. This suggests that the deep learning algorithm may have trouble correctly classifying smaller datasets. To address this, it would be necessary to increase the size of the dataset and perform additional training on the model.

Fig. 5. Model train and test vs Validation loss (CNN)

6 Conclusion and future work

In this article, we present a study on automatic Arabic fake news detection. As the use of social media continues to rise, the problem of fake news is becoming more prevalent. To address this issue, researchers have been working on finding solutions to protect society from fake news. In this study, we reviewed various studies related to fake news detection and presented a taxonomy of methods based on classical ML and advanced DL strategies. The study includes three different datasets and evaluates the performance of ML classifiers like SVM, Naive Base, and Decision Tree based on accuracy, precision, and recall. The results showed that SVM had the highest accuracy of 95% in fake news detection. In the second part of the study, we conducted experiments on fake news detection methods using deep learning models, including LSTM, BiLSTM, and CNN. By fine-tuning important hyper-parameters and using techniques like word2vec and Tf-idf, the models were optimized to achieve higher accuracy. The results showed that CNN had the highest accuracy of 95%. Furthermore, the use of the Algerian corpus for embedding improved the Arabic fake news detection in Deep learning models compared to linear models. Future studies aim to build a larger Arabic fake news dataset and conduct further experiments using deep learning models.

Bibliography

- [1] Hunt Allcott and Matthew Gentzkow. Social media and fake news in the 2016 election. *Journal of economic perspectives*, 31(2):211–36, 2017.
- [2] Tayyaba Rasool, Wasi Haider Butt, Arslan Shaukat, and M Usman Akram. Multi-label fake news detection using multi-layered supervised learning. In *Proceedings of the 2019 11th international conference on computer and automation engineering*, pages 73–77, 2019.
- [3] Noam Chomsky and Edward Herman. A propaganda model. *Manufacturing Consent: the Political Economy of the Mass Media*. 2d ed. New York: Pantheon Books, pages 1–35, 2002.
- [4] Arkaitz Zubiaga, Maria Liakata, Rob Procter, Geraldine Wong Sak Hoi, and Peter Tolmie. Analysing how people orient to and spread rumours in social media by looking at conversational threads. *PLoS one*, 11(3):e0150989, 2016.
- [5] KP Krishna Kumar and G Geethakumari. Detecting misinformation in online social networks using cognitive psychology. *Human-centric Computing and Information Sciences*, 4(1):14, 2014.
- [6] Stefan Helmstetter and Heiko Paulheim. Weakly supervised learning for fake news detection on twitter. In *2018 IEEE/ACM International Conference on Advances in Social Networks Analysis and Mining (ASONAM)*, pages 274–277. IEEE, 2018.
- [7] Xichen Zhang and Ali A Ghorbani. An overview of online fake news: Characterization, detection, and discussion. *Information Processing & Management*, 57(2):102025, 2020.
- [8] Keonyoung Park and Hyejoon Rim. Social media hoaxes, political ideology, and the role of issue confidence. *Telematics and Informatics*, 36:1–11, 2019.
- [9] Kai Shu, Amy Sliva, Suhang Wang, Jiliang Tang, and Huan Liu. Fake news detection on social media: A data mining perspective. *ACM SIGKDD explorations newsletter*, 19(1):22–36, 2017.
- [10] Hadeer Ahmed, Issa Traore, and Sherif Saad. Detecting opinion spams and fake news using text classification. *Security and Privacy*, 1(1):e9, 2018.
- [11] Julio CS Reis, André Correia, Fabrício Murai, Adriano Veloso, and Fabrício Benvenuto. Supervised learning for fake news detection. *IEEE Intelligent Systems*, 34(2):76–81, 2019.
- [12] Verónica Pérez-Rosas, Bennett Kleinberg, Alexandra Lefevre, and Rada Mihalcea. Automatic detection of fake news. *arXiv preprint arXiv:1708.07104*, 2017.
- [13] Arvinder Pal Singh Bali, Mexson Fernandes, Sourabh Choubey, and Mahima Goel. Comparative performance of machine learning algorithms for fake news detection. In *International conference on advances in computing and data sciences*, pages 420–430. Springer, 2019.
- [14] William Yang Wang. ”liar, liar pants on fire”: A new benchmark dataset for fake news detection. *arXiv preprint arXiv:1705.00648*, 2017.
- [15] Aman Agarwal, Mamta Mittal, Akshat Pathak, and Lalit Mohan Goyal. Fake news detection using a blend of neural networks: An application of deep learning. *SN Computer Science*, 1(3):1–9, 2020.

- [16] Ayat Abedalla, Aisha Al-Sadi, and Malak Abdullah. A closer look at fake news detection: A deep learning perspective. In *Proceedings of the 2019 3rd International Conference on Advances in Artificial Intelligence*, pages 24–28, 2019.
- [17] Maysoon Alkhair, Karima Meftouh, Kamel Smaïli, and Nouha Othman. An arabic corpus of fake news: Collection, analysis and classification. In *International Conference on Arabic Language Processing*, pages 292–302. Springer, 2019.
- [18] Vladimir Vapnik. *Statistical learning theory*. Wiley, 1998.
- [19] Andrew McCallum, Kamal Nigam, et al. A comparison of event models for naive bayes text classification. In *AAAI-98 workshop on learning for text categorization*, volume 752, pages 41–48. Citeseer, 1998.
- [20] Jiang Su, Jelber S Shirab, and Stan Matwin. Large scale text classification using semi-supervised multinomial naive bayes. In *Proceedings of the 28th International Conference on Machine Learning (ICML-11)*, pages 97–104. Citeseer, 2011.
- [21] Karen Spärck Jones. A Statistical Interpretation of Term Specificity and Its Application in Retrieval. *Journal of Documentation*, 28:11–21, 1972.
- [22] Andry Chowanda and Alan Darmasaputra Chowanda. Recurrent neural network to deep learn conversation in indonesian. *Procedia computer science*, 116:579–586, 2017.
- [23] Ralf C Staudemeyer and Eric Rothstein Morris. Understanding lstm—a tutorial into long short-term memory recurrent neural networks. *arXiv preprint arXiv:1909.09586*, 2019.
- [24] Guozheng Rao, Weihang Huang, Zhiyong Feng, and Qiong Cong. Lstm with sentence representations for document-level sentiment classification. *Neurocomputing*, 308:49–57, 2018.
- [25] Saad Albawi, Tareq Abed Mohammed, and Saad Al-Zawi. Understanding of a convolutional neural network. In *2017 international conference on engineering and technology (ICET)*, pages 1–6. Ieee, 2017.
- [26] Anirudha Ghosh, Abu Sufian, Farhana Sultana, Amlan Chakrabarti, and Debashis De. Fundamental concepts of convolutional neural network. In *Recent Trends and Advances in Artificial Intelligence and Internet of Things*, pages 519–567. Springer, 2020.