



HAL
open science

An approach to approximate reasoning based on the Dempster rule of combination

Philippe Chatalic, Didier Dubois, Henri Prade

► **To cite this version:**

Philippe Chatalic, Didier Dubois, Henri Prade. An approach to approximate reasoning based on the Dempster rule of combination. Bulletin pour les sous-ensembles flous et leurs applications, 1985, 25, pp.118-123. hal-04077220

HAL Id: hal-04077220

<https://hal.science/hal-04077220v1>

Submitted on 21 Apr 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

An approach to approximate reasoning based on Dempster
rule of combination*

P. Chatalic, D. Dubois, H. Prade

Université Paul Sabatier
Laboratoire Langages et Systèmes Informatiques
118, route de Narbonne
31062 Toulouse Cedex

Extended abstract

The problem of automated reasoning in a knowledge base containing uncertain items of information is addressed. The proposed methodology takes advantage of Dempster-Shafer's theory of evidence to deal with uncertainty.

1 - Knowledge representation

The knowledge base contains facts and rules. Elementary facts are of the form "x is A" where A is a subset of some frame of discernment X, and x is a variable defined on X ; what the fact says is that the (unknown) value of x lies in subset A. Composite facts referring to Cartesian products of frames can be contemplated. An elementary rule is of the form "if x is A, then y is B" and is viewed as a composite fact "(x,y) is $\bar{A}+B$ " where \bar{A} is the complement of A in X, + denotes the dual of the Cartesian product, and $\bar{A}+B$ is a subset of the Cartesian product $X \times Y$. Namely $\bar{A}+B = \overline{A \times \bar{B}}$ and is the set-theoretic counterpart of the ordinary logical implication.

* Prepared for presentation at the 8th IASTED Inter. Symp. on Robotics and Artificial Intelligence, Toulouse, France, June 18-20, 1986.

A fact $F = "x \text{ is } A"$ may be uncertain. Uncertainty on F is expressed by means of a grade of credibility $Cr(A) \in [0,1]$ which expresses the extent to which F is held for certain. The following conventions are adopted

$Cr(A) = 1$ means that F is a sure fact.

$Cr(A) = 0$ means that F is a totally uncertain fact.

It is actually assumed that Cr is a belief function (Shafer [6]) on the frame X , deriving from a basic probability assignment m in the sense that

$$Cr(A) = \sum \{m(B) \mid \emptyset \neq B \subseteq A\} \quad (1)$$

where $m(B)$ is positive and $\sum_{B \subseteq X} m(B) = 1$. The quantity $Cr(\bar{A})$ expressing the

credibility of the fact " x is not A ", is such that $Cr(A) + Cr(\bar{A}) \leq 1$. The quantity $Pl(A) = 1 - Cr(\bar{A}) \geq Cr(A)$ is the grade of plausibility of F , and is 0 as soon as the fact F is a certainly false. The knowledge provided by the expert about fact F is supposedly $Cr(A) = \alpha$. Using a principle of minimum specificity (Dubois and Prade [3]), the less arbitrary basic probability assignment satisfying (1) is given by

$$m_F(A) = \alpha \quad ; \quad m_F(X) = 1 - \alpha \quad (2)$$

when $Cr(A) = \alpha$ is the only available knowledge about F . Similarly an uncertain rule $R = "if X \text{ is } A, \text{ then } Y \text{ is } B"$ is assigned a grade of credibility $\beta = Cr(\overline{A \times B})$, and is represented by the basic assignment m_R :

$$m_R(\overline{A \times B}) = \beta \quad , \quad m_R(X \times Y) = 1 - \beta \quad (3)$$

2 - Outline of the approximate reasoning methodology

Let F_1, \dots, F_m be a set of facts and R_1, \dots, R_n be a set of rules, all of which are allowed to be uncertain. Let F be a fact the truth of which must be established, the approximate reasoning procedure runs as follows :

1. Define a frame Ω as the smallest set containing the frames of F_i , $i = 1, m$, R_j , $j = 1, n$, and F . In other words, if the knowledge base pertains to p variables x_1, \dots, x_p , then $\Omega = X_1 \times X_2 \times \dots \times X_p$.
2. Calculate the cylindrical extension of the basic assignments m_{F_i} and m_{R_j} of facts and rules on Ω . Combine the extended basic assignments via Dempster rule [6].
3. Project the so-obtained basic assignment m on the frame Z pertaining to F . Compute $Cr(F)$ and $Pl(F)$ by (1).

Dempster rule of combination merges two basic assignments m_1 and m_2 on the same frame Ω into a basic assignment \hat{m} defined by, $\forall A \subseteq \Omega$

$$\hat{m}(A) = \frac{m(A)}{1 - m(\emptyset)} \quad (4)$$

and

$$\begin{aligned} m(A) &= \sum \{m_1(A_1) \cdot m_2(A_2) \mid A_1 \cap A_2 = A\} \\ &= [m_1 \cap m_2](A) \end{aligned} \quad (5)$$

(5) is a random set intersection, which assumes that the bodies of evidence defined by m_1 and m_2 are independent [2]. (4) is a normalization operation which gets rid of the conflicts between m_1 and m_2 ; the inconsistency between the two bodies of evidence is measured by $m(\emptyset)$. In the above procedure only (5) is applied in order not to artificially hide the partial inconsistency of the knowledge base. The operations of cylindrical extensions and projections are defined in Shafer [7]. This procedure is very similar to Zadeh's approach to approximate reasoning. Here we use plausibility functions instead of possibility measures, and Dempster rule instead of a fuzzy set-theoretic joint operation. Note that Dempster rule is associative and commutative.

3 - Application to modus ponens under uncertainty

As an example, consider a simple knowledge base containing a fact F expressed as an axiom $\vdash p$ in propositional logic and a rule $R = \text{"if } F, \text{ then } G\text{"}$, expressed as another axiom $\vdash p \rightarrow q$. Let $\alpha = Cr_1(p)$, $\beta = Cr_2(p \rightarrow q)$. Let $\underline{1}$ denote

the tautology. We define the two basic assignments, using (2) and (3)

$$\begin{aligned} m_F(p) &= \alpha & ; & & m_F(\mathbb{1}) &= 1-\alpha \\ m_R(p \rightarrow q) &= \beta & ; & & m_R(\mathbb{1}) &= 1-\beta \end{aligned}$$

Using (5) we get

$$m(p \wedge q) = \alpha \cdot \beta ; m(p \rightarrow q) = \beta \cdot (1-\alpha) ; m(p) = \alpha(1-\beta) ; m(\mathbb{1}) = (1-\alpha)(1-\beta).$$

Note that no normalization step is required.

The fact to be ascertained is q . Using (1), in the language of logic, we obtain

$$Cr(q) = \sum \{m(s) \mid s \rightarrow q = \mathbb{1}\} = \alpha \cdot \beta$$

It is easy to see that $PL(q) = 1 - Bel(\text{not } q) = 1$. Hence we obtain the following generalization of modus ponens

$$\begin{array}{l} Cr_1(p) = \alpha \\ Cr_2(p \rightarrow q) = \beta \\ \hline Cr(q) = \alpha \cdot \beta ; PL(q) = 1 \end{array}$$

Note that classical modus ponens is recovered letting $Cr_1(p) = 1$ and $Cr_2(p \rightarrow q) = 1$. Moreover if one is totally ignorant about the truth of p ($Cr_1(p) = 0$) or $p \rightarrow q$ ($Cr_2(p \rightarrow q) = 0$) then $Cr(q) = 0$. Hence the above pattern of reasoning is consistent with propositional logic.

4 - Towards a distributed reasoning procedure

Contrastedly with usual approximate reasoning schemes in expert systems the procedure outlined in section 2 simultaneously applies all rules to all facts. Especially propagation and combination of uncertainty are not performed in separate steps [1], nor progressively on some inference network [5].

Hence the result obtained by the procedure is exact, in so far as the facts and rules are independent, but the actual computation can be very tedious (Gordon & Shortliffe [4]). To decrease this computational burden one idea is to decompose the knowledge base into a network of sub-bases which reflects the structure of the available information. Each sub-base receives as input the results obtained by applying the general methodology on upstream sub-bases, and produces some results in turn, etc ... This distributed computation scheme is made possible due to the associativity and commutativity of Dempster rule.

However the fact that sub-bases are related via a network implies that the inputs of a sub-base may not be independent. Namely if x_1 and x_2 are two input variables of a sub-base S and m_1, m_2 are the respective basic assignment, then the joint basic assignment may not be $[m_1 \cap m_2]$ for instance if m_1 and m_2 were obtained from some evidence pertaining to the same variable x (and possibly others). This implies that x_1 and x_2 must be outputs of the same sub-base, and that the joint basic assignment m_{12} on $X_1 \times X_2$ must be calculated via the procedure of section 2. The reason why $m_{12} \neq m_1 \cap m_2$ is that Dempster rule is not idempotent ($m \cap m \neq m$), and that the basic assignment m describing x appears twice in the expression of $m_1 \cap m_2$, while it appears only once in m_{12} .

An approximate reasoning algorithm involving a knowledge base decomposition step is currently under implementation.

References

- [1] - Dubois, D., Prade, H. Combination and propagation of uncertainty with belief functions - a reexamination. Proc. 9th Int. Joint of Conf. on Artificial Intelligence, Los Angeles, 1985, 111-113.
- [2] - Dubois, D., Prade, H. A set-theoretic view of belief functions. To appear in the Int. Journal of General Systems, 1986.
- [3] - Dubois, D., Prade, H. Properties of measures of information in evidence and possibility theories, submitted to Fuzzy Sets and Systems, 1986.
- [4] - Gordon, J., Shortliffe, E. A method for managing evidential reasoning in a hierarchical hypothesis space. Artificial Intelligence, 26, 323-357, 1985.

- [5] - Kim, J., Pearl, J. A computational model for combined causal and diagnostic reasoning in inference systems, Proc. 8th Int. Joint Conf. on Artificial Intelligence, Karlsruhe, FRG, 1983, 190-193.
- [6] - Shafer, G. A Mathematical Theory of Evidence, Princeton Univ. Press, 1976.
- [7] - Shafer, G. Belief functions and possibility measures, to appear in "The Analysis of Fuzzy Information" (J.C. Bezdek, Ed.), 1986, CRC Press.
- [8] - Zadeh, L.A. A theory of approximate reasoning, in : "Machine Intelligence", Vol. 9, Wiley, N.Y., 1979, 149-194.