

# Physical processes matters! Recommendations for sampling microplastics in estuarine waters based on hydrodynamics

Sophie Defontaine, Isabel Jalón-Rojas

### ▶ To cite this version:

Sophie Defontaine, Isabel Jalón-Rojas. Physical processes matters! Recommendations for sampling microplastics in estuarine waters based on hydrodynamics. Marine Pollution Bulletin, 2023, 191, pp.114932. 10.1016/j.marpolbul.2023.114932 . hal-04093809

## HAL Id: hal-04093809 https://hal.science/hal-04093809

Submitted on 10 May 2023

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

### <sup>1</sup> Graphical Abstract

- <sup>2</sup> Physical processes matters! Recommendations for sampling microplastics in estuarine
- <sup>3</sup> waters based on hydrodynamics
- ${\scriptstyle 4}$  Sophie Defontaine  $^{(1)}$  and Isabel Jalón-Rojas  $^{(1)}$



### ₅ Highlights

## 6 Physical processes matters! Recommendations for sampling microplastics in estuarine

- v waters based on hydrodynamics
- ${\scriptstyle 8}$  Sophie Defontaine  $^{(1)}$  and Isabel Jalón-Rojas  $^{(1)}$
- Strategies and methods for sampling microplastics in estuarine waters are reviewed
- The need of considering hydrodynamics when planning in-situ surveys are highlighted
- Recommendations on when, where and how sampling are discussed in relation to hydrodynamics
- Recommendations on when, where and how sampling are discussed in relation to hydrody namics

Physical processes matters! Recommendations for sampling
 microplastics in estuarine waters based on hydrodynamics

Sophie Defontaine <sup>(1)</sup> and Isabel Jalón-Rojas <sup>(1)</sup>

17 18

<sup>(1)</sup> Univ. Bordeaux, CNRS, Bordeaux INP, EPOC, UMR 5805, F-33600 Pessac, France

### 19 Abstract

Monitoring the abundance and characteristics of microplastics in estuarine waters is crucial for understanding the fate of microplastics at the land-sea continuum, and for developing policies and legislation to mitigate associated risks. However, if protocols to monitor microplastic pollution in ocean waters or beach sediments are well established, they may not be adequate for estuarine environments, due to the complex 3D hydrodynamics. In this note, we review and discuss sampling methods and strategies in relation to the main environmental forcing, estuarine hydrodynamics, and their spatio-temporal scales of variability. We propose recommendations about when, where and how to sample microplastics to capture the most representative picture of microplastic pollution. This note opens discussions on the urgent need for standardized methods and protocols to routinely monitor microplastics in estuaries which should, at the same time, be easily adaptable to the different systems to ensure consistency and comparability of data across different studies.

20 Keywords: Microplastics, estuary, sampling, monitoring, physical processes, hydrodynamics

#### <sup>21</sup> 1. Introduction

Estuaries form the connection between marine and fluvial waters. They are highly productive 22 ecosystems that provide important environmental, social and economic services (Barbier et al., 23 2011). Estuaries are, however, highly susceptible to both natural and human disturbances. Like 24 other aquatic systems around the world, estuaries are vulnerable to plastic pollution (Browne 25 et al., 2010). In particular, the abundance and risks associated with microplastic particles and 26 fibres (MPs), defined as plastics lower than 5 mm (Frias and Nash, 2019), are of high concern. 27 Their similar dimension to sediments and planktonic organisms make them easily ingestible by 28 the aquatic biota. The ingestion of MPs can be responsible for gut abrasion and blockage, as 29 well as intoxication by sorbed contaminants or toxic additives used in the compounding of plastics 30 (Andrady, 2011; Kazour et al., 2020). Living organisms may also develop on the MP surface in the 31 form of biofilms (Amaral-Zettler et al., 2020). MPs may thus act as dispersal vectors of pathogens 32 in moving estuarine waters (Forero-López et al., 2022). 33

Estuaries are critical areas for plastic pollution due to their interface nature between the ocean 34 and land. They are convergence areas of marine-based plastic pollution (Kuczenski et al., 2022), 35 land-based plastic pollution from rivers (Lebreton et al., 2017), and also intrinsic estuarine-based 36 plastic pollution from industries, cities, fishing, and port activities (Napper et al., 2022). In a 37 similar way that estuaries are sinks for sediments, they can represent a temporary or permanent 38 sink for MPs (Fok and Cheung, 2015; Nel et al., 2020; Simon-Sánchez et al., 2019). Estuarine 39 hydrodynamic processes can form convergence zones of MPs or Estuarine MP Maxima (EMPM) 40 within the estuary (Díez-Minguito et al., 2020; Bermúdez et al., 2021). Even after being trapped 41 during long periods of time, MPs can still be flushed from estuaries by extreme events at time scales 42 from annual to pluriannual (Tramoy et al., 2020). The high ecological values of estuaries together 43 with their double role as an ocean source and a sink have motivated numerous research questions 44 and attracted the recent attention of the interdisciplinary plastic research community (Gallagher 45 et al., 2016; Gray et al., 2018; Hitchcock and Mitrovic, 2019; Sadri and Thompson, 2014; Zhao 46 et al., 2014). 47

In situ observations of microplastic concentrations in the abiotic compartment is a key approach 48 to address emergent research questions on plastic pollution at the land-sea continuum, e.g.: (1) the 49 sources and generation of MPs; (2) the pathways by which MPs reach estuarine, coastal and ocean 50 waters; (3) the abundance, distribution and fate of MPs through the continuum ecosystems; (4) the 51 transport mechanisms driving spatio-temporal variations and promoting the flushing of MPs to the 52 ocean; (5) MPs ageing, weathering and biofouling; and (6) ecosystems exposition and risks, among 53 others. Numerous protocols have been developed to study MP contamination in ocean surface 54 waters or beaches (Besley et al., 2017; Hanke et al., 2013; Masura et al., 2015; Miller et al., 2017, 55 2021). However, these protocols or strategies may not be suitable to evaluate MP contamination in 56 estuaries and transitional waters. Most of these protocols are based on the assumption that MPs 57 are floating on the surface or have been deposited on the bed depending on their density. The 58 complex three-dimensional hydrodynamics in estuaries can make this assumption, and therefore 59 these protocols, inappropriate. Table 1 compares sampling strategies previously implemented in 60 the water matrix of different estuaries around the world, highlighting that most of them focused on 61 surface water. 62

<sup>63</sup> The specific hydrodynamics and properties of estuarine waters play a crucial role in the distri-

bution, transport and trapping of MPs (Malli et al., 2022; Jalón-Rojas et al.). Estuarine waters 64 are characterised by a changing density due to varying salinity and temperature that will largely 65 impact the buoyancy of MPs (Defontaine et al., 2020). Estuarine waters are also rich in sediment 66 and living organisms (blooms) that may favour MP flocculation. Andersen et al. (2021) suggested 67 that the estuarine residence times of some MPs are long enough for sediment adhesion and possibly 68 biofouling to occur. Flocculation and biofouling can modify the dynamical behaviour of particles 69 (Andersen et al., 2021; Jalón-Rojas et al., 2022) and even induce the sinking of initially buoyant 70 MPs (Kaiser et al., 2017; Laursen et al., 2022). The variety of forcing influencing estuarine hy-71 drodynamics at different time scales, such as wind, tide, river discharge, and waves, also largely 72 affects MP transport. However, only a few studies in the literature specify the tidal phase, current 73 velocities, or water properties (e.g. salinity, turbidity) at the time of sampling (e.g. Defontaine 74 et al. (2020); Gasperi and Cachot (2021), see Table 1). Compared to river or ocean transport, the 75 three-dimensional estuarine circulation greatly increases the complexity of the dynamical behaviour 76 of MPs and vertical transport plays a key role. Due to this complexity and the youth of this research 77 field, the contamination, distribution and fluxes of MPs in estuaries are largely unknown. 78

In this manuscript, we sustain that to keep gaining knowledge on MP pollution in estuaries, 79 monitoring protocols should be linked to estuarine hydrodynamics and their typical spatio-temporal 80 scales. We also identify the lack of consistent and standardised methods and protocols for these 81 systems (Table 1) as a limitation to inter-compare different systems and keep gaining understand-82 ing. The present work provides technical recommendations and suggestions for monitoring MPs 83 in estuarine waters, focusing on sampling strategies; i.e. digestion, density separation, extraction, 84 counting and chemical characterisation techniques being out of the scope of this note. Here, we 85 present some of the most used techniques with their advantages and disadvantages depending on 86 the type of estuary to be studied. In light of this, this note aims to answer the following questions 87 : (i) when to monitor MPs in estuaries, (ii) where to monitor MPs in estuaries, (iii) and how to 88 monitor MPs in estuaries. Good practices when sampling MPs are also discussed. 89

#### <sup>90</sup> 2. When to monitor MP in estuaries?

Two elements can affect the spatio-temporal variability of MPs in an estuary: flow patterns 91 and MP sources. The environmental forcing (e.g., tides, river discharge, wind, waves) affecting 92 the flow and the underlying physical processes driving the transport of suspended particulate mat-93 ter (e.g., density stratification, exchange flow, tidal mixing, stokes drift, tidal pumping; Fig. 1) 94 are well-known from decades of research in estuarine physics and sediment transport (Winterw-95 erp and Van Kesteren, 2004; Scully and Friedrichs, 2007; Jay, 2010; Geyer and MacCready, 2014; 96 Burchard et al., 2018). MP inputs from various sources (fluvial, marine and local) introduce ad-97 ditional temporal variability in MP abundance and distribution. This variability may depend on 98 the environmental forcing (e.g. river and surface runoff inputs), or on human activities schedule 99 (e.g. boat-based sources, sewage output). Advanced knowledge of the local hydrodynamics and the 100 potential sources is therefore required to determine when to collect MPs. 101

Various key time scales should be considered when planning samplings in estuaries, namely tidal, fortnightly and seasonal time scales. The particular importance of a given time scale is strongly related to the dominant forcing of the estuarine dynamics and is, therefore, site-specific (Jay, 2010; Jalón-Rojas et al., 2017). In estuaries dominated by tides, MP concentration can vary

significantly between ebb and flood tides (Oo et al., 2021). This difference can be related to various 106 processes such as tidal asymmetry (the flood or ebb dominance of currents). For example, in a 107 flood-dominated estuary, sinking MPs could have a higher rate of resuspension and mixing during 108 flood tides. Microplastic concentration may also vary over the tidal cycle in stratified and salt-wadge 109 estuaries where tidal motion is weaker. This can be due to variations in currents and salinity driven 110 by tidal variations in vertical mixing and the along-channel density gradient. Defontaine et al. 111 (2020) show that the transport of MPs in suspension may be contained by the pychocline due to 112 the turbulence damping induced by density stratification, whereas periods of intense mixing led to 113 homogeneous concentration along the water column. However, fewer studies sampled microplastics 114 at different tidal phases (Tab. 1). Given the importance of the tidal time scale, we recommend 115 sampling always at the same tidal phases to allow the inter-comparison of samples and, as far as 116 possible, sampling at different key tidal phases (e.g. flood, ebb, high water, low water). 117

Estuarine physical processes may change from spring to neap tides or from equatorial to tropical 118 tides (Defontaine et al., 2022; Valle-Levinson and Schettini, 2016). Microplastic concentration may 119 therefore vary at the fortnightly time scale (Stead et al., 2020), analogously to suspended sediment 120 concentrations (Jalón-Rojas et al., 2015). In addition, estuaries can be subject to the seasonal 121 variability of forcing (e.g. river flow, wind) that may impact the stratification, residual currents, 122 and therefore MP transport trends. In particular, the estuarine residual circulation (which includes 123 several processes such as density-driven circulation, wind-driven circulation, internal asymmetry, 124 non-linear tidal motion and the Stokes drift) can be subject to seasonal changes related to the 125 annual river flow cycle and the precipitation/evaporation balance (Jay, 2010). To take into account 126 all these variability time scales, it is highly recommended to monitor during full tidal cycles, under 127 contrasting tidal ranges and river flow conditions. 128

Other forcing and processes such as wind gusts, sea breeze, harbour seiches and waves may also play critical roles in MP dispersion at different time scales. Browne et al. (2010) show that a prevailing wind direction can be responsible for MP accumulation at downwind sites of the Tamar estuary. Sánchez-Hernández et al. (2021) also showed that MP abundance was higher during periods of strong winds. In addition, wind and waves may also trigger vertical mixing of plastic debris (Kukulka et al., 2012).

In summary, contrasting conditions of prevailing forcing (e.g. low/high river flow, spring/neap 135 tides, wind/unwind conditions, heavy swell/calm sea conditions) should be considered when plan-136 ning monitoring campaigns. Table 2 summarizes key recommendations about when sampling mi-137 croplastics depending on the main forcing and hydrodynamic processes of a given site. The post-138 processing of MP samples is expensive in terms of time and human resources, which can inevitably 139 affect the final choice of the monitoring periods. When all the representative time scales of vari-140 ability are not considered, results should be analysed keeping in mind that MP concentrations are 141 only representative of the selected conditions. 142

The discussion of MP concentrations at the different key time scales should also consider the variability of MP inputs from sources (Tab.2). Sources such as urban storm-water runoff or wastewater effluents may have a variable discharge depending on the weather forecast (rainfall) or the peak period of city occupation (e.g. tourism). Significant links between rainfall and MP concentration have been found in the literature as it drains the land-based MP pollution through rivers to estuaries (Lima et al., 2015; Hitchcock, 2020). The wet season could therefore represent a period of a strong abundance of MPs. However, the dry season may represent a period of denser population and thus an increase of MP inputs from surrounding cities and shores. Collection during the wet and dry seasons is therefore relevant to investigate potential seasonal differences in contamination. In addition, wastewater effluent contamination may also vary between weekends and weekdays, and between flood and ebb tides (e.g. WWTP discharge during ebb tide to favour flushing). Samplings only on weekdays should be envisaged (Miller et al., 2021).

#### 155 3. Where to monitor MP in estuaries?

As in many environmental pollution studies, the number of sampling sites and their location is of 156 the foremost importance to ensure a truly representative study by probabilistic sampling. However, 157 as explained above for the sampling frequency, the particularly expensive cost and time-consuming 158 laboratory analyses that follow MP collection may be a strong limitation. Compared to lakes, rivers 159 or the ocean, MP distribution in estuaries can strongly vary spatially in the three dimensions over 160 small spatial and temporal scales (Malli et al., 2022; Jalón-Rojas et al.). A compromise should be 161 found between spatial statistical coverage and time/financial costs. The site selection should then be 162 restricted to a few sites as representative of the whole estuary as possible. Table2 also summarizes 163 key recommendations on sampling locations depending on the major forcing and hydrodynamic 164 processes. 165

Intratidal and subtidal circulation may vary along the longitudinal and lateral axes as well as 166 water properties affecting the dispersion of suspended particles such as MPs (Lam et al., 2020). 167 Different locations along and across the estuarine channel should thus be considered (Tab.2). Even if 168 the choice of the locations should be based on the specific characteristics of the study site, a general 169 recommendation is to sample at different sites along the longitudinal density gradient, as physical 170 processes driving the transport of MPs and MP buoyancy vary over this gradient (Malli et al., 171 2022; Jalón-Rojas et al.) (Fig. 1). For instance, density-driven circulation is a physical process 172 directly related to the density gradient. In estuaries characterized by decreasing salinity from the 173 ocean toward the upper estuary, light MPs might be transported as wash load to the ocean by a 174 surface seaward flow, while dense MPs might be transported as bed load by a landward flow near 175 the bottom (Defontaine et al., 2020). Wind stress can also promote a two-layer circulation (Li and 176 Li, 2011). Recent studies based on numerical and idealized models have suggested that estuarine 177 circulation may form hotspots of microplastics, also called Estuarine MicroPlastic Maxima (EMPM) 178 (Díez-Minguito et al., 2020; Bermúdez et al., 2021). In estuaries or estuarine regions dominated 179 by tides, tidal pumping can also generate longitudinal circulation and MP trapping (Stead et al., 180 2020). In flood-dominated estuaries, the tidal wave may become increasingly asymmetric (higher 181 flood than ebb currents) along the estuarine channel depending on the competition between friction 182 and channel convergence. Non-buoyant MPs may be only resuspended and transported landward 183 during floods if the bed shear stress during ebbs does not exceed the critical shear stress. This 184 net landward transport of MPs may also form EMPM (Jalón-Rojas et al.). Readers can refer to 185 Burchard et al. (2018) for a whole explanation of estuarine trapping mechanisms. Longitudinal 186 gradients and hotspots of MPs can therefore be key estuarine features and should be considered 187 when planning monitoring campaigns. 188

The specific location of EMPMs may be difficult to predict as it may depend on the physical properties of the particles. In other words, different EMPM may happen for different types of

MPs (Jalón-Rojas et al.), but more research is needed to understand this phenomenon. In some 191 estuaries, EMPM might correspond to estuarine turbidity maximum (Díez-Minguito et al., 2020). 192 These potential zones of accumulation should be considered in the conception of field campaigns 193 and during the data analysis. In particular, when using filtering processes, the huge quantity of 194 sediments or living organisms contained in estuarine waters may lead to the clogging of filters or 195 nets (Hanke et al., 2013). If such areas should not be avoided during sampling, the choice of larger 196 mesh sizes for filtration may be an option. It must be noted that cleaning nets or sieves during 197 field campaigns is very challenging. 198

Estuary cross-sections are generally composed of a navigation channel and shoals, where the 199 hydrodynamics may largely vary and induce differential advection of suspended matter (McSweeney 200 et al., 2016). Banks with vegetation can be sinks of MPs (Carmen et al., 2021; Stead et al., 2020). A 201 particular phenomenon of great importance for the accumulation and transport of MPs is estuarine 202 fronts (Largier, 1993). Fronts are related to strong convergence currents at surface waters that 203 form visible lines of foam and debris, promoting lateral gradients of MP concentration (Wang et al., 204 2022). To adequately account for the lateral variation of contamination, sampling locations should 205 also be spread across the channel, at least two points to compare channel and shoals or the regions 206 inside and outside the front (Tab.2). It should be noted that trawling nets can be difficult to 207 operate in the front and can become rapidly clogged due to the high litter abundance (Green et al., 208 2018). On the other hand, locations with morphological specificity (e.g. sills) or with distinctive 209 hydrodynamic features (e.g. bends) should be avoided unless studied on purpose, as they may 210 introduce site-specific phenomena (Tab.2). 211

All the physical processes mentioned above are characterized by strong three-dimensional com-212 ponents. Vertical transport became particularly important in shallow waters. For instance, vertical 213 mixing is a key process in transferring suspended particulate matter from the bottom to the surface 214 and for keeping small particles in suspension (Shamskhany and Karimpour, 2022). Surface sam-215 pling is certainly not representative of MP contamination, underestimating MP fluxes by avoiding 216 suspended MPs inside the water column (Defontaine et al., 2020; Gasperi and Cachot, 2021). For 217 example, Defontaine et al. (2020) have shown that vertical density stratification affected MP abun-218 dance and size distribution through the water column of the Adour estuary: MP concentration and 219 size distribution was different (similar) in surface and bottom waters during stratification (well-220 mixed) periods. We recommend sampling three depths in the water column to compare surface, 221 mid-column and bottom contamination, especially in highly-stratified estuaries, or at least two 222 depths when time and human resources are limited (Tab.2). 223

Local sources (e.g., sewage networks, industrial outflows, rainwater networks or marinas) should 224 be also considered when planning sampling locations. Recent studies have shown that MP pollution 225 is largely correlated to the proximity to urban areas (Lebreton et al., 2017; Rodrigues et al., 2019; 226 Yonkos et al., 2014). Unless otherwise desired, the sampling locations should be placed away 227 from such local sources to be as representative of the whole estuary pollution as possible (Tab.2). 228 However, the analysis of pollution pathways is particularly important for management and policy 229 regulations, as well as for developing numerical studies. In this sense, it is particularly interesting 230 to sample MP source outflows to estimate discharged loads to the estuary (Bailey et al., 2021). 231

		1	)		
Study area	Sampling time	Mesh size	$\operatorname{Depth}$	Sampling volume	Reference
Trawling nets					
Adour Estuary, France	flood and ebb tides	300 μm - 5 mm	Surface, subsurface (1 m), Bottom (1 m)	Net : $45 \text{ to } 146 \text{ m}^3$ , Pump : 2.8 to $5.1 \text{ m}^3$	Defontaine et al. (2020)
Douro Estuary, Portugal	ebb tide	$30\mu\mathrm{m}$ - $500\mu\mathrm{m}$	Subsurface (1-2 m)	$235 \text{ m}^3$	Rodrigues et al. (2019)
Tamar Estuary, UK	flood and ebb tides	$300 \ \mu m - 5 \ mm$	Surface	$270\mathrm{m}^3$	Sadri and Thompson (2014)
Solent Estuary, UK	high tide	$300 \ \mu m$ - $5 \ mm$	Surface		Gallagher et al. (2016)
Ebro Estuary, Spain		$5\mu m$ - $5m m$	Surface		Simon-Sánchez et al. (2019)
Ría de Vigo, Spain	flood tide	$300 \ \mu m$ - $5 \ mm$	Surface	$60 \mathrm{m}^3$	Díez-Minguito et al. (2020)
Guadalquivir, Spain	flood and ebb tides	1  mm - 5  mm		ı	Bermúdez et al. (2021)
Chesapeake Bay, USA	ı	330 µm - 5 mm	Surface	$105-210{ m m}^3$	Yonkos et al. (2014), Bikker et al. (2020)
Delaware Bay, USA	low tide	200 $\mu \mathrm{m}$ - 5 mm	Surface	$259-292{ m m}^3$	Cohen et al. (2019)
Tampa Bay, USA		$300 \ \mu m - 5 \ mm \\ 1.2 \ \mu m - 5 \ mm$	Subsurface (1-2 m)	Net: $35 \text{ m}^3$ , bottle : 1 L	McEachern et al. (2019)
Clyde, Bega and Hunter Estuaries, Australia	ebb tide	$45\mu\mathrm{m}$ - $5\mathrm{mm}$	Surface	1	Hitchcock and Mitrovic (2019)
			Surface,		
Seine Estuary, France	ebb and flood tides	$300 \mu \mathrm{m} - 5 \mathrm{mm}$	Subsurface (50 cm), Bottom	ı	Gasperi and Cachot (2021)
Chao Phraya Estuary, Thailand	flood and ebb tides	$335 \ \mu m - 5 \ mm$	Surface	$\sim 60  { m m}^3$	Oo et al. $(2021)$
Raritan Hudson Estuary, USA		$250 \ \mu m$ - $5 \ mm$	Surface	$\sim 40m3/s$	Bailey et al. (2021)
Pearl Estuary, China		333 $\mu {\rm m}$ - 5 mm	Surface	$\sim 80m3/s$	Lam et al. (2020)
Pumping systems					
Yangtze Estuary, China		$32 \mu\mathrm{m}$ - $5 \mathrm{mm}$	Subsurface (1 m)		Zhao et al. (2014)
Changjiang Estuary, China	,	$70 \mu m$ - $5 mm$	Subsurface (50 cm)	100  L	Xu et al. (2018)
Minjiang Estuary, China	ebb tide	333 $\mu \mathrm{m}$ - 5 mm	Subsurface (30 cm)	20 L	Zhao et al. $(2015)$
Terengganu Estuary, Malaysia		$20\mu\mathrm{m}$ - $5\mathrm{mm}$	Subsurface (1-2 m)	1200 L	Taha et al. (2021)
Grab sampling					
Pearl Estuary, China		$50 \mu \mathrm{m}$ - $5 \mathrm{mm}$	Surface	5 L	Yan et al. $(2019)$
Tecolutla Estuary, Mexico		$1.2\mu\mathrm{m}$ - $5\mathrm{mm}$	Subsurface (30 cm)	5 L	Sánchez-Hernández et al. (2021)
Klang Estuary, Malaysia		$300 \mu\mathrm{m}$ - $5 \mathrm{mm}$	Surface	1 L	Zaki et al. (2021)
Juilong Estuary, China	ebb and flood	$45\mu\mathrm{m}$ - $5\mathrm{mm}$	Surface	105 L	Wu et al. (2022)
Others					
Winyah Bay, USA	1	$63 \ \mu m$ - $2 \ mm$	Surface	4 L	Gray et al. (2018)
Itchen Estuary, UK	ebb and flood	$0.45 \ \mu m$ - $5 \ mm$	Surface	NA	Stead et al. (2020)

world und the est gies in differ 1.1 ÷ -5 Table 1: Com

Estuarine characteristics	Hydrodynamic processes	When	Where
Tides	tidal pumping, tidal straining, tidal mixing, Stokes drift	ebb/flood/slacks (semi-diurne, diurne), neap/spring	along the tidal intrusion, surface/mid depth/bottom
Stratification	two-layer flow, gravitational circulation, stratification-induced turbulence damping	ebb/flood, spring/neap, wet/dry season	along the salinity intrusion, surface/mid depth/bottom
River	tide-river interaction, convergence area	wet/dry season	fluvial area, convergence areas, surface/mid depth/bottom
Fronts	shear fronts, tidal intrusion fronts	ebb and/or flood	$\begin{array}{l} {\rm inside/outside\ front,}\\ {\rm surface} \end{array}$
Wind	wind mixing, wind driven-circulation	wind/unwind conditions	banks in the downwind direction, surface/subsurface
Waves	wave mixing, resuspension	swell/calm conditions	mouth of the estuary, banks at the entrance, surface/subsurface/bottom
Morphology	lateral circulation, differential advection	ebb/flood	thalweg/shoals, away from sills, bends
MP sources	-	ebb/flood, weekdays/weekends, tourist season wet/dry season	MP sources (WWTPs, sewage outflows, mouth/head of the estuary, industrial outflows), away from the sources

Table 2: Recommendations about when and where to sample MP depending on the main characteristics and hydrodynamic processes of an estuarine system

#### 232 4. How to monitor MP in estuaries?

The choice of the sampling method is not trivial when sampling MPs as it generally defines the 233 lower MP size within the sample. If a consensus has been reached regarding the larger size limit 234 of MPs to be 5 mm, it is not the case with the lower size limit. Some studies have defined a lower 235 size limit of 1  $\mu m$ , and plastic particles being smaller as nanoplastics (Thompson et al., 2009; Frias 236 and Nash, 2019). However, the smaller size limit is defined operationally by the size of the finer 237 mesh, sieve or filter pore used during sampling. Table 1 compares sampling methods employed in 238 previous studies. These methods are diverse and imply different lowest-size limits. For example 239 trawling nets classically only capture MPs greater than 300  $\mu m$  (lowest mesh size), while the lowest 240 size of MP collected with a pumping system or bottle sampling depends on the sieve size or filter 241 pore, which can go down to 1  $\mu m$ . Sampling techniques may be responsible for some sorting in 242 MP collection. In particular, fibres are complex to collect due to the thin and elongated shape that 243 allows them to pass through nets and sieves. Therefore, the different available sampling methods 244 should be carefully evaluated during the study design. The two crucial characteristics to consider 245 are the volume of analysed water and the finest mesh size, sieve or filter pore used. The possibility of 246 sampling at different depths to capture the intrinsic vertical variability of estuaries, and during short 247 periods to capture tidal variability, can also be important criteria to select a sampling method in 248 estuaries. In this section, the advantages and disadvantages of the most commonly used techniques 249

<sup>250</sup> are presented.

**Trawling nets.** As classical protocols for sampling MPs were based on the hypothesis that 251 most MPs are floating at surface waters, the most commonly used techniques are trawling nets such 252 as plankton, neuston or manta nets (Gallagher et al., 2016; McEachern et al., 2019; Simon-Sánchez 253 et al., 2019; Yonkos et al., 2014). Such nets are generally equipped with a rectangular opening and 254 two floats to sample large volume in surface waters. On the other hand, bongo nets may be equipped 255 with round openings and depressor weights to allow collection inside the water column. However, 256 the sampling depth is hard to target precisely with a depressor weight. The volume of filtered 257 water is estimated thanks to a flowmeter that is fixed on the opening frame (Hanke et al., 2013; 258 Prata et al., 2019). Large volumes of water can be easily sampled ensuring solid statistical data 259 and reducing the impact of background contamination. Paired bongo nets present the advantage to 260 allow sampling duplicates. Trawling net seems to be the most common technique used in estuaries 261 (Tab. 1), which permits comparison between sites. 262

The mesh size of the net is one of the most restrictive elements of trawling nets. A standard mesh 263 of 300  $\mu m$  is generally mounted on such systems that impede finer MPs to be collected, leading to 264 an underestimation of the contamination (Green et al., 2018; Lindeque et al., 2020). However, some 265 suppliers offer finer mesh sizes that may be considered. In the Seine River, a comparison between 266 a plankton net equipped with an 80  $\mu m$  mesh and a manta net equipped with a classical 330  $\mu m$ 267 mesh revealed that concentration may be largely underestimated (several orders of magnitude) with 268 the larger mesh size (330  $\mu m$ ), even though a greater diversity of shape and types may be captured 269 (Dris et al., 2015). Nevertheless, trawling nets with fine meshes are more susceptible to clogging, 270 leading to a reduced volume of filtered water and to the collection of MPs finer than the mesh size 271 (Dris et al., 2018). To avoid such drawbacks, it is recommended to deploy fine mesh trawling in 272 relatively clear waters, which is not usual in (turbid) estuaries. 273

Trawling nets are towed at the rear of the vessel and have the benefit to be easy to deploy in 274 coastal areas. However, they may be not appropriate for narrow channels or very busy shipping 275 lanes. Such techniques may even be forbidden in some parts of the estuary to not disturb harbour 276 activities and navigation. It is highly recommended to contact local authorities before deploying 277 such equipment in estuaries. The European Commission recommends deploying trawling net out of 278 the wake zone due to turbulence leading to unrepresentative sampling (Hanke et al., 2013). Michida 279 et al. (2019) study recommends conducting trawling surveys in conditions where wave heights are 280 under 0.5 meters as trawling nets can be relatively difficult to manipulate in rougher conditions. 281

**Pumping system.** Pumping systems generally consist in a high-capacity pump that pours 282 waters through a set of sieves (Defontaine et al., 2020; Xu et al., 2018; Zhao et al., 2015). In some 283 cases, water samples are collected in jars to be filtered at the laboratory. This method presents 284 different advantages. First, it allows us to precisely choose the finest MP size to be collected (e.g. 285 70  $\mu m$ , 50  $\mu m$  or 5  $\mu m$ ) as a function of the finest mesh size or filter pore. Second, this system 286 can easily collect MPs at different depths in the water column. A pressure sensor and a depressor 287 weight need to be fixed to the pump inlet to ensure a vertical fall and precisely estimate the depth 288 of measurement. Third, this method is relatively easy to set up on the field and duplicates can 289 readily be collected with a second pumping system working in parallel. 290

Nevertheless, the use of such technologies may introduce some contamination by the plastic components of the pumping system and can trigger the fragmentation of MPs due to shear stress during

pumping (Enfrin et al., 2020; Skalska et al., 2020). Another major drawback is that, depending on the pump capacity, the operation may take hours to collect some cubic meters of water (Defontaine et al., 2020). During such a long operation, the estuarine hydrodynamics may have changed and may not be representative of specific conditions. A compromise has to be found between a large volume of water to gain statistically reliable data and a short operating time representative of one hydrodynamic state.

Bottle sampling. Grab sampling is a commonly used technique to estimate suspended sed-299 iment concentration. It holds some advantages. For instance, it is simple to operate and allows 300 us to collect all types of MPs, including those difficult to capture with other techniques such as 301 fibres. Several studies have shown that fibres are more efficiently collected with bottle sampling 302 than with nets (Rebelein et al., 2021). The subsequent filtration at the laboratory with fine pore 303 filters can capture small MPs (down to  $1 \,\mu m$ ). Contamination is also lower compared to nylon net 304 and pumping system (Prata et al., 2019). Nevertheless, laboratory analyses are longer than with 305 other methods as no pre-sieving is realised in the field. The major drawback of this method is 306 the very small volume of water that is analysed, which leads to the need for replicates and thus 307 additional laboratory costs. Dubaish and Liebezeit (2013) have shown that replicates from bottle 308 samples displayed larger heterogeneity, especially for films and fragments. Although fragments and 309 films may be underestimated by grab sampling, the concentrations of fibres may yield between 3 and 310 4 orders of magnitude greater than those estimated by common zooplankton net methods (Green 311 et al., 2018). Therefore, bulk sampling may be envisaged to study fibres, but it is less recommended 312 when all types of MPs are investigated. 313

Automatic samplers, continuous plankton recorder and continuous-flow centrifuges. 314 Recently, new technologies have been developed to investigate microplastic pollution in a more 315 automatic way. Automatic rosette water samplers or even ROV have been used for MP sampling 316 in ocean waters (La Daana et al., 2018; Dai et al., 2018; Choy et al., 2019). However, such massive 317 equipment required a lift arm and is not adapted for shallow estuarine waters. Continuous flow 318 centrifuges are able to separate particles denser than ambient waters from less dense particles and, 319 when coupled with a filtration system, may be used for sampling MPs (Hildebrandt et al., 2019). 320 However, it lasts several hours to process 100 L of water, so it may not be adapted to estuarine 321 dynamics time scales. In-situ filtration devices consisting of a high-capacity pump associated with 322 a filtration device (e.g. in-line steel filters, mesh bag) have shown promising results in sampling 323 MPs (Li et al., 2020; Liu et al., 2019; Karlsson et al., 2020; Harrold et al., 2022). They can be 324 equipped with a flowmeter and pressure sensor. However, such systems do not sample the surface 325 microlayer, where light MPs may accumulate, to keep the pump inlet underwater during sampling 326 (Karlsson et al., 2020). To our knowledge, there are no field studies in the literature using such 327 new technologies in estuarine waters. However, it could be interesting to compare them with the 328 most commonly used methods. 329



Figure 1: Key processes in regards to microplastic sampling strategies in estuaries

#### 330 5. Best practice

When sampling microplastics, some good practices need to be applied to avoid sample contami-331 nation. It is important to ensure that samples are not affected by background contamination in the 332 field or laboratory. Laboratory utensils should be made of glass or metal as far as possible, e.g. MPs 333 should be stored in glass jars and petri-slides, and metallic sieves are preferred. They should be 334 properly rinsed with pure water and covered with aluminium foil to avoid airborne contamination 335 prior to any contact with the sample (Green et al., 2018). Synthetic clothing should be avoided 336 when researchers recover and manipulate samples; cotton clothes should be favoured (Hanke et al., 337 2013). 338

When using trawling nets, they should be carefully rinsed between tows to reduce background 339 contamination. Nets should be rinsed from the outside of the net and never through the net 340 opening (Hanke et al., 2013). In order to investigate the potential background contamination, 341 blank analyses should be carried out. It is recommended that laboratory analyses are carried out 342 by a unique analyst to limit the analyst bias in the results (Green et al., 2018). During recovering 343 and manipulation of samples on the field, the materials should be placed upwind to avoid additional 344 contamination by the analyst. Trawling nets should be positioned by the side of the ship instead 345 of at the rear when possible to avoid MP contamination from the ship and vertical mixing by wake 346 and bow waves. 347

Replicates are standard practice to measure variability in sample collection and analysis. When small volumes of water are considered during sampling (e.g. grab sampling), replicate samples may be necessary to avoid heterogeneity in samples. Miller et al. (2021) recommend duplicating every ten samples or more if the study focuses on microfibers. Another good but uncommon practice is to collect a wide range of physical parameters simultaneously to MP samples. MP abundance and distribution alone are very difficult to interpret and compare which may lead to biased conclusions. We highly recommend collecting additional data such as water levels, current intensity, water properties (e.g. salinity, turbidity, organic content) and weather forecast (e.g. rainfall, wind, waves).

#### 357 6. Research priorities

Measuring the abundance and distribution of MPs in estuaries and identifying their sources is the 358 primary step in gaining understanding of their dynamics and fate, evaluating environmental risks, 359 and establishing future mitigation measures and management strategies. Nevertheless, as discussed 360 in this work, sampling MPs in estuarine waters is not trivial. No established protocols have been 361 developed so far to harmonise sampling methods in the water compartment. Given that different 362 sampling methods and strategies can lead to concentration differences by orders of magnitude 363 (Green et al., 2018), there is a critical need to establish standardized sampling protocols that ensure 364 consistency and the inter-comparison of systems. However, it is also important for the protocols 365 to be flexible, as estuaries are complex environments with a wide range of physical, chemical, and 366 biological characteristics. Protocols should therefore take into account all the particularities of 367 a specific estuarine environment (complex 3D hydrodynamics, ETM, variety of MP sources ..). 368 Nevertheless, some elements may be harmonized such as the lower size limit of the collected MPs 369 (e.g. mesh size, filter pores) and the minimum volume of sampled water. Although an optimal 370 technique is highly dependent of the study site and the specific objectives, manual or automated 371 high-capacity pumping system associated with any kind of filtering system presents a large number 372 of advantages: easily available for deployment at different depths in complex areas (e.g. navigation, 373 shoals with vegetation), collection of large volumes of water (statistically reliable data) in relative 374 short period of time (representative of one hydrodynamic state). The monitoring protocol should 375 cover the main time scales of variability (tidal cycles, spring/neap tidal cycles, contrasting conditions 376 of river flow or wind) and the estuarine regions characterised by different hydrodynamic regimes. 377 While these time scales and representative sampling locations strongly depend on the dominant 378 forcing and may vary among systems, the hydro-meteorological conditions under which MPs have 379 been collected should be clearly stated in the papers (tidal phase, current velocity, wind, waves, 380 salinity etc...). Even if this study focuses on microplastic pollution, similar considerations should 381 be taken into account for sampling other kinds of pollutants in estuarine environments. 382

<sup>383</sup> Unlike classical sediment concentration analyses, MP concentration analyses have substantial <sup>384</sup> financial and time costs that may not be neglected in the field campaign design. A relevant per-<sup>385</sup> spective is to test new methods of automatic sampling of MPs, reducing financial and time costs <sup>386</sup> during laboratory analyses and field sampling.

#### 387 Acknowledgments

This work was supported by the French National Agency for Research in the context of PLAS-TINEST project (grant N°ANR-22-CE01-0011-01).

#### 390 References

- Amaral-Zettler, L.A., Zettler, E.R., Mincer, T.J., 2020. Ecology of the plastisphere. Nature Reviews
   Microbiology 18, 139–151.
- 393 Andersen, T.J., Rominikan, S., Olsen, I.S., Skinnebach, K.H., Fruergaard, M., 2021. Flocculation of
- PVC microplastic and fine-grained cohesive sediment at environmentally realistic concentrations.
   The Biological Bulletin 240, 42–51.
- Andrady, A.L., 2011. Microplastics in the marine environment. Marine pollution bulletin 62,
   1596–1605.
- Bailey, K., Sipps, K., Saba, G.K., Arbuckle-Keil, G., Chant, R.J., Fahrenfeld, N., 2021. Quantification and composition of microplastics in the raritan hudson estuary: comparison to pathways
  of entry and implications for fate. Chemosphere 272, 129886.
- Barbier, E.B., Hacker, S.D., Kennedy, C., Koch, E.W., Stier, A.C., Silliman, B.R., 2011. The value
  of estuarine and coastal ecosystem services. Ecological monographs 81, 169–193.
- Bermúdez, M., Vilas, C., Quintana, R., González-Fernández, D., Cózar, A., Díez-Minguito, M.,
  2021. Unravelling spatio-temporal patterns of suspended microplastic concentration in the natura
  2000 guadalquivir estuary (sw spain): Observations and model simulations. Marine Pollution
  Bulletin 170, 112622.
- Besley, A., Vijver, M.G., Behrens, P., Bosker, T., 2017. A standardized method for sampling and
  extraction methods for quantifying microplastics in beach sand. Marine Pollution Bulletin 114,
  77–83.
- Bikker, J., Lawson, J., Wilson, S., Rochman, C., 2020. Microplastics and other anthropogenic
  particles in the surface waters of the Chesapeake Bay. Marine Pollution Bulletin 156, 111257.
- Browne, M.A., Galloway, T.S., Thompson, R.C., 2010. Spatial patterns of plastic debris along
  estuarine shorelines. Environmental science & technology 44, 3404–3409.
- Burchard, H., Schuttelaars, H.M., Ralston, D.K., 2018. Sediment trapping in estuaries. Annual
  review of marine science 10, 371–395.
- Carmen, B., Krång, A.S., Infantes, E., 2021. Microplastic retention by marine vegetated canopies:
   simulations with seagrass meadows in a hydraulic flume. Environmental Pollution 269, 116050.
- Choy, C.A., Robison, B.H., Gagne, T.O., Erwin, B., Firl, E., Halden, R.U., Hamilton, J.A., Katija,
  K., Lisin, S.E., Rolsky, C., et al., 2019. The vertical distribution and biological transport of
  marine microplastics across the epipelagic and mesopelagic water column. Scientific reports 9,
  1–9.
- Cohen, J.H., Internicola, A.M., Mason, R.A., Kukulka, T., 2019. Observations and simulations of
  microplastic debris in a tide, wind, and freshwater-driven estuarine environment: the Delaware
  Bay. Environmental Science & Technology 53, 14204–14211.

<sup>425</sup> Dai, Z., Zhang, H., Zhou, Q., Tian, Y., Chen, T., Tu, C., Fu, C., Luo, Y., 2018. Occurrence of mi-<sup>426</sup> croplastics in the water column and sediment in an inland sea affected by intensive anthropogenic

- Defontaine, S., Sous, D., Tesan, J., Monperrus, M., Lenoble, V., Lanceleur, L., 2020. Microplastics
  in a salt-wedge estuary: Vertical structure and tidal dynamics. Marine Pollution Bulletin 160, 111688.
- <sup>431</sup> Defontaine, S., Walther, R., Sous, D., 2022. Variability of subtidal flow in a narrow meandering
  <sup>432</sup> stratified estuary. Estuarine, Coastal and Shelf Science 266, 107716.
- <sup>433</sup> Díez-Minguito, M., Bermúdez, M., Gago, J., Carretero, O., Viñas, L., 2020. Observations and
  <sup>434</sup> idealized modelling of microplastic transport in estuaries: the exemplary case of an upwelling
  <sup>435</sup> system (ría de vigo, nw spain). Marine Chemistry 222, 103780.
- Dris, R., Gasperi, J., Rocher, V., Saad, M., Renault, N., Tassin, B., 2015. Microplastic contamination in an urban area: a case study in greater paris. Environmental Chemistry 12, 592–599.
- Dris, R., Gasperi, J., Rocher, V., Tassin, B., 2018. Synthetic and non-synthetic anthropogenic
  fibers in a river under the impact of paris megacity: Sampling methodological aspects and flux
  estimations. Science of the Total Environment 618, 157–164.
- Dubaish, F., Liebezeit, G., 2013. Suspended microplastics and black carbon particles in the jade
  system, southern north sea. Water, air, & soil pollution 224, 1–8.
- Enfrin, M., Lee, J., Gibert, Y., Basheer, F., Kong, L., Dumée, L.F., 2020. Release of hazardous
  nanoplastic contaminants due to microplastics fragmentation under shear stress forces. Journal
  of hazardous materials 384, 121393.
- Fok, L., Cheung, P.K., 2015. Hong kong at the pearl river estuary: A hotspot of microplastic
  pollution. Marine pollution bulletin 99, 112–118.
- Forero-López, A., Brugnoni, L., Abasto, B., Rimondino, G., Lassalle, V., Ardusso, M., Nazzarro,
  M., Martinez, A., Spetter, C., Biancalana, F., et al., 2022. Plastisphere on microplastics: In situ
  assays in an estuarine environment. Journal of Hazardous Materials 440, 129737.
- Frias, J., Nash, R., 2019. Microplastics: finding a consensus on the definition. Marine pollution
  bulletin 138, 145–147.
- Gallagher, A., Rees, A., Rowe, R., Stevens, J., Wright, P., 2016. Microplastics in the solent estuarine
  complex, uk: an initial assessment. Marine Pollution Bulletin 102, 243–249.
- Gasperi, J., Cachot, J., 2021. Projet Plastic-Seine: Flux et impacts des microplastiques dans
  l'estuaire de la Seine. Technical Report. Programme Seine-Aval 6.
- Geyer, W.R., MacCready, P., 2014. The estuarine circulation. Annual review of fluid mechanics
  46, 175–197.
- 459 Gray, A.D., Wertz, H., Leads, R.R., Weinstein, J.E., 2018. Microplastic in two south carolina
- estuaries: Occurrence, distribution, and composition. Marine pollution bulletin 128, 223–233.

activities. Environmental pollution 242, 1557–1565.

- Green, D.S., Kregting, L., Boots, B., Blockley, D.J., Brickle, P., Da Costa, M., Crowley, Q., 2018. A
  comparison of sampling methods for seawater microplastics and a first report of the microplastic
  litter in coastal waters of ascension and falkland islands. Marine pollution bulletin 137, 695–701.
- Hanke, G., Galgani, F., Werner, S., Oosterbaan, L., Nilsson, P., Fleet, D., Kinsey, S., Thompson,
  R., Palatinus, A., Van Franeker, J., et al., 2013. Guidance on monitoring of marine litter in
  european seas: a guidance document within the common implementation strategy for the marine
  strategy framework directive. .
- Harrold, Z., Arienzo, M.M., Collins, M., Davidson, J.M., Bai, X., Sukumaran, S., Umek, J., 2022.
  A peristaltic pump and filter-based method for aqueous microplastic sampling and analysis. ACS
  ES&T Water 2, 268–277.
- Hildebrandt, L., Voigt, N., Zimmermann, T., Reese, A., Proefrock, D., 2019. Evaluation of continuous flow centrifugation as an alternative technique to sample microplastic from water bodies.
  Marine environmental research 151, 104768.
- 474 Hitchcock, J.N., 2020. Storm events as key moments of microplastic contamination in aquatic
  475 ecosystems. Science of the Total Environment 734, 139436.
- Hitchcock, J.N., Mitrovic, S.M., 2019. Microplastic pollution in estuaries across a gradient of human
  impact. Environmental Pollution 247, 457–466.
- Jalón-Rojas, I., Defontaine, S., Díez-Minguito, M., Bermúdez, M., . Transport of microplastic
  debris in estuaries, in: Treatise on estuarine and coastal science.
- Jalón-Rojas, I., Romero-Ramírez, A., Fauquembergue, K., Rossignol, L., Cachot, J., Sous, D.,
  Morin, B., 2022. Effects of biofilms and particle physical properties on the rising and settling
  velocities of microplastic fibers and sheets. Environmental Science & Technology .
- Jalón-Rojas, I., Schmidt, S., Sottolichio, A., 2015. Turbidity in the fluvial Gironde Estuary (southwest France) based on 10-year continuous monitoring: sensitivity to hydrological conditions.
  Hydrology and Earth System Sciences 19, 2805–2819.
- Jalón-Rojas, I., Schmidt, S., Sottolichio, A., 2017. Comparison of environmental forcings affecting
  suspended sediments variability in two macrotidal, highly-turbid estuaries. Estuarine, Coastal
  and Shelf Science 198, 529–541.
- Jay, D.A., 2010. Estuarine variability. Cambridge University Press. p. 62–99.
   doi:10.1017/CBO9780511676567.005.
- Kaiser, D., Kowalski, N., Waniek, J.J., 2017. Effects of biofouling on the sinking behavior of
   microplastics. Environmental research letters 12, 124003.
- Karlsson, T.M., Kärrman, A., Rotander, A., Hassellöv, M., 2020. Comparison between manta
  trawl and in situ pump filtration methods, and guidance for visual identification of microplastics
  in surface waters. Environmental science and pollution research 27, 5559–5571.

496 Kazour, M., Jemaa, S., El Rakwe, M., Duflos, G., Hermabassiere, L., Dehaut, A., Le Bihanic, F.,

<sup>497</sup> Cachot, J., Cornille, V., Rabhi, K., et al., 2020. Juvenile fish caging as a tool for assessing mi-

croplastics contamination in estuarine fish nursery grounds. Environmental Science and Pollution

- Kuczenski, B., Vargas Poulsen, C., Gilman, E.L., Musyl, M., Geyer, R., Wilson, J., 2022. Plastic
   gear loss estimates from remote observation of industrial fishing activity. Fish and Fisheries 23,
   22–33.
- Kukulka, T., Proskurowski, G., Morét-Ferguson, S., Meyer, D.W., Law, K.L., 2012. The effect of
  wind mixing on the vertical distribution of buoyant plastic debris. Geophysical Research Letters
  39.
- La Daana, K.K., Gårdfeldt, K., Lyashevska, O., Hassellöv, M., Thompson, R.C., O'Connor, I.,
  2018. Microplastics in sub-surface waters of the arctic central basin. Marine pollution bulletin
  130, 8–18.
- Lam, T.W.L., Fok, L., Lin, L., Xie, Q., Li, H.X., Xu, X.R., Yeung, L.C., 2020. Spatial variation of
  floatable plastic debris and microplastics in the pearl river estuary, south china. Marine Pollution
  Bulletin 158, 111383.
- Largier, J.L., 1993. Estuarine fronts: how important are they? Estuaries 16, 1–11.
- Laursen, S., Fruergaard, M., Andersen, T., 2022. Rapid flocculation and settling of positively
  buoyant microplastic and fine-grained sediment in natural seawater. Marine Pollution Bulletin
  178, 113619.
- Lebreton, L., Van Der Zwet, J., Damsteeg, J.W., Slat, B., Andrady, A., Reisser, J., 2017. River
  plastic emissions to the world's oceans. Nature communications 8, 1–10.
- Li, D., Liu, K., Li, C., Peng, G., Andrady, A.L., Wu, T., Zhang, Z., Wang, X., Song, Z., Zong, C.,
  et al., 2020. Profiling the vertical transport of microplastics in the West Pacific Ocean and the
  East Indian Ocean with a novel in situ filtration technique. Environmental Science & Technology
  54, 12979–12988.
- Li, Y., Li, M., 2011. Effects of winds on stratification and circulation in a partially mixed estuary.
   Journal of Geophysical Research: Oceans 116.
- Lima, A., Barletta, M., Costa, M., 2015. Seasonal distribution and interactions between plankton
   and microplastics in a tropical estuary. Estuarine, Coastal and Shelf Science 165, 213–225.
- Lindeque, P.K., Cole, M., Coppock, R.L., Lewis, C.N., Miller, R.Z., Watts, A.J., Wilson-McNeal,
- A., Wright, S.L., Galloway, T.S., 2020. Are we underestimating microplastic abundance in the marine environment? a comparison of microplastic capture with nets of different mesh-size.
- Environmental Pollution 265, 114721.
- Liu, K., Zhang, F., Song, Z., Zong, C., Wei, N., Li, D., 2019. A novel method enabling the accurate quantification of microplastics in the water column of deep ocean. Marine Pollution Bulletin 146,

532 462–465.

<sup>499</sup> Research 27, 3548–3559.

Malli, A., Corella-Puertas, E., Hajjar, C., Boulay, A.M., 2022. Transport mechanisms and fate of microplastics in estuarine compartments: A review. Marine Pollution Bulletin 177, 113553.

Masura, J., Baker, J., Foster, G., Arthur, C., 2015. Laboratory methods for the analysis of microplastics in the marine environment: Recommendations for quantifying synthetic particles in waters and sediments.

- McEachern, K., Alegria, H., Kalagher, A.L., Hansen, C., Morrison, S., Hastings, D., 2019. Microplastics in tampa bay, florida: abundance and variability in estuarine waters and sediments.
  Marine pollution bulletin 148, 97–106.
- McSweeney, J.M., Chant, R.J., Sommerfield, C.K., 2016. Lateral variability of sediment transport in the d elaware e stuary. Journal of Geophysical Research: Oceans 121, 725–744.
- Michida, Y., Chavanich, S., Chiba, S., Cordova, M.R., Cozsar Cabanas, A., Glagani, F., Hagmann,
  P., Hinata, H., Isobe, A., Kershaw, P., et al., 2019. Guidelines for harmonizing ocean surface
  microplastic monitoring methods. version 1.1.
- Miller, E., Sedlak, M., Lin, D., Box, C., Holleman, C., Rochman, C.M., Sutton, R., 2021. Recommended best practices for collecting, analyzing, and reporting microplastics in environmental
  media: Lessons learned from comprehensive monitoring of san francisco bay. Journal of hazardous
  materials 409, 124770.
- Miller, M.E., Kroon, F.J., Motti, C.A., 2017. Recovering microplastics from marine samples: a review of current practices. Marine Pollution Bulletin 123, 6–18.
- Napper, I.E., Wright, L.S., Barrett, A.C., Parker-Jurd, F.N., Thompson, R.C., 2022. Potential microplastic release from the maritime industry: Abrasion of rope. Science of the Total Environment
  804, 150155.
- Nel, H.A., Smith, G.H.S., Harmer, R., Sykes, R., Schneidewind, U., Lynch, I., Krause, S., 2020.
  Citizen science reveals microplastic hotspots within tidal estuaries and the remote scilly islands,
  united kingdom. Marine Pollution Bulletin 161, 111776.
- Oo, P.Z., Boontanon, S.K., Boontanon, N., Tanaka, S., Fujii, S., 2021. Horizontal variation of
   microplastics with tidal fluctuation in the chao phraya river estuary, thailand. Marine Pollution
   Bulletin 173, 112933.
- Prata, J.C., da Costa, J.P., Duarte, A.C., Rocha-Santos, T., 2019. Methods for sampling and
  detection of microplastics in water and sediment: a critical review. TrAC Trends in Analytical
  Chemistry 110, 150–159.
- Rebelein, A., Int-Veen, I., Kammann, U., Scharsack, J.P., 2021. Microplastic
  fibers—underestimated threat to aquatic organisms? Science of The Total Environment 777,
  146045.
- Rodrigues, S., Almeida, C.M.R., Silva, D., Cunha, J., Antunes, C., Freitas, V., Ramos, S., 2019.
  Microplastic contamination in an urban estuary: abundance and distribution of microplastics
  and fish larvae in the Douro estuary. Science of the Total Environment 659, 1071–1081.

Sadri, S.S., Thompson, R.C., 2014. On the quantity and composition of floating plastic debris
entering and leaving the tamar estuary, southwest england. Marine pollution bulletin 81, 55–60.

Sánchez-Hernández, L.J., Ramírez-Romero, P., Rodríguez-González, F., Ramos-Sánchez, V.H.,
Montes, R.A.M., Rubio, H.R.P., Sujitha, S., Jonathan, M., 2021. Seasonal evidences of microplastics in environmental matrices of a tourist dominated urban estuary in gulf of mexico,
mexico. Chemosphere 277, 130261.

- Scully, M.E., Friedrichs, C.T., 2007. Sediment pumping by tidal asymmetry in a partially mixed
  estuary. Journal of Geophysical Research: Oceans 112.
- Shamskhany, A., Karimpour, S., 2022. Entrainment and vertical mixing of aquatic microplastics
  in turbulent flow: The coupled role of particle size and density. Marine Pollution Bulletin 184, 114160.
- Simon-Sánchez, L., Grelaud, M., Garcia-Orellana, J., Ziveri, P., 2019. River deltas as hotspots of
   microplastic accumulation: The case study of the ebro river (nw mediterranean). Science of the
   total environment 687, 1186–1196.
- Skalska, K., Ockelford, A., Ebdon, J.E., Cundy, A.B., 2020. Riverine microplastics: Behaviour,
   spatio-temporal variability, and recommendations for standardised sampling and monitoring.
   Journal of Water Process Engineering 38, 101600.
- Stead, J.L., Cundy, A.B., Hudson, M.D., Thompson, C.E., Williams, I.D., Russell, A.E., Pabortsava, K., 2020. Identification of tidal trapping of microplastics in a temperate salt marsh system
  using sea surface microlayer sampling. Scientific reports 10, 1–10.
- Taha, Z.D., Amin, R.M., Anuar, S.T., Nasser, A.A.A., Sohaimi, E.S., 2021. Microplastics in
  seawater and zooplankton: a case study from terengganu estuary and offshore waters, malaysia.
  Science of The Total Environment 786, 147466.
- Thompson, R.C., Moore, C.J., Vom Saal, F.S., Swan, S.H., 2009. Plastics, the environment and human health: current consensus and future trends. Philosophical transactions of the royal society B: biological sciences 364, 2153–2166.
- Tramoy, R., Gasperi, J., Colasse, L., Tassin, B., 2020. Transfer dynamic of macroplastics in estuaries—New insights from the Seine estuary: Part 1. Long term dynamic based on date-prints on
  stranded debris. Marine Pollution Bulletin 152, 110894.
- Valle-Levinson, A., Schettini, C.A., 2016. Fortnightly switching of residual flow drivers in a tropical
   semiarid estuary. Estuarine, Coastal and Shelf Science 169, 46–55.
- Wang, T., Zhao, S., Zhu, L., McWilliams, J.C., Galgani, L., Amin, R.M., Nakajima, R., Jiang, W.,
- <sup>602</sup> Chen, M., 2022. Accumulation, transformation and transport of microplastics in estuarine fronts.
- <sup>603</sup> Nature Reviews Earth & Environment 3, 795–805.
- Winterwerp, J.C., Van Kesteren, W.G., 2004. Introduction to the physics of cohesive sediment dynamics in the marine environment. Elsevier.

- Wu, Y., Wang, S., Wu, L., Yang, Y., Yu, X., Liu, Q., Liu, X., Li, Y., Wang, X., 2022. Vertical
  distribution and river-sea transport of microplastics with tidal fluctuation in a subtropical estuary,
  china. Science of The Total Environment 822, 153603.
- Xu, P., Peng, G., Su, L., Gao, Y., Gao, L., Li, D., 2018. Microplastic risk assessment in surface
  waters: A case study in the Changjiang Estuary, China. Marine pollution bulletin 133, 647–654.
- Yan, M., Nie, H., Xu, K., He, Y., Hu, Y., Huang, Y., Wang, J., 2019. Microplastic abundance,
- distribution and composition in the Pearl River along Guangzhou city and Pearl River estuary,
   China. Chemosphere 217, 879–886.
- Yonkos, L.T., Friedel, E.A., Perez-Reyes, A.C., Ghosal, S., Arthur, C.D., 2014. Microplastics in four estuarine rivers in the Chesapeake Bay, USA. Environmental science & technology 48, 14195–14202.
- Zaki, M.R.M., Ying, P.X., Zainuddin, A.H., Razak, M.R., Aris, A.Z., 2021. Occurrence, abundance,
- and distribution of microplastics pollution: an evidence in surface tropical water of klang river estuary, malaysia. Environmental Geochemistry and Health 43, 3733–3748.
- Zhao, S., Zhu, L., Li, D., 2015. Microplastic in three urban estuaries, China. Environmental
   Pollution 206, 597–604.
- Zhao, S., Zhu, L., Wang, T., Li, D., 2014. Suspended microplastics in the surface water of the
  yangtze estuary system, china: first observations on occurrence, distribution. Marine pollution
  bulletin 86, 562–568.