

# Design of an Autonomous Ride-sharing Service through a Graph Embedding Integrated Dial-a-ride Problem: Application to the Last-mile Transit in Lyon City

Omar Rifki, Nicolas Chiabaut, Jean-Pierre Nicolas

# ► To cite this version:

Omar Rifki, Nicolas Chiabaut, Jean-Pierre Nicolas. Design of an Autonomous Ride-sharing Service through a Graph Embedding Integrated Dial-a-ride Problem: Application to the Last-mile Transit in Lyon City. Transportation Research Board (TRB) Annual Meeting 2021, Jan 2021, Virtual conference, United States. hal-04116307

# HAL Id: hal-04116307 https://hal.science/hal-04116307

Submitted on 3 Jun2023

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

- **1** Design of an Autonomous Ride-sharing Service through a Graph Embedding Integrated
- 2 Dial-a-ride Problem: Application to the Last-mile Transit in Lyon City
- 3 4

### 5 **Omar Rifki**

- 6 Univ. Lyon, École Urbaine de Lyon,
- 7 Univ. Gustave Eiffel, ENTPE, LICIT, UMR \_T 9401 /
- 8 LAET, UMR 5593 CNRS, LYON, France.
- 9 Email: <u>omar.rifki@gmail.com</u>
- 10

### 11 Nicolas Chiabaut

- 12 Univ. Lyon, Univ. Gustave Eiffel, ENTPE, LICIT
- 13 UMR \_T 9401, F-69518, LYON, France
- 14 Email: <u>nicolas.chiabaut@entpe.fr</u>
- 15

### 16 Jean-Pierre Nicolas

- 17 Univ. Lyon, ENTPE, LAET,
- 18 UMR 5593 CNRS, LYON, France.
- 19 Email: jeanpierre.nicolas@entpe.fr
- 20
- 21 22
- 23 Word Count : 7,210 words + 1 table (250 words per table) = 7,460 words
- 24 25

# 26

27

## 28

# 29 AUTHOR CONTRIBUTIONS

- 30 The authors confirm contribution to the paper as follows: study conception and design: OR, NC, JPN;
- 31 *data collection: OR; analysis and interpretation of results: OR, NC, JPN; draft manuscript preparation:*
- 32 OR. All authors reviewed the results and approved the final version of the manuscript.

# 1 ABSTRACT

2 Autonomous vehicles are anticipated to revolutionize ride-sharing services and subsequently enhance the 3 public transportation systems through a first-last mile transit service. Within this context, a fleet of

4 autonomous vehicles can be modeled as a Dial-a-Ride-Problem with certain features. In this study, we

5 propose a holistic solving approach for this problem, which combines the mixed-integer linear

6 programming formulation with a novel graph dimension reduction method based on the graph embedding

7 framework. This latter method is effective since accounting for heterogeneous travel demands of the

covered territory tends to increase the size of the routing graph drastically, thus rendering exact solving of
small instances computationally infeasible. An application is provided for the real transport demand of the

industrial district of *"Vallée de la Chimie"* in Lyon city, France. Instances involving more than 50

11 transport requests, and 10 vehicles could be easily solved. Results suggest that this method generates

12 routes of reduced nodes with a lower vehicle kilometers traveled compared to the constrained K-means

based reduction. Reductions in terms of GHG emissions are estimated to be around 75% lesser than the private vehicle mode in our applied service. A sensitivity analysis is also provided.

15

16 **Keywords:** Shared Autonomous Mobility, First-Last Mile Service, Vehicle Routing, Node Embeddings.

#### 1 **1. INTRODUCTION**

2

3 The urban expansion in most cities around the world followed an automobile-oriented pattern, leading to the emergence of several low-density metropolitan areas, thus increasing the overall infrastructure costs 4 for public transportation (PT) (Sinha, 2003 [35]). Since then and due to this reason, PT systems have 5 been relegated to a secondary role behind private car use in urban mobility. The PT cover for low-density 6 areas and commercial and industrial districts outside the city is limited. Shared mobility, which is the 7 shared use of vehicles, bicycles, and other means of transport to access PT networks, started to appear to 8 9 be a viable solution to this issue, known as the first- and last-mile commute. The concept of shared mobility is not novel in itself, and could be traced back to the 1990s where it was popular, and even to the 10 vear of 1948 for the first car-sharing program (Shaheen & Chan, 2016 [36]). Yet, the major shift in shared 11 mobility is still expected by many to happen with the advent of shared autonomous vehicles (SAV). 12 Several AV manufacturers and service transportation provider companies have heavily invested and 13 adopted specific ride-sharing plans, e.g., Waymo in Phoenix area (Waymo, 2020 [41]), Jaguar Land 14 Rover (Jaguar Land Rover, 2020 [20]), and eventually Amazon, a fresh new competitor in this market 15 share (Amazon, 2020 [2]). 16

17

The factors making SAV an attractive transit mode are mainly economic, for both sides of customers and 18 PT and transportation network entities. Due to lower operational and investment costs over fixed routes, 19 transportation companies could propose services at fair prices with a higher frequency. Higher customer 20 satisfaction and time reductions may be equally obtained compared with other transit modes such as park-21 and-ride and active modes. Another argument in favor of SAV lies in the environmental sustainability of 22 this technology, which is mainly due to the application of electric vehicles in SAV services. Autonomous 23 fleets could reduce GHG emissions by up to 73% compared to conventional taxi fleets (Bauer et al., 2018 24 [3]). It was shown that each SAV could replace around 11, respectively from 5 to 10 privately owned 25 26 vehicles, with an increase of 10%, resp. from 6 to 89% travel distance via agent-based simulations of the city of Austin, Texas (Fagnant & Kockelman, 2014 [10]), resp. Lisbon (International Transport Forum, 27 28 2015 [19]). The existence of empty trips justifies this latter increase. All these favorable reports led to a resurgence of small-size experimentations of SAV services in Europe, the U.S., and globally. Just in Lyon 29 city in France, where the case study of this paper is located, there are currently three experimentations: 30 Navya shuttle buses in the Confluence area, around Groupama stadium, and Mia buses in the Meyzieu-31 Décine suburb area. Therefore, there is a great need of efficient design models for the short-time 32 33 deployment of SAVs, especially to handle the first-last mile transit issue (see Hyland & Mahmassani (2017) [18] for a taxonomy of SAV fleet management problem classes to accompany this current mobility 34 shift). 35 36

A critical component of the design of an SAV service is the vehicle assignment or the process of 37 matching customer requests to vehicles. Most SAV approaches rely on rule-based assignment methods, 38 e.g., Gurumurthy & Kockelman (2018) [16]. Optimization models are almost not used here. This is 39 because SAV studies are mostly on-demand systems, that are dynamic systems that require solving 40 approaches that are computationally cost-efficient and easy to implement (Narayanan et al., 2020 [30]). 41 On the other hand, SAV models that are reservation-based, or in other terms static systems that could be 42 solved beforehand, are relying in general on optimization. However, they are quite few in number, e.g., 43 Levin (2017) [22], Ma et al. (2017) [24]. Both Levin (2017) and Ma et al. (2017) proposed a linear 44 programming model to modelize an SAV fleet. In this study, we propose using the famous routing 45 problem of the Dial-a-Ride-Problem (DARP), which is derived from the classical Vehicle Routing 46 Problem (VRP) with additional constraints to account for pickup and drop-off requests. VRP and DARP 47 are both computationally intractable and can be pinned down as mixed-integer linear programming 48 models. According to Ho et al. (2018) [17], the largest instance solved to optimality for the basic DARP 49 with time windows is up to 8 vehicles and 96 requests, which is quite small for practical deployment of an 50 SAV service. Therefore, a mechanism has to be found in order to reduce the dimension of the routing 51

graph. To address this research gap, we develop a new reduction method based on the graph embedding 1

- framework, specifically around the node2vec algorithmic framework (Grover and Leskovec, 2016 [14]), 2 3
- which will be seen later. The problem we solve is a reservation-based SAV service.
- 4

A second objective is to design an SAV service as close as it would work in a real environment. First, this 5 was done by the choice of an application territory. We choose an industrial district in Lyon city (France), 6 called "Vallée de la Chimie" (VC). Although VC is one of the biggest chemical and petrochemical parks 7 in Europe, it is poorly served by public transport systems. It presents a concrete application of the last-8 9 mile transit. This study focuses on a classical commute problem between the city center and suburbs where two transportation alternatives compete: highway and rapid transit system. Second, we aim to 10 generate realistic traffic demand accounting for intermodality, i.e., using multiple transport modes on the 11 same trip. The traditional four-step travel models could only produce demand matrices for separate modes 12 (McNally, 2007 [26]). We have relied on a Land Use and Transport Interactions (LUTI) model-based tool 13 called OPTIREL to account for intermodality, without using agent-based simulations. OPTIREL has been 14 previously applied to design new subway lines in Paris among other projects. Therefore, the problem we 15 solve is tested on VC for the commute problem with a local rapid transit system. 16

17

The remainder of the paper is organized as follows. A brief literature review on the integration of PT-18 SAV system, the DARP problem, and the graph embedding framework is presented in the next section. 19 Section 3 introduces the optimization model and the solving approach, while Section 4 describes the 20 study case and the generation of traffic demand. In Section 5, we experimentally evaluate the benefit of 21 22 the designed last-mile service, before concluding on some final thoughts.

23

#### 2. LITERATURE REVIEW 24

25

26 In this section, we briefly review the literature of interest in this paper within the following three subsections. 27

28

#### **Integration of PT-SAV systems** 29

Several recent studies are starting to explore the benefits of integrating SAV services with existing PT 30 systems. The most commonly adopted approach in this regard is agent-based simulations, whether it 31 concerns the integration, e.g., Shen et al. (2018) [37], Pinto et al. (2020) [31], or merely the intersection 32 33 of PT-SAV systems, e.g., Fagnant & Kockelman (2014) [10]. Liang et al. (2016) [23] proposed an optimization model for an automated taxi service serving the last mile transit of a train system. Their 34 results are shown for a train station in Delft and include comparisons with human-driven taxis. Shen et al. 35 36 (2018) [37] simulate several scenarios of integrating bus lines with SAVs for the first-mile connectivity during the morning peak hours. Their results based on the Singapore PT show significant savings if low-37 38 demand buses are substituted by SAVs, savings that go up to 860 passenger car unit-kilometers. Pinto et al. (2020) [31] proposed a bi-level optimization framework to simultaneously modelize the joint transit 39 network parameters and the SAV mobility service. The lower-level problem is a dynamic combined mode 40 41 choice – traveler assignment problem, while the upper-lever is a modified transit network frequency setting problem. Their results are given for the Chicago metropolitan area. A more detailed review of 42 overall SAV services is provided by Narayanan et al. (2020) [30]. 43

44

#### **Dial-a-Ride problems** 45

46 Designing vehicle routes and schedules for collective people transportation such that each user request has a pickup and a drop-off point locations are referred to as Dial-a-Ride systems, as in early versions of 47 this service, customers have to phone their requests. From a modeling perspective, DARP belongs to the 48 49 family of routing problems. It is a variant of the vehicle routing problem (VRP), precisely the capacitated VRP with pickup and delivery and Time Windows, with a hands-on transporting passengers rather than 50 goods. Early solving approaches include Psaraftis (1980) [33], who solved the single-vehicle DARP using 51

dynamic programming, and Jaw et al. (1986) [21], who developed one of the first heuristics to the multi-1 vehicle DARP. For the exact approaches, Branch-and-Bound and their derived algorithms are the most 2 applied, e.g., Ropke et al. (2007) [34], Gschwind & Irnich (2014) [15]. Concerning metaheuristics, those 3 based on local search, especially those combining local search elements with other metaheuristics 4 currently constitute state-of-the-art solvers, e.g. Masmoudi et al. (2016) [25]. Applications of DARPs are 5 overall real-life problems with a diverse range of backgrounds, starting from the standard application to 6 the elderly and disabled people transportation to health care services, to the current emerging applications 7 in public transportation and shared mobility (Ho et al. 2018 [17], Mourad et al. 2019 [28]). For a more 8 9 comprehensive review of the problem classes, solving algorithms, and the applications of the DARP, see Cordeau & Laporte (2007) [8], Molenbruch et al. (2017) [29], and Ho et al. (2018) [17]. 10 11

### 12 Graph embeddings

Graph embedding is a powerful method to represent a graph into a low-dimensional vector space by 13 preserving as much as possible its topological structure. It addresses the research question of efficient 14 graph analytics, since traditional methods suffer from the curse of dimensionality and space cost. 15 Essential graph analytic tasks, such as graph classification, node clustering, and link prediction, become 16 17 scalable to large instances. Representation learning and visualization is another research problem tackled by graph embeddings. There are three main categories of graph embeddings: probabilistic, matrix 18 factorization-based, and deep learning-based methods (see Goyal & Ferrara, 2018 [13] for a survey on the 19 topic). Probabilistic models learn the embedding of graphs through random walks. The samplings given 20 by those walks can capture the neighborhood structure of nodes, connectivities, and other graph 21 properties such as node centrality. Compared with other probabilistic models like DeepWalk (Perozzi et 22 al., 2014 [32]) and LINE (Tang et al., 2015 [38]), the probabilistic model of node2vec (Grover & 23 Leskovec, 2016 [14]) is shown to perform better. This is why we chose *node2vec* implementation for the 24 graph embedding in the current study. The random walk exploration of this algorithm interpolates 25 between breadth-first (BFS) and depth-first (DFS) searches in order to construct a more informative 26 embedding. 27

28

# 29 **3. PROPOSED METHOD**

30

Figure 1 illustrates the flowchart of the proposed approach. It is composed of two main distinct blocks: 31 optimization according to the DARP formulation, and the graph reduction mechanism. Given a set of 32 33 stations in the studied area, the method's inputs are the origin-destination (OD) matrix of the traffic demand, i.e., the number of customers traveling between any two stations, the duration of travel and the 34 traveled distance between all couples of stations. The earliest visit time, service time, and latest visit time 35 36 for each O-D couple of the demand matrix are also input data. Routing problems in their general formulation are defined on an underlying graph where the set of vertices corresponds to the depot and 37 38 points to visit, and the set of arcs weighted with costs to travel, generally distances or travel times, represent shortest paths between stations. On this defined routing graph, each point has to be visited only 39 once by precisely one vehicle. Since each initial station could be a pickup and a drop-off point to all the 40 41 remaining stations, and taking into account all traffic demand inputs of the OD matrix of the area, the dimension of the routing graph to be solved can quickly increase. If *n* is the total number of stations, the 42 graph dimension could attain a maximum of n(n-1) points to visit without counting the depots. We 43 assume that the vehicle's capacity is greater or equal to every entry of the OD demand matrix. This will 44 prevent us from duplicating the same O-D couple of stations in the routing graph to account for the total 45 demand. The graph reduction mechanism we propose aims to detect groups of pickup and drop-off couple 46 47 points to be merged, and output a reduced graph that can be easily solvable by a mixed-integer programming solver. Note that clustering and community detection algorithms could be used as well in 48

1 the step of forming groups<sup>1</sup>. We use the constrained K-means clustering method proposed Bradley et al.

2 (2000) [5] for comparison matter. Our method is overall a model-based heuristic around a central 3 component of mathematical programming. More details of the two main parts of our model is presented

4 in the following.



5

Figure 1. Flowchart showing the method's main modules.

6 7

### 8 Mathematical formulation

9 In this study, we build on Cordeau (2006) [7] three-index formulation  $x_{ij}^k$  of the DARP by considering a 10 new objective function and adding new variables. The points to visit are partitioned into two sets: the set 11 of pickup points P and the set of drop-off points D, such that each demand request of the OD demand 12 matrix has a pickup point  $i \in P$ , a corresponding delivery point which will be denoted  $deliv(i) \in D$ , a 13 maximum riding time  $L_i$ , and a maximum waiting time  $M_i$ . Each point  $i \in P \cup D$  has a service time  $ser_i$ 14 , the earliest time to visit  $tw_i^{early}$ , a latest time to visit  $tw_i^{late}$ , and a demand load denoted  $req_i$ , such that for 15  $i \in P$ ,  $req_i \ge 0$  and  $req_{deliv(i)} = -req_i$ .

16

17 *K* is the set of vehicles. Each vehicle  $k \in K$  has a capacity  $Q_k \in \mathbb{N}$ , GHG emissions up to  $E_k$  by 18 kilometer, starts from the depot denoted  $s_k$  and ends at the depot denoted  $e_k$ . Let  $D_{start} = [s_k: k \in K]$  be 19 the set of all start depots and  $D_{end} = [e_k: k \in K]$  the set of all end depots. For all  $j \in D_{start} \cup D_{end}$ , the 20 values  $serv_j = req_j = 0$  are fixed. We associate different start and end depots to each vehicle to make the 21 model more general. However, all these depots may correspond to the same geographical location, which 22 coincide in the case of our application to the transit station of the PT network.

23

The underlying routing graph G = (V, A) has a vertex set equal to  $V = P \cup D \cup D_{start} \cup D_{end}$ . The arc set is defined as  $A = [(i, j): (i \in D_{start}, j \in P) \lor (i \in D, j \in D_{end}) \lor (i, j \in P \cup D, i \neq j, i \neq deliv(j))]$ ,

2 1 This is different from cluster and route methods, which first apply a clustering algorithm to the input visiting points, and
3 second generate optimal routes for each cluster, e.g., Chen et al. (2020) [6].

- 4
- 5

and the weights of the graph are given by  $c_{ij}$  and  $d_{ij}$ , which denote respectively the duration to travel and 1 the distance from i to j. 2

3

7

The decision variable  $x_{ij}^k$  indicates whether the arc (i, j) is traversed by vehicle  $k \in K$  or not,  $r_i$  and  $w_i$ 4 gives respectively the riding time and the waiting time for the request associated with pickup  $i \in P$ ,  $t_i^k$  is 5

the arrival time at point *i* using vehicle k, and  $q_i^k$  is the load of the vehicle k when leaving the point *i*. 6

8 In addition to minimizing total travel times for all vehicles, the degree of customer dissatisfaction in the 9 sense of Psaraftis (1980) [33] is also minimized plus to the greenhouse gas emissions due to the transport of passengers. Plausible values of  $E_k$  are drawn from the life-cycle assessment (LCA) conducted by 10 Gawron et al. (2019) [12].  $(\omega_1, \omega_2, \omega_3)$  gives the weights between the three quantities in the objective 11 function. The model is as follows. 12

13 14

$$\underset{15}{\text{Min}} \omega_1 \sum_{k \in K} \sum_{i,j \in V} c_{ij} x_{ij}^k + \omega_2 \sum_{i \in P} (r_i + w_i) + \omega_3 \sum_{k \in K} \sum_{i \in V} \sum_{j \in V} E_k d_{ij} x_{ij}^k$$

$$(1)$$

16 17

18 Subject to:

19 
$$\sum_{\substack{i \in P \\ k}} x_{s_k i}^k = \sum_{\substack{i \in D \\ k}} x_{i e_k}^k = 1 \qquad (k \in K), \qquad (2)$$

20 
$$\sum_{k \in K} \sum_{j \in V} x_{ij}^{\kappa} = 1 \qquad (i \in P), \qquad (3)$$

21 
$$\sum_{\substack{j \in V \\ k}} x_{ij}^k - \sum_{\substack{j \in V \\ deliv[i]j}} x_{deliv[i]j}^k = 0 \qquad (i \in P, k \in K),$$
(4)

22 
$$\sum_{j \in V} x_{ji}^{\kappa} - \sum_{j \in V} x_{ij}^{\kappa} = 0 \qquad (i \in P \cup D, k \in K),$$
(5)

23 
$$t_{j}^{k} \ge \left(t_{i}^{k} + ser_{i} + c_{ij}\right) x_{ij}^{k} \qquad (i, j \in V, k \in K),$$
24 
$$t_{deliv(i)}^{k} \ge t_{i}^{k} + ser_{i} + c_{ideliv(i)} \qquad (i \in P, k \in K),$$
(6)

$$25 tw_i^{early} \le t_i^k \le tw_i^{late} (i \in P \cup D, k \in K), (8)$$

26 
$$q_{j}^{k} \ge (q_{i}^{k} + req_{i}) x_{ij}^{k} \qquad (i, j \in V, k \in K),$$
27 
$$r_{i} \ge t_{deliv(i)}^{k} - (t_{i}^{k} + ser_{i}) \qquad (i \in P, k \in K),$$
(10)

33

The routing constraints (2)-(5) ensure that each vehicle starts and ends at its corresponding depot points in 34 constraint (2), each request is answered in constraint (3), the same vehicle is used for pickup and drop-off 35 36 in constraint (4), and the flow conservation in constraint (5). Constraint (6) tracks the service time, while 37 constraint (7) ensures that pickup points are visited before their delivery points, and time window constraints are given in (8). Constraint (9) tracks the load of vehicles, which is needed later to compute 38 39 the vehicle occupancy rate (VOR) indicator. Constraints (10) and (11) are respectively relative to the riding time and the waiting time for each request. Constraints (12)-(15) represent the binary and the 40 bounding restrictions for the decision variables. Note that the current mixed-integer programming solvers 41

2

can efficiently handle indicator constraints as in (6) and (9). Other useful constraints to add concern the 1 battery management aspect, which includes the recharge time, the battery energy consumption and 2 detours to recharge stations as in Bongiovanni et al. (2019) [4]. Recent simulations (Vosooghi et al., 2020 3 [40]) suggest that a best strategy for SAV could be deploying batteries with more charging space to avoid 4 charging the battery within the rush hours of the morning and the evening peaks, otherwise alternating 5 6 charging and routing could drastically increase the passenger kilometer traveled. For this reason and for the time being, we suppose that battery charging operations are set outside the routing process, and that 7 vehicles are set to be initially charged before transporting customers. 8

9

For the heuristic to determine the number of vehicles |K| (mentioned in Figure 1), we use the following formula for vehicles with an identical capacity  $Q = Q_k$ :

12

vehicles 
$$(m) = \sum_{i,j \in V^2, i \neq j} demand(i, j)/(n \times Q).$$

13 14

15 *m* is an estimate of the average number of O-D requests each vehicle is expected to answer during the 16 time horizon (usually m=3 or 4).

17 18

### **19** Graph reduction mechanism

The steps of the graph reduction are listed in the below algorithm. At first, *node2vec* is applied to the 20 routing graph G, which is introduced in the previous section and is weighted by the travel durations 21  $(c_{ij})_{i,j} \in A$ , for the following inputs: the desired dimension size of the embedding *d*, the number of random 22 walks to launch from each node and their length, plus other parameters related to the guided exploration 23 strategy of the walks. Thereafter, each node of G can be represented by a feature vector of dimension d. 24 To obtain a similarity matrix S for the nodes of G, we apply the cosine similarity, which is defined for 25 any two real-valued vectors  $v_1$  and  $v_2$  as the cosine of the angle  $\theta$  between them, i.e., 26  $\cos(\theta) = v_1 \cdot v_2 / (||v_1|| \times ||v_2||)$ . Other measures of similarity and distances could be also used at this step. 27 This step is important because it gives a quantification of the similarity between any two nodes of G 28 while taking into account as much as possible the topology structure of the graph. 29

30

The remaining steps concern merging the points to visit. We opt for merging pick-up and drop-off (P-D) couples two by two. This gives us more flexibility in the rate of contraction of the graph G, and allows us to quickly compute the optimal order within the merged P-D couples. For each two P-D couples  $(p_1, deliv(p_1), p_2, deliv(p_2))$ , we compute the following average similarity using the similarity matrix S

35

$$simil(p_1, p_2) = (S(p_1, p_2) + S(deliv(p_1), deliv(p_2)) + S(p_1, deliv(p_1))) / 6 + (S(p_2, deliv(p_2)) + S(p_2, deliv(p_1)) + S(p_1, deliv(p_2))) / 6,$$
(2)

(17)

38

which indicates how close the two couples are. Note that we affect a higher input parameters for BFS 39 over DFS in the guided search of node2vec to favor closer nodes within the vicinity of each node of G. 40 After ranking pairs of the P-D couples by their similarity, we choose the top  $r \times ||P| \cup |D||/2$  pairs, with 41 *r* is the rate of contraction of the graph. The following step proceeds by computing the optimal order of 42 visiting points within each of the chosen pairs. There are only six possible orders respecting the pickup 43 and drop-off constraints among the total 32, which are shown in Figure 2-a. For each optimal order, we 44 output two aggregated nodes in the novel graph, i.e., if an optimal order is for instance 45  $(p_1, deliv(p_1), p_2, deliv(p_2))$ , the new nodes will correspond to  $p' = (p_1, deliv(p_1))$  and 46

 $deliv(p') = (p_2, deliv(p_2))$ . The final step updates the graph weights involving the new nodes, as shown 1 in Figure 2-b. Distances between nodes are updated in the same manner. The graph reduction algorithm 2 has an overall time complexity of  $O(|V|^2)$ , since *node2vec* runs in  $O(|V|^2)$  and the number of pairs of P-3 D couples processed in the merging steps is at maximum *COMBIN*  $\left|n=(|P| \cup |D|)/2, k=2\right| \le |V|^2/8$ . 4

5 6

> 7 8

Algorithm: node2vec-based graph reduction

**Inputs:** The routing graph G = (V, A), the contraction rate *r*.

- 1. Apply the *node2vec* algorithm to *G*.
- 2. Compute the similarity matrix S of G using the cosine measure on the embedding of 1.
- 3. Compute for each two P-D couples  $(p_1, deliv(p_1), p_2, deliv(p_2))$  the value  $simil(p_1, p_2)$ .
- 4. Select the top  $r \times ||P| \cup |D||/2$  similar pairs of P-D couples.
- 5. Compute the optimal order of points to visit within each chosen pair.
- 6. Update the graph's costs for the arcs going to/coming from the newly merged nodes.



12 13 14

Figure 2. Possible arrangements for a pair of P-D couples in (a), and the updated travel costs involving merged P-D pairs in (b).

1 2

# 4. CASE STUDY: THE INDUSTRIAL DISTRICT OF "VALLÉE DE LA CHIMIE", LYON CITY

3 In this section, we describe the studied territory and the process used to generate the input demand data.

#### 4 5 **Territory**

6 Lyon is the second-largest urban area of France and is home to several industrial hubs. The largest of 7 them is "Vallée de la Chimie" (VC) for approximately  $17 km^2$ . Situated about 10 km away from city 8 center, VC has currently over 1,000 companies, 6 research and development centers, mostly working in 9 the chemical, energy and the environmental sectors, and it attracts over 20,000 jobs (Métropole de Lyon, 10 2020 [27]).

11

In terms of mobility infrastructure, a Rapid Transit System (RTS) links VC to the city center on a regular 12 schedule (each 30 min in rush hours, otherwise once by hour). There are quite few buses connecting VC 13 to Lyon city (in total three, two are drawn in the right map of Figure 3 in light red lines). The highway A7 14 also crosses the territory. This artery is essential for logistic transportation and gets severely congested in 15 the morning rush hours, as A7 is also the south entry point to the city. Commuting to work accounts for a 16 significant part of mobility flows from/to VC. By considering the low PT supply and the highway's high 17 saturation, a typical last-mile transit issue occurs. A number of experimentations to overcome this issue 18 are currently conducted in this territory: Personal Rapid Transit (PRT) from the Esprit project (Esprit, 19 20 2019 [9]) and a demand-responsive transit (DRT) service from the local PT service (TCL, 2020 [39]). VC constitutes a good study example for the SAV deployment. 21

22

23 This test case is finally classic and generalizable to several other mobility situations all over the world.

- Indeed, it corresponds to the framework of a commute problem with two main alternatives: PT and the
- 25 private vehicle which experiments bottleneck.
- 26



Figure 3. The placement of VC within the Lyon urban area in the left map, and the transport network connecting VC in the right map. Source: <u>www.openstreetmap.org/</u>.

#### **Demand generation** 1

To generate the traffic demand, we apply a Land Use and Transport Interaction (LUTI) model. LUTI 2 models are spatial interaction models that integrate the socio-demographic and economic features of the 3 population to the transport infrastructure and mobility features, to answer questions such as, what is the 4 transport modal share of a middle-sized income household living in the suburb to commute to work to the 5 6 city center. With LUTI models, the cause/effect relationships between land use and transport become well understood, and the mobility patterns are well identified. It is noteworthy that LUTI models are 7 extensively used for urban and transport plannings (see Acheampong et al., 2015 [1] for a review on the 8 9 topic).

10

We use the LUTI model called OPTIREL, which has the advantage to account for intermodality. 11 OPTIREL proceeds by decomposing the area's space according to the transport mode used from/to the 12 target territory. For instance, the first zone of the studied territory is solely accessible by walking, the 13 14 second zone is larger and is accessible by bus or RTS system (from/to the territory), the third zone is even larger. It delimits areas accessible by private vehicles combined with relay parking. In this manner, it is 15 possible to define mobility solutions combining several modes in the step of the modal decomposition. 16 17 The classical four-step travel models define zones according to the administrative or the population census based spatial decomposition, which turns out to be a rigid assumption for combining several 18 19 modes in the third step of modal share. The traffic demand considered in our application corresponds to the PT demand arriving in the territory by train during the morning peak [7h-10h]. This interval will set 20 our time horizon. Ten stations are defined for the planned SAV service, which correspond to stations of 21 22 the Esprit project (Esprit, 2019 [9]), and cover the north part of VC. They are shown in Figure 4. The main transit station is "Gare Feyzin" which will coincide with the depots of all vehicles. We can notice 23 from our input OD demand matrix, generated by OPTIREL, and shown in Figure 4, that traffic coming 24 from "Gare Feyzin" is the highest. Interestingly, the traffic is also high from the stations "Hector 25 Berlioz" and "Thomas" which are the closest stations to the transit station. Finally, duration and distances 26 between stations are generated using web mapping services. 27 28



49

50

51

Figure 4. The locations of the ten stations considered in the study (left map), and the input OD demand matrix (right plot), which is colored according to the demand intensity: green=low, yellow and orange=middle, and red=high.

### 1 5. RESULTS

2 3

4

In this section, we test the proposed method on the study case and show its usefulness.

#### 5 **Parameters setting**

6 For solving the DARP, ILOG CPLEX 12.10 solver is used, with the termination criteria set to a relative gap of 1%. Although the routing graph is reduced, we have noticed that the problem (1)-(15) takes 7 extended time to find a first solution, which is not the case for the problem (1)-(15) excluding the 8 9 precedence constraint (7). Thus, we solve the latter problem in a first step, rearrange the points to visit for each vehicle by solving the single-vehicle DARP problem (1)-(15), and then consider this solution a 10 starting point for our main optimization. The effect of adding an initial good quality starting point is 11 beneficial in our CPLEX solving process. In the absence of precise data about the customers' time 12 windows, we set the constraints (8) to two time windows, each with one hour duration, and uniformly at 13 14 random partition P and D points on the two time windows, with the condition that each dropoff point has 15 the same time window of its pickup point. We do not consider customers waiting times  $W_i$  with this configuration of time windows. A fixed service time  $ser_i = 1$  minute is associated to each point to visit 16  $i \in P \cup D$ . In the baseline scenario, capacity vehicles 17 we set the of to  $Q=25>20=max_{i,j \in V^2, i\neq j} demand(i, j)$ , the number of vehicles to vehicles (m=3)=4, the maximum 18 riding time to L=15 minutes, and the weights of the objective function to  $(\omega_1, \omega_2, \omega_3) = (1, 1, 0, 1)$ . The 19 GHG emission rate is chosen to be equal to  $E_k = 0.171 \text{ Kg} \text{CO}_2 - eq/km$ , which corresponds to the short-20 range electric autonomous taxi scenarios in Gawron et al. (2019) [12]. For the input parameters of 21 node2vec, the dimension size is set to 30, while the walk length is equal to 6 for 1000 random walks 22 launched from each node. Since *node2vec* is a stochastic method, we launch this method multiple times, 23 24 exactly 50 times for each configuration of Q and L, then choose the instance with the minimal inside travel time. This latter value is given by the summation of travel times inside the reduced nodes. For 25 instance, the inside travel time of the graph of Figure 2-b is equal to  $C_{ii} + C_{kl}$ . The calculation is done for 26 each configuration of *Q* and *L* as the possible arrangements of P-D couples could be less than six (Figure 27 2-a). All experiments are performed on an Intel(R) Core(TM) i7-8750H CPU @ 2.20GHz machine with 28 29 32 GB RAM memory. 30

31

#### 32 Constrained K-means

The constrained K-means clustering proposed by Bradley et al. (2000) [5] extends the traditional algorithm ensuring that each cluster contains at least a minimum number of elements. The problem of minimum cost flow optimization is used to solve the new formulation. Similarly, it is possible to add a maximum size constraint to clusters. In order to have a fair comparison with *node2vec*, we associate to each pickup node a value similar to the average of the expression (17) :

38

41

$$cost_{avg}(p) = \sum (c_{pq} + c_{deliv(p)deliv(q)} + c_{pdeliv(p)} + c_{qdeliv(q)} + c_{pdeliv(q)} + c_{qdeliv(p)})/12 + \sum (c_{qp} + c_{deliv(q)deliv(p)} + c_{deliv(p)p} + c_{deliv(q)q} + c_{deliv(q)p} + c_{deliv(p)q})/12.$$

This expression has twelve terms for each  $q \in P$  to account for the asymmetry of the travel times  $c_{ij}$ . Clusters are generated with a maximum size of two and a minimum size of one, for the clustering with the best inside travel time among 50 runs.

- 45
- 46
- 47
- 48
- 2
- 3

#### Indicators 1

Two main performance measures are used: the vehicle kilometers traveled (VKT), and the vehicle 2 occupancy rate (VOR). Two additional measures are extracted from them. VKT indicates the total 3 distance traveled by all vehicles of K to satisfy the demand, and is equal to, 4

- $VKT(x) = \sum_{k \in K} \sum_{i,j \in V^2, i \neq j} d_{ij} x_{i,j}^k.$
- 5

12

We also use a correlated measure to VKT, which is the total GHG emissions generated for all trips to

6 provide an order of magnitude of SAV emissions :  $GHG[x] = E_k VKT[x]$ . To get a glimpse of the GHG 7

environmental gain of using SAV, which is previously established in the literature, we show the gap: 8

9 
$$GHG_{gain}(x) = \frac{GHG_{pv}(demand) - GHG(x)}{GHG_{pv}(demand)},$$

with  $GHG_{pv}(demand)$  represents GHG emissions estimated for the input demand and the personal 10 vehicle mode. 11

13 The third measure VOR is an average of the load rate of all vehicles at each step of the routing, and is 14 equal to.

15 
$$VOR(x,q) = \frac{1}{|K|} \frac{1}{|P| \cup |D|} \sum_{k \in K} \sum_{i,j \in P \cup D, i \neq j} x_{ji}^{k} \frac{q_{i}^{k}}{Q}.$$

VOR can also be seen as an index of comfort of the mobility service. The last measure, the zero 16 17 occupancy rate (ZOR) is equal to the percentage of trips between any two stations which have an occupancy rate equal to zero, and is given by, 18

19 
$$ZOR(x,q) = \frac{1}{|K|} \sum_{k \in K} \sum_{i,j \in P \cup D, i \neq j, q_i^k = 0} \frac{x_{ji}^k}{(|P| \cup |D|) - 1}.$$

All measures are computed on the original non-reduced problem. 20

21 22

#### 23 **Baseline scenario**

Accounting for the total demand of VC leads to solving a problem of 54 points to visit<sup>2</sup> plus the dummy 24 start and end vehicle depots, which is a computationally hard problem for k>2 vehicles. The graph 25 reduction mechanism makes this optimization more manageable. CPLEX solver could attain a solution 26 for the baseline scenario within a relative MIP gap of 23% in 0.28, 277.17, and 3609.62 seconds when the 27 28 graph contraction rate is respectively 50%, 45%, and 40%. In the rest of the study, we set the contraction 29 rate of the routing graph at r=50%. Figure 5 illustrates the SAV routes obtained for the baseline scenario. This scenario has a total traveled distance of VKT = 65.46 (respectively 74.44 km) for an 30 31 average occupation rate of VOR=42.1% (resp. 31.6%), and a total emissions of GHG=11.12 (resp. 32  $12.73 \text{ Kg CO}_2 - eq$ ) for node2vec (resp. constrained K-means) based node reduction. By drawing on the estimates of the vehicle occupancy rate and the GHG emissions of private vehicles computed for the 33 34 Lyon urban area (François et al, 2017 [11]), we obtain :

35 
$$GHG_{pv}(demand) = \sum_{i, j \in V^2, i \neq j} demand(i, j) \times d_{ij} \frac{175 g CO_2 - eq/Km}{1.33 \text{ person/car}} = 43.8 \text{ Kg CO}_2 - eq.$$

Therefore, compared to the private vehicle mode, the SAV service leads to a reduction of 74.61% of 36 GHG emissions for the territory of VC when relying on the *node2vec* reduction. 37

38 39

**<sup>2</sup>** The number of points to visit for the full OD demand matrix of Figure 4 is 180 points. We have only 54 points in our input 2 3 data, since some O-D couples have a null demand.



Figure 5. SAV routes for the baseline scenario with the graph embedding

reduction (first row) and the K-means based reduction (second row).

1

2 3

4

5

# 6 Sensitivity analysis

Figure 6 shows the sensitivity analysis performed on the baseline scenario, by varying the fleet size |K|, 7 the maximum riding time L, and the vehicle's capacity Q. For a number of vehicles equal to 1, 5, and 10, 8 9 the total traveled distance VKT slowly decreases to be resp. 67.70, 64.53, and 59.88 km for the node2vec 10 reduction. K-means clustering generates tours in the same decreasing trend, but with higher VKT, which is an indication of a lower performance to find best pairs of P-D couples to merge. While |K| is 11 multiplied by 10, VKT of node2vec is divided by 1.13. Having more vehicles actually allows more 12 13 flexibility for the routing optimization to produce efficient assignments of vehicles to the transport requests. VKT is decreasing in function of Q, which is expected since larger capacities imply smaller 14 tours. Node2vec is again much efficient than K-means reduction in this regard. VKT is overall stable 15 under varying L. As some values of L and Q may constraint the number of possible arrangements of 16 Figure 2-a, an oscillatory effect when varying L and Q could be seen for VKT and VOR index as well. 17 *GHG*<sub>*aain*</sub> plots on the other hand show the substantial cut in terms of GHG emissions if SAV are deployed 18 instead of private vehicles, especially for the *node2vec* method. The reduction corresponds to resp. 19 20 73.57% and 76.62% of GHG emissions if the fleet size is equal to resp. 1 and 10. Concerning the vehicle occupation rate, we notice that this rate is not affected much by the size |K| and the riding time L, and 21 22 oscillates around the mean value of 35%. The vehicle's capacity Q, on the other hand, has some influence on VOR. VOR decreases from 38.5 (resp. 43.3%) to 24.9 (resp. 22.7%) when the capacity increases from 23

1 20 to 50 for *node2vec* (resp. K-means) reduction. This particular point should be carefully considered by 2 the designers of SAV services to achieve a fair tradeoff between users' comfort and the costs for an 3 additional capacity of automated vehicles and buses. As for empty trips, ZOR is solely impacted by the 4 size |K|. This index decreases for an increase of |K|, otherwise it has a constant value around 10%.

5 6

# 7 6. CONCLUSION

8

9 In this study, we propose a model-based heuristic design for a shared autonomous vehicle (SAV) service by combining the formulation of the Dial-a-Ride-Problem (DARP) and a graph reduction mechanism. 10 This latter procedure is based on the graph embedding framework *node2vec*, and allows us to merge 11 similar couples of pickup and drop-off points, and hence solving instances with a large number of O-D 12 requests and fleet size. A study case analysis is provided for an industrial district of the Lyon urban area 13 (France), wherein the traffic demand is generated by a LUTI model. In the paper, we address in a classical 14 commute problem between city center and suburbs where two transportation alternatives compete: 15 16 highway and rapid transit system (RTS). The SAV service is deployed as a last-mile transit for the RTS. 17 Our results suggest that *node2vec* is more efficient for node reduction than the constrained K-means (in terms of vehicle traveled distance), in addition around 75% reduction of GHG emissions are gained by 18 SAV service when compared to the private vehicle choice. 19

20

The limitations of the study mainly concerns the maximum reduction rate, which is currently 50% as reduction is done by merging couples of pickup and drop-off pairs, and the specificity of our application case. One natural improvement is to enlarge the reduction mechanism to three pickup and drop-off pairs. We also think that integrating the current approach with the LUTI model would generate precise partitions of the mode share for the studied territory and population, which would in return help to fix the adequate parameters of the SAV service, i.e., load capacity, fleet size, maximum riding time, in a causeand-effect loop.

28

29

# 30 ACKNOWLEDGEMENTS

This work is supported by "Lyon Urban School" (ANR-17-CONV-0004) of Université de Lyon, within the program "Investissements d'Avenir" (ANR-11-IDEX-0007) operated by the French National Research Agency (ANR). We would like to warmly thank Guy Bourgeois for making the data of OPTIREL available.

35

36



 Figure 6. Sensitivity analysis on the baseline scenario of the fleet size (first column), the clients

maximum riding time (second column) and the vehicles' capacity (third column) for the indicators

VKT (fist row), VOR (second row), ZOR (third row) and GHG gain (fourth row).

Table 1. Numerical values of the sensitivity analysis (plotted in Figure 6).

Fixed parame ters	Variable paramet er	VKT [Km]		VOR [%]		ZOR [%]		GHG	
								[Kg CO2-eq]	
		N2V	K-means	N2V	K-means	N2V	K-means	N2V	K-means
Q = 25 L = 15 min	K  =1	67.7	78.7	30.8	29.4	35.2	38.9	11.6	13.45
	K  =2	67.0	76.8	41.7	29.9	17.6	19.4	11.5	13.13
	K  =3	65.6	75.8	32.2	36.9	11.7	13.0	11.2	12.97
	K  =4	65.5	74.4	42.1	31.6	8.8	9.7	11.2	12.73
	K  =5	64.5	73.0	43.5	29.4	7.0	7.8	11.0	12.49
	K  =6	62.8	73.9	42.4	36.9	5.9	6.5	10.7	12.63
	K  =7	61.6	73.7	42.5	38.7	5.0	5.6	10.5	12.61
	K  =8	60.4	72.6	39.8	35.4	4.4	4.9	10.3	12.41
	K  =9	59.3	72.6	38.6	38.2	3.9	4.3	10.1	12.41
	K  =10	59.9	73.2	39.4	38.1	3.5	3.9	10.2	12.51
K  =4 Q = 25	L = 10min	64.3	72.0	30.3	31.7	9.7	9.7	11.0	12.31
	L = 11min	66.1	70.9	38.6	33.8	9.7	9.7	11.3	12.1
	L = 12min	65.4	68.5	34.9	40.4	9.3	9.3	11.2	11.7
	L = 13min	69.7	73.2	36.5	42.2	9.7	9.3	11.9	12.5
	L = 14min	66.0	74.2	36.4	32.4	8.8	10.2	11.3	12.7
	L = 15min	69.8	75.8	35.5	30.1	9.3	10.2	11.9	13.0
	L = 16min	67.4	74.9	32.8	41.9	8.8	9.3	11.5	12.8
	L = 17min	67.5	71.6	34.4	32.4	9.7	10.2	11.5	12.2
	L = 18min	71.9	76.6	33.6	29.6	10.2	10.2	12.3	13.1
	L = 19min	71.8	74.9	38.7	27.6	9.7	10.2	12.3	12.8
	L = 20min	68.1	73.2	37.5	37.8	9.3	9.3	11.6	12.5
K  = 4 L = 15 min	Q = 20	70.9	70.1	38.5	43.3	9.7	9.7	12.1	11.0
	Q = 25	68.2	73.3	32.4	38.2	9.7	9.3	11.7	12.5
	Q = 30	63.1	70.8	40.5	40.7	7.4	8.3	10.8	12.1
	Q = 35	62.4	80.1	34.0	24.8	7.4	9.3	10.7	13.7
	Q = 40	62.5	78.3	28.1	24.0	8.3	9.3	10.7	13.4
	Q = 45	54.1	70.6	33.6	24.3	6.9	7.4	9.3	12.1
	Q = 50	51.6	66.2	24.9	22.7	6.5	7.4	8.8	11.3

### 1 **REFERENCES**

- Acheampong RA, Silva EA. Land use–transport interaction modeling: A review of the literature and
   future research directions. Journal of Transport and Land use. 2015 Jan 1;8(3):11-38.
- 4

2. Amazon. Article titled "Amazon Buys Autonomous Taxi Company Zoox. Look Out, Uber and Lyft.",
by Eric J. Savitz. 2020, June 26. URL: <u>https://www.barrons.com/articles/amazon-buys-autonomous-taxi-</u>
<u>company-zoox-51593187053</u> [accessed July 20, 2020].

8

9 3. Bauer GS, Greenblatt JB, Gerke BF. Cost, energy, and environmental impact of automated electric taxi
fleets in Manhattan. Environmental science & technology. 2018 Mar 28;52(8):4920-8.

- 4. Bongiovanni C, Kaspi M, Geroliminis N. The electric autonomous dial-a-ride problem. Transportation
   Research Part B: Methodological. 2019 Apr 1;122:436-56.
- 14

5. Bradley PS, Bennett KP, Demiriz A. Constrained k-means clustering. Microsoft Research, Redmond.
2000 May;20(0):0.

17

6. Chen S, Wang H, Meng Q. Solving the first-mile ridesharing problem using autonomous vehicles.Computer-Aided Civil and Infrastructure Engineering. 2020 Jan;35(1):45-60.

- 20
  21 7. Cordeau JF. A branch-and-cut algorithm for the dial-a-ride problem. Operations Research. 2006
  22 Jun;54(3):573-86.
- 23
  24 8. Cordeau JF, Laporte G. The dial-a-ride problem: models and algorithms. Annals of operations research.
  25 2007 Sep 1;153(1):29-46..
- 26
  27 9. ESPRIT Project, 2019. URL: <u>http://www.esprit-transport-system.eu/</u> [accessed November 23, 2020]
  28

10. Fagnant DJ, Kockelman KM. The travel and environmental implications of shared autonomous
vehicles, using agent-based model scenarios. Transportation Research Part C: Emerging Technologies.
2014 Mar 1;40:1-3.

- 11. François C, Gondran N, Nicolas JP, Parsons D. Environmental assessment of urban mobility:
   combining life cycle assessment with land-use and transport interaction modelling—application to Lyon
   (France). Ecological Indicators. 2017 Jan 1;72:597-604.
- 36
  37 12. Gawron JH, Keoleian GA, De Kleine RD, Wallington TJ, Kim HC. Deep decarbonization from
  38 electrified autonomous taxi fleets: Life cycle assessment and case study in Austin, TX. Transportation
  39 Research Part D: Transport and Environment. 2019 Aug 1;73:130-41.
- 40

- 41 13. Goyal P, Ferrara E. Graph embedding techniques, applications, and performance: A survey.
  42 Knowledge-Based Systems. 2018 Jul 1;151:78-94.
- 43
- 44 14. Grover A, Leskovec J. node2vec: Scalable feature learning for networks. InProceedings of the 22nd
  45 ACM SIGKDD international conference on Knowledge discovery and data mining 2016 Aug 13 (pp.
  46 855-864).
  47
- 48 15. Gschwind T, Irnich S. Effective handling of dynamic time windows and its application to solving the
   dial-a-ride problem. Transportation Science. 2015 May;49(2):335-54.
- 50

16. Gurumurthy KM, Kockelman KM. Analyzing the dynamic ride-sharing potential for shared 1 autonomous vehicle fleets using cellphone data from Orlando, Florida. Computers, Environment and 2 Urban Systems. 2018 Sep 1;71:177-85. 3

- 4 17. Ho SC, Szeto WY, Kuo YH, Leung JM, Petering M, Tou TW. A survey of dial-a-ride problems: 5 Literature review and recent developments. Transportation Research Part B: Methodological. 2018 May 6 1;111:395-421. 7
- 9 18. Hyland MF, Mahmassani HS. Taxonomy of shared autonomous vehicle fleet management problems to inform future transportation mobility. Transportation Research Record. 2017;2653(1):26-34. 10
- 11

- 19. Organisation for Economic Co-operation and Development. Urban mobility system upgrade: How 12 shared self-driving cars could change city traffic. OECD Publishing; 2015. 13
- 14
- 20. Jaguar Land Rover, Article titled "Jaguar Land Rover reveals Project Vector autonomous ride-share 15 vehicle", by Alistair Charlton, 2020 Feb 19. URL: https://www.gearbrain.com/jaguar-land-rover-project-16 17 vector-2645188684.html [accessed July 20, 2020].
- 18
- 19 21. Jaw JJ, Odoni AR, Psaraftis HN, Wilson NH. A heuristic algorithm for the multi-vehicle advance 20 request dial-a-ride problem with time windows. Transportation Research Part B: Methodological. 1986 Jun 1;20(3):243-57. 21
- 22
- 22. Levin MW. Congestion-aware system optimal route choice for shared autonomous vehicles. 23 Transportation Research Part C: Emerging Technologies. 2017 Sep 1;82:229-47. 24
- 25
- 23. Liang X, de Almeida Correia GH, Van Arem B. Optimizing the service area and trip selection of an 26 electric automated taxi system used for the last mile of train trips. Transportation Research Part E: 27 28 Logistics and Transportation Review. 2016 Sep 1;93:115-29.
- 29
- 30 24. Ma J, Li X, Zhou F, Hao W. Designing optimal autonomous vehicle sharing and reservation systems: A linear programming approach. Transportation Research Part C: Emerging Technologies. 2017 Nov 31 32 1;84:124-41. 33
- 25. Masmoudi MA, Hosny M, Braekers K, Dammak A. Three effective metaheuristics to solve the multi-34 35 depot multi-trip heterogeneous dial-a-ride problem. Transportation Research Part E: Logistics and Transportation Review. 2016 Dec 1;96:60-80. 36
- 37
- 26. McNally MG. The four-step model. Emerald Group Publishing Limited; 2007 Sep 14. 38
- 39 40 27. Métropole de Lyon. Vallée de la Chimie Presentation, 2020. URL: 41 https://lyonvalleedelachimie.fr/en/home/ [accessed July 27, 2020].
- 42 28. Mourad A, Puchinger J, Chu C. A survey of models and algorithms for optimizing shared mobility. 43 Transportation Research Part B: Methodological. 2019 May 1;123:323-46. 44
- 45 46
- 29. Molenbruch Y, Braekers K, Caris A. Typology and literature review for dial-a-ride problems. Annals 47 of Operations Research. 2017 Dec 1;259(1-2):295-325. 48
- 30. Narayanan S, Chaniotakis E, Antoniou C. Shared autonomous vehicle services: A comprehensive 49 50 review. Transportation Research Part C: Emerging Technologies. 2020 Feb 1;111:255-93.
- 51
- 2

Pinto HK, Hyland MF, Mahmassani HS, Verbas IÖ. Joint design of multimodal transit networks and
 shared autonomous mobility fleets. Transportation Research Part C: Emerging Technologies. 2019 Jun
 22.

4

32. Perozzi B, Al-Rfou R, Skiena S. Deepwalk: Online learning of social representations. InProceedings
of the 20th ACM SIGKDD international conference on Knowledge discovery and data mining 2014 Aug
24 (pp. 701-710).

- 9 33. Psaraftis HN. A dynamic programming solution to the single vehicle many-to-many immediate
   request dial-a-ride problem. Transportation Science. 1980 May;14(2):130-54.
- 11

8

34. Ropke S, Cordeau JF, Laporte G. Models and branch-and-cut algorithms for pickup and delivery
problems with time windows. Networks: An International Journal. 2007 Jul;49(4):258-72.

- 14
  15 35. Sinha KC. Sustainability and urban public transportation. Journal of Transportation Engineering. 2003
  16 Jul;129(4):331-41.
- 17

36. Shaheen S, Chan N. Mobility and the sharing economy: Potential to facilitate the first-and last-mile
 public transit connections. Built Environment. 2016 Dec 1;42(4):573-88.

20 21 37

37. Shen Y, Zhang H, Zhao J. Integrating shared autonomous vehicle in public transportation system: A
supply-side simulation of the first-mile service in Singapore. Transportation Research Part A: Policy and
Practice. 2018 Jul 1;113:125-36.

24

38. Tang J, Qu M, Wang M, Zhang M, Yan J, Mei Q. Line: Large-scale information network embedding.
InProceedings of the 24th international conference on world wide web 2015 May 18 (pp. 1067-1077).

- 27
  28 39. TCL, Transport à la demande, 2020. URL: <u>https://www.tcl.fr/transport-a-la-demande-vallee-de-la-</u>
  29 <u>chimie (</u>in french) [accessed July 27, 2020].
- 30

40. Vosooghi R, Puchinger J, Bischoff J, Jankovic M, Vouillon A. Shared autonomous electric vehicle
service performance: Assessing the impact of charging infrastructure. Transportation Research Part D:
Transport and Environment. 2020 Apr 1;81:102283.

- 34
- 41. Waymo. Article titled "Autonomous ridesharing isn't dead: How Waymo is adapting to the post-
- 36 COVID era" by Ronan Glon, 2000, July 3. URL: <u>https://www.digitaltrends.com/cars/waymo-in-post-</u>
- 37 <u>covid-era/</u> [accessed July 20, 2020].
- 38