

#### On the application of the Schoenberg quasi-interpolant for complexity reduction in trajectory generation [Poster]

Vincent Marguet, Florin Stoican, Ionela Prodan

#### ▶ To cite this version:

Vincent Marguet, Florin Stoican, Ionela Prodan. On the application of the Schoenberg quasi-interpolant for complexity reduction in trajectory generation [Poster]. European Control Conference 2023, Jun 2023, Bucharest, Romania. hal-04126046

HAL Id: hal-04126046

https://hal.science/hal-04126046

Submitted on 12 Jun 2023

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



# On the application of the Schoenberg quasi-interpolant for complexity reduction in trajectory generation

Vincent Marguet <sup>1</sup> Florin Stoican <sup>2</sup> Ionela Prodan <sup>1</sup>



<sup>1</sup>Univ. Grenoble Alpes, Grenoble INP<sup>†</sup>, LCIS, F-26000, Valence, France <sup>†</sup>Institute of Engineering and Management Univ. Grenoble Alpes **UGA** Email: { vincent.marguet, ionela.prodan } @lcis.grenoble-inp.fr

<sup>2</sup>Faculty of Automatic Control and Computers, Politehnica University of Bucharest, ACSE, Bucharest, Romania, Email:florin.stoican@upb.ro

### Highlights

- Employ the Schoenberg operator to approximate nonlinear functions (which stem from cost and/or constraints representation in an optimisation-based trajectory generation problem);
- Present a motion planning algorithm which efficiently provides feasible trajectories via Schoenberg-based approximations.

#### **B-spline** curves

We consider the parametrization of a trajectory z(t) with B-spline curves as a linear combination of control points and B-spline basis functions:

$$z(t) = \sum_{k=0}^{n-1} P_k B_{k,p,\xi}(t) = \mathbf{PB}_{p,\xi}(t), \forall t \in [0,T],$$
 (1)

with  $\mathbf{P} = [P_0 \dots P_{n-1}]$  the matrix which gathers the control points,  $\mathbf{B}_{p,\xi}(t) = \begin{bmatrix} B_{0,p,\xi}(t) & \dots & B_{n-1,p,\xi}(t) \end{bmatrix}^{\top}$  the basis vector,  $\xi = \{\tau_0 \le \tau_1 \le ... \le \tau_m\}$  a knot sequence starting at 0 and ending at T. If  $m \ge p + 2$ , we can define B-splines of order up to p over the knot sequence.

### **Schoenberg operator**

The Schoenberg operator [Lyche et al. 2018] approximates a function, denoted as  $f(\cdot)$ , by interpolating it as weighted sum of B-splines basis functions and the function's values in the Greville points of the B-spline basis:


$$\tilde{f}(t) = \sum_{k=0}^{\tilde{n}-1} f(\tilde{t}_k) \tilde{B}_{k,\tilde{p},\tilde{\xi}}(t), \qquad (2)$$

where the Greville points are

$$\tilde{t}_k = \frac{\tilde{\tau}_{k+1} + \dots + \tilde{\tau}_{k+\tilde{p}-1}}{\tilde{p} - 1}.$$
(3)

### Trajectory generation for a fixed-wing UAV

Let us consider a 2D 3-DOF model of a fixed wing UAV, [Beard and McLain 2012], where the position (x(t), y(t)) and the heading (yaw) angle  $\psi(t) \in [0; 2\pi]$  rad are the state variables. Their dynamics are described by the following equations, where  $V_a(t)$  and  $\phi(t)$  are the inputs, the airspeed velocity and the roll angle, respectively:



$$\dot{x}(t) = V_a(t)\cos\psi(t),$$
 (4a)  $\dot{y}(t) = V_a(t)\sin\psi(t),$  (4b)  $\dot{\psi}(t) = rac{g\,\tan\phi(t)}{V_a(t)}.$  (4c)

$$\dot{\psi}(t) = rac{g \, an \phi(t)}{V_a(t)}.$$
 (4

We consider as flat output (for more details on flatness and the UAV's flat representation see [Fliess et al. 1995], [Prodan et al. 2013]) the position of the aircraft

 $z(t) = [z_1(t) \ z_2(t)]^{\top} = [x(t) \ y(t)]^{\top}.$ 

Thus, we are able to express all the state variables and inputs via the flat output and its first and second derivatives:

$$x(t) = z_1(t),$$
 (5a)  
 $y(t) = z_2(t),$  (5b)

$$\psi(t) = \arctan\left(\frac{\dot{z}_2(t)}{\dot{z}_1(t)}\right),$$
 (5c)

$$V_a(t) = \sqrt{\dot{z}_1^2(t) + \dot{z}_2^2(t)},$$
 (5d)

$$\phi(t) = \arctan\left(\frac{1}{g}\frac{\ddot{z}_2(t)\dot{z}_1(t) - \dot{z}_2(t)\ddot{z}_1(t)}{\sqrt{\dot{z}_1^2(t) + \dot{z}_2^2(t)}}\right). \tag{5e}$$

This will allow to reformulate the various costs/constraints in terms of the flat output z(t) which will be further parameterized as in (1).

### Schoenberg-based approximation of the optimization problem

Motion planning often reduces to solving a constrained optimization problem of the form

$$\min_{z(t)} \int_0^T \mathcal{C}(z(t)) \mathsf{d}t$$
 (6a)

s.t. 
$$g_i(z(t)) \le 0, \ 0 \le t \le T,$$
 (6b)

$$h_{i}(z(t)) \leq 0, \ 0 \leq t \leq T,$$
 (65)  $h_{i}(z(t)) = 0, \ 0 \leq t \leq T.$ 

The goal is to find a trajectory z(t) which minimizes the cost  $\mathcal{C}(\cdot)$  from (6a) while simultaneously respecting the inequality (6b) and equality constraints (6c) over the time interval [0, T].

To better illustrate the subsequent ideas let us particularize (6) by taking z(t) as in (5). Then, we have that:

- the cost  $\mathcal{C}(\cdot)$  minimizes the trajectory length along the time horizon [0,T];
- $\blacksquare$  the bounds on the velocity's magnitude are denoted by  $\underline{v}$  and  $\overline{v}$ , respectively;
- $\blacksquare$  the bounds on the roll angle are denoted by  $\phi$  and  $\overline{\phi}$ , respectively;
- the way-points passing (through  $p_i$  at  $t_i$ ) conditions.

Thus, (6) is instantiated to the particular form:

$$\min_{z(t)} \quad \int_0^T \|\dot{z}(t)\| dt \tag{7a}$$

s.t. 
$$\underline{v} \le ||\dot{z}(t)|| \le \overline{v}, \ \forall t \in [0, T]$$
 (7b)  
 $\underline{\phi} \le \phi(t) \le \overline{\phi}, \ \forall t \in [0, T]$  (7c)  
 $\underline{z}(t_j) = p_j, \forall j.$  (7d)

Parameterizing z(t) as in (1) allows to reformulate (7) into

$$\min_{P_k,B_k(t)} \int_0^T f_c(t) \mathrm{d}t,$$
 (8a) s.t.  $\underline{v}^2 \leq f_v(t) \leq \overline{v}^2,$  (8b)

$$\underline{v}^2 \le f_v(t) \le \overline{v}^2, \tag{8b}$$

$$\tan(\underline{\phi}) \le f_\phi(t) \le \tan(\overline{\phi}), \tag{8c}$$

$$\sum_{k=0}^{n-1} P_k B_{k,p}(t_j) = p_j, \forall j, \tag{8d}$$

with the notations

$$f_c(t) = \sqrt{\sum_{k_1, k_2 = 0}^{n-2} (P'_{k_1})^{\top} P'_{k_2} B_{k_1, p-1}(t) B_{k_2, p-1}(t)},$$

$$f_v(t) = \sum_{k_1, k_2 = 0}^{n-2} (P'_{k_1})^{\top} P'_{k_2} B_{k_1, p-1}(t) B_{k_2, p-1}(t),$$
(9a)

$$f_v(t) = \sum_{k_1, k_2 = 0}^{n-2} (P'_{k_1})^{\top} P'_{k_2} B_{k_1, p-1}(t) B_{k_2, p-1}(t),$$
(9b)

$$f_{\phi}(t) = \frac{\sum_{k_1=0}^{n-3} \sum_{k_2=0}^{n-2} \left(P_{k_1}^{"}\right)^{\top} Q P_{k_2}^{"} B_{k_1,p-2}(t) B_{k_2,p-1}(t)}{g \sqrt{\sum_{k_1,k_2=0}^{n-2} \left(P_{k_1}^{"}\right)^{\top} P_{k_2}^{"} B_{k_1,p-1}(t) B_{k_2,p-1}(t)}}, \tag{9}$$

where  $Q=\begin{bmatrix}0&-1\\1&0\end{bmatrix}$  and  $P_k',P_k''$  are used as short-hands for the control points associated to the first and second order derivatives of the B-spline curve.

Using again the illustrative example from (8) we apply (2) thrice, once to approximate the nonlinear cost (8a), once to approximate the velocity in (8b) and once to approximate the roll angle in (8c). Correspondingly, the approximations are

$$\tilde{f}_{\{c,v,\phi\}}(t) = \sum_{k=0}^{n-1} f_{\{c,v,\phi\}}(\tilde{t}_k) B_{k,\tilde{p},\tilde{\xi}}(t), \tag{10}$$

which allow to approximate:

1 the cost from (8a) as

$$\int_{0}^{T} \tilde{f}_{c}(t) dt = \int_{0}^{T} \sum_{k=0}^{\tilde{n}-1} f_{c}(\tilde{t}_{k}) B_{k,\tilde{p},\tilde{\xi}}(t) = \sum_{k=0}^{\tilde{n}-1} \left[ f_{c}(\tilde{t}_{k}) \int_{0}^{T} B_{k,\tilde{p},\tilde{\xi}}(t) dt \right]$$
(11)

**1** the velocity inequalities  $\underline{v}^2 \leq f_c(t) \leq \overline{v}^2$  from (8b) by

$$\underline{v}^2 \le \sum_{k=0}^{n-1} f_v(\tilde{t}_k) B_{k,\tilde{p},\tilde{\xi}}(t) \le \overline{v}^2, \tag{12}$$

If the roll angle inequalities  $tan(\phi) \leq f_{\phi}(t) \leq tan(\overline{\phi})$  from (8c) by

$$\tan(\underline{\phi}) \le \sum_{k=0}^{n-1} f_{\phi}(\tilde{t}_k) B_{k,\tilde{p},\tilde{\xi}}(t) \le \tan(\overline{\phi}). \tag{13}$$

Introducing approximations (11)–(13) and keeping the already linear equality (8d)leads to the approximated constrained-optimization problem [Marguet et al. 2023]


$$\min_{P_k} \quad \epsilon^2$$
 (14a)


$$-\epsilon \leq \sum_{k=0}^{\tilde{n}-1} \left[ f_c(\tilde{t}_k) \int_0^T B_{k,\tilde{p}}(t) dt \right] \leq \epsilon, \tag{14b}$$
s.t. 
$$\underline{v}^2 \leq f_v(\tilde{t}_k) \leq \overline{v}^2, \ 0 \leq k \leq \tilde{n} - 1, \tag{14c}$$


s.t. 
$$\underline{v}^2 \le f_v(\tilde{t}_k) \le \overline{v}^2, \ 0 \le k \le \tilde{n} - 1,$$
 (14c) 
$$\tan(\underline{\phi}) \le f_\phi(\tilde{t}_k) \le \tan(\overline{\phi}), \ 0 \le k \le \tilde{n} - 1,$$
 (14d)

$$p_j = \sum_{k=0}^{n-1} P_k B_{k,p}(t_j), \forall j.$$
 (14e)

#### **Simulation results**







Simulation data	Numerical Value	
Gravitational acceleration $g$	9.81 $m/s^2$	
Velocity control input	$V_a \in [18\ 25]\ \mathrm{m/s}$	
Bank control input	$\phi \in [-0.43 \ 0.43] \ {\rm rad}$	
Altitude	150 m	
Simulation time $T$	150 s	
Way-point list	$\mathbb{P}=\{(1000,1000,150),(1100,$	
	250,150),(400,0,150),(-250,	
	250,150), (400,500,150)}	
Number of control points $n$	10	
Order of the B-spline curves $p$	4	
Number of greville points $\tilde{n}$	20	
T     4   N		

Table 1. Numerical values of the simulations

Due to the approximation error, the velocity constraint was tightened from 40%, centered in the middle of its interval.

Number of inequality constraints of (8) $\infty$ Computational time of (8) $-$ Number of inequality constraints of (14) $60$ Computational time of (14) $145 \ s$ Number of iterations to solve (14) $608$	Simulation Results	Numerical Value
Number of inequality constraints of (14) $60$ Computational time of (14) $145 s$	Number of inequality constraints of (8)	$\infty$
Computational time of (14) 145 $s$	Computational time of (8)	
. ,	Number of inequality constraints of (14)	60
Number of iterations to solve (14) 608	Computational time of (14)	145 s
	Number of iterations to solve (14)	608

Table 2. Computational time analysis for the approximated curves

### **Future work**

- Extend this algorithm to multiple UAVs, taking into account "inter-UAV" constraints like communication range among them and collision avoidance
- Apply this algorithm to other UAV models: Quadcopter Crazyflie that we are using in the Esisarium platform.
- Study the approximation error caused by the Schoenberg operator in order to obtain bounds to know a priori the constraints tightening.

## References

- Marguet, V., F. Stoican, and I. Prodan (2023). "On the application of the Schoenberg quasi-interpolant for complexity reduction in trajectory generation". In: 2023 European Control Conference (ECC). IEEE.
- Lyche, T., C. Manni, and H. Speleers (2018). "Foundations of spline theory: B-splines, spline approximation, and hierarchical refinement". In: Splines and PDEs: From Approximation Theory to Numerical Linear Algebra. Prodan, I., S. Olaru, R. Bencatel, J. B. de Sousa, C. Stoica, and S.-I. Niculescu (2013). "Receding horizon flight control for trajectory tracking of autonomous aerial vehicles". In: Control Engineering Practice 21.10.
- Beard, R. W. and T. W. McLain (2012). Small unmanned aircraft: Theory and practice. Princeton university press. Fliess, M., J. Lévine, P. Martin, and P. Rouchon (1995). "Flatness and defect of non-linear systems: introductory theory and examples". In: International journal of control 61.6.