



HAL
open science

Sleptsov Nets are Turing-complete

Bernard Berthomieu, Dmitry A Zaitsev

► **To cite this version:**

| Bernard Berthomieu, Dmitry A Zaitsev. Sleptsov Nets are Turing-complete. 2023. hal-04139308

HAL Id: hal-04139308

<https://hal.science/hal-04139308>

Preprint submitted on 23 Jun 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Sleptsov Nets are Turing-complete

Bernard Berthomieu

LAAS-CNRS
 Université de Toulouse, CNRS,
 Toulouse, France
 7, avenue du Colonel Roche,
 31031 Toulouse cedex 4, France
Bernard.Berthomieu@laas.fr

Dmitry A. Zaitsev

I3S, CNRS,
 Université Côte d'Azur,
 2000, route des Lucioles,
 Les Algorithmes - bât. Euclide B,
 06900 Sophia Antipolis, France
daze@acm.org

1. Introduction

The present paper proves that a *Sleptsov net* (SN) is Turing-complete, that considerably improves, with a brief construct, the previous result [1] that a *strong* SN is Turing-complete.

Remind that, unlike Petri nets, an SN always fires enabled transitions at their *maximal firing multiplicity*, as a single step, leaving for a nondeterministic choice of which fireable transitions to fire. A strong SN restricts nondeterministic choice to firing only the transition having the highest firing multiplicity.

The proof pattern follows [1], simulating a *Shepherdson and Sturgis register machine* (RM), proven to be Turing complete [2]. Remind that an RM implements three operations over a finite set of registers, each register storing a nonnegative magnitude: increment, decrement (when a register is greater than zero), and zero check. Here we present an SN that implements zero check (fig. 1a) having same, as in [1], simple nets for increment (fig. 1b) and decrement (fig. 1c) implementation.

The results have been obtained and double-checked within modeling system Tina [3] which upcoming version supports SNs.




Fig. 1. SN components simulating instructions of RM.

2. Zero check with an SN

Lemma 1. SN in fig. 1a implements zero check of variable X .

Proof.

a) Suppose $X = 0$.

In $\bar{\mu} = \{p_1\}$, the only fireable sequence $\sigma = t_1 t_2 t_6$ fires:

$$\{p_1\} \xrightarrow{t_1} \{1 \cdot p_5, 2 \cdot p_2\} \xrightarrow{t_2} \{p_2, p_3\} \xrightarrow{t_6} \{p_6\}.$$

A token within place p_6 indicates that value of X equals to zero.

b) Suppose $X > 0$.

In $\bar{\mu} = \{p_1, X \cdot p_5\}$, the only fireable sequence $\sigma = t_1 (2 \cdot t_2) t_3$ fires:

$$\{p_1, X \cdot p_5\} \xrightarrow{t_1} \{2 \cdot p_2, (X + 1) \cdot p_5\} \xrightarrow{t_2} \{2 \cdot p_3, (X - 1) \cdot p_5\} \xrightarrow{t_3} \{p_4, X \cdot p_5\}.$$

A token within place p_4 indicates that value X is greater than zero.

Marking of other places, except of $\{p_1, p_4, p_6\}$, is not changed.

■

Proof of Lemma 1 is additionally illustrated via trace of the net images, with highlighted in red firing transitions, obtained in system Tina [3], in the line below a series of images, the number of firing copies is indicated in case it is greater than unit. We use letter X to specify both a register of RM and its value; besides we use local numbering of places and transitions within constructs of fig. 1, which are remunerated during composition of SN simulating an RM [1].

Theorem 1. SN simulates RM.

Directly follows from Lemma 1 and RG simulation technique [1].

Corollary. SN is Turing-complete.

Directly follows from Theorem 1 and [2].

3. Conclusion

We have proven that an SN is Turing-complete i.e. capable of universal computations without any additions.




Fig. 2. Trace of zero check transition firing sequences.

References

1. Dmitry A. Zaitsev, Strong Sleptsov nets are Turing complete, Information Sciences, Volume 621, 2023, Pages 172-182, ISSN 0020-0255, <https://doi.org/10.1016/j.ins.2022.11.098>
2. J.C. Shepherdson, H.E. Sturgis, Computability of recursive functions, J. ACM 10 (2) (1963) 217–255.
3. B. Berthomieu, P.-O. Ribet, F. Vernadat, The tool TINA – Construction of Abstract State Spaces for Petri Nets and Time Petri Nets, Int. J. Production Res. 42 (14) (July 2004), 2741-2756. <https://projects.laas.fr/tina>