

Is 70 Zn(d,x) 67 Cu the best way to produce 67 Cu for medical applications?

Etienne Nigron, Arnaud Guertin, Ferid Haddad, Thomas Sounalet

▶ To cite this version:

Etienne Nigron, Arnaud Guertin, Ferid Haddad, Thomas Sounalet. Is $^{70}\rm{Zn}(d,x)^{67}\rm{Cu}$ the best way to produce $^{67}\rm{Cu}$ for medical applications?. Advances in Radioactive Isotope Science 2023, Jun 2023, Avignon, France. hal-04143034

HAL Id: hal-04143034 https://hal.science/hal-04143034

Submitted on 27 Jun 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Is ⁷⁰Zn(d,x)⁶⁷Cu the best way to produce ⁶⁷Cu for medical applications?

Etienne NIGRON^{a,b*,} Arnaud GUERTIN^a, Férid HADDAD^{a,b}, Thomas SOUNALET^a

^a Laboratory SUBATECH, CNRS/IN2P3, IMT Atlantique, Université de Nantes, 4, rue Alfred Kastler, 44307 Nantes, France.

^b GIP ARRONAX, 1 rue Aronnax, 44817 Saint Herblain, France

⁶⁷Cu medical interest

- Therapeutic use in internal radiotherapy.
- $-\beta$ -emitter with a maximum energy of 561 keV (3 mm in water) [1].
- Comparable to ¹⁷⁷Lu currently used in internal vectorised radiotherapy [2].
- SPECT imaging possible with the 184.6 keV (48.7%) γ emission.
- Personalised treatment for patients with the therasnostic approach : ⁶⁴Cu (12.7 h) and ⁶⁷Cu.
- ⁶⁴Cu production route is well defined (a biomedical cyclotron delivering protons on a ⁶⁴Ni target). [4]
- Production route for ⁶⁷Cu are not well defined.

$$\begin{array}{c} 67 Cu \ \mbox{(lD card)} \\ 67 Cu \ \mbox{(lexit} 0.00\%) \\ 67 Cu \ \mbox{(lexit} 0.0\%) \\ 7_{1/2} = 61.83 \ \mbox{h}. \\ \beta \ \mbox{and} \ \gamma \ \mbox{(mitter:} \\ \beta \ \mbox{(mov)} \ \mbox{(mov)} \ \mbox{(mitter:} \\ \beta \ \mbox{(mov)} \ \mbox{(mitter:} \\ \beta \ \mbox{(mov)} \ \mbox{(mitter:} \\ \beta \ \mbox{(mov)} \ \mbox{(mov)$$

*nigron@arronax-nantes.fr

Identify the best route to produce ⁶⁷Cu with the highest yield and purity. Motivation

⁶⁷Cu production route

Why the 70 Zn(d,x) reaction?

- The target allows the separation of Cu.
- High purity ⁶⁷Cu is achievable.
- ⁶⁴Cu production can be avoided.
- ⁷⁰Zn exists and is available in metal form.
- Possibility to make thick targets.
- The yield seems promising but needs to be refined \rightarrow complete the production cross section. [5]

The stacked-foils method

- Stacked thin foils to make multiple cross section measurements in a single irradiation.
- The beam intensity was measured in two ways:
 - Trough the monitor cross section ^{nat}Ti(d,x)⁴⁸V : (uncertainty ~8%).
 - vacuum (uncertainty $\sim 2\%$).

confidence that the experience was under control.

	Energy threshold for Cu isotopes (MeV)				
	Reaction	⁶³ Cu	⁶⁴ Cu	⁶⁵ Cu	⁶⁷ Cu
	⁶⁷ Zn(d,x)	7.9	0	0	2.1
>	⁶⁸ Zn(d,x)	18.5	10.3	0.1	4.6
	⁷⁰ Zn(d,x)	34.6	26.4	16.2	0

S.Takacs (1997) ^{nat}Ti(d,x)⁴⁸V S.Takacs (2001) 350 △ S.Takacs (2007) **a** 300 • K. Gagnon (2010) 250 * M.U.Khandaker (2013) M.U Khandaker (2015) —IAEA recommended values This work

⁷⁰Zn Targets

High purity (97.5%) ⁷⁰Zn metal powder was used to prepare targets by electrodeposition as done in previous work using ⁶⁸Zn [5].

- The selected backing is natural nickel, ^{nat}Ni.
- > 30 min of electrodeposition to achieve ca. 10 µm of thickness.
- Thickness was measured before irradiation.

Electrodeposition device

⁷⁰Zn deposit on ^{nat}Ni





In our stacked foils experiments, the beam intensity has been obtained using an instrumented Faraday cup and monitor reaction ^{nat}Ti(d,x)⁴⁸V, Conclusions ^{nat}Ni(d,x)⁵⁶Co, ^{nat}Ni(d,x)⁵⁶Co and ^{nat}Ni(d,x)⁶¹Cu. These values are in agreement indicating that the experiment was well controlled.

Our new data on ⁷⁰Zn(d,x)⁶⁷Cu allows to clearly identifying the maximum of the cross section around 30 mb for an incident energy of 23 MeV.

- This production route is of great interest as it limits strongly the production of ⁶⁴Cu that is directly linked to the level of ⁶⁸Zn impurity in the target.
- With a 26 MeV deuteron beam and a target of 576 µm, the production yield is estimated to be 6.4 MBq/µA/h and allowing the production of 16.4 GBq with a specific activity of 27.9 TBq/mg for an irradiation of 40 h with an intensity of 80 µA followed by a decay period of 70 min and with a 100% enriched ⁷⁰Zn target.
- This amount of ⁶⁷Cu activity produced with high specific activity and without ⁶⁴Cu is suitable for clinical studies.

[1] NIST (National Institute of Standards and Technology), Software online, "Stopping Powers and Ranges for Electrons (estar)".

References [2] C. Bailly, A. Vidal, C. Bonnemaire, F. Krarber-Bodéré, M. Chérel, A. Pallardy, C. Rousseau, E. Garcion, F. Lacoeuille, F. Hindré, S. Valable, M. Bernaudin. C. Bodet-Hindré, M. Bourgeois, « Potential for Nuclear Medicine Therapy for Gliobastoma Treatment », Front. Pharmacol. vol. 10 p772, 2019.

[3] "Chart of Nuclides from National Nuclear Data Center (NNDC)." [Online]. Database NuDat 2.8

[4] A. Hermanne, F. Tárkányi, S. Takács, S. F. Kovalev, and A. Ignatyuk, "Activation cross sections of the production of the medical radionuclide 64Cu," Nucl. Insts Methd Phys. Res. Sect. B Beam Interact. with Mater. Atoms, vol. 258, no. 2, pp. 308–312, 2007. [5] G. Pupillo, T. Sounalet, N. Michel, L. Mou, J. Esposito, and F. Haddad, "New production cross sections for the theranostic radionuclide 67Cu," Nucl. Instruments Methods Phys. Res. Sect. B Beam Interact. with Mater. Atoms, vol. 415, no. October 2017, pp. 41–47, 2018.

[6] A. Hermanne et al., "Reference Cross Sections for Charged-particle Monitor Reactions", Nucl. Data Sheets, vol. 148, pp. 338–382, 2018.

- [7] S. Takács, M. Sonck, B. Scholten, A. Hermanne, and F. Tárkányi, "Excitation functions of deuteron induced nuclear reactions on (nat)Ti up to 20 MeV for monitoring deuteron beams," Appl. Radiat. Isot., vol. 48, no. 5, pp. 657–665, 1997.
- [8] S. Takács et al., "New cross-sections and intercomparison of deuteron monitor reactions on Al, Ti, Fe, Ni and Cu," Nucl. Instruments Methods Phys. Res. Sect. B Beam Interact. with Mater. Atoms, vol. 174, no. 3, pp. 235–258, 2001.
- [9] S. Takács, F. Tárkányi, B. Király, A. Hermanne, and M. Sonck, "Evaluated activation cross sections of longer-lived reactions on nat Ni," Nucl. Insts Methd Phys. Res. Sect. B Beam Interact. with Mater. Atoms, vol. 260, no. 2, pp. 495–507, 2007.
- [10] K. Gagnon, M. A. Avila-Rodriguez, J. Wilson, S. A. McQuarrie, "Experimental deuteron cross section measurements using single ^{nat}Ti foils from 3 to 9 MeV with special reference to the prod. of ⁴⁷V and ⁵¹Ti," Nucl. Inst Methd Phys. Res. Sect. B Beam Int. Mater. Atoms, vol. 268, no. 9, pp. 1392–1398, 2010. [11] M. U. Khandaker, H. Haba, J. Kanaya, and N. Otuka, "Excitation functions of (d,x) nuclear reactions on natural titanium up to 24 MeV," Nucl. Instruments Methods Phys. Res. Sect. B Beam Interact. with Mater. Atoms, vol. 296, pp. 14–21, 2013.

2023

- [12] M. U. Khandaker, H. Haba, M. Murakami, and N. Otuka, "Production cross-sections of long-lived radionuclides in deuteron-induced reactions on natural zinc up to 23 MeV," Nucl. Insts Methd Phys. Res. Sect. B Beam Interact. with Mater. Atoms, vol. 346, pp. 8–16, 2015.
- [13] J. Kozempel, K. Abbas, F. Simonelli, A. Bulgheroni, U. Holzwarth, and N. Gibson, "Preparation of 67Cu via deuteron irradiation of 70Zn", Radiochim. Acta, vol. 100, no. 7, pp. 419–423, 2012.



