



**HAL**  
open science

## Melt pool modelling for additive manufacturing (MOBAFA)

Stephane Gounand, Dihya Mezi, Guilhem Roux, Jean-Paul Garandet, Hicham Maskrot

► **To cite this version:**

Stephane Gounand, Dihya Mezi, Guilhem Roux, Jean-Paul Garandet, Hicham Maskrot. Melt pool modelling for additive manufacturing (MOBAFA). LIDESP 2023 - Liquid Interfaces, Drops and Sprays, Jun 2023, Udine, Italy. , 2023. hal-04155618

**HAL Id: hal-04155618**

**<https://hal.science/hal-04155618>**

Submitted on 7 Jul 2023

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution - NonCommercial - NoDerivatives 4.0 International License

# Melt Pool Modelling for Additive Manufacturing (MOBAFA)


Stéphane Gounand<sup>1</sup>, Dihya Mezi, Guilhem Roux, Jean-Paul Garandet, Hicham Maskrot

<sup>1</sup> stephane.gounand@cea.fr – <https://cv.hal.science/stephane-gounand>

Des-Service de recherche en matériaux et procédés avancés (SRMA)


CEA, Université Paris-Saclay, F-91191, Gif-sur-Yvette, France

## Additive Manufacturing




3D metal printing. Laser-Powder Bed Fusion (L-PBF) process [1]

## Liquid melt pool




Melt pool physical phenomena [1]




## Simulation goals ?

- Physical insights;
- Defect control: cracks, porosity, ejecta, bead stability. . .
- Process optimization: quality, speed. . .




Porosity and projections

## From multi-physics welding simulation. . .



PWR vessel head ©NRC



Melt pool velocity and temperature [2]

Finite Element toolbox Cast3M [3]

$$\rho_0 \frac{\partial \mathbf{u}}{\partial t} + \rho_0 (\nabla \mathbf{u}) \cdot \mathbf{u} \stackrel{\Omega}{=} -\nabla p^* + \nabla \cdot \boldsymbol{\tau} + \mathbf{f}_{\text{Bou}} + \mathbf{f}_{\text{Ext}}$$

$$\nabla \cdot \mathbf{u} \stackrel{\Omega}{=} 0$$

$$\mathbf{u} \stackrel{\partial \Omega \setminus \Gamma}{=} \mathbf{u}_0$$

$$\mathbf{u} \cdot \mathbf{n} \stackrel{\Gamma}{=} \frac{\partial \mathbf{x}_\Gamma}{\partial t} \cdot \mathbf{n} - \frac{\dot{m}}{\rho_0}$$

$$-p^* + (\boldsymbol{\tau} \cdot \mathbf{n}) \cdot \mathbf{n} + \rho_0 g z \stackrel{\Gamma}{=} \gamma \left( \frac{1}{R_1} + \frac{1}{R_2} \right) + s$$

$$(\boldsymbol{\tau} \cdot \mathbf{n}) \cdot \mathbf{t} \stackrel{\Gamma}{=} \frac{\partial \gamma}{\partial T} \nabla_s \gamma + s$$

$$\theta \stackrel{\partial \Gamma}{=} \theta_0 \text{ ou } \mathbf{x}_\Gamma \stackrel{\partial \Gamma}{=} \mathbf{x}_0$$

$$\rho_0 \frac{\partial h}{\partial t} + \rho_0 \mathbf{u} \cdot \nabla h \stackrel{\Omega}{=} \nabla \cdot \lambda \nabla T + s$$


Steady free-surface laminar Navier-Stokes

## . . . to multi-physics additive manufacturing simulation (AM)


### Characteristic values

	Welding	AM
$P_{\text{source}}$ (W)	$1.10^3$	$1.10^2$
$r_{\text{source}}$ (m)	$5,0.10^{-3}$	$5,0.10^{-5}$
$\mathbf{u}_{\text{source}}$ ( $\text{m} \cdot \text{s}^{-1}$ )	$1,0.10^{-3}$	1,0
Mass addition	Wire	Powder

Process parameters



Single-pass validation experiments [4]



Multiscale numerical methods

## Post-doctoral work, 2022-2023 (Dihya Mezi)

- Up-to-date bibliography;
- Implementation of laser-matter interaction: evaporation and recoil pressure models;
- Comparison: numerical simulation vs Baumard's experiments [4].

## Bibliographie

- [1] T. DebRoy et al. Additive manufacturing of metallic components – process, structure and properties. **Progress in Materials Science**, 92: 112 – 224, 2018.
- [2] Minh Chien Nguyen, Marc Medale, Olivier Asserin, Stéphane Gounand, and Philippe Gilles. Sensitivity to welding positions in GTA welding with a 3D multiphysics numerical model. **Numerical Heat Transfer, Part A: Applications**, 71(3):233–249, 2017. URL <https://dx.doi.org/10.1080/10407782.2016.1264747>.
- [3] Cast3m. Cast3m Web site. <http://www-cast3m.cea.fr/>.
- [4] Anaïs Baumard, Danièle Ayrault, Olivier Fandeur, Cyril Bordreuil, Frédéric Deschaux-Beaume, and Anne-Laure Vetele. Numerical prediction of grain structures formation during Laser Beam Melting of Single-Track 316L Stainless Steel. **Computational Materials Science**, 2020. URL <https://www.sciencedirect.com/science/article/pii/S0264127520309709>.