



HAL
open science

Accounting for Forest Growth Uncertainty due to Climate Change in Harvest Scheduling

Martin B Bagaram, Sándor F Tóth, Andrés Weintraub

► **To cite this version:**

Martin B Bagaram, Sándor F Tóth, Andrés Weintraub. Accounting for Forest Growth Uncertainty due to Climate Change in Harvest Scheduling. Operations Research Perspectives, In press. hal-04162661

HAL Id: hal-04162661

<https://hal.science/hal-04162661v1>

Submitted on 15 Jul 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution - NonCommercial 4.0 International License

Accounting for Forest Growth Uncertainty due to Climate Change in Harvest Scheduling

Martin B. Bagaram^{a,b}, Sándor F. Tóth^{a,1}, Andrés Weintraub P.¹

^a*School of Environmental & Forest Sciences, University of Washington, Box 352100, Seattle, WA 98195, USA*

^b*Department of Industrial & Systems Engineering, University of Washington, Seattle, WA 98195-2650, USA*

^c*Department of Industrial Engineering, University of Chile, República 701, Santiago, Chile*

Abstract

Climate change affects forest growth and yield, making it difficult to make optimal harvest decisions without knowing the future climate. We propose a multi-stage stochastic programming framework to address this uncertainty. Our proposed framework requires an a priori construction of scenario trees where the branches represent non-anticipativities of future climate paths affecting forest growth. We illustrate our model with four climate paths using a case study in Washington State, United States. Using this case, we study as to whether it is optimal to expect a positive climate effect on yield or not. We find in this particular case that it is optimal to be optimistic. We conclude that multi-stage stochastic programs with non-anticipativity constraints can be used to analyze the effects of decision makers' perception of uncertain futures on the optimality of their decisions.

Keywords: data driven optimization, climate change, harvest planning, uncertainty, forest

1. Introduction

2 The sustainable provision of forest products and services is at the core of
3 strategic (long-term) forest planning. Although there are a multitude of stew-
4 ards objectives that might guide decision makers in charge of forest manage-
5 ment, such as habitat conservation [46, 41, 47] or wildfire hazard reduction [42],

6 timber investment companies maximize net present value for their sharehold-
7 ers. To manage forests as financial assets, these companies need to be able to
8 forecast the future growth of their inventories with a certain level of accuracy.
9 Using historical data from the past to predict the future has its limits because
10 climate change increasingly affects forest growth via more frequent fires, slides,
11 windstorms, drought or other “disturbances” [14]. Climate change is often cited
12 as the primary concern for public forest sectors in the United States and beyond
13 De Pellegrin Llorente et al. [11].

14 Growth and yield parameters are used to parameterize forest harvest schedul-
15 ing models. These models optimize as to which forest units or stands should
16 be prescribed which treatments, e.g. harvest- or thinning actions, and when to
17 best meet management objectives such as maximizing NPV. When these input
18 parameters are known with certainty, *deterministic* harvest scheduling mod-
19 els can be used (e.g., [45], [41], [36], and [5]). However, deterministic models
20 are inadequate when forest growth is subject to considerable variation due to
21 climate change. Multi-stage stochastic programming models allow analysts to
22 make robust decisions in the present and have an optimal plan for future con-
23 tingencies with limited information about future growth or productivity. The
24 stochastic model considers the range of possible future growth and yield instead
25 of a single deterministic one. These alternative futures, also known as scenarios,
26 are simply discretizations of random parameters along their predicted but un-
27 certain domains. The set of relevant scenarios can be structured as a *scenario*
28 *tree* where each node is a possible future state of the forest in terms of volume
29 and each branch is a possible trajectory of subsequent growth leading to the
30 next state (node). Each “path” through this tree is a scenario with computed
31 probability. This structured discretization of future states of interest is crucial
32 in multi-stage stochastic programming. Too coarse of a discretization can lead
33 to sub-optimal decisions [40], whereas too high of a resolution can render the
34 program computationally intractable.

35 Previous studies that incorporated climate change uncertainty in forest har-
36 vest scheduling (e.g., [2, 16]) used scenarios generated by experts without taking

37 into account the degree of change in forest growth resulting from climate varia-
38 tions and whether the scenarios sufficiently captured the underlying growth un-
39 certainty. The scenarios were identified as possible futures but without knowing
40 the associated probabilities of these futures, it remains unclear how this infor-
41 mation should be incorporated in the models. The unique challenge of building
42 stochastic harvest scheduling models under climate change is that climate uncer-
43 tainty occurs at three levels. First, climate change is forecast as climate paths or
44 pathways each of which represents a set of assumptions about the future such as
45 advancement in technology, human population growth, or CO₂ emissions. The
46 problem is that we have no information about the probability of these climate
47 paths and thus it is not possible to incorporate them in the stochastic program
48 with conventional methods.

49 Second, there is uncertainty with regards to how forests would respond in
50 terms of growth under each climate path. Thus, even if we knew which climate
51 path would materialize, there is still uncertainty as to what degree actual growth
52 would change under that path. A study conducted on how forest growth would
53 change in the face of four different climate paths in the Pacific Northwest United
54 States [28] illustrates this layer of uncertainty. The results showed that forest
55 behavior under each one of those climate paths will be different depending on the
56 location and the altitude of the forest. Similar results were obtained in Brazil
57 [14]. Considering all possible climate paths, with all possible associated growth
58 responses, could make the stochastic model too unwieldy and its solutions less
59 than optimal.

60 Lastly, because of climate change mitigation efforts and the advancement in
61 technology, there is no guarantee that if the climate of the next decade repre-
62 sents one of the climate paths, then the same climate will remain in the following
63 decades. Indeed, because of mitigation efforts, it is possible to transition from
64 one climate path to a different one in the same decade. It is important to high-
65 light that the objective of generating the scenario tree is not to have a perfect
66 scenario tree but a tree that adequately captures the underlying stochastic pro-
67 cess that is suitable for strategic planning. Thus, it is important to determine

68 what the desired characteristics of a suitable tree should be and how one can de-
69 termine whether or not a given tree adequately represents the underlying
70 stochastic space.

71 The objective of this paper is to devise a method for incorporating forest
72 growth uncertainty associated with climate change into harvest scheduling mod-
73 els. The novelty of the approach stems from the unique characteristic of climate
74 uncertainty and its layered effects on decision making in forestry as described
75 above. In a nutshell, we propose that each climate path is considered individ-
76 ually in its own stochastic program first. In the absence of empirical evidence
77 with regards to the probability distribution of forest growth responses to specific
78 climate scenarios, we assign arbitrary distributions, such as normal and uniform
79 theoretical distributions, to the growth response under each scenario. We then
80 solve the stochastic program for each distribution and each climate scenario. If
81 using the stochastic solution from one climate path in place of the stochastic
82 solution provided by a different climate path yields a stochastic objective func-
83 tion value that is within the associated bounds, then we consolidate those two
84 paths into one.

85 We develop a very comprehensive harvest scheduling model that is suit-
86 able for both tactical and strategical harvest planning which integrates all the
87 constraints in the forest industry in particular the spatial constraints. To our
88 knowledge, most papers limit themselves to simplified harvest models. We show
89 as well that if the decision maker is more interested in maximizing their net
90 present value, then the optimal attitude they should have is to expect an opti-
91 mistic climate change which predicts an increase of forest growth.

92 The rest of this paper is organized as follows. We start with a review of
93 the scenario generation literature for stochastic programming in Section 2. In
94 Section 3, we present the scenario generation procedure we propose specifically
95 for forest harvest scheduling under climate change. In Section 4, we apply the
96 methodology to a case study; and finally in Section 5, we discuss the results and
97 provide some conclusions and recommendation for future work.

98 **2. Literature review**

99 To begin, it is worth emphasizing that though this paper deals with stochas-
100 tic programming, the uncertainty in mathematical models can be addressed in
101 different ways such as robust optimization, stochastic programming, and chance
102 constrained optimization [3, 10, 34]. The aim of robust optimization is to guar-
103 antee feasibility over the specified uncertainty set [44]. It is known that when
104 the full set of uncertainty is considered, robust optimization results in the worst-
105 case solution that will likely be very expensive in terms of foregone objective
106 function value. This is because robust optimization produces solutions that
107 must be feasible under every possible scenario no matter how unlikely. Accord-
108 ing to Apap and Grossmann [3], robust optimization is only suitable for short
109 term planning where feasibility is the main concern. In contrast, forest harvest
110 scheduling is a very long-term planning problem.

111 In stochastic programming, the decision maker must make a decision at the
112 beginning of the planning horizon without knowing what values some uncertain
113 parameter(s) affecting the model will take in subsequent planning periods. After
114 a period in which the uncertainty might reveal itself, the decision maker can
115 take a recourse action at a cost (to the objective function). Depending on
116 whether the sequence of initial decisions and taking recourse actions occurs once
117 or more than once, the model must be cast as a two- or multi-stage stochastic
118 program. Because multistage stochastic programming does not fix all actions
119 that should be taken in advance, it is a method suitable for long term planning
120 such as harvest scheduling [3]. However, unlike robust optimization, stochastic
121 programming relies on the discretization of the continuous uncertain parameters
122 and the probability associated with each realization of the uncertainty. Each
123 realization of the uncertain parameters is known as a scenario and the set of
124 scenarios form the scenario tree. The scenario tree generation constitutes the
125 first step for building multistage stochastic programming models.

126 There are many methods for building scenario trees. These methods include
127 moment matching, sampling average approximation, clustering and conditional

128 sampling. Moment matching is a method aiming at matching statistical mo-
129 ments between the scenario tree and the distribution of the random parame-
130 ter. The technique was developed by Fleishman [15] for univariates, however
131 Høyland et al. [25] extended its use to multivariate cases. The principle of
132 this method is to generate a scenario tree with certain properties (with mo-
133 ments such as average, standard deviation, skewness and kurtosis) matching
134 the ones of the theoretical distribution of the random parameter. A description
135 of the steps to undertake for implementing moment matching is described in
136 [25]. A shortcoming of the method is that the scenario generation step itself
137 requires solving an optimization problem that is not linear. Furthermore, as
138 shown by [21] and highlighted by [32] there could be many theoretical distribu-
139 tions having the same first moments such as the one listed. The method has
140 been mainly successfully applied for scenario generation in portfolio manage-
141 ment [26, 25, 37]. Nevertheless, [40] tested the performance of the method for
142 forest harvest scheduling with price uncertainty with limited success.

143 The sampling average approximation (SAA) technique is relatively simple
144 to implement. It consists of drawing repetitively many samples from the distri-
145 bution of the random parameter and solving the optimization problem for each
146 of these samples. If the sample size is large enough, the average solution will
147 approximate the true solution [4]. To that end, Mak et al. [33] showed that the
148 expectation of individual solutions corresponds to the lower bound on the true
149 solution of the stochastic model and that the bound monotonically increases as
150 the sample size increases (for minimization problems). For a formal description,
151 the reader is referred to Löhndorf [32]. Sample average approximation (SAA)
152 has been applied in several fields such as portfolio selection [49], supply chain
153 design and supply chain network, transportation [43, 9], personnel assignment
154 [38] and forest planning under climate change uncertainty [4]. One limitation of
155 the method is that it may require solving hundreds or thousands of optimization
156 problems in order to achieve stability. Although the method performs well for
157 two-stage problems, it does not yield the level of flexibility a decision maker
158 may need in multi-stage problems.

159 The idea of scenario clustering is to generate a set of data paths known as a
160 ‘fan’ [7] that represents possible futures and then to proceed into grouping these
161 paths into a scenario tree. This technique is sometimes referred to as distribu-
162 tion free scenario generation since it relies on generating paths that correspond
163 to past scenarios [13] or experts view of the future [21, 20]. The advantage
164 of scenario clustering is to reduce the computational burden a fully rendered
165 scenario tree might impose on the stochastic program [44]. Nevertheless, the
166 technique inherits the drawbacks of the methods used for generating the initial
167 scenario tree [50]. The technique has been extensively employed in the field
168 where the future behavior of the stochastic process is deemed to be identical to
169 previous observations. Particular domains of applications of the method include
170 portfolio management [18, 21, 7], interest rate management in investments [39],
171 hydroelectric power management [12, 17, 50], and reservoir management [30].

172 None of the aforementioned methods is suitable without modifications for
173 harvest scheduling with climate uncertainty. For instance, in the case of [2,
174 16], forest growth scenarios resulting from climate change were provided by
175 an independent research. Therefore, the scenario tree might not be tailored
176 to address the level of uncertainty in forest growth. In addition, because the
177 scenario tree was given in these studies, they did not explicitly consider the
178 two levels of uncertainty that are considered in this research. In the following
179 section, we describe our methodological approach in overcoming the challenges
180 that harvest scheduling under climate uncertainty poses especially when we
181 consider forest growth prediction from statistical models.

182 **3. Methodology**

To formally introduce the scenario generation procedure, we present the general form of the stochastic problem we intend to solve. Let us consider that the stochastic problem of interest is presented as (1) where ξ is the continuous random vector which does not depend on x ; the expectation is taken with respect to ξ . X is the set of constraints that the decision variable vector x needs to

satisfy, and z^* is the true objective function value of the stochastic program.

$$z^* = \min_{x \in X} \mathbb{E} f(x, \xi) \tag{1}$$

However, we cannot solve directly problem (1) because of the presence of the continuous random vector ξ , we can use the approximation of (1) by

$$\tilde{z} = \min_{x \in X} \mathbb{E} f(x, \tilde{\xi}), \tag{2}$$

183 where $\tilde{\xi}$ is the discretization of the random continuous vector into a scenario
 184 tree (see Section 3.1 for formal definition of the scenario tree). Since $\tilde{\xi}$ is discrete
 185 realizations of the random vector ξ , we could rewrite (2) using the summation.
 186 However, we leave this definition for later once we have defined the structure of
 187 $\tilde{\xi}$.

188 *3.1. Scenario trees generation*

189 *3.1.1. Scenario tree structure*

Before diving into how to build scenario trees, first let's briefly describe the scenario tree structure. The random process in multistage stochastic programming can be represented as a "scenario tree" which has the following structure. Let \mathcal{T} denote the set of periods in the planning horizon with $T = |\mathcal{T}|$ being the number of stages at which decisions can be made. A node of the scenario tree represents the realization of the uncertain parameters and variables at a given time period. It is a possible state of the forest at a given time $t \in \mathcal{T}$. Let n and \mathcal{N} describe the node and the lexicographically numbered set of nodes $\{1, \dots, |\mathcal{N}|\}$ in the tree, respectively. From each node n , for $t \in \mathcal{T} \setminus \{T\}$ there is at least one branch leading to another node m with probability P_m . Let Ω represent the finite set of representative scenarios in the tree. A scenario $\omega \in \Omega$ is a particular realization of the uncertain parameter represented as a path from the root-node to a leaf-node (terminal nodes). Each scenario ω has a probability or weight denoted by w^ω . Note that $\sum_{\omega \in \Omega} w^\omega = 1$. We can now rewrite (2) as:

$$\tilde{z} = \min_{x \in X} \sum_{\omega=1}^{|\Omega|} w^\omega f(x, \omega), \tag{3}$$

190 where $f(\cdot, \omega)$ is the optimization function evaluated for the scenario ω .

191 Decisions are made at each stage and implemented in the subsequent period.
 192 For instance, in Figure 1, $t = 1$ represents the first stage (stage 1). At the first
 193 stage, the decision maker needs to decide which forest units will be harvested
 194 in the first period without knowing which scenario will occur. The period is the
 195 time between two consecutive stages. Hence, $t = 1$ marks the beginning of the
 196 first period and $t = 2$ marks its end. In the example of Figure 1, we have three
 197 stages and two periods. The value of the random parameter is only revealed in
 198 periods while the decision needs to be taken at the stage before the uncertainty
 199 is revealed. The natural question becomes: What is the procedure to generate
 200 the scenarios necessary for solving (3)? and what is the appropriate number of
 201 scenarios $|\Omega|$? We address the two questions in the next sections.




Figure 1: Scenario tree representation of stochastic programming. The scenario tree shows five scenarios with three stages

202 *3.1.2. Scenario generation procedure*

203 Scenario generation is more than a science, it is an art [8] that gives the
204 modeler the flexibility to decide on the structure of the scenario tree through
205 discretization of the random vector. Fine discretization of the continuous ran-
206 dom vector leads to a computationally intractable stochastic program, while a
207 coarse discretization leads to a tree that may completely alter the structure of
208 the underlying stochastic process the scenario tree ought to represent. Although
209 many researchers focused on scenarios' generation for stochastic programming,
210 the scenario tree is not an end but a wherewithal to solve stochastic programs.
211 The scenario tree, therefore, ought to have some properties like stability, un-
212 biasedness and minimal stochastic optimality gap¹. These properties will be
213 discussed in Section 3.2.

214 The framework used for building scenario trees in this research is based
215 on conditional sampling. The method consists of fitting at each node of the
216 scenario tree a conditional probability density function and sampling from it
217 the values that successor nodes will have. Hence, except the root-node which
218 has no predecessor node, the value of each node depends on its predecessor's
219 value. This method has the advantage of controlling the range of values that
220 each node may take depending on the process that led to it. In addition, the
221 modeler could specify edge cases that should be represented by the scenario
222 tree.

223 The procedure implemented for scenario generation is inspired from [1], how-
224 ever, with many differences. It consists of dividing the sampling space of for-
225 est growth change into an equal number of parts corresponding to number of
226 branches the scenario tree should have at the given stage. To illustrate the
227 method, let's suppose the random parameter is normally distributed as illus-
228 trated in Figure 2. In the figure, $t = \{1, 2, 3\}$ represents stages at which deci-
229 sions are taken. Let L and U be the lower and the upper bounds, respectively, of
230 the support of the random parameter ξ . The node a is the root-node and there

¹This is different from MIP optimality gap

231 is no growth change associated with it. However, the values of nodes b, c and d
 232 are drawn from a normal distribution with mean μ_a , standard deviation σ_a and
 233 support Ξ_a . We denote by Φ_a the associated cumulative density function. For
 234 all nodes j in the scenario tree, we require that $\Xi_j \subseteq [L, U]$. Notice that for
 235 normally distributed random variables with mean μ_a and variance σ_a^2 , 99.73%
 236 of the cumulative density is within the interval $\Xi'_a = [\mu_a - 3\sigma_a, \mu_a + 3\sigma_a]$. Let
 237 β designate the number of branches that should originate from node a (β is
 238 the number of successor nodes). Let's divide Ξ'_a into equal intervals of width
 239 $w = 6\sigma_a/\beta$. The probability associated with each one of the successor nodes is
 240 given using the cumulative density for the interval in which the successor node
 241 is uniformly drawn from. For instance, the value of $b \in [L, \mu_a - 3\sigma_a + w]$ with a
 242 probability of P_b which is the cumulative density of that interval. For example,
 243 from Figure 2, $\beta = 3$, $w = 2\sigma_a$. Hence, nodes b and c , for instance, are uniformly
 244 drawn from interval $[L, \mu_a - \sigma_a]$ with a probability of 0.16 and $[\mu_a - \sigma_a, \mu_a + \sigma_a]$
 245 with a probability of 0.68, respectively, In other words, $P_b = \Phi_a(\mu_a - \sigma_a) = 0.16$
 246 and $P_c = \Phi_a(\mu_a + \sigma_a) - \Phi_a(\mu_a - \sigma_a) = 0.68$. To build the scenario tree, we
 247 repeat the process for each node until the leaf nodes corresponding to the ter-
 248 minal stage. As shown, in Figure 2, we arbitrarily chose the number of branches
 249 $\beta = 3$. One may wonder whether such a value of β , dictating the number of
 250 scenarios in the scenario tree, is justified. The question is what represents the
 251 appropriate number of branches suitable? To answer to this question, we need
 252 to assess the properties of the generated scenario tree.

253

254 3.2. Properties of a good scenario tree

255 Since the process of generating scenario trees described in Section 3.1 is
 256 stochastic, two runs of the scenario generation procedure might lead to two
 257 different scenario trees. However, this difference should not be significant as
 258 to affect the optimal solution of the stochastic programming. If the difference
 259 is substantial, then the scenario tree is not stable. This stability in scenario
 260 generation is measured through in-sample stability and out-of-sample stability




Figure 2: Growth change scenario generation process

261 [27].

262 3.2.1. In-sample stability

In-sample stability measures whether the difference in the solution using two different scenario trees generated from the same process is just due to the randomness in the process and not to the structure of the scenario tree. Let's suppose we generate two scenario trees $\tilde{\xi}_1$ and $\tilde{\xi}_2$ with the same structure (same number of scenarios and same number of branches at each stage). By in-sample stability, the objective function values of the two scenario trees are approximately equal as:

$$\min_{x \in X} \mathbb{E} f(x, \tilde{\xi}_1) \approx \min_{x \in X} \mathbb{E} f(x, \tilde{\xi}_2). \quad (4)$$

A different way of expressing in-sample stability is to consider $\tilde{\xi}_1, \tilde{\xi}_2, \dots, \tilde{\xi}_k$ scenario trees with increasing size, such that $|\tilde{\xi}_1| < |\tilde{\xi}_2| < \dots < |\tilde{\xi}_{k-1}| < |\tilde{\xi}_k|$ where $|\cdot|$ is the number of scenarios. If there is in-sample stability then

$$\min_{x \in X} \mathbb{E} f(x, \tilde{\xi}_{k-1}) \approx \min_{x \in X} \mathbb{E} f(x, \tilde{\xi}_k). \quad (5)$$

263 In other words, increasing the size of the scenario tree does not alter the solution
 264 and therefore, the scenario tree reached in-sample stability.

265 3.2.2. Out-of-sample stability

Out-of-sample stability is guaranteed if for two scenario trees $\tilde{\xi}_1$ and $\tilde{\xi}_2$ with the same structure, we can write:

$$\mathbb{E} \left[f \left(\arg \min_{x \in X} \mathbb{E} \left[f(x, \tilde{\xi}_1) \right], \xi \right) \right] \approx \mathbb{E} \left[f \left(\arg \min_{x \in X} \mathbb{E} \left[f(x, \tilde{\xi}_2) \right], \xi \right) \right]. \quad (6)$$

266 In practice, (6) is impossible to evaluate because we cannot evaluate the value
 267 of the approximated solution on each value of the continuous random vector.
 268 After all, we would not need the scenario tree if we could solve directly the
 269 continuous random process expressed by ξ .

Since (6) is impossible to verify, we can check out-of-sample stability by implementing a Monte-Carlo like approach [33, 40] and assuming out-of-sample stability if we can state that

$$\frac{1}{n} \sum_{i=1}^n f(\tilde{x}^1, \tilde{\xi}_i) \approx \frac{1}{n} \sum_{i=1}^n f(\tilde{x}^2, \tilde{\xi}_i), \quad (7)$$

270 where $\tilde{\xi}_1, \dots, \tilde{\xi}_n$ are i.i.d scenario tree samples of the same structure like $\tilde{\xi}$ and
 271 $\tilde{x}^k = \arg \min_{x \in X} \mathbb{E} \left[f(x, \tilde{\xi}_k) \right], \quad k = 1, 2.$

272 3.2.3. Alternative stability measurement

273 A different way we measured the scenario tree stability since we are confident
 274 the scenario generation procedure possesses sufficient randomness, was through
 275 relative stability measurement [19]. We generated a given number of scenarios of
 276 the same structure and computed the objective function for each one of them.
 277 We can find the largest (z^+) and the smallest (z^-) objective function values
 278 and compute the relative variability as $(z^+ - z^-)/z^+$. Then, we picked the
 279 scenario structure with a minimum number of scenarios that leads to a relative
 280 variability lower than a threshold fixed, say 1% or 0.5% (low variability means
 281 high stability).

282 *3.2.4. Unbiasedness*

283 Even when in-sample and out-of-sample stability are guaranteed, the dis-
 284 cretization could still lead to a biased solution. The scenario tree leads to unbi-
 285 ased solutions if the expected solution and the true solution are approximately
 286 equal such as:

$$\mathbb{E} \left[f \left(\arg \min_{x \in X} [\mathbb{E} f(x, \tilde{\xi})], \xi \right) \right] \approx \min_{x \in X} \mathbb{E} f(x, \xi). \quad (8)$$

287 Although (8) is important for assuring that the scenario generation leads to
 288 a solution diverging little from the true solution, it cannot be evaluated since
 289 the original problem cannot be solved because of the presence of the continuous
 290 random vector ξ . Kaut and Wallace [27] recommend to approximate the con-
 291 tinuous variable through a ‘reference tree’. Such a tree is the biggest possible
 292 tree that can be solved and it must be generated from a process known to be
 293 unbiased. We can assume an unbiased scenario tree if on one hand, the process
 294 that generates the tree is random and on the other hand, the scenario tree fulfills
 295 the aforementioned properties.

296 *3.3. Confidence interval on stochastic optimality gap*

We have stated that it is impossible to solve the original problem with the
 continuous random vector ξ , as consequence, its approximation with $\tilde{\xi}$ was re-
 quired. Even if the approximation leads to a scenario tree with the aforemen-
 tioned properties (in-sample and out-of-sample stability, unbiasedness), we still
 need to know to what extent the objective function value of the approxima-
 tion diverges from the true optimal value. The stochastic optimality gap $e(\tilde{\xi}, \xi)$
 evaluates the error (negative bias in the case of minimization problems) of ap-
 proximating ξ by $\tilde{\xi}$. Hence, $e(\tilde{\xi}, \xi)$ is computed as:

$$e(\tilde{\xi}, \xi) = \mathbb{E} f(\tilde{x}, \xi) - \min_{x \in X} \mathbb{E} f(x, \xi) \quad (9)$$

$$= \mathbb{E} f(\tilde{x}, \xi) - z^* \quad (10)$$

$$= \mu_{\tilde{x}} ; \quad (11)$$

where $\mu_{\tilde{x}}$ is the stochastic optimality gap of the solution \tilde{x} obtained from the scenario tree $\tilde{\xi}$. Since we cannot evaluate the stochastic optimality gap directly, we can assess its bounds. The computation of those bounds are provided in Bayraksan and Morton [6]. We can estimate the stochastic optimality gap by computing its upper bound. We readily know that its lower bound is zero, corresponding to the solution from the scenario tree approximation which is as good as the true solution. The stochastic optimality gap of a candidate solution \hat{x} is given by:

$$G_n(\hat{x}) = \frac{1}{n} \sum_{i=1}^n f(\hat{x}, \tilde{\xi}_i) - \min_{x \in X} \frac{1}{n} \sum_{i=1}^n f(x, \tilde{\xi}_i); \quad (12)$$

297 where $\tilde{\xi}_i$ is a scenario tree from the discretization of the random parameter
 298 ξ . Note that the term $G_n(\hat{x})$ is always positive. In-sample stability increases
 299 with the number of scenarios (the number of branches at each stage) for the
 300 four climate paths (Figure 3). The relative stability presented in Table 4 shows
 301 that except for the climate path B1, when the random parameter is uniformly
 302 distributed, which has a relative stability less than 1% when considering three
 303 branches at Consequently, it is necessary to define its upper bound. There are
 304 many methods used to that end. Those methods include multiple replications
 305 procedure (MRP), two replications procedure (TRP) and single replication pro-
 306 cedure (SRP) [33, 6]. However, in this research, we focus on MRP presented in
 307 Algorithm 1 because it allows to compute more robust bounds.

Algorithm 1 MRP

Input: Candidate solution \hat{x} , the number of samples n , the number of replications n_G and $\alpha \in [0, 1]$

- 1: **for** $i = 1, 2, \dots, n_G$ **do**
- 2: Sample i.i.d observations $\tilde{\xi}_{i1}, \tilde{\xi}_{i2}, \dots, \tilde{\xi}_{in}$ from the distribution of ξ
- 3: Calculate $G_n^i(\hat{x})$ using the (12)
- 4: **end for**
- 5: Calculate gap estimate \bar{G}_{n_G} and variance $s_G^2(n_G)$

$$\bar{G}_{n_G} = \frac{1}{n_G} \sum_{i=1}^{n_G} G_n^i(\hat{x}) \quad s_G^2(n_G) = \frac{1}{n_G - 1} \sum_{i=1}^{n_G} \left(G_n^i(\hat{x}) - \bar{G}_{n_G} \right)^2$$

- 6: Output the one-sided confidence interval on $\mu_{\hat{x}}$

$$\mu_{\hat{x}} = \left[0, \bar{G}_{n_G} + \frac{t_{n_G-1, \alpha} s_G(n_G)}{\sqrt{n_G}} \right]$$

308 As highlighted by Bayraksan and Morton [6], although the stochastic op-
309 timality gap is not normally distributed, from the central limit theorem, since
310 \bar{G}_{n_G} is the mean of i.i.d random variables it can be approximated to a normal
311 distribution.

312 3.4. Convergence of two climate paths

313 We have so far covered how to generate good scenario trees for the purpose
314 of stochastic programming; we have computed the bounds on the stochastic
315 optimality gap that arise from approximating the continuous random vector by
316 a scenario tree. However, we still have an issue of how to deal with the different
317 climate scenarios (climate paths) that are forecast by climate scientists. We
318 present here a method for reducing the number of climate paths that are worthy
319 of consideration. Let's suppose two climate paths i and j ($i \neq j$). We can solve
320 (2) for the two climate paths to obtain the tuple of solutions and objective
321 function values (\hat{x}_i, \hat{z}_i) and (\hat{x}_j, \hat{z}_j) corresponding to climate paths i and j ,
322 respectively. We claim that the two climate paths are not different if they have

323 the same solution. However, because it is possible to have multiple optimal
 324 solutions or to have two different solutions that lead to the same objective
 325 function value, we use the objective function to evaluate the similarity between
 326 the two climate paths.

Hence, we conclude convergence if using the solution \hat{x}_i from climate path i in the function of climate path j leads to the same objective function as \hat{z}_i . Put differently, we claim convergence of two climate paths i and j if

$$\hat{z}_i \approx \mathbb{E} \left[f_i \left(\arg \min_{x \in X} \mathbb{E}[f_j(x, \tilde{\xi})], \tilde{\xi} \right) \right]; \quad (13)$$

where f_i and f_j are the objective functions of the optimization problem for climate paths i and j , respectively. If there is convergence, then one of the climate paths is sufficient to capture the underlying random process and there is no need to consider both climate paths. In practice, we can conclude that the two scenario paths lead to the same solution if the right hand side term of (13) belongs to the confidence interval of z_i^* . From the previous sections, we have all the material to compute the confidence interval on the true objective function value z_i^* of the climate path i using a candidate solution \hat{x}_i as follows:

$$z_i^* \in \left[\hat{z}_i, \hat{z}_i + \left(\overline{G}_{n_G}(\hat{x}_i) + \frac{t_{n-1, \alpha} s_G(n_G)}{\sqrt{n_G}} \right) \right]. \quad (14)$$

327
 328 The confidence interval in (14) is one sided. It is computed taking into
 329 account the stochastic optimality gap from Algorithm 1. For minimization
 330 problems, \hat{z} is negatively biased; which means that $\mathbb{E} \hat{z} \leq z^*$ [33, Theorem
 331 1]. This stems from the fact that the solution from the discretization is more
 332 optimistic because it only considers a finite number of scenarios we optimize
 333 against.

334 3.5. Practical considerations

In practice, it is difficult to compute the stochastic optimality gap ($G_n(\hat{x})$ arising from the discretization of the random parameter), as defined in (12). The difficulty stems from the impossibility to solve certain mixed integer

programs to the full optimality in a reasonable clock time. Here, we need to highlight that the optimality gap discussed is related to the mixed integer program (MIP) and the solver used to solve the MIP. That gap (g) is computed by comparing the objective value of the incumbent solution (x) to the best lower bound \mathcal{L} (for minimization problems) as follows:

$$g = \frac{f(x) - \mathcal{L}}{f(x) + \varepsilon}, \quad (15)$$

335 where ε is a small quantity that prevents from dividing by zero. $g = 0$ means
 336 that the incumbent solution x is the optimal solution of the MIP. However, for
 337 harvest scheduling MIPs, it is difficult to achieve such a solution in a reasonable
 338 time. The common practice is to set an acceptable stopping optimality gap,
 339 $g > 0$. Unfortunately, this simplification affects (12). We cannot guarantee
 340 anymore that each $G_n(\hat{x})$ is positive because the solution to $\min_{x \in X} \sum_{i=1}^n f(x, \tilde{\xi}_i)$
 341 might not be the true optimal solution. We solve this issue by computing the
 342 lower bound on the stochastic optimality gap as computed in (12) by only using
 343 positive $G_i(\hat{x})$. We compute both the lower bound ($G_n^l(\hat{x})$) and upper bound
 344 ($G_n^u(\hat{x})$) on the stochastic optimality gap using (16)

$$G_n(\hat{x}) = \begin{cases} G_n^l(\hat{x}) = \frac{1}{n} \sum_{i=1}^n f(\hat{x}, \tilde{\xi}_i) - \min_{x \in X} \frac{1}{n} \sum_{i=1}^n f(x, \tilde{\xi}_i) & \text{if (12) is positive} \\ G_n^u(\hat{x}) = \frac{1}{n} \sum_{i=1}^n f(\hat{x}, \tilde{\xi}_i) - \frac{1}{n} \sum_{i=1}^n \mathcal{L}_i, & \text{Otherwise} \end{cases} \quad (16)$$

345
 346 where \hat{x} is a candidate solution of the stochastic program, $\tilde{\xi}_i$ is a scenario tree
 347 from the discretization of the uncertain parameter, and \mathcal{L}_i is the lower bound
 348 obtained while solving the stochastic mixed integer program with an optimality
 349 gap g . As a consequence, from the Algorithm 1, we have to compute the mean
 350 stochastic optimality gap by computing its lower and upper values as $\overline{G}_{n_G}^l$ and
 351 $\overline{G}_{n_G}^u$, respectively.

352 4. Case study

353 4.1. Climate change data

354 Although climate experts define several potential climate paths known as
355 representative concentration pathways [48], in this research, we are more in-
356 terested in how climate change influences forest growth rather than the actual
357 climate change parameters such as precipitation, temperature, etc. There exist
358 two paradigms to translate climate data into forest growth. The two paradigms
359 are known as process-based modeling and statistical or empirical modeling.
360 Process-based models are known for offering the flexibility to integrate different
361 interactions that explain forest growth. However, these models are mostly suit-
362 able for short rotation forests such as eucalyptus plantations [35, 2, 16] which
363 are not the kind of forests in the Pacific Northwest. It goes without saying that
364 the empirical modeling is more suitable for this study. Hence, using empirical
365 modeling, Latta et al. [28] showed that in the Pacific Northwest, the four cli-
366 mate paths forecast by climate experts will affect forest growth disparately. The
367 authors predicted also what the change of potential forest growth will be in 100
368 years. As results, they provided the potential mean annual increment (pMAI)
369 of forests for the year 2100.

370 In Table 1, $pMAI$ refers to the potential mean annual increment change,
371 which is the average forest growth change in one year. The value in the table
372 represents the potential mean annual increment change that will be observed in
373 100 years. It is assumed that the change will be linear from now (year 2020)
374 up to that year. The four climate paths, A1B, A2, B1, and Commit (hereafter
375 referred to as C) correspond to different climate forecast in response to human
376 activities, technological advancement, population growth, etc. The values in
377 Table 1, represents the expected pMAI, however, the values were calculated
378 from a spatial auto-regressive model developed in Latta et al. [29]. The model
379 used as input environmental parameters such as the slope, air moisture, tem-
380 perature, precipitation, and predicted forest growth. As results, there is a large
381 uncertainty on the predicted pMAI and the prediction interval is quite large

382 [29]. To account for this uncertainty, we use the prediction interval instead of
 383 the expected pMAI in harvest scheduling models.

Table 1: *Potential mean annual increment change*

	A1B	A2	B1	Commit
pMAI ($m^3/ha/year$)	2.5	3.1	1.3	0.2

384 4.2. Scenario trees

385 To generate scenario trees, we use the conditional sampling method described
 386 in Section 3.1. Forest growth change used is the one presented in Table 1. The
 387 statistical model predicting the forest growth change had a root mean squared
 388 error δ . We use the error term δ to build the 99% prediction interval of the
 389 growth change associated with each climate path. For practicality, we used the
 390 predicted growth change $\pm 3\delta$ ($pMAI \pm 3\delta$) to build the lower and upper bounds
 391 of the predicted growth change. We generated scenario trees for each climate
 392 path by sampling within the lower and upper bounds of the prediction interval
 393 (see Section 3.1 for more details).

394 To generate the scenarios for each climate path, we propose supposing for-
 395 est growth change ξ , within each prediction interval follows either a normal or
 396 uniform distribution. The normal distribution assigns high probabilities to sce-
 397 narios that are closer to the expected predicted forest growth change, whereas
 398 uniform distribution assigns the same probabilities to all scenarios within the
 399 prediction interval. The objective of having the two distributions is to test the
 400 sensitivity of the solutions to different probability schemes.

401 The planning horizon adopted in this experiment is 50 years divided into five
 402 periods (with five decision stages as well). For each distribution, we generated
 403 scenario trees by using $\beta = \{2, 3, 4, 5\}$ corresponding to two, three, four, and five
 404 branches at each stage and leading to 16, 81, 256, and 625 scenarios, respectively.
 405 For each branching scheme, we proceeded into generating ten replications of the

406 scenario tree with the same structure. These replications served into computing
 407 in-sample, out-of-sample stability and the convergence of two climate paths.

408 There are a few assumptions this research relies on. First, we assume the
 409 forest of interest is small enough in size that our management decisions do not
 410 significantly affect climate change. Consequently, the stochastic programming
 411 is the one with exogenous uncertainty [22, 3]. If we were interested in managing
 412 forests at a global level, then we would have had to consider a case where
 413 our decisions may affect back climate change. In this latter case, the stochastic
 414 programming is known as stochastic programming with endogenous uncertainty
 415 [24, 23]. Second, the growth change is linear from one period to another. Third,
 416 although forest growth changes, the forest site will still be suitable for the species
 417 of interest and therefore there is no need to worry about species shifting from
 418 one site to another. This assumption is warranted by the first assumption that
 419 the study area is relatively small.

420 4.3. Optimization model

421 In this section, we present the optimization model that served as harvest
 422 scheduling model. The main objective of harvest scheduling in commercial
 423 forests is the maximization of the net present value from the harvest actions
 424 during the planning horizon. The list of parameters, variables and sets is re-
 425 ported in Table 2.

426 4.3.1. Objective function

The objective function which aims at maximizing the expected net present
 value considering all the scenarios can be written in the form of:

$$\max_{\omega \in \Omega} \sum w^\omega \left[\sum_{t \in \mathcal{T}} \left(p_t H_t^\omega - \sum_{s \in \mathcal{S}} c_{st} x_{st}^\omega \right) + \sum_{s \in \mathcal{S}} p_0 n_s^\omega \right]. \quad (17)$$

427 We make sure to subtract from the revenue we get from the harvest of each
 428 forest unit, the cost of replanting the same unit. Hence, we balance between the
 429 revenue from harvesting a unit and the cost of replanting it. The objective func-
 430 tion (17) maximizes the net present value while meeting various sustainability
 431 and logical restrictions.

Table 2: Nomenclature

Indices

s	Stand
t	Time of harvest or the year
ω, ω'	Scenario

Variables

H_t^ω	Volume harvested in year t under scenario ω (m^3)
n_s^ω	Binary variable: 1 if stand s should not be harvested during the whole planning horizon under scenario ω ; and 0 otherwise
x_{st}^ω	Binary variable: 1 if stand s is scheduled to be harvested in year t under scenario ω ; and 0 otherwise
z_{st}	Binary: 1 if stand s has been harvested before the current management such that the stand is not green-up yet at time t ; and 0 otherwise. It is not an actual variable since it is defined while building the model

Parameters

A_{max}	Maximum contiguous area that should not be exceeded during harvest for green-up (120 acres in Washington state)
a_s	Area of stand s (ha)
age_{st}	Age of stand s at the end of the planning horizon if harvested in year t (yr)
age_s	Current age of the stand s (yr)
age_{s0}	Age of stand s at the end of the planning if not harvested during the planning horizon (yr)
b	Minimum age that a stand can have before it is considered green-up or old enough to not be considered as an opening
c_{st}	Discounted cost of regenerating stand s in year t (\$)
f_{max}	Allowable upper bound of percentage of fluctuation of volume of wood
f_{min}	Allowable lower bound of percentage of fluctuation of volume of wood
p_0	Discounted value of the forest at the end of the planning horizon if it is not harvested (\$)
p_t	Discounted price of wood in year t under scenario ω (\$)
v_{st}^ω	Productivity of stand s if harvested in year t according to scenario ω (m^3/ha)
w^ω	Weight or probability of scenario ω

Sets

\mathcal{B}	Set of stands that are big such that their area exceeds A_{max}
\mathcal{C}	Set of stands forming a minimum infeasible cluster. (They don't include large units which size exceeds A_{max})
\mathcal{K}_s	Set of stands neighbor to the stand s
Λ	Set of minimally infeasible clusters. (They don't include large units which area exceed the maximum opening size)
\mathcal{S}	Set of stands
\mathcal{T}	Set of years for the planning horizon
Ω	Set of scenarios in the scenario tree

432 4.3.2. Constraints

- (a) A stand can be harvested only once during the planning horizon

$$n_s^\omega + \sum_{t \in \mathcal{T}} x_{st}^\omega = 1 \quad \forall s \in \mathcal{S} \quad \forall \omega \in \Omega \quad (18)$$

- (b) Volume of wood harvested each period

$$\sum_{s \in \mathcal{S}} a_s v_{st}^\omega x_{st}^\omega = H_t^\omega \quad \forall t \in \mathcal{T} \quad \forall \omega \in \Omega \quad (19)$$

- (c) Wood flow constraints

$$H_t^\omega - (1 - f_{min})H_{t+1}^\omega \geq 0 \quad \forall t \leq |\mathcal{T}| - 1, \quad \forall \omega \in \Omega \quad (20)$$

$$H_t^\omega - (1 + f_{max})H_{t+1}^\omega \leq 0 \quad \forall t \leq |\mathcal{T}| - 1, \quad \forall \omega \in \Omega \quad (21)$$

- (d) Spatial configuration restrictions (Adjacency rules)

$$\sum_{s \in \mathcal{C}} \left(z_{st} + \sum_{\substack{q=t-b \\ q>0}}^t x_{sq}^\omega \right) \leq |\mathcal{C}| - 1 \quad \forall t \in \mathcal{T}, \quad \forall \mathcal{C} \in \Lambda, \quad \forall \omega \in \Omega \quad (22)$$

$$x_{st}^\omega + z_{it} + \sum_{\substack{q=t-b \\ q>0}}^t x_{iq}^\omega \leq 1 \quad \forall t \in \mathcal{T}, \quad \forall s \in \mathcal{B}, \quad \forall i \in \mathcal{K}_s, \quad \forall \omega \in \Omega \quad (23)$$

$$\sum_{i \in \mathcal{K}_s} \sum_{\substack{q=t-b \\ q>0}}^t x_{iq}^\omega \leq M(1 - x_{st}^\omega - z_{st}) \quad \forall t \in \mathcal{T}, \quad \forall s \in \mathcal{B}, \quad \forall \omega \in \Omega \quad (24)$$

$$z_{st} = 1 \quad \text{if } s \text{ harvested in } t' \text{ and } t < b + t' \text{ with } t' \in [-b, 0] \quad (25)$$

- (e) Ending inventory (ending age)

$$\sum_{s \in \mathcal{S}} a_s \left[\sum_{t \in \mathcal{T}} age_{st}^\omega x_{st}^\omega + age_{s0}^\omega n_s^\omega \right] \geq \sum_s a_s age_s. \quad \forall \omega \in \Omega \quad (26)$$

- (f) Non anticipativity

$$x_{st}^\omega = x_{st}^{\omega'} \quad \omega \neq \omega' \quad \forall s, t \quad (27)$$

433 If two scenarios ω and ω' are indistinguishable at time t , then the decision
434 in the two scenarios should be the same at that time t .

(g) Nature of variables

$$H_t^\omega \in \mathbb{R}^+, x_{st}^\omega \in \{0, 1\}, n_{st}^\omega \in \{0, 1\} \quad \forall t \in \mathcal{T}, \quad \forall s \in \mathcal{S}, \quad \forall \omega \in \Omega \quad (28)$$

435 *4.3.3. Meaning of the constraints*

436 Constraint set (18) states that each forest unit can only be harvested once
437 for each scenario. We use the variable n_s^ω as a counter of the stands that are not
438 scheduled for harvest during the whole planning horizon. The set of constraints
439 (19) computes the volume of wood harvested in each period for each scenario.
440 As we can see, the parameter v_{st}^ω depends on the scenario ω . Constraint sets (20)
441 and (21) are volume flow restrictions and they ensure that the volume of wood
442 harvested in period t is within f_{min} and f_{max} percentage of the one harvested
443 in the period $t - 1$. The set of constraints (26) states that the age of the forest
444 at the end of the planning horizon should be greater or equal to the current
445 age of the forest. This set of constraints is a proxy for sustainability; it ensures
446 that resources are not depleted during the planning horizon. Constraint set (27)
447 imposes non-anticipativity for scenario ω and ω' . It states that if there are two
448 scenarios ω and ω' that are indistinguishable in time t , then the decision should
449 be the same for the two scenarios up to that time t .

450 Constraints (22), (23), (24) and (25) refer to the green-up constraints. Green-
451 up constraints or green-up rules are a set of regulations that aim at limiting the
452 size of the openings and the length of time before adjacent forest units can be
453 harvested. A_{max} is the maximum opening area that contiguous forest units
454 harvested can create. A forest unit is considered as an opening if the forest in
455 that unit is not older than b . In practice we do not need the variable z_{st} since
456 its values will be defined while building the model. However, for easiness of
457 the model and its readability, that variable was necessary. Constraints (22) say
458 only a feasible cluster is allowed. It includes the fact that there might be stands
459 that have not yet reached the green-up requirement at the start of the planning
460 because those stands were harvested in the previous planning. Constraints (23)
461 impose that a large unit cannot be scheduled for harvest if it is adjacent to
462 any other unit that is not green-up yet. The units that are adjacent and not

463 green-up yet could be of two sources. They could originate from the previous
464 harvest planning in which case the stands on that unit are less than b years old
465 prior to this planning. The second case is that the stand is harvested either
466 in an anterior or the current year. Constraint set (24) says that if there is a
467 large stand harvested then no neighbor to that stand can be eligible for harvest.
468 Notice that for any t , $x_{st}^\omega + z_{st} \leq 1, \forall \omega, s$. This equation is deactivated if the
469 large stand is unscheduled for harvest (M is a big number). Constraint set (25)
470 just informs that the values of z are defined while building the model. $z_{st} = 1$
471 if the stand has been harvested in the prior management such that it is still
472 considered not green-up yet in time t .

473 During implementation, Constraint set (22) is written slightly differently as
474 follows:

$$\sum_{s \in \mathcal{C}} \sum_{\substack{q=t-b \\ q > 0}}^t x_{sq}^\omega \leq \max \left(0, |\mathcal{C}| - 1 - \sum_{s \in \mathcal{C}} z_{st} \right) \quad t \in \mathcal{T}, \quad \forall \mathcal{C} \in \Lambda, \quad \forall \omega \in \Omega \quad (29)$$

475 This reformulation is important because the value of $\sum_{s \in \mathcal{C}} z_{st}$ can be greater
476 than $|\mathcal{C}| - 1$. Let's for example have a cluster of two stands ($|\mathcal{C}| = 2$) that
477 were harvested in the previous planning such that the two stands are not green-
478 up yet at t^* , thus $\sum_{s \in \mathcal{C}} z_{st^*} = 2$. With the new formulation, the right-hand
479 side will be zero; as a result, the cluster cannot be harvested until the stands
480 have reached the harvestable age. This situation arises because we do not have
481 control over previous managements and how minimally infeasible clusters were
482 defined. Equations (28) define the domain of the variables.

483 4.3.4. Recourse constraints

484 Although the above model is sufficient to define the harvest scheduling, we
485 still need to define the structure of the recourse variables in case the decision
486 maker assumes a climate path, say A2, will occur and actually climate path C,
487 for instance, materializes. Notice that except the wood flow constraints (Con-
488 straint sets (20) and (21)), all other constraints will remain satisfied. Hence, to
489 satisfy the wood flow constraints, we suppose that in case of shortage of wood
490 in any time period, because we were expecting one climate path and a different

491 one occurred, we have to purchase wood on the market from a competitor to
 492 fulfill the demand. It goes without saying that the price at which we buy the
 493 wood exceeds the price at which we would sell ours. The rational behind this
 494 reasoning is that the competitor has no incentive to sell to us their wood. In
 495 sum, we incur a high cost for not having enough inventory to fulfill the implicit
 496 demand. Similarly, in case of excess of wood, we incur a cost of holding excessive
 497 inventory. Wood flow constraints are one of the most important policy in forest
 498 management planning. It ensures employment and the stability of the involved
 499 local communities [31]. To implement these policies, we need to define a set of
 500 variables and parameters.

501 First, let π_t^+ be the cost of holding inventory $e_t^{+\omega}$ in case the wood we
 502 produce in period t exceeds the maximum allowable harvest in period t (\overline{H}_t^ω)
 503 from the wood flow constraints of the scenario ω . Second, let π_t^- be the price at
 504 which we buy wood on the market in case we have a shortage of production if
 505 the wood we produce in period t is below the minimum volume, \underline{H}_t^ω , required
 506 by the wood flow constraints by a value of $e_t^{-\omega}$. We can compute the shortage
 507 volume and the excess of inventory by using (30) and (31), respectively.

$$e_t^{-\omega} = \max(\underline{H}_t^\omega - H_t^\omega, 0) \quad (30)$$

$$e_t^{+\omega} = \max(H_t^\omega - \overline{H}_t^\omega, 0) \quad (31)$$

Note that $e_t^{+\omega} * e_t^{-\omega} = 0, \forall t, \omega$ because we cannot have at the same time
 shortage and excess. The new objective function becomes

$$\max_{\omega \in \Omega} \sum w^\omega \left[\sum_{t \in \mathcal{T}} \left(p_t H_t^\omega - \pi_t^+ e_t^{+\omega} - \pi_t^- e_t^{-\omega} - \sum_{s \in \mathcal{S}} c_{st} x_{st}^\omega \right) \right]. \quad (32)$$

508 This objective is necessary in computing the net present value if the decision
 509 maker plans for one climate path and actually a different climate path occurs.
 510 Since the decision variables are fixed, this is just computing the new objective
 511 function value of wrongly assuming the future climate path.

512 *4.3.5. Values of the model's parameters*

513 The methodology was tested on Phyllis Perry forest with 89 stands at differ-
 514 ent maturity age. The planning horizon was 50 years divided into five planning
 periods of ten years each.

Table 3: *Optimization model parameters*

Parameter	Value
b	5 years
f_{min}	15%
f_{max}	15%
π_t^+	$0.8p_t$
π_t^-	$2p_t$
Discount rate	3.5%
Planning horizon	50 years
Length of a period	10 years

515
 516 We solved the models for all data sets using IBM ILOG CPLEX 64-bit 12.9.0
 517 on a Dell Power Edge 510 Server with an Intel Xeon(R) CPU, E5-2680 v3 @2.50
 518 GHz (two processors) with 256 GB RAM and the Windows Server 2012R2 64-
 519 bit operating system. The optimization model was implemented on Python.
 520 We ran CPLEX using the default settings except limiting the run time to 24h
 521 (wall clock time) and setting the optimality gap (g) to 2% for each model. We
 522 excluded from the analysis all models that terminated because of time limit.
 523 Table 3 summarises the values of several parameters used in the optimization
 524 model. To check for stability, we generated ten replications of each scenario tree
 525 structure.

526 *4.4. Experimental results*

527 *4.4.1. In-sample stability*

528 In-sample stability increases with the number of scenarios (the number of
 529 branches at each stage) for the four climate paths (Figure 3). The relative

530 stability presented in Table 4 shows that except for the climate path B1, when
 531 the random parameter is uniformly distributed, which has a relative stability less
 532 than 1% when considering three branches at each stage ($\beta = 3$), all other climate
 533 paths reach that stability level when four branching is considered ($\beta = 4$). The
 534 four branching at each stage corresponds to 256 growth scenarios.




Figure 3: In-sample stability analysis

Table 4: Percentage of stability using maximum and minimum values for both normal and uniform distributions (relative stability)

Branch (# scenarios)	Normal				Uniform			
	A1B	A2	B1	C	A1B	A2	B1	C
2 (16)	1.21	2.15	3.06	1.65	1.63	1.88	2.49	2.34
3 (81)	1.20	1.37	1.34	1.11	1.05	1.09	0.86	1.46
4 (256)	0.69	0.44	0.66	0.73	0.43	0.40	0.31	0.59
5 (625)	0.45	0.34	0.35	0.50	0.39	0.38	0.37	0.43

535 *4.4.2. Out-of-sample stability*

536 We get high out-of-sample stability when considering four branching (or 256
 537 scenarios) compared to five branching ($\beta = 5$ or 625 scenarios). However, these
 538 stabilities do not appear to be statistically different. The trade-off between
 539 the time required to solve the problem with 625 scenarios and the increase of
 540 out-of-sample stability does not motivate the adoption of the scheme with five
 541 branching. Hence, the best sampling schema is four branching at each stage
 542 leading to 256 scenarios (Figure 4).




Figure 4: *Out-of-sample stability analysis*

543 *4.4.3. Stochastic optimality gap*

544 The results of the upper and lower bounds on stochastic optimality gap for
 545 the four climate paths are reported in Table 5. The lower bound of the stochastic
 546 optimality gap ranges from 0.09% to 0.18% corresponding to the climate path
 547 A1B and C, respectively, when the growth is normally distributed. However,
 548 the upper bound on the stochastic optimality is less than 2%.

Table 5: *Stochastic optimality gap on each climate path. The percentage of the bound is relative to the mean NPV*

Distribution	Climate path	Mean NPV(\$)	\bar{G}_{30}^l (\$)	\bar{G}_{30}^l (%)	\bar{G}_{30}^u (\$)	\bar{G}_{30}^u (%)
Normal	A1B	3,354,555	2,980	0.09	62,593	1.87
	A2	3,387,797	6,063	0.18	65,974	1.95
	B1	3,278,346	3,914	0.12	60,970	1.86
	C	3,208,195	5,743	0.18	58,427	1.82
Uniform	A1B	3,355,126	4,677	0.14	63,121	1.88
	A2	3,391,432	4,401	0.13	65,150	1.92
	B1	3,272,744	5,609	0.17	63,356	1.94
	C	3,200,770	4,444	0.14	60,942	1.90

549 *4.4.4. Convergence of climate paths*

550 Table 6 displays the expected net present value that we get if we commit to
551 each of the climate paths. The expected NPV is high when we manage the forest
552 expecting climate path A2 regardless of if that climate path actually materializes
553 or not. Managing the forest expecting climate path C leads to the lowest NPV.
554 The results of two-way ANOVA shows that the expected NPV we get depends
555 on the climate path we commit to (Table 7). However, the distribution of the
556 random parameter for each climate path has no significant effect. In other
557 words, the probabilities of the scenarios did not have any significance on the
558 value of the NPV.

559 Figure 5 presents the summary of the net present value (NPV) of managing
560 the forest expecting one climate path while the materialized climate path may
561 be the same or a different one. For instance, if we manage the forest expecting
562 climate path A1B and climate path A2 occurs, the NPV is expected to increase,
563 although it remains in the uncertainty margin. However, if climate path B1 or
564 C occurs, then the obtained NPV will be much lower than the one we would
565 get if actually the climate A1B had occurred. Similarly, if we expect climate
566 A2, for instance, and climate path C occurs, the NPV obtained is much higher

Table 6: *Expected NPV when the forest is managed expecting a specific climate path regardless of which climate path actually materializes for both the normal and the uniform distributions. SD = standard deviation*

Distribution	Climate	NPV(\$)	SD(NPV)
Normal	A1B	3,335,126	30,825.77
	A2	3,352,117	33,563.86
	B1	3,288,788	27,300.93
	C	3,244,643	26,940.26
Uniform	A1B	3,333,478	33,689.93
	A2	3,350,849	38,496.11
	B1	3,285,235	29,311.52
	C	3,238,941	28,359.64

Table 7: *Two-way ANOVA of the NPV distribution and the climate path (climate) as factors*

	df	Sum Sq	Mean Sq	F Value	Pr(>F)
Distribution	1	3.70E+08	3.70E+08	0.3784	0.5394
Climate	3	2.93E+11	9.77E+10	99.888	<2e-16
Distribution × Climate	3	1.24E+08	4.14E+07	0.0423	0.9884
Residuals	152	4.87E+10	9.79E+08		

567 than the NPV we would get if we managed the forest expecting climate path C
568 and it actually materialized. This second analysis may be counter intuitive. It
569 seems like if we knew which climate path would occur, we would make the best
570 decision here and now, and therefore the NPV should be higher for such a good
571 foresee. The second thing one may wonder is whether we are not over-harvesting
572 if we plan foreseeing an optimistic forest growth climate path, say climate path
573 A2, and actually climate path C materializes. The following paragraphs address
574 these two points.

575 First, when we plan for an optimistic climate path, the best decision is to




Figure 5: *Net present value from a management expecting one climate path versus the materialization of a different climate path. Dashed blue lines correspond to the confidence of the NPV from a correct prediction of the climate path.*

576 increase the volume of forest harvested here and now (harvested in the first
 577 period) because the future forest growth will increase and compensate the vol-
 578 ume we may have over-harvested here and now. Second, the discounting affects
 579 revenues and costs that we incur in the future, hence the future actions are
 580 less significant. It is clear, therefore, that if we only care about the ending age
 581 inventory requirement (constraint set (26)) and the wood flow, the best decision
 582 is to plan for optimistic future forest growth and if we lack forest material in the
 583 future, we can still purchase wood even at a higher cost as long as the ending
 584 age constraint is satisfied.

585 Second, we can see as illustrated on Figure 6, that the volume of wood
 586 harvested is the same by the end of the planning horizon, regardless of if the
 587 management anticipated correctly the climate path to occur or not. Indeed, if
 588 we expect an optimistic climate path, say A2, we tend to increase the volume of
 589 wood harvested in the first period. However, if a less optimistic climate path,
 590 say C, occurs, we will harvest less volume in the future compared to the volume

591 we would have harvested if we knew from the beginning that the climate path
 592 C would occur.




Figure 6: *Cumulative volume of wood harvested in each period when planning for either climate paths A2 and C and actually any of the two materializes for normally distributed growth change. The letters on the bars designate the actual climate path that occurred*

593 5. Conclusions and discussion

594 In this study, we have developed a framework for incorporating forest growth
 595 and yield uncertainty due to climate change in harvest scheduling models. We
 596 considered forest growth change with different climate paths separately. We
 597 generate growth scenarios within the prediction interval of each climate path.
 598 Increasing the number of scenarios allows to capture the variability of the forest
 599 growth that affects optimal management decisions. However, there is no real
 600 benefit at increasing that number beyond a given point since it increases the
 601 problem computational complexity without significantly increasing the quality
 602 of the scenario tree. The analysis showed that out of the four climate paths
 603 considered, one may just focus on the two extreme climate paths, namely climate

604 path A2 and C since the decisions one makes considering the two others (climate
605 path A1B and B2) are included in the decision if these two climate paths.

606 Subsequently, at the high level, it does not really matter which climate
607 path will materialize; the optimal decision is to plan forest harvests expecting
608 an optimistic climate, which in this study is climate path A2. Whether the
609 uncertainty of the forest response is normally or uniformly distributed around
610 its expected value, the results have shown that there is no significant impact
611 considering one or the other.

612 Although, we advocate that the decision maker ought to have an optimistic
613 attitude expecting a future increase of the forest growth in the context of Pa-
614 cific northwest, this recommendation can be viewed with skepticism especially
615 for a large forestry company. The idea of purchasing forest products in case
616 of shortage makes sense for a small company but may not be appealing to a
617 large company that is the leading in the industry. Similarly, we would like to
618 stress that this recommendation has to be taken with caution since it is not a
619 sustainable practice if the whole forest industry adopt it. One way this caution
620 can be integrated in the model is to reinforce the wood flow constraints to be
621 feasible for all climate paths.

622 One of the limitations of this research is that we supposed that climate
623 change will affect forest growth without any feedback from our management
624 decisions. Although this assumption was valid for our case, it is a limitation
625 of this research. Similarly, we supposed that if there is a shortage of wood
626 supply because of our management decisions, then we could procure some wood
627 from competitors. This might not be true if all decision makers adopt this
628 attitude. Moreover, supposing just two distributions of the random variable may
629 be limiting. In the continuation of this research, we intend to use distributionally
630 robust optimization to integrate more distributions in the harvest scheduling and
631 at the same time consider all the climate paths at once. Finally, we supposed
632 in this research that the price of wood is independent from climate change.
633 Although we do not have enough evidence to refute this assumption, we do
634 think it might not be the case. Wood can become a prime commodity if climate

635 change leads to a substantial reduction in forest growth. However, this change
636 can be attenuated by the technological advancement that can reduce the need
637 of wood for construction.

638 [1] Alonso-Ayuso, A., Escudero, L. F., Guignard, M., and Weintraub, A. (2018).
639 Risk management for forestry planning under uncertainty in demand and
640 prices. *European Journal of Operational Research*, 267(3):1051–1074.

641 [2] Álvarez-Miranda, E., Garcia-Gonzalo, J., Ulloa-Fierro, F., Weintraub, A.,
642 and Barreiro, S. (2018). A multicriteria optimization model for sustainable
643 forest management under climate change uncertainty: An application in Por-
644 tugal. *European Journal of Operational Research*, 269(1):79–98.

645 [3] Apap, R. M. and Grossmann, I. E. (2017). Models and computational strate-
646 gies for multistage stochastic programming under endogenous and exogenous
647 uncertainties. *Computers and Chemical Engineering*, 103:233–274.

648 [4] Bagaram, M. B. and Tóth, S. F. (2020). Multistage sample average approxi-
649 mation for harvest scheduling under climate uncertainty. *Forests*, 11(11):1230.

650 [5] Bagaram, M. B., Tóth, S. F., Jaross, W. S., and Weintraub, A. (2020). A
651 parallelized variable fixing process for solving multistage stochastic programs
652 with progressive hedging. *Advances in Operations Research*, 2020:117.

653 [6] Bayraksan, G. and Morton, D. P. (2006). Assessing solution quality in
654 stochastic programs. *Mathematical Programming*, 108(2-3):495–514.

655 [7] Beraldi, P. and Bruni, M. E. (2013). A clustering approach for scenario tree
656 reduction: An application to a stochastic programming portfolio optimization
657 problem. *Top*, 22(3):1–16.

658 [8] Casey, M. S. and Sen, S. (2005). The Scenario Generation Algorithm for
659 Multistage Stochastic Linear Programming. *Mathematics of Operations Re-
660 search*, 30(3):615–631.

- 661 [9] Chunlin, D. and Liu, Y. (2012). Sample Average Approximation Method
662 for Chance Constrained Stochastic Programming in Transportation Model of
663 Emergency Management. *Systems Engineering Procedia*, 5:137–143.
- 664 [10] Crespi, G. P., Kuroiwa, D., and Rocca, M. (2018). Robust optimization:
665 Sensitivity to uncertainty in scalar and vector cases, with applications. *Op-*
666 *erations Research Perspectives*, 5:113–119.
- 667 [11] De Pellegrin Llorente, I., Eyvindson, K., Mazziotta, A., Lms, T., Eggers,
668 J., and hman, K. (2023). Perceptions of uncertainty in forest planning: Con-
669 trasting forest professionals perspectives with the latest research. *Canadian*
670 *Journal of Forest Research*.
- 671 [12] Dembo, R. S., Chiarri, A., Martin, J. G., and Paradinas, L. (1990). Man-
672 aging Hidroeléctrica Española’s Hydroelectric Power System. *Interfaces*,
673 20(1):115–135.
- 674 [13] Dupacová, J., Consigli, G., and Wallace, S. W. (2000). Scenarios for Mul-
675 tistage Stochastic Programs. *Annals of Operations Research*, 100:25–53.
- 676 [14] Elli, E. F., Sentelhas, P. C., and Bender, F. D. (2020). Impacts and uncer-
677 tainties of climate change projections on Eucalyptus plantations productivity
678 across Brazil. *Forest Ecology and Management*, 474(March):118365.
- 679 [15] Fleishman, A. I. (1978). A method for simulating non-normal distributions.
680 *Psychometrika*, 43(4):521–532.
- 681 [16] Garcia-Gonzalo, J., Pais, C., Bachmatiuk, J., Barreiro, S., and Weintraub,
682 A. (2020). A Progressive Hedging Approach to Solve Harvest Scheduling
683 Problem under Climate Change. *Forests*, 11(2):224.
- 684 [17] Gröwe-Kuska, N., Heitsch, H., and Römisch, W. (2003). Scenario reduction
685 and scenario tree construction for power management problems. *2003 IEEE*
686 *Bologna PowerTech - Conference Proceedings*, 3:152–158.

- 687 [18] Gülpinar, N., Rustem, B., and Settergren, R. (2004). Simulation and op-
688 timization approaches to scenario tree generation. *Journal of Economic Dy-*
689 *namics and Control*, 28(7):1291–1315.
- 690 [19] Guo, Z., Wallace, S. W., and Kaut, M. (2019). Vehicle Routing with
691 Space- and Time-Correlated Stochastic Travel Times: Evaluating the Objec-
692 tive Function. *INFORMS Journal on Computing*, Articles i(September):1–17.
- 693 [20] Heitsch, H. and Römisch, W. (2009). Scenario tree modeling for multistage
694 stochastic programs. *Mathematical Programming*, 118(2):371–406.
- 695 [21] Hochreiter, R. and Pflug, G. C. (2007). Financial scenario generation for
696 stochastic multi-stage decision processes as facility location problems. *Annals*
697 *of Operations Research*, 152(1):257–272.
- 698 [22] Hooshmand, F. and MirHassani, S. (2016). Efficient constraint reduction
699 in multistage stochastic programming problems with endogenous uncertainty.
700 *Optimization Methods and Software*, 31(2):359–376.
- 701 [23] Hooshmand, F. and MirHassani, S. A. (2018). Reduction of nonanticipa-
702 tivity constraints in multistage stochastic programming problems with en-
703 dogenous and exogenous uncertainty. *Mathematical Methods of Operations*
704 *Research*, 87(1).
- 705 [24] Hooshmand Khaligh, F. and MirHassani, S. (2016). A mathematical model
706 for vehicle routing problem under endogenous uncertainty. *International*
707 *Journal of Production Research*, 54(2):579–590.
- 708 [25] Høyland, K., Kaut, M., and Wallace, S. W. (2003). A Heuristic for Moment-
709 Matching. *Computational Optimization and Applications*, 24:169–185.
- 710 [26] Høyland, K. and Wallace, S. W. (2001). Generating Scenario Trees for
711 Multistage Decision Problems. *Management Science*, 47(2):295–307.
- 712 [27] Kaut, M. and Wallace, S. W. (2007). Evaluation of scenario-generation
713 methods for stochastic programming. *Pacific Journal of Optimization*,
714 3(2):257–271.

- 715 [28] Latta, G., Temesgen, H., Adams, D., and Barrett, T. (2010). Analysis of
716 potential impacts of climate change on forests of the United States Pacific
717 Northwest. *Forest Ecology and Management*, 259(4):720–729.
- 718 [29] Latta, G., Temesgen, H., and Barrett, T. M. (2009). Mapping and imputing
719 potential productivity of Pacific Northwest forests using climate variables.
720 *Canadian Journal of Forest Research*, 39(6):1197–1207.
- 721 [30] Li, Q. Q., Li, Y. P., Huang, G. H., and Wang, C. X. (2018). Risk aver-
722 sion based interval stochastic programming approach for agricultural water
723 management under uncertainty. *Stochastic Environmental Research and Risk*
724 *Assessment*, 32(3):715–732.
- 725 [31] Liu, C. M. (2002). A Primal-dual Steepest-edge Method for Even-flow
726 Harvest Scheduling Problems. *International Transactions in Operational Re-*
727 *search*, 9(1):33–50.
- 728 [32] Löhndorf, N. (2016). An empirical analysis of scenario generation meth-
729 ods for stochastic optimization. *European Journal of Operational Research*,
730 255(1):121–132.
- 731 [33] Mak, W. K., Morton, D. P., and Wood, R. K. (1999). Monte Carlo bound-
732 ing techniques for determining solution quality in stochastic programs. *Op-*
733 *erations Research Letters*, 24(1):47–56.
- 734 [34] Marla, L., Rikun, A., Stauffer, G., and Pratsini, E. (2020). Often, the RO
735 Approach and the CCProbst Modeling and Planning: Insights from Three
736 Industrial Applications. *Operations Research Perspectives*, page 100150.
- 737 [35] Miehle, P., Battaglia, M., Sands, P. J., Forrester, D. I., Feikema, P. M.,
738 Livesley, S. J., Morris, J. D., and Arndt, S. K. (2009). A comparison of four
739 process-based models and a statistical regression model to predict growth of
740 Eucalyptus globulus plantations. *Ecological Modelling*, 220(5):734–746.

- 741 [36] Moriguchi, K., Ueki, T., and Saito, M. (2020). Establishing optimal forest
742 harvesting regulation with continuous approximation. *Operations Research*
743 *Perspectives*, 7(April):100158.
- 744 [37] Ponomareva, K., Roman, D., and Date, P. (2015). An algorithm for
745 moment-matching scenario generation with application to financial portfo-
746 lio optimisation. *European Journal of Operational Research*, 240(3):678–687.
- 747 [38] Pour, A. G., Naji-Azimi, Z., and Salari, M. (2017). Sample average approx-
748 imation method for a new stochastic personnel assignment problem. *Com-
749 puters and Industrial Engineering*, 113:135–143.
- 750 [39] Pranevicius, H. and Sutiene, K. (2007). Scenario tree generation by clus-
751 tering the simulated data paths. *Proceedings of 21st European Conference on*
752 *Modeling and Simulation*, page 203208.
- 753 [40] Rios, I., Weintraub, A., and Wets, R. J. (2016). Building a stochastic
754 programming model from scratch: a harvesting management example. *Quan-
755 titative Finance*, 16(2):189–199.
- 756 [41] Ross, K. L. and Tóth, S. F. (2016). A model for managing edge effects in
757 harvest scheduling using spatial optimization. *Scandinavian Journal of Forest*
758 *Research*, 31(7):646–654.
- 759 [42] Schroder, S. A., Tóth, S. F., Deal, R. L., and Ettl, G. J. (2016). Multi-
760 objective optimization to evaluate tradeoffs among forest ecosystem ser-
761 vices following fire hazard reduction in the Deschutes National Forest, USA.
762 *Ecosystem Services*, 22:328–347.
- 763 [43] Schütz, P., Tomasgard, A., and Ahmed, S. (2009). Supply chain design un-
764 der uncertainty using sample average approximation and dual decomposition.
765 *European Journal of Operational Research*, 199(2):409–419.
- 766 [44] Séguin, S., Fleten, S. E., Côté, P., Pichler, A., and Audet, C. (2017).
767 Stochastic short-term hydropower planning with inflow scenario trees. *Euro-
768 pean Journal of Operational Research*, 259(3):1156–1168.

- 769 [45] St. John, R. and Tóth, S. F. (2015). Spatially explicit forest har-
770 vest scheduling with difference equations. *Annals of Operations Research*,
771 232:235257.
- 772 [46] St John, R., Tóth, S. F., and Zabinsky, Z. B. (2018). Optimizing the geom-
773 etry of wildlife corridors in conservation reserve design. *Operations Research*,
774 66(6):1471–1485.
- 775 [47] Tóth, S. F., Haight, R. G., Snyder, S. A., George, S., Miller, J. R., Gregory,
776 M. S., and Skibbe, A. M. (2009). Reserve selection with minimum contigu-
777 ous area restrictions: An application to open space protection planning in
778 suburban Chicago. *Biological Conservation*, 142(8):1617–1627.
- 779 [48] van Vuuren, D. P., Edmonds, J., Kainuma, M., Riahi, K., Thomson, A.,
780 Hibbard, K., Hurtt, G. C., Kram, T., Krey, V., Lamarque, J. F., Masui,
781 T., Meinshausen, M., Nakicenovic, N., Smith, S. J., and Rose, S. K. (2011).
782 The representative concentration pathways: An overview. *Climatic Change*,
783 109(1):5–31.
- 784 [49] Wang, W. and Ahmed, S. (2008). Sample average approximation of ex-
785 pected value constrained stochastic programs. *Operations Research Letters*,
786 36(5):515–519.
- 787 [50] Xu, B., Zhong, P.-A., Zambon, R. C., Zhao, Y., and Yeh, W. W.-G.
788 (2015). Scenario tree reduction in stochastic programming with recourse for
789 hydropower operations. *Water Resources Research*, 51(8):6359–6380.