



**HAL**  
open science

## On the time reversal method for fault diagnosis on a beam: some preliminary results

Mélessandre Huguet, Alireza Ture Savadkoohi, Claude-Henri Lamarque,  
Manuel Collet

### ► To cite this version:

Mélessandre Huguet, Alireza Ture Savadkoohi, Claude-Henri Lamarque, Manuel Collet. On the time reversal method for fault diagnosis on a beam: some preliminary results. *Surveillance, Vibrations, Shock and Noise*, Institut Supérieur de l'Aéronautique et de l'Espace [ISAE-SUPAERO], Jul 2023, Toulouse, France. hal-04165904

**HAL Id: hal-04165904**

**<https://hal.science/hal-04165904>**

Submitted on 19 Jul 2023

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# Fault diagnosis of a beam by time reversal method: numerical approach

Mélessandre HUGUET<sup>1</sup>, Alireza TURE SAVADKOOHI<sup>1</sup>, Claude-Henri LAMARQUE<sup>1</sup>,  
Manuel COLLET<sup>2</sup>

<sup>1</sup>Univ Lyon, ENTPE, Ecole Centrale de Lyon, CNRS, LTDS, UMR5513, 69518 Vaulx-en-Velin, France

<sup>2</sup>Univ Lyon, Ecole Centrale de Lyon, CNRS, ENTPE, LTDS, UMR5513, 69130 Ecully, France  
melissandre.huguet@entpe.fr

## 1 Introduction

Structural health monitoring (SHM) is an important approach in order to evaluate the health state and so the safety and security of structures such as bridges. It also helps to maintain and to extend their servicibilities, to detect and predict their failures. This approach regroups several techniques such as vibration based inspections, acoustic, ultrasonic or magnetic field and radiographic methods. They are based on analyzing variations of some system's characteristics and mapping them to the state of the systems and materials. For instance, in vibration based SHM, the variations of system characteristics in linear and nonlinear dynamics, e.g., frequency and damping shifts, changes of mode shapes and backbone curves, are directly related to the current state of the system.

## 2 Damage detection with time reversal method

### 2.1 The time reversal method

In this study, we use an ultrasonic technique for SHM, known as the Time Reversal (TR) method. This technique is based on the time reversibility of the solutions of wave equation in a lossless medium. Effectively, we can observe in equation (1) that there is only even order derivative. So if  $p(\vec{r}, t)$  is a solution of the problem, then  $p(\vec{r}, -t)$  is a solution too [1].

$$\operatorname{div}\left(\frac{1}{\rho(\vec{r})}\overrightarrow{\operatorname{grad}}(p(\vec{r}, t))\right) - \frac{1}{\rho(\vec{r})c(\vec{r})^2}\frac{\partial^2 p(\vec{r}, t)}{\partial t^2} = 0 \quad (1)$$

The TR is applied in three global steps:

- i) an excitation wave is applied via one set of array of transducers at a point A;
- ii) then, signal are recorded by other set of array of transducers at a point B;
- iii) they are time reversed and are reinjected to the medium at point B and recorded again at point A.

If the wave emitted in step (i) is reflected by a damage, then the re-emitted wave in step (iii) converges towards the reflecting damage. The signal recorded at step (iii) is called "reconstructed signal". Then by comparing the input wave (emitted in step (i)) and the reconstructed wave we can detect the presence of a damage [2, 3].

### 2.2 Principle of experiment

We apply this method on two beams of dimensions  $700 \times 50 \times 5mm$ . The beams are in aluminium and one of them has a rib of depth  $2mm$ . The transducers are piezoelectric patches (PZT) placed on both sides of the damage. The geometry of the damaged beam can be seen in Figure 1. The input wave is a Ricker wavelet defined at a center frequency  $f_c$  and following the equation (2) :

$$f(t) = \left(1 - 2\left(\pi f_c \left(t - \frac{1.25}{f_c}\right)\right)^2\right) \exp\left(-\left(\pi f_c \left(t - \frac{1.25}{f_c}\right)\right)^2\right) \quad (2)$$




Figure 1: Geometry of the damaged beam

After recording the reconstructed wave we compare it with the input wave. From the healthy beam we can observe that the reconstructed wave is a scaled version of the input wave. If damage exists, the reconstructed signal contains a scaled version of the input wave and time shifted components due to the damage. A scheme of the reconstructed signal is presented in Figure 2 where the time shifted component can be observed.




Figure 2: Comparison of input wave and reconstructed signal in case of healthy and damaged structure

### 3 Discussion and conclusion

The experiment showed that we are able to reconstruct the shape of the signal. However, during applying TR method, following items should be taken into account:

- i- controlling the input wave in order to limit the superposition of emitted and reflected wave
- ii- recording the signal during an adapted time in order to catch the damaged component
- iii- differentiate the signal due to damage and those due to boundaries.

For the first point (i), the idea is to choose a wavelet which is locally concentrated such as Ricker wavelet for example. But also to choose an adapted wavelength. For the second point (ii), several measures have to be done in order to choose the best recording and re-emitting window. Finally for the last point (iii), knowing the geometry of the structure we can identify component due to boundaries. Moreover several experiments can also be done with different positions of transducers in order to obtain a better view of the structures. These experiments can help in the localization of the damaged too by measuring the delay of the time shifted component in the reconstructed signal.

## 4 Acknowledgment

The authors would like to thank the following organizations for supporting this research : (i) The Ministère de la Transition Écologique and (ii) LABEX CELYA (ANR-10-LABX-0060) of the Université de Lyon within the program "Investissement d'Avenir" (ANR-11-IDEX-0007) operated by the French National Research Agency (ANR)

## References

- [1] Mathias Fink, *Time reversal of ultrasonic fields - part i. basic principles*, IEEE transactions on ultrasonics, ferroelectrics, and frequency control, 39(5):555-566.
- [2] Hyun Woo Park, Seung Bum Kim, and Hoon Sohn. *Understanding a time reversal process in lamb wave propagation*. Wave Motion, 46(7) :451-467, 2009.
- [3] Aiko Furukawa, Keita Kojima, Junji Kiyono, Kenzo Toki, and Fusanori Miura. *Fundamental study on structural damage detection method for plate structures based on the time reversal technique*.