



HAL
open science

A Nature-Based Solutions Planning Framework for Urban Flood Mitigation at Catchment-Scale

Wenhui Wu, Behzad Jamali, Kefeng Zhang, Ana Deletic

► **To cite this version:**

Wenhui Wu, Behzad Jamali, Kefeng Zhang, Ana Deletic. A Nature-Based Solutions Planning Framework for Urban Flood Mitigation at Catchment-Scale. Novatech 2023, Jul 2023, Lyon, France. hal-04168338

HAL Id: hal-04168338

<https://hal.science/hal-04168338>

Submitted on 21 Jul 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

11^e Conférence internationale

LYON 2023 — L'eau dans la ville | Urban water

Organisée par

graie
PÔLE
EAU & TERRITOIRES

OTTHU

METROPOLE
GRAND LYON

novatech
L'eau dans la ville | Urban water


A Nature-Based Solutions (NBS) Planning Framework for Urban Pluvial Flood Mitigation at Catchment-Scale

Un dispositif pour planifier des solutions basées sur la nature pour réduire les effets des inondations urbaines à l'échelle d'un bassin versant

By Wenhui Wu, Kefeng Zhang, Behzad Jamali, Lucy Marshall and Ana Deletic



Pluvial Flooding: A Growing Challenge




- Regions with *high confidence increase*
- Regions with *medium confidence increase*
- Regions with *high confidence decrease*
- Regions with *medium confidence decrease*

(Source: IPCC, 2021)

NBS for Pluvial Flood Mitigation

2. Runoff/Flood Assessment



Trends

- Place NBS where feasible
- High computational demand in detailed flood modelling
- Lack target-oriented planning at catchment scale


Framework for Planning NBS to Meet Catchment Flood Mitigation Targets

1. Quantify Catchment Flood Volume vs. Flood Damage

Flood models: SWMM + CA-ffé
(Rossman, 2010; Jamali et al., 2019)

2. Set Catchment Flood Damage Reduction Targets

- Targets: reduce flood damage return periods



3. Set Catchment Flood Volume Reduction Threshold

- Filter scenarios of effective impervious area reduction in priority subcatchments


4. Set Subcatchment Runoff Volume Reduction Targets

- Calculate required % reduction in runoff volume in subcatchments

5. Select NBS Using Design Curves



- NBS sizing according to subcatchment runoff volume reduction targets

6. Check Reduction in Flood Damage



Case Study: Coogee Catchment, Sydney, Australia


<https://doi.org/10.1016/j.watres.2023.11988>
8



Highly urbanised catchment 2.9km² in size, 5-10% Slope. Priority subcatchments for NBS implementation in Green.

(Source: Coogee Bay Flood Study Final Report - Randwick City Council, 2013)



1. Catchment Flood Volume vs. Flood Damage



2. Flood Damage Reduction Targets



Targets	Reduction in Flood Damage Return Period
---------	---

- | | |
|---|------------------------------------|
| 1 | 5%AEP (60min) to 10%AEP (60min) |
| 2 | 10%AEP (60min) to 20%AEP (90min) |
| 3 | 20%AEP (90min) to 50%AEP (90min) |
| 4 | 50%AEP (90min) to 63.2%AEP (90min) |



Distribution of Critical Duration (min)
Under Design Storm of 5%AEP

3. Set Catchment Flood Volume Reduction Threshold



Generate Flood Volume Reduction Scenarios under 5%AEP 60min Design Storm

- Monte Carlo: Sobol sampling sequence
- Sample 0-100% reduction in Effective Impervious Area (EIA) in each priority subcatchment

Scenario 1:

- Sub 1 – 20% EIA Reduction
- ...
- Sub 19 – 40%

...

Scenario X:

- Sub 1 – 10% EIA Reduction
- ...
- Sub 19 – 50%




Scenario	Reduced Flood Volume (1000m ³)
1	<12.353 ☹️
...	
X	≥12.353 😊

Total Number of Scenarios X = 10240

- Top 100 Scenarios

4. Set Subcatchment Runoff Volume Reduction Targets


Top 100 Scenarios	% Reduction in Subcatchment Runoff Volume		
	Sub 1	...	Sub 19
1	20		40
...			
100			



5. Select NBS Using Design Curves


- Bioretention as an example
- Global sensitivity analysis (Sobol) on site characteristics and NBS design parameters

Group	Parameters	
Site Characteristics	Rainfall	
	Subcatchment Size (100% impervious)	
	Subcatchment Width	
	Subcatchment Slope	
	Manning's n for impervious area	
	Depression storage for impervious area	
	Subcatchment Soil Minimum infiltration rate	
Bioretention Design	Effective Storage Capacity	Surface area (% of subcatchment area)
		Filter layer depth
		Storage layer depth
	Extended detention depth	
	Hydraulic conductivity	




(Adopted from Goh et al., 2019)

Representative Design Curves




6. Reduction in Flood Damage

- Representative NBS strategies for Flood Damage Reduction Target 1 (5%AEP → 10%AEP)



Cost: Bioretention Surface Area

Benefit: Reduction in Flooding Annual Average Damage



Implications and Future Work

- An effective framework for selecting NBS strategies to meet catchment-scale flood damage reduction targets
 - Easy to understand message: to reduce the damage level from one AEP to another
 - Flexibility in choice of NBS using design curves
- Damage reduction targets are catchment-specific (importance of design storm selection)
 - More comprehensive cost-benefit analysis (Life Cycle Cost)
 - Need to consider long-term performance – continuous simulation using rainfall records



Blue-Green Systems




IWA Publishing's newest **Open Access** journal brings together cutting edge research on sustainable, energy efficient and environmentally responsible water use in cities and their regions, including innovative approaches such as Sponge Cities, Low Impact Development, Nature Based Solutions and Water Sensitive Urban Design.

- **NEW Impact Factor: 4.6; Citescore: 6.3**

Papers will report significant advances in the following categories:

- Technology
- Fundamental science
- Applications/demonstrations
- Planning the urban environment
- Policy management

Environmental Science



Environmental Science
Water Science and Technology



Editors-in-Chief

Ana Deletic

School of Civil and Environmental Engineering, Queensland University of Technology, **Australia**


Jiuhui Qu


Research Center for Eco-Environmental Sciences, Chinese Academy of Sciences **China**





iwaponline.com/bgs

Supplementary

Runoff Volume Reduction (%)








- ☆ Target Damage Reduction Level
- Baseline
- NBS Strategy 1 Most Damage Reduction
- NBS Strategy 2 Least Bioretention Area
- NBS Strategy 3 Average

Annual Exceedance Probability (AEP)

Reduction in Annual Average Damage of Flooding

Flood Damage Reduction Targets		Representative Strategies		
		NBS Strategy 1 Most Damage Reduction	NBS Strategy 2 Least Bioretention Area	NBS Strategy 3 Average
1	5%AEP (60min) to 10%AEP (60min)	1.222	0.994	1.018
2	10%AEP (60min) to 20%AEP (90min)	1.156	1.076	0.960
3	20%AEP (90min) to 50%AEP (90min)	1.544	1.495	1.479
4	50%AEP (90min) to 63.2%AEP (90min)	0.934	0.752	0.738

Reduction in Annual Average Damage vs. Bioretention Effective Storage Capacity



Distribution of Sub' Runoff Volume Reduction Targets under two most cost-effective NBS implementation strategies

