

SPEKTRE, a linear radiofrequency device for investigating edge plasma physics

F. Brochard, D Genève, V Bobkov, E Faudot, S Heuraux, Daniele del Sarto, Maxime Lesur, N Louis, A. Ghizzo, Etienne Gravier, et al.

▶ To cite this version:

F. Brochard, D Genève, V Bobkov, E Faudot, S Heuraux, et al.. SPEKTRE, a linear radiofrequency device for investigating edge plasma physics. 49th EPS Conference on Plasma Physics, Jul 2023, Bordeaux, France. . hal-04171521

HAL Id: hal-04171521

https://hal.science/hal-04171521

Submitted on 26 Jul 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

SPEKTRE, a linear radiofrequency device for investigating edge plasma physics

F. Brochard^{1,*}, D. Genève¹, S. Heuraux¹, V. Bobkov², D. Del Sarto¹, E. Faudot¹, A. Ghizzo¹,

E. Gravier¹, N.Lemoine¹, M. Lesur¹, N. Louis³, J. Moritz¹, T. Reveillé¹, V. Rohde², U. Stroth²,

G. Urbanczyk², F. Volpe³, H. Zohm²

Université de Lorraine, Institut Jean Lamour, CNRS, F-54000 Nancy, France
 Max-Planck Institute für Plasma Physics, Boltzmannstr. 2, D-85748 Garching, Germany

3 Renaissance Fusion, F-38600 Fontaine, France

* frederic.brochard@univ-lorraine.fr









métropole GrandNancy







SPEKTRE (Sheaths, Plasma Edge & Kinetic Turbulence Radiofrequency Experiment) is a research platform in plasma physics and nuclear fusion, currently under construction in the Institut Jean Lamour (Nancy). SPEKTRE is the result of a cooperation within a research agreement between the University of Lorraine and the IPP Garching. It will produce a plasma 40 cm in diameter and 6 m long, under a maximum magnetic field of 0.5 Tesla generated by 13 large flat coils of the former W7-AS stellarator. The first plasma is scheduled for late 2023, and will be followed by a gradual ramp-up to enable research in the following areas:

- Physics of RF sheaths and ICRF heating;
- Instabilities in magnetized plasmas, turbulent transport of impurities;
- · Targeted studies on plasma-wall interactions, including liquid metal wall;
- Beyond the scope of fusions plasmas, surface treatments by magnetized plasmas.

Conceptual Design

SPEKTRE was originally designed to be a step beyond the IShTAR device [1].

The final design integrates the IShTAR's helicon source chamber and 13 planar coils from former W7-AS stellarator, in the frame of a research agreement between MPG-IPP and the University







CAD views of the assembled device with and without the coils, respectively.

- Main vacuum vessel 5 97 m long ø 0 9 m
- Plasma diameter 0.4 m
- 42 ports available for diagnostics





Side view (top) and B-field configuration in the main chamber @ 0.5 T (bottom)



The Skyfall-I LM test bed at Renaissance Fusion (top left), scheme of principle (top right) and design implementation of the LM test-bed on SPEKTRE for dedicated campaigns with Renaissance Fusion (bottom).



Current status and next steps

Current status:

- Coils and supporting structures are in place
- Main vacuum vessel is being manufactured and will be installed in September 2023.
- Helicon plasma source is being adapted to the new vacuum vessel, new RF generator arriving this fall.

Next steps:

- First plasma in Dec. 2023 (no B field in the main coils)
- Coils connected to cooling and power supplies by summer 2024, first experiments with homogeneous 0.1 T by sept. 2024.
- Installation of banks of capacitors for 0.5 T operation and ICRF generator and antenna expected by mid-2026.

edge plasmas, Rev. Scientific Instrum. 90, 083506 (2019).



installation of the main vacuum vessel

Operational Phase I

B-field: max 0.1 T, stationary.

Technical capabilities

- RF power: 6 kW @ 13.56 MHz (only helicon source).
- Cold ions, $T_{\rm e}$ in the eV range and low plasma density expected ($10^{16}-10^{18}~{\rm m}^{-3}$ with H), derived from $0^{\rm th}$ order model. H plasmas dominated by longitudinal losses, He plasmas dominated by radial losses.

(2023 - 2025)

- Development, testing and installation of diagnostics and main auxiliary systems.
- Fundamental investigations on plasma instabilities in large, lowmagnetized plasma columns [2].
- First experiments with LM SkyFall test-bed (Renaissance Fusion).
- Education & training.

(from 2026/2027)

Operational Phase II

Technical capabilities

- and still 0.1T stationary in dedicated campaigns.
 RF power: 20 kW @27.2 MHz (helicon source) and up to 100 kW ICRF @ 13.56 MHz.
- Standard scenario: B = 0.44 T, 120 kW RF.

He n_e (m⁻³) 3.4 10¹⁶ (a) 6.5 10¹⁶ (a) 2.7 10¹⁹ (b) 3.5 10¹⁹ (b) T_e (eV) ~10 (1-100) ~10 (1-100) T_i (eV) 6.5 - 26 6 - 10

Expected plasma parameters at B = 0.5T with (a) 20 kW RF, T_e = 100 eV; (b) 120 kW RF, T_e = 1 eV

Research Program

- RF sheath and ICRH:
 - Exp. & modelling of RF sheaths & their effects around antennas (Petra-M + TORIC)
 - Interpretation of RFA and Probe diagnostics in RF plasmas
 - RF active compensation based on the excitation of slow waves
 - Arcing in presence of RF field
 - Improving RF coupling while minimizing heat flux and impurity release [3]
- Turbulent transport and impurity transport
 - Experimental characterization of impurity transport and comparison with modelling with GYSELA « R∞ » version
 - $\bullet\,$ Propagation of waves in the $\mu\text{-wave}$ range in turbulent plasma
- **Dedicated PWI investigations**
 - Thresholds for triggering and sustaining unipolar arcs in magnetized plasma (exp. and PIC simulations)
 - Impurity and droplets release by arcs
 - Physics and control of flowing liquid metal walls, link to the release and transport
 of metal impurities (experiments, PIC and GYSELA simulations)
- Fundamentals of magnetized plasmas
- Diagnostics and software development, including AI and real-time control
- Surface treatments by low-temperature magnetized plasmas (0.1 T): improving uniformity for large samples
- Education & training

Conclusion and perspectives

SPEKTRE is a new magnetized plasma research facility about to start operation. After a first operational phase during which the machine will be progressively upgraded, SPEKTRE will acquire some fairly unique features (a large-volume, well-magnetized plasma column with 100 kW of ICRF heating) combined with many diagnostic possibilities, that will make it an accessible instrument for the study of phenomena of broad interest in magnetized plasmas.

The SPEKTRE team is widely open to collaborations

[3] G. Urbanczyk, Main challenges of heating plasma with waves at the Ion Cyclotron Resonance Frequency (ICRF), in « Advances in Fusion Energy Research — Theory, models, algorithms and Application », IntechOpen, London.10.5772/intechopen.105394. ISBN: 978-1-80356-279-7 (2022).

Acknowledgement: This work has been carried out within the framework of the EUROfusion Consort

References

[1] I. Shesterikov, K. Krombe, A. Kostic et al., IShTAR: a test facility to study the interaction between RF wave and

[2] M.J. Pueschel, G. Rossi, D. Told, P.W. Terry, F. Jenko and T.A. Carter, A basic plasma test for gyrokynetics: GDC

turbulence in LAPD, Plasma Phys. Control. Fusion 59, 024006 (2017). G. Rossi, Electromagnetic turbulence and

transport in increased beta LAPD plasmas, UCLA Electronic Theses and Disseration, 2021.



