

Molecular dynamics approach for the calculation of the surface loss probabilities of neutral species in argon-methane plasma

Glenn-christopher Otakandza-Kandjani, Pascal Brault, Maxime Mikikian, Armelle Michau, Khaled Hassouni

▶ To cite this version:

Glenn-christopher Otakandza-Kandjani, Pascal Brault, Maxime Mikikian, Armelle Michau, Khaled Hassouni. Molecular dynamics approach for the calculation of the surface loss probabilities of neutral species in argon-methane plasma. Plasma Processes and Polymers, 2024, 21, pp.e2300120. 10.1002/ppap.202300120. hal-04176502v2

HAL Id: hal-04176502 https://hal.science/hal-04176502v2

Submitted on 9 Aug 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



DOI: 10.1002/ppap.202300120

AND POLYMERS

Check for updates

RESEARCH ARTICLE

Molecular dynamics approach for the calculation of the surface loss probabilities of neutral species in argon-methane plasma

Glenn-Christopher Otakandza-Kandjani¹ | Pascal Brault¹ | Maxime Mikikian¹ | Armelle Michau² **□** Khaled Hassouni²

¹GREMI, UMR7344, CNRS - Université d'Orléans, Orléans, France

²LSPM, UPR3407, CNRS/Université Sorbonne Paris Nord, Villetaneuse, France

Correspondence

Pascal Brault, GREMI, UMR7344, CNRS - Université d'Orléans, 45067 Orléans Cedex 2, France. Email: pascal.brault@univ-orleans.fr


Funding information

National Scholarship Agency of Gabon; CaSciModOT; Agence Nationale de la Recherche: MONA project. Grant/Award Number: ANR-18-CE30-0016

Abstract

Molecular dynamics simulations are carried out for calculating the surface loss probabilities of neutral species from an argon-methane plasma. These probabilities are the sum of the sticking and surface recombination probabilities. This study considers both the formation of reactive and nonreactive volatile species for evaluating recombination probabilities. Results show that stable species are reflected when hydrocarbon film starts growing on the surface. CH3 is mainly lost by surface recombination leading to the formation of volatile products while

very little contributes to film growth. C2H has surface loss probability in agreement with the literature. While C₂H loss is usually attributed to sticking on the surface, our results show that its main loss process is due to surface recombination.



KEYWORDS

C:H film, hydrocarbon plasma, molecular dynamics, sticking probability, surface loss probability, surface recombination probability

INTRODUCTION 1

Low-temperature hydrocarbon plasmas are weakly ionized gases, containing a variety of different species (electrons, ions, neutrals, radicals, etc). [1-3] These plasmas are an important tool for the fabrication of materials such as carbon nanotubes, nanowalls, and other advanced carbon nanostructures. [4,5] These materials have a wide range of applications, such as composite

materials for construction, drug delivery, energy storage and conversion, and so on. [6,7] These plasmas are also used to deposit thin films of diamond and diamond-like carbon (DLC),[8,9] commonly used for their infrared transparency or as hard coatings for tools and optical devices. [10-12] However, despite this interest, the complexity of the chemical reactions that take place in these plasmas makes their understanding and control quite difficult, since they are governed by reactions occurring ______

This is an open access article under the terms of the Creative Commons Attribution License, which permits use, distribution and reproduction in any medium, provided the original work is properly cited.

© 2023 The Authors. Plasma Processes and Polymers published by Wiley-VCH GmbH.

both in the volume and on the surrounding surfaces. Surface reactions can significantly affect the plasma phase chemistry. These reactions depend on the surface properties (e.g. materials, structure, density of dangling bonds), and on the energy and nature of the incoming particles interacting with the surface. The sticking probability is a key parameter that provides information about the contribution of the plasma species to the growth of films on the surface. The calculation of the sticking probabilities is based on empirical approaches and their values can sometimes be very rough approximations since their experimental measurements are relatively complex. [15,16]

The sticking probabilities are often estimated to be zero for nonradical neutral species since they are not expected to contribute to film growth. Thus, the growth of a hydrocarbon (C:H) film on the surface results from radicals and ions impinging on the surface. The sticking probabilities of ions impinging on the surface are assumed to be close to one and are determined by numerical simulations. The sticking probabilities of ions impinging on the surface are

To calculate the sticking probability for radical neutral species, one approach is to measure the "surface loss probability (β)" also named "surface reaction probability." [15,16] In these works, this probability is defined as the sum of the sticking probability and the probability that the species reacts via surface reactions to form a nonreactive volatile product (also called surface recombination probability). [13,15,16] Therefore, this surface loss probability, which is equal to the upper limit of the sticking probability, is at present used to estimate the sticking probability of various hydrocarbon radicals. [15]

Hopf et al.^[15] experimentally measured the surface loss probabilities of various hydrocarbon radicals during the growth of amorphous hydrogenated carbon films (a-C:H, with H to C ratio greater than or equal to 1, i.e., soft films). Based on the spatial variation of the thickness of the a-C:H film (deposition profile), the authors derived the surface loss probability and then estimated the sticking probability. They found that the surface loss probability of the C₂H radical was about 0.9 in acetylene-based plasmas and 0.8 in other hydrocarbon plasmas. Using these values, the authors were able to determine the sticking probability by estimating the surface recombination probability. For the CH₃ radical, its surface loss probability is estimated to be less than 0.01 and may change depending on the plasma conditions.^[16]

The question that we wish to address in our study is to calculate independently sticking and surface recombination probabilities of the species during the growth of C:H films in argon-methane plasmas by atomistic methods, taking into account the formation of both reactive (usually not considered) and nonreactive volatile products.

Molecular dynamics (MD) simulations have been widely used to calculate sticking probability (S), and reflection probability (r) of gas species interacting with a surface. [21–27] Knowledge of the reflection probability, allows us to deduce the surface loss probability β , since $r = 1 - \beta$. [13]

For example, Sharma et al.^[24] performed MD simulations to determine the reflection probabilities of hydrocarbon molecules and radicals on an a-C:H surface. The authors observed that these reflection probabilities decreased with increasing incident energy of the radical, leading to an increase in surface loss. On the other hand, the authors observed that at low energies (up to 0.75 eV) stable hydrocarbon species (neutral, nonradical species) had a reflection probability of 100% (i.e., no loss at the surface) and that hydrocarbon radicals with fewer hydrogen atoms had high surface loss probabilities compared with those with more hydrogen atoms.

Alman and Ruzic^[25] studied the reflection probabilities of hydrocarbon radicals on a "soft" and "hard" carbon surface using MD simulations. The "soft" surface was a layer of a-C:H redeposited on a graphite surface, and the "hard" surface was a graphite network bombarded with hydrogen. The authors found that the surface loss probabilities of hydrocarbon radicals were higher on the soft surface than on the hard surface. And as for the stable neutral species, the authors found that regardless of the type of surface, they were completely reflected at low energy and underwent fragmentation at high energy (from about 2 eV).

MD simulations are therefore relevant to determine either the sticking probability or the reflection probability of a species. To our knowledge, these methods have not yet been used to distinguish losses due to sticking from those due to surface recombination.

Therefore, the goal of our study is to determine the surface loss probabilities of the major neutral species (H_2 , CH_4 , C_2H_4 , C_2H_2 , and CH_3 , excluding Ar) of an argon–methane plasma at room temperature (300 K) using MD simulations. These surface loss probabilities are calculated by determining the sticking and surface recombination probabilities (taking into account non-reactive and reactive volatiles) of each of these species during the growth of a C:H film on a stainless steel surface. These initial neutral species interacting with the surface are obtained from a 1D kinetic model of a low-pressure Ar/4% CH_4 plasma created by a radiofrequency discharge. [28–30]

This article is organized as follows: In the next section, we present the methodology and computational details. In Section 3, we first present the sticking probabilities of each neutral species on two types of surfaces: a pristine surface and a surface covered with a

C:H film. In Section 4, we discuss the surface loss probabilities of these same species during the growth of the C:H film and we present a mass spectrum of the formed volatile products.

2 | METHODOLOGY AND COMPUTATIONAL DETAILS

2.1 | MD

MD is a powerful computational method for modeling matter at the atomic scale. It consists in numerically solving Newton's equations of motion (Equation 1) of particles (atoms or molecules) forming a system whose interactions are determined by an interatomic potential describing the forces between these particles.^[31,32]

$$\vec{F}_{i} = m_{i} \frac{d^{2} \vec{r}_{i}}{dt^{2}} = -\frac{\partial U}{\partial \vec{r}_{i}} (\vec{r}_{1}, \vec{r}_{2}, \vec{r}_{3}, ..., \vec{r}_{N}).$$
 (1)

Solving Equation (1) requires the availability of the interatomic potential U, which must be a function of the coordinates of each atom i. It also requires two sets of initial conditions, positions, and velocities, which can be derived from experiments or kinetic models.

Our study is based on the interaction of hydrocarbon species with electrodes described by a stainless steel surface composed of iron (Fe), chromium (Cr), molybdenum (Mo), and nickel (Ni). The potential describing the different interactions of our system can be written like this:

$$U_{\text{system}} = U_{\text{HC}} + U_{\text{surf}} + U_{\text{HC-surf}},$$
 (2)

where $U_{\rm HC}$ stands for the C-C, C-H, and H-H interactions, $U_{\rm surf}$ for the interactions between the surface atoms (Fe, Cr, Mo, and Ni) and $U_{\rm HC-surf}$ for the interactions between the atoms of the hydrocarbon molecules and those of the surface.

Reactive interatomic potentials including bond-breaking and bond-forming processes are necessary to describe $U_{\rm HC}$. The simplest and most robust potential is the REBO (Reactive Empirical Bond Order) potential, which has been extended to AIREBO (Adaptive Intermolecular Reactive Empirical Bond Order) to include long-range and torsional forces. Another class of reactive interatomic potentials includes partial charge dynamics in addition to bond order. Among them, COMB (Charge Optimized Many Body) and ReaxFF (Reactive Force Field) are the most commonly used. Teaching density functional theory (DFT) to select the best potential describing the reactions leading to

the growth of hydrocarbon polymers on a silver substrate. Their DFT study predicted a reaction without an energy barrier, which is verified for REBO and the Arvanpour parameterization of ReaxFF, [41] whereas the other potentials indicated the existence of an unphysical reaction barrier. [40] Therefore, based on this work and considering the widespread use of the REBO potential for modeling interactions involving hydrocarbons^[21,40,42–45] and its computational speed compared with ReaxFF,[46] the REBO potential was chosen in this work to describe U_{HC} . The REBO potential captures essential aspects of chemical bonding, especially for reactions in which covalent bonds are broken and formed. It distinguishes between radical and nonradical hydrocarbon species based on the concept of bond order. Radicals are modeled by assigning fractional bond orders to specific bonds. In contrast, nonradical hydrocarbon species are generally assigned integer bond orders corresponding to standard single, double, or triple bonds, depending on their connectivity and the number of valence electrons.^[34]

The interactions between the atoms of the surface $(U_{\rm surf})$ are built using the embedded-atom method, and the interactions between the atoms of the hydrocarbon molecules and the surface $(U_{\rm HC-surf})$ were modeled using the Lennard–Jones (LJ) potential. [42,51]

2.2 | Input data

Input data, that is, initial main neutral species, are obtained from a one-dimensional (1D) fluid model^[28,29] that mimics the experimental conditions of a low-pressure capacitively coupled Ar/CH₄ radio frequency plasma generated in a 2.54 cm discharge gap between 20 cm diameter electrodes. The operating conditions of the 1D fluid model are listed in Table 1, and the corresponding initial neutral species are listed in Table 2.

2.3 | Simulation approach

Our approach to model the interaction processes between the neutral species, listed in Table 2, and the surface consists in depositing the species from a region above the surface and giving them initial velocities directed toward that surface, as shown in Figure 1a. The surface is a stainless steel slab that mimics the electrodes of an experimental device. Its composition is Fe₆₇Cr₁₇Ni₁₄Mo₂, that is, 67% Fe, 17% Cr, 14% Ni, and 2% Mo. Periodic boundary conditions apply to the lateral boundaries (*x-y*) of the system (Figure 1a) and deposition occurs in the *z*-direction (i.e., (001) orientation of the slab). The stainless steel slab of size $4.018 \times 4.018 \times 1.4 \text{ nm}^3$ contains 1960 atoms and is divided into three zones as shown in

16128696, Downloaded from https://onlinelibrary.wiley.com/doi/10.1002/ppap.202300120 by Cochraen France, Wiley Online Library on [09/08/2023], See the Terms and Conditions (https://onlinelibrary.wiley.com/erms-and-conditions) on Wiley Online Library for rules of use; OA articles are governed by the applicable Creative Commons Licensen

Figure 1a. [40,42,52,53] The bottom fixed atom zone prevents the movement of the slab upon impact of species on the surface. The thermostated atoms zone (or stochastic zone) is the zone where a Langevin thermostat was applied to dissipate heat and absorb the energy of the upper zone. The freely moving atoms zone (or reaction zone) is the zone

TABLE 1 Reference data of the 1D fluid model from which the input data of our study are derived.

Reference conditions	
Temperature	300 K
Pressure	70 Pa
Vrf	100 V
Frequency	13.56 MHz
Interelectrode distance	2.54 cm
Secondary emission electron probabilities	0.01
Percentage of argon	96
Percentage of methane	4

TABLE 2 Main neutral species resulting from the 1D fluid model used as input for the MD simulations.

Main neutral species	Molar fractions
H_2	3.20×10^{-2}
CH ₄	1.40×10^{-2}
C_2H_4	5.40×10^{-3}
C ₂ H	3.20×10^{-3}
C_2H_2	2.70×10^{-3}
CH ₃	2.30×10^{-3}

Note: Argon is not included in our simulations. [30]

where the incident species and surface atoms can interact freely and without constraint. To mimic the flow of the species to the surface, the molecules are sent to the surface one after the other.

MD model for the calculation of the individual sticking probability

First simulations were performed to determine the individual sticking probability of the different species on a pristine surface (Figure 1a) and on a surface covered with a previously deposited hydrocarbon film (Figure 1b). This C:H film contains a total of 975 carbon and hydrogen atoms with an H:C ratio of 0.6. The surface and the impinging species are set at room temperature (i.e., 300 K). Several simulations were performed. Each of them consists of the impingement of a molecule, 100 times, at a rate of one molecule every 2000 time steps (0.25 fs) over a 50 ps time. To obtain significant statistics, five simulations (with different initial positions and velocities) are performed for the deposition on both surfaces.

2.3.2 | MD model for the calculation of surface loss probabilities during C:H film growth

The goal of these simulations is to determine the surface loss probabilities of each neutral species during the growth of the C:H film on the surface. To perform these simulations, all neutral species (49,600 molecules in total) are sent to the pristine surface (Figure 1a) at a rate of one molecule every 2000 time steps (i.e., every 500 fs) for a total time of 26 ns, taking into account the mole fraction of each species (Figure 2, 800 times repeating the cell framed in pink).




FIGURE 1 (a) Stainless steel slab mimicking pristine electrodes. It is composed of 67% Fe (silver color), 17% Cr (ocher color), 14% Ni (ice blue color), and 2% Mo (tan color). This surface is characterized by three zones (fixed, thermostated, and reactive). (b) Same surface is covered with a hydrocarbon film.




FIGURE 2 Schematic representation of the initial layout of the system for sending all species together (one by one). The cell framed in pink represents the deposition of a cycle of neutral species repeated 800 times.

Such a rate of deposition is high as often in MD simulation. The effect of this unphysically high flux is compensated by the substrate thermostat, which prevents unphysically high-temperature increase due to energy transfer at impact.

The species are sequentially released, from a random position above the substrate, toward the surface with velocities randomly selected in a Maxwell–Boltzmann velocity distribution at 300 K.^[54,55] Five simulation runs (with different initial velocity sets) were also performed.

All the MD simulations were carried out using the open-source code LAMMPS (Large-scale Atomic/Molecular Massively Parallel Simulator). [56] VMD software was used to visualize the MD results and Python scripts were written for data processing. [57,58]

All plots in this study were obtained from the average over the five simulations with very small standard deviations (on the order of 10^{-4}).

3 | RESULTS AND DISCUSSION

3.1 | Sticking probability (S) on pristine and hydrocarbon film-covered surface

In this section, we present the individual interaction of each species (i.e., the impingement of only 100 molecules of each neutral species per simulation, according to the procedure described in subsection 2.3.1) with a pristine

surface (Figure 1a) and a surface covered with a C:H hydrocarbon film (Figure 1b) by determining the sticking probability (S). This describes the ratio between the number of atoms (or molecules) that adsorb or "stick" to the surface and the total number of atoms that strike this surface during the same period. [21] Its value lies between 0 (no atom sticks) and 1 (all atoms that hit the surface stick) and is defined as follows:

$$S = \frac{N_{\text{st}} \quad (\text{with} \quad z \le z_c)}{N},\tag{3}$$

where $N_{\rm st}$ is the number of atoms or molecules sticking to the surface and N the total number of incident species, $z_{\rm c}$ is the critical height, above which there are no more bonded atoms/molecules to the growing film. All species with $z>z_{\rm c}$ are considered as reflected. The sticking probabilities of the different neutral species on a pristine stainless steel surface (S_0) and on a stainless steel surface covered with a C:H film $(S_{\rm c})$ are presented in Figure 3.

It can be observed that the S_0 of all neutral species on a pristine surface (Figure 3 blue bar) is high (around 0.8, except for H_2) compared with the values S_c on the surface covered with the C:H film (Figure 3 green bars). This is due to the fact that on the pristine surface, the species easily find a stable anchoring site to be able to stick whereas on the surface covered with the C:H film, the search for a reactive site is more difficult. With the exception of the C_2H radical (which has the highest S_c because of its very reactive character), the other species have S_c lower than 0.2. For the CH_3 radical, the low S_c is explained by the fact that this molecule requires dangling bond sites on the surface of the C:H film to be able to stick. [22,59-61]




FIGURE 3 Sticking probability of the main neutral species of argon-methane plasma on a pristine stainless steel surface (blue bars) and on a stainless steel surface covered with a C:H film previously deposited (green bars).

16128869, 0, Downloaded from https://onlinelibrary.wiley.com/doi/10.1002/ppap.202300120 by Cochrane France, Wiley Online Library on [09/08/2023]. See the Terms and Conditions (https://onlinelibrary.wiley

and-conditions) on Wiley Online Library for rules of use; OA articles are governed by the applicable Creative Commons License

The sticking probability of C_2H obtained in our study is rather different from the one used in the literature (about 0.8)^[15,16] and is supposed to be obtained on amorphous C:H film surfaces. The value obtained in our study, which is close to that in the literature, is the value calculated on a pristine surface, whereas the value calculated on a C:H film is $\frac{1}{2}$ times lower than the value used in the literature while it was expected to be similar. Before drawing any conclusion on this discrepancy, in the next section, we will discuss the surface reaction probabilities of each neutral species when releasing all the initial neutral species one after each other as shown in Figure 2.

3.2 | Surface loss probabilities of main neutrals species during film growth

Various phenomena can occur during the interaction of neutral species with the surface. They can return to the gas phase with a reflection probability r, and react with other species at the surface to form volatile hydrocarbons (C_xH_y) with a recombination probability γ (these volatile species diffuse at the surface and are then desorbed into the gas phase) or form a chemical bond with the surface with a sticking probability S (film formation). These last two events result in the loss of the particle from the gas phase and are described by the surface loss (or surface reaction) probability $\beta = S + \gamma$. [13,15,62] The set of these events for a single specie is shown in Figure 4 and is summarized by the following expression:

$$r + S + \gamma = r + \beta = 1. \tag{4}$$

Figure 5a–c represent, respectively, the temporal evolutions of the sticking probability *S*, the surface recombination




FIGURE 4 Illustration of the surface mechanisms (reflection, recombination, and sticking) during the interaction of a neutral species with the surface. (adapted from Benedikt^[13]).




FIGURE 5 Temporal evolutions of the sticking probability S (a), surface recombination probabilities γ (b), and surface loss probabilities β (c) of each neutral species during the growth of the C:H film.

probability γ , and the surface loss probability β of each neutral species during the growth of the C:H surface film from a pristine surface. For this part, the neutral species were sent together one after the other, as described in subsection 2.3.2, to achieve a collective behavior that would allow the experiments to be mimicked.

In Figure 5a we see that, at the early time, (between 0 and 1 ns), except for H_2 , the sticking probabilities of the

stable hydrocarbon species, namely CH₄, C₂H₂, C₂H₄, are high (between 0.6 and 0.9), and then decrease as the C:H film grows on the surface, becoming almost 0 after 5 ns. This behavior is due to the fact that these molecules stick easily when the surface is pristine (i.e., without a C:H film on the surface), but when the C:H film starts to form on the surface, their sticking is lowered, as also shown in Figure 3 for the individual sticking probabilities. It is also observed that these stable molecules do not participate in the surface reactions to form volatile species, since their surface recombination probabilities are almost zero over time (Figure 5b). This is justified by the fact that these species are very little reactive and thus less involved in the formation of new species.^[13,20] This leads finally to low surface loss probabilities for all these stable species (Figure 5c) and indicates that they return to the gas phase after the very first nanoseconds without any change.

In the literature, the growth of C:H films in hydrocarbon plasmas is assumed to be due to radicals and the stable species are usually considered to be fully reflected by the surface. [13,18,20,28] This assumption is true when the surface is no longer pristine (presence of a C:H film). At the beginning of the deposition, we observe that the stable species are not fully reflected when the surface is pristine, and they contribute to growth. They are fully reflected only once the C:H first layers are formed, screening thus the interactions with the stainless steel surface. So their role in the formation of the first monolayer should not be neglected.

However, in experiments, it is very unlikely that electrodes are pristine at the ignition of plasma, which means that the behavior of the stable species in the first times observed in our simulations is not experimentally accessible. On the other hand, their behavior in the presence of a C:H film on the surface is consistent with the literature. [13,15,16,20,63] Furthermore, Sharma et al. [24] also observed through MD simulations that these species (H₂, CH₄, C₂H₂, C₂H₄, and H₂) were fully reflected after their interaction with a C:H surface at room temperature. Nevertheless, the interaction of incident neutral species with a pristine surface is relevant because it provides information about the contribution of stable species to the formation of the first hydrocarbon monolayer in the very first times of simulation or plasma ignition, after that the role of the substrate is quickly screened by the growing film.

For the CH₃ radical (Figure 5a), *S* is high in the first instants (between 0 and 1 ns) and becomes constant to a very low value (0.02) after 5 ns, which implies that this radical contributes to the film growth only at the very beginning. Indeed, once a C:H film is formed on the surface, the CH₃ radical needs available dangling bond

sites to be able to stick, [22,59] which is much more difficult.

In a review paper by $Jacob^{[20]}$ about the surface growth of hydrocarbon films, the sticking probability of CH_3 is shown to be negligible. This probability can increase depending on the available surface dangling bonds, $^{[64,65]}$ which are created by ionic or atomic hydrogen bombardment. $^{[66,67]}$ Atomic hydrogen and ions are not considered in the present study and this effect cannot be evidenced by our simulations.

Moreover, the presence of species more reactive than CH_3 , such as C_2H , can reduce its sticking to the surface. This was observed, for example, in the work of Bauer et al. [59] studying film deposition in pulsed inductively coupled methane plasmas, where the authors found that the CH_3 radical played a role in film growth only at pressures where highly reactive radicals such as C_2H were deactivated.

We can also observe in Figure 5b that the surface recombination probability $\gamma(\text{CH}_3)$ increases nearly linearly with time showing that CH_3 does contribute to the formation of volatile products, and thus can play a role in the gas-phase plasma chemistry. These results lead to a high $\beta(\text{CH}_3)$ in the early time deposition (<1 ns), which then decreases to a minimum value and then slowly increases [due to the behavior of $\gamma(\text{CH}_3)$] reaching a value around 0.6 after 22 ns. In the literature, [15,16,68] β (CH₃) is considered to be smaller than 0.01, since the surface loss probability is very often expressed in terms of the sticking coefficient, [18] and thus $\gamma(\text{CH}_3)$ is largely neglected. The present results show that $\gamma(\text{CH}_3)$ cannot be neglected and should therefore be taken into account.

Concerning the C_2H radical, it is observed that S (C₂H) (Figure 5a) is the highest in the first instants (<1 ns) and then slowly decreases but remains larger than the sticking probabilities of the other molecules. For example, we can see that $\beta(C_2H)$ is higher than $\beta(CH_3)$, which is consistent with the work of Sharma et al., [24] who find that radicals with fewer hydrogen atoms have a higher surface loss probability than those with more hydrogen atoms. These observations indicate that the C₂H radical is the main precursor of the growth of the C:H film on the electrode surface. This radical is one of the species that do not require a specific adsorption site on the surface to chemisorbs due to its highly reactive nature. [13,17,18,59] However, we can observe that the decrease of $S(C_2H)$ [(Figure 5a) is counterbalanced by the temporal increase of $\gamma(C_2H)$, leading to an almost constant $\beta(C_2H)$ (Figure 5c) (around a value of 0.8) after 1 ns.

This value of 0.8 for $\beta(C_2H)$ agrees well with the experimental value obtained by Hopf et al. on amorphous hydrogenated carbon film surfaces.^[15] These authors

OTAKANDZA-KANDJANI ET AL. obtained at the end of the film growth (Table 3). The first reason is that the simulations carried out to obtain the values of Figure 3 are carried out over a period of 50 ps and species are sent individually, whereas in those of Table 3, the species are sent all together over a time of 26 ns. In the latter case, this may lead to competition between species for finding a place to stick leading to a decrease of the sticking coefficient. Also, as can be seen in Figure 5, at a certain point in the simulation, there is a saturation of the sticking probability of the individual species. This means that the values obtained after the growth of the film (Table 3) are expected to be closer to the real conditions than the values in Figure 3. Gas phase species formed during growth of C:H films

obtained a value of $\beta(C_2H) = 0.9$ for acetylene-based discharges and $\beta(C_2H) = 0.8$ for other hydrocarbon discharges. However, the authors assumed that $\gamma(C_2H)$ is lower than 0.1 and thus that $S(C_2H) \approx 0.8$ for all hydrocarbon discharges. This value of S(C2H) is commonly used in the literature, [69] particularly for kinetic models of hydrocarbon plasmas.[14,18,28,29,70-72] These values are not in agreement with those obtained in our simulations $S(C_2H) = 0.25$ and $\gamma(C_2H) = 0.55$ at steadystate after 15 ns. This significant difference might be due to the fact that the authors consider only the formation of nonreactive volatile products when estimating the recombination probability γ and therefore assume that the C₂H radical forms only C₂H₂ in the abstraction reaction: $C_2H + H$ (surface) $\rightarrow C_2H_2 + \text{surface}$. The authors consider that the surface recombination probability corresponding to this reaction is lower than 0.1. In contrast, our study includes both volatile reactive and nonreactive product formation at the surface. The present MD simulations indicate that the formation of reactive volatile products at the surface is important and cannot be neglected, as it will be shown also in section 3.3.

In addition, the authors^[15] determined the surface loss probabilities of radicals at the surface of C:H films with a hydrogen-to-carbon ratio greater than or equal to 1, while in our study this ratio is smaller than 1 for the film grown by MD. This difference in the H/C ratio can play a role as shown in Alman and Ruzic.^[25]

This could justify the underestimation of γ (C₂H) in their study because C:H films with an H:C ratio ≥1 are softer and therefore lead to deeper penetration of atoms into the hydrocarbon film, increasing the sticking probability. [24-26] Moreover, it is known that the surface loss probability of radicals strongly depends on plasma parameters such as temperature or surface composition.[26]

All the values obtained at the end of the simulation are summarized in Table 3 for each species.

Differences are observed between the values of the sticking probabilities of the different neutral species obtained in Figure 3 for the covered surface and those

Figure 6 shows the time evolution of the C_n carbon clusters (i.e., all molecules with n carbon atoms, regardless of the number of hydrogen atoms), here limited to C₁ to C_{>9}, formed by surface reactions during the growth of the C:H film. It should be noted that for the C₁ and C₂ clusters, the initial reflected molecules and the produced molecules corresponding to an initial species, are not counted. Cluster C>9 represents the sum of all clusters with a size greater than 9. Large clusters are formed through direct interaction of impinging species with the surface or by rapid reactions between molecules reemitted in the gas phase just above the surface. It can be observed that, with the exception of the C₁ cluster quantity, which is almost zero, the other C_2 - $C_{>9}$ clusters show an approximately linear temporal evolution with C₃ and C₄ clusters being the two main clusters over time. These observations are consistent with the evolutions of the surface recombination probabilities $\gamma(CH_3)$ and γ (C₂H) in Figure 5b as these impinging molecules are at the origin of the reemitted C₃ and C₄ clusters.

Figure 7 shows the mass spectrum of the species reemitted in the gas phase, at the end of the runs (26 ns). The initially stable nonreactive hydrocarbon species (CH₄, C₂H₂, and C₂H₄) are the species, most re-emitted

Species	S	γ	β
C_2H	$0.25 \ (0.8^{[15]})$	$0.55 \ (< 0.1^{[15]})$	$0.8 \; (0.8/0.9^{[15]})$
CH ₃	0.02 (~10 ^{-4[66]})	0.54	$0.56 \ (<0.01^{[15]})$
$\mathrm{CH_4}$	< 0.001	0.02	0.02
C_2H_4	0.001	0.004	0.005
C_2H_2	0.014	0.006	0.02
H_2	0.002	0.008	0.01

TABLE 3 Values of sticking probability (S), surface recombination probability (γ) , and surface loss probability (β) of each species after C:H film growth, values available in the literature are put in brackets.

in the gas phase. This is consistent with the fact that they are nearly totally reflected after surface interactions.

In the inset of Figure 7, we have identified some of the main other volatile species formed at the surface. We can observe the presence of reactive (e.g., C₄H₂, C₄H₃, C_6H_3 , etc.) and nonreactive (e.g., C_2H_6 , C_3H_4 (CH \equiv C -CH₃), etc.) species. These observations highlight that the reactions of radicals on the surface lead not only to the formation of nonreactive volatile products, as shown in the literature, [13,15] but also to reactive volatile products.[13,15] This confirms that the formation of reactive species has to be considered when calculating the probability of surface recombination. Moreover, species such as C₄H₂, C₄H₃, and C₆H₃ are widely known in hydrocarbon plasmas for contributing to the growth of films and large molecules.[13,17,18,73] In a previous study, [30] their importance, as well as the one of C₆H₄, was reported for the growth of large molecules in the volume phase. This means that the amount of reactive






FIGURE 6 Temporal evolution of the C_1 to $C_{>9}$ clusters reemitted during the growth of the C:H film in the gas phase. The molecules corresponding to the initial species are not included in the count of C_1 and C_2 clusters. The $C_{>9}$ clusters represent the sum of all clusters whose size is larger than 9 carbon atoms.

and nonreactive volatile products is significant and therefore cannot be neglected. In addition, the volatile reactive species that are re-emitted in the gas phase may contribute to the reaction mechanisms that lead to the growth of hydrocarbon chains or solid particles in the volume phase. In the previous section, we noted that the surface recombination probability resulting in a reactive or nonreactive volatile molecule is not negligible, especially for CH3 and C2H radicals. Although this quantity is difficult to measure experimentally, [15] its rough estimation (by, e.g., neglecting the formation of reactive volatile products or underestimating the amount of nonreactive volatile products) leads to a large loss of information in the interpretation of the surface loss probabilities of the CH₃ and C₂H radicals. The separate calculation of the sticking and surface recombination probabilities is therefore necessary to obtain a clear overview and understanding of the behavior of the different radical species during their interaction with the surface. As shown by the present study, the separate calculation of these two quantities is more accessible through MD simulations.

4 | CONCLUSION

In this study, reactive MD was used to investigate the surface loss probabilities of various neutral species (H_2 , CH_4 , C_2H_4 , C_2H_4 , C_2H_2 , and CH_3) in an argon–methane plasma. The sticking probabilities of each of these species were calculated on both a pristine surface and a surface coated with a C:H film. The results showed that the sticking probabilities were higher on a pristine surface than on the surface covered with the C:H film. In the subsequent simulations, the neutral species were sent to a pristine surface together and their sticking probability (S) and surface recombination probability (Y) were determined. Both reactive and nonreactive volatiles were considered in the Y estimation, in contrast to





the literature which only considers nonreactive volatiles. This analysis provided valuable information on the surface loss probability ($\beta = S + \gamma$) of the main neutral species in the Ar/CH₄ plasma during C:H film growth. The study revealed that stable species, particularly CH₄, C₂H₄, and C₂H₂, contributed to the initial formation of the hydrocarbon films and that they were subsequently fully reflected with probabilities S and γ very close to zero. Among the radicals, it was observed that CH₃ contributed more to the formation of volatile species than to the growth of the C:H film, while the C₂H radical was identified as the main precursor of film growth and volatile species formation with a surface loss probability (0.8) that corresponds to the typical value found in the literature. However, a difference was observed between the values of $S(C_2H)$ and $\gamma(C_2H)$ and those estimated in the literature. C₃H₄ and C₄H₃ species were identified as the main molecules (reactive and nonreactive) re-emitted during the growth of the C:H film. Although this study highlights the importance of recombination processes at the surface, which is generally underestimated in existing kinetic models, this work may have certain limitations due to the H/C ratio of the resulting film and the fact that the effects of charged species impinging on the surface are not considered. It paves the way for future simulations involving ions in the deposition processes, keeping in mind that the corresponding flux remains small compared with neutral fluxes.

ACKNOWLEDGMENTS

The authors are grateful to the Fédération Calcul Scientifique et Modélisation Orléans Tours (CaSciModOT) for the numerical resources made available to us. This work has been supported by the National Scholarship Agency of Gabon (ANBG) and the French National Research Agency (ANR) through the MONA project (ANR-18-CE30-0016).

CONFLICT OF INTEREST STATEMENT

The authors declare no conflict of interest

DATA AVAILABILITY STATEMENT

Data that support the findings of this study are available from the corresponding author upon reasonable request.

ORCID

Pascal Brault http://orcid.org/0000-0002-8380-480X

Armelle Michau http://orcid.org/0000-0002-7669-0277

REFERENCES

[1] M. Jiménez-Redondo, I. Tanarro, V. J. Herrero, *Plasma Sources Sci. Technol.* 2022, 31(no. 6), 065003. https://doi.org/10.1088/1361-6595/ac70f8

- [2] S. Stoykov, C. Eggs, U. Kortshagen, J. Phys. D: Appl. Phys. 2001, 34(no. 14), 2160. https://doi.org/10.1088/0022-3727/34/14/312
- I. B. Denysenko, E. Wahl, S. Labidi, M. Mikikian, H. Kersten,
 T. Gibert, *Plasma Process. Polym.* 2019, 16(no. 6), 1800209.
 https://doi.org/10.1002/ppap.201800209
- [4] M. Tanemura, K. Iwata, K. Takahashi, Y. Fujimoto, F. Okuyama, H. Sugie, V. Filip, J. Appl. Phys. 2001, 90(no. 3), 1529. https://doi.org/10.1063/1.1382848
- [5] K. Ostrikov, Rev. Mod. Phys. 2005, 77(no. 2), 489. https://doi. org/10.1103/RevModPhys.77.489
- [6] Carbon Nanomaterials and their Nanocomposite-Based Chemiresistive Gas Sensors, (Ed: S. Dhall) Elsevier Science Publishing Co. Inc., 2023. https://doi.org/10.1016/C2019-0-04471-8
- [7] A. M. Díez-Pascual, Int. J. Mol. Sci. 2022, 23, 9321. https://doi. org/10.3390/ijms23169321
- [8] M. Frenklach, H. Wang, Phys. Rev. B: Condens. Matter Mater. Phys. 1991, 43(no. 2), 1520. https://doi.org/10.1103/ PhysRevB.43.1520
- [9] K. Kobayashi, N. Mutsukura, Y. Machi, *Thin Solid Films* 1991, 200(no. 1), 139. https://doi.org/10.1016/0040-6090(91) 90036-W
- [10] A. H. Lettington, Carbon 1998, 36(no. 5-6), 555. https://doi. org/10.1016/S0008-6223(98)00062-1
- [11] A. A. Khan, J. A. Woollam, Y. Chung, Solid-State Electron. 1984, 27(no. 4), 385. https://doi.org/10.1016/0038-1101(84) 90173-4
- [12] L. Hu, D. S. Hecht, G. Grüner, Chem. Rev. 2010, 110(no. 10), 5790. https://doi.org/10.1021/cr9002962
- [13] J. Benedikt, J. Phys. D: Appl. Phys. 2010, 43(no. 4), 043001. https://doi.org/10.1088/0022-3727/43/4/043001
- [14] I. B. Denysenko, E. von Wahl, M. Mikikian, J. Berndt, S. Ivko, H. Kersten, E. Kovacevic, N. A. Azarenkov, J. Phys. D: Appl. Phys. 2020, 53(no. 13), 135203. https://doi.org/10.1088/1361-6463/ab6625
- [15] C. Hopf, K. Letourneur, W. Jacob, T. Schwarz-Selinger, A. von Keudell, *Appl. Phys. Lett.* **1999**, 74(no. 25), 3800. https://doi.org/10.1063/1.124184
- [16] A. Keudell, C. Hopf, T. Schwarz-Selinger, W. Jacob, Nucl. Fusion 1999, 39(no. 10), 1451. https://doi.org/10.1088/0029-5515/39/10/307
- [17] J. R. Doyle, J. Appl. Phys. 1997, 82(no. 10), 4763. https://doi. org/10.1063/1.366333
- [18] K. De Bleecker, A. Bogaerts, W. Goedheer, Phys. Rev. E 2006, 73(no. 2), 026405. https://doi.org/10.1103/PhysRevE.73. 026405
- [19] W. Eckstein, Computer Simulation of Ion-Solid Interactions, in Springer Series in Materials Science 10vol. 10, Springer Berlin Heidelberg, Berlin, Heidelberg 1991. https://doi.org/ 10.1007/978-3-642-73513-4
- [20] W. Jacob, Thin Solid Films 1998, 326(no. 1–2), 1. https://doi. org/10.1016/S0040-6090(98)00497-0
- [21] L. Schwaederlé, P. Brault, C. Rond, A. Gicquel, *Plasma Process. Polym.* 2015, 12(no. 8), 764. https://doi.org/10.1002/ppap.201400223
- [22] E. D. de Rooij, A. W. Kleyn, W. J. Goedheer, *Phys. Chem. Chem. Phys.* 2010, 12(no. 42), 14067. https://doi.org/10.1039/c0cp00637h

16128696, Downloaded from https://onlinelibrary.wiley.com/doi/10.1002/ppap.202300120 by Cochraen France, Wiley Online Library on [09/08/2023], See the Terms and Conditions (https://onlinelibrary.wiley.com/erms-and-conditions) on Wiley Online Library for rules of use; OA articles are governed by the applicable Creative Commons Licensen

- [23] K. Ohya, Y. Kikuhara, K. Inai, A. Kirschner, D. Borodin, A. Ito, H. Nakamura, T. Tanabe, J. Nucl. Mater. 2009, 390-391, 72. https://doi.org/10.1016/j.jnucmat.2009.01.072
- [24] A. R. Sharma, R. Schneider, U. Toussaint, K. Nordlund, J. Nucl. Mater. 2007, 363-365, 1283. https://doi.org/10.1016/j. jnucmat.2007.01.180
- [25] D. A. Alman, D. N. Ruzic, J. Nucl. Mater. 2003, 313-316, 182. https://doi.org/10.1016/S0022-3115(02)01428-9
- [26] D. A. Alman, D. N. Ruzic, Phys. Scr. 2004, T111(no. 1), 145. https://doi.org/10.1238/Physica.Topical.111a00145
- [27] P. Träskelin, E. Salonen, K. Nordlund, J. Keinonen, C. H. Wu, J. Nucl. Mater. 2004, 334(no. 1), 65. https://doi. org/10.1016/j.jnucmat.2004.04.334
- [28] G. Tetard, A. Michau, S. Prasanna, J. Mougenot, P. Brault, K. Hassouni, Plasma Sources Sci. Technol. 2021, 30(no. 10), 105015. https://doi.org/10.1088/1361-6595/ac2a17
- [29] G. Tetard, A. Michau, S. Prasanna, J. Mougenot, P. Brault, K. Hassouni, Plasma Process. Polym. 2022, 19(no. 5), 2100204. https://doi.org/10.1002/ppap.202100204
- [30] G. O. Kandjani, P. Brault, M. Mikikian, G. Tetard, A. Michau, K. Hassouni, Plasma Process. Polym. 2023, 20(no. 4), 2200192. https://doi.org/10.1002/ppap.202200192
- [31] E. C. Neyts, P. Brault, Plasma Process. Polym. 2017, 14(no. 1-2), 1600145. https://doi.org/10.1002/ppap.201600145
- [32] D. B. Graves, P. Brault, J. Phys. D: Appl. Phys. 2009, 42(no. 19), 194011. https://doi.org/10.1088/0022-3727/42/19/194011
- [33] T. Liang, Y. K. Shin, Y. T. Cheng, D. E. Yilmaz, K. G. Vishnu, O. Verners, C. Zou, S. R. Phillpot, S. B. Sinnott, A. van Duin, Annu. Rev. Mater. Res. 2013, 43(no. 1), 109. https://doi.org/10. 1146/annurev-matsci-071312-121610
- [34] D. W. Brenner, O. A. Shenderova, J. A. Harrison, S. J. Stuart, B. Ni, S. B. Sinnott, J. Phys.: Condens. Matter 2002, 14(no. 4), 783. https://doi.org/10.1088/0953-8984/14/4/312
- [35] S. J. Stuart, A. B. Tutein, J. A. Harrison, J. Chem. Phys. 2000, 112(no. 14), 6472. https://doi.org/10.1063/1.481208
- [36] T. C. O'Connor, J. Andzelm, M. O. Robbins, J. Chem. Phys. 2015, 142(no. 2), 024903. https://doi.org/10.1063/1.4905549
- [37] J. Yu, S. B. Sinnott, S. R. Phillpot, Phys. Rev. B: Condens. Matter Mater. Phys. 2007, 75(no. 8), 085311. https://doi.org/ 10.1103/PhysRevB.75.085311
- [38] T.-R. Shan, B. D. Devine, J. M. Hawkins, A. Asthagiri, S. R. Phillpot, S. B. Sinnott, Phys. Rev. B: Condens. Matter Mater. Phys. 2010, 82(no. 23), 235302. https://doi.org/10. 1103/PhysRevB.82.235302
- [39] A. C. T. van Duin, S. Dasgupta, F. Lorant, W. A. Goddard, J. Phys. Chem. A 2001, 105(no. 41), 9396. https://doi.org/10. 1021/jp004368u
- [40] M. Zarshenas, K. Moshkunov, B. Czerwinski, T. Leyssens, A. Delcorte, J. Phys. Chem. C 2018, 122(no. 27), 15252. https://doi.org/10.1021/acs.jpcc.8b01334
- [41] M. Aryanpour, A. C. T. van Duin, J. D. Kubicki, J. Phys. Chem. A 2010, 114(no. 21), 6298. https://doi.org/10.1021/jp101332k
- [42] P. Brault, M. Ji, D. Sciacqua, F. Poncin-Epaillard, J. Berndt, E. Kovacevic, Plasma Process. Polym. 2022, 19(no. 1), 2100103. https://doi.org/10.1002/ppap.202100103
- [43] J. J. Végh, D. B. Graves, Plasma Process. Polym. 2009, 6(no. 5), 320. https://doi.org/10.1002/ppap.200800223
- [44] E. Neyts, M. Eckert, A. Bogaerts, Chem. Vap. Depos. 2007, 13(no. 6-7), 312. https://doi.org/10.1002/cvde.200606551

- [45] W. L. Quan, X. W. Sun, Q. Song, Z. J. Fu, P. Guo, J. H. Tian, J. M. Chen, Appl. Surf. Sci. 2012, 263, 339. https://doi.org/10. 1016/j.apsusc.2012.09.057
- [46] S. J. Plimpton, A. P. Thompson, MRS Bull. 2012, 37(no. 5), 513. https://doi.org/10.1557/mrs.2012.96
- [47] M. S. Daw, S. M. Foiles, M. I. Baskes, Mater. Sci. Rep. 1993, 9(no. 7-8), 251. https://doi.org/10.1016/0920-2307(93) 90001-U
- [48] X. W. Zhou, H. Wadley, R. A. Johnson, D. J. Larson, N. Tabat, A. Cerezo, A. K. Petford-Long, G. Smith, P. H. Clifton, R. L. Martens, T. F. Kelly, Acta Mater. 2001, 49(no. 19), 4005. https://doi.org/10.1016/S1359-6454(01)00287-7
- [49] X. W. Zhou, R. A. Johnson, H. N. G. Wadley, Phys. Rev. B: Condens. Matter Mater. Phys. 2004, 69(no. 14), 144113. https://doi.org/10.1103/PhysRevB.69.144113
- [50] C.-M. Lin, H.-L. Tsai, Intermetallics 2011, 19(no. 3), 288. https://doi.org/10.1016/j.intermet.2010.10.008
- [51] D. W. Jacobson, G. B. Thompson, Comput. Mater. Sci. 2022, 205, 111206. https://doi.org/10.1016/j.commatsci.2022. 111206
- [52] D. Toton, C. D. Lorenz, N. Rompotis, N. Martsinovich, L. Kantorovich, J. Phys.: Condens. Matter. 2010, 22(no. 7), 074205. https://doi.org/10.1088/0953-8984/22/7/074205
- [53] S. Wang, K. Komvopoulos, Sci. Rep. 2020, 10(no. 1), 8089. https://doi.org/10.1038/s41598-020-64625-w
- G. E. P. Box, M. E. Muller, Ann. Math. Stat. 1958, 29(no. 2), 610. https://doi.org/10.1214/aoms/1177706645
- [55] S. Sharma, P. Kumar, R. Chandra, in Micro and Nano Technologies, Molecular Dynamics Simulation of Nanocomposites Using BIOVIA Materials Studio, Lammps and Gromacs (Ed: Sumit Sharma), Elsevier, Amsterdam, 2019, pp. 1-38. https://doi.org/10.1016/B978-0-12-816954-4.00001-2
- [56] A. P. Thompson, H. M. Aktulga, D. S. Bolintineanu, W. M. Brown, P. S. Crozier, P. J. in 't Veld, A. Kohlmeyer, S. G. Moore, T. D. Nguyen, R. Shan, M. J. Stevens, J. Tranchida, C. Trott, S. J. Plimpton, Comput. Phys. Commun. 2022, 271, 108171. https://doi.org/ 10.1016/j.cpc.2021.108171
- [57] W. Humphrey, A. Dalke, K. Schulten, J. Mol. Graphics 1996, 14(no. 1), 33. https://doi.org/10.1016/0263-7855(96)00018-5
- [58] T. E. Oliphant, Comput. Sci. Eng. 2007, 9(no. 3), 10. https:// doi.org/10.1109/MCSE.2007.58
- [59] M. Bauer, T. Schwarz-Selinger, W. Jacob, A. von Keudell, J. Appl. Phys. 2005, 98(no. 7), 073302. https://doi.org/10.1063/ 1.2061890
- [60] M. Meier, A. Keudell, J. Appl. Phys. 2001, 90(no. 7), 3585. https://doi.org/10.1063/1.1397285
- [61] A. von Keudell, W. Jacob, Prog. Surf. Sci. 2004, 76(no. 1-2), 21. https://doi.org/10.1016/j.progsurf.2004.05.001
- [62] C. Hopf, T. Schwarz-Selinger, W. Jacob, A. von Keudell, J. Appl. Phys. 2000, 87(no. 6), 2719. https://doi.org/10.1063/1. 372246
- [63] A. Keudell, Plasma Sources Sci. Technol. 2000, 9(no. 4), 455. https://doi.org/10.1088/0963-0252/9/4/302
- [64] M. Sode, T. Schwarz-Selinger, W. Jacob, H. Kersten, J. Appl. Phys. 2014, 116(no. 1), 013302. https://doi.org/10.1063/1.4886123
- [65] M. Sode, W. Jacob, T. Schwarz-Selinger, H. Kersten, J. Appl. Phys. 2015, 117(no. 8), 083303. https://doi.org/10.1063/1. 4913623

- [66] A. von Keudell, *Thin Solid Films* **2002**, *402*(no. 1–2), 1. https://doi.org/10.1016/S0040-6090(01)01670-4
- [67] W. Möller, Appl. Phys. A Solids Surf. 1993, 56(no. 6), 527. https://doi.org/10.1007/BF00331402
- [68] A. von Keudell, T. Schwarz-Selinger, W. Jacob, J. Appl. Phys. 2001, 89(no. 5), 2979. https://doi.org/10.1063/1.1343894
- [69] D. Hegemann, Plasma Process. Polym. 2023, 20(5), e2300010. https://doi.org/10.1002/ppap.202300010
- [70] I. B. Denysenko, E. von Wahl, S. Labidi, M. Mikikian, H. Kersten, T. Gibert, E. Kovačević, N. A. Azarenkov, *Plasma Phys. Controlled Fusion* 2019, 61(no. 1), 014014. https://doi.org/10.1088/1361-6587/aade2d
- [71] C. De Bie, B. Verheyde, T. Martens, J. van Dijk, S. Paulussen, A. Bogaerts, *Plasma Processes Polym.* 2011, 8(no. 11), 1033. https://doi.org/10.1002/ppap.201100027

- [72] W. Bohmeyer, D. Naujoks, A. Markin, I. Arkhipov, B. Koch, D. Schröder, G. Fussmann, J. Nucl. Mater. 2005, 337–339, 89. https://doi.org/10.1016/j.jnucmat.2004.10.107
- [73] V. De Vriendt, S. M. Miladinovic, J. L. Colaux, F. Maseri,
 C. L. Wilkins, S. Lucas, *Langmuir* 2011, 27(no. 14), 8913. https://doi.org/10.1021/la2003035

How to cite this article: G.-C. Otakandza-Kandjani, P. Brault, M. Mikikian, A. Michau, K. Hassouni, *Plasma. Process. Polym.* **2023**, e2300120. https://doi.org/10.1002/ppap.202300120