

Real-time monitoring of snowmelt infiltration in steep permafrost-affected rock slopes using fluorescent dyes

Matan Ben-Asher, Florence Magnin, Jean-Yves Josnin, Josué Bock, Emmanuel Malet, Antoine Chabas, Marine Quiers, Amaël Poulain, Yves Perette

▶ To cite this version:

Matan Ben-Asher, Florence Magnin, Jean-Yves Josnin, Josué Bock, Emmanuel Malet, et al.. Real-time monitoring of snowmelt infiltration in steep permafrost-affected rock slopes using fluorescent dyes. 6th European Conference on Permafrost (EUCOP6), Jun 2023, Puigcerda, France. hal-04195991

HAL Id: hal-04195991 https://hal.science/hal-04195991v1

Submitted on 5 Sep 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.











Real-time monitoring of snowmelt infiltration in steep permafrostaffected rock slopes using fluorescent dyes

Matan Ben-Asher¹, Florence Magnin¹, Jean-Yves Josnin¹, Josue Bock¹, Emmanuel Malet¹, Antoine Chabas¹, Marine Quiers¹, Amaël Poulain², Yves Perrette¹.

¹EDYTEM Lab, Université de Savoie, CNRS, Le Bourget-du-Lac, France. ²TRAQUA S.A., Namur, Belgium.

Background

Little is known about the connectivity between surface water and subsurface fractures in steep permafrostaffected rock slopes. Here we present a novel high-elevation field experiment designed to monitor real-time infiltration in rock fractures at Aiguille du Midi (3842 m a.s.l), in the Mont-Blanc massif. An existing tunnel that was carved for access to visitors, allows the collection of water directly from fractures that cross the tunnel walls. We monitored the water flow rate, temperature, and electrical conductivity in two adjutant fractures. In addition we installed a fluorescence probe and inserted two different fluorescent dyes: amino-acid-G and sulphorhodamine-B, into snow patches at the surface, in two locations directly above the fractures (5-15 m) to

track the water source. We sampled water from the monitored fractures and other locations in the tunnel.

Study site - Aiguille du Midi (3842 m a.s.l), Mont-Blanc massif, French Alps.


The Aiguille du Midi lies on the NW side of the Mont-Blanc Massif. Its summit consists of three granite peaks (North, Central. A tourist cable car runs from Chamonix to the north peak, where galleries and an elevator are carved in the rock mass, providing year-round excess to the otherwise extreme and inaccessible environment.



Results

Lag time of peak water flow during the melt season

Lagged cross-correlations analysis show that peak water flow is lagged by ~6 hours after peak air temperature outside and by ~3 hours after peak rock surface temperatures




Comparison of June 2022 with 2023


2023 was significantly comparison with snowfall – As of mid-June 2023 no flow documented




Experimental setup

- Real-time measurements of:
- Flow rate in two locations
- Water fluorescence
- Water temperature
- Water conductivity Rock surface temperature
- Water sampling for
- Stable isotopes (¹⁸O/D)
- Major elements
- Fluorescence









Diurnal changes

Diurnal fluctuations in flow rate range between <1 L/hour in the morning to >10 L/hour in the late afternoon, and correlate with oscillations in air and surface temperatures, with a 3-6




hours lag time, respectively



Real-time flow monitoring system

28/7/2022

30/6/2022



Key observations The fluorescent tracer from the lower terrace was found in the water from the first flow events until mid-May and remained in the water until mid-June. The tracer from the upper terrace was never observed.

- Significant water continued for 3 weeks after the fluorescent tracer disappeared from the water.
- Flow continued after all snow cover was gone
- The two adjacent fractures show different flow regimes (box 1 and box 2).
- Initiation of continuous flow follows the heating of the rock surface and air temperatures above 0°C.

Further work

In April 2023 two fluorescent tracers were inserted again in the same location:

1) amino acid G – lower terrace (same as in 2022). 2) fluorescein (new tracer) – Upper terrace (same location as sulphorhodamine-B in 2022).

Monitoring continues with more frequent water sampling (once a week) for laboratory analysis, including major elements and stable isotopes

Summary and conclusions

- Our results from the real-time monitoring of the water flow from fractures in permafrost-affected rock slope show clear evidence of high connectivity between snowpack at the surface and sub-surface fractures.
- The initiation of a continuous flow period corresponds to an increase of surface temperatures above 0°C
- Strong diurnal changes in flow rate are observed and correlate with surface temperatures.
- The observation of flow after no snow cover was visible (mid-July) points to potential indirect sources such as runoff from upslope or ice storage in the fractures.

Acknowledgment

This research is funded by the Agence Nationale de la Recherche Françaises (French National Agency for Research), project: ANR-19-CE01-0018 WISPER.