

Cryogrinding and sieving techniques as challenges towards producing controlled size range microplastics for relevant ecotoxicological tests

Tony Gardon, Ika Paul-Pont, Gilles Le Moullac, Claude Soyez, Fabienne Lagarde, Arnaud Huvet

► To cite this version:

Tony Gardon, Ika Paul-Pont, Gilles Le Moullac, Claude Soyez, Fabienne Lagarde, et al.. Cryogrinding and sieving techniques as challenges towards producing controlled size range microplastics for relevant ecotoxicological tests. Environmental Pollution, 2022, 315, 120383 (9p.). 10.1016/j.envpol.2022.120383. hal-04203897

HAL Id: hal-04203897 https://hal.science/hal-04203897v1

Submitted on 17 May 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Cryogrinding and sieving techniques as challenges towards producing controlled size range microplastics for relevant ecotoxicological tests

Gardon Tony ^{1, *}, Paul-Pont Ika ², Le Moullac Gilles ¹, Soyez Claude ¹, Lagarde Fabienne ³, Huvet Arnaud ⁴

¹ Ifremer, ILM, IRD, Univ Polynésie Française, UMR EIO, F-98719, Taravao, Tahiti, Polynésie Française, France

² Univ Brest, Ifremer, CNRS, IRD, LEMAR, F-29280, Plouzané, France

³ Institut des Molécules et Matériaux du Mans, IMMM - UMR CNRS 6283, Le Mans Université, Avenue Olivier Messiaen, 72085, Le Mans, France

⁴ Univ Brest, Ifremer, CNRS, IRD, LEMAR, F-29280, Plouzané, France

* Corresponding author : Tony Gardon, email address : tony.gardon@ifremer.fr

Abstract :

The impact of microplastics (MP) has attracted much attention from the scientific community and many laboratory assessments have been made of their effects on aquatic organisms. To produce MP from real environmental plastic waste, which would enable more realistic experiments, we used plastic pearl farming equipment from French Polynesian lagoons. Here, the pearl oyster Pinctada margaritifera could encounter MP coming from their breakdown in its surrounding environment. We tested an established method based on mechanical cryogenic grinding and liquid sieving. Our desired size range was 20-60 μm, corresponding to the optimal particle size ingested by P. margaritifera. The protocol was effective, generating MP particles of 20-60 µm (~17,000-28,000 MP µg-1), but also produced too many smaller particles. The peak in the desired size range was thus flattened by the many small particles <3 µm (~82,000-333,000 MP µg-1; 53-70% of total analysed particles), visible at the limit of Coulter counter analysis (cut-off point: 2 µm). Laser diffraction analysis (cut-off point: 0.4 µm) provided greater detail. showing that \sim 80–90% of the total analysed particles were <1 μ m. Diverging particle size distributions between those expected based on sieving range and those really observed, highlight the need to perform fine-scaled particle size distribution analyses to avoid underestimating the number of small micro- and nanoplastics (MNP) and to obtain an exact estimation of the fractions produced. Size and microstructure characterization by scanning electron microscopy suggested spontaneous particle self-assembly into crystal superstructures, which is the supposed cause of the divergence we observed. Overall, our results emphasize that particle self-assembly is a technical hurdle requiring further work and highlight the specific need to finely characterize the size distribution of MNP used in ecotoxicological experiments to avoid overestimating effects.

Graphical abstract



Highlights

 "Homemade" microplastics may underestimate exposure level and overestimate impact. ► Particle sieving range was inconsistent with size distribution. ► Particle self-assembly may cause biased sieving and size distribution. ► Particle size distribution needs to be systematically characterized very finely. ► For standardization, it is vital to improve microplastic manufacture and sizing.

Keywords: Laboratory experiment, Microplastic production, Sieving, Particle self-assembly, Uncontrolled size distribution, Underestimated concentration

60 1. Introduction

Microplastic particles (MP, <5 mm) are the most numerically abundant form of solid waste on 61 Earth (Eriksen et al., 2014). Over the past fifteen years, the scientific community has studied 62 this global concern by evaluating environmental concentrations in different marine 63 compartments (Eriksen et al., 2014; Cózar et al., 2014; Woodall et al., 2014; van Sebille et al., 64 2015), as well as the adverse effects on aquatic organisms in laboratory conditions (reviewed 65 in Thornton Hampton et al., 2022). Historically, the vast majority of laboratory experiments 66 used a single polymer type, in pieces of spherical shape (*i.e.* microbeads), and particle 67 concentrations mostly higher (in number of particles per volume) than those found in the field 68 (Phuong et al., 2016; Lenz et al., 2016). These biases were mainly caused by a lack of more 69 70 appropriate polymer types and shapes, and uncertainties regarding in situ concentrations of particles below 300 µm. Although an increasing number of papers now aim to consider the 71 heterogeneity of microplastics (*i.e.* by including a variety of particle shapes, sizes, polymer 72 types, surface properties; Rochman et al., 2019), the gap between potential and actual risks 73 remain concrete considering the lack of relevance in ecological terms (Connors et al., 2017; de 74 75 Sá et al., 2018).

A rigorous understanding of the environmental impacts of MP on marine biota requires fine 76 77 evaluation of concentrations and characteristics of the smallest MP sizes in order to conduct relevant environmental experiments in laboratory conditions. The first step to using more 78 realistic MP scenarios is to conduct an evidence-based approach, which means targeting the 79 most relevant particles in terms of shape (i.e. fragments rather than spheres), size (i.e. 80 polydisperse rather than monodisperse), polymers (*i.e.* those mostly found locally), and surface 81 properties (i.e. aging and biofilm). For instance, recent studies demonstrating physical and 82 chemical differences between weathered plastics and pristine ones or post-production consumer 83 products have highlighted the need to use materials for ecotoxicology tests that are as similar 84

as possible to those found *in situ* (Jahnke et al., 2017). Using collected weathered plastics, such
as beached macroplastic litter, to produce MP therefore offers a way to obtain relevant test
materials for impact assessment studies (Kühn et al., 2018).

In the lagoons of French Polynesia, pearl farming has been identified as a specific source of 88 plastic pollution through the accumulation of operational and abandoned plastic equipment (*e.g.* 89 ropes, collectors, buoys) (Andréfouët et al., 2014). A recent monitoring study in pearl farming 90 lagoons revealed a widespread contamination by MP in both seawater and cultured pearl oyster 91 (Gardon et al., 2021). Among the possible ecological disturbances discussed in Andréfouët et 92 al. (2014), one comes from a preliminary experiment conducted by Gardon et al. (2018) 93 94 highlighting a dose effect of polystyrene microbeads on energy balance (Gardon et al., 2018) and dose-specific transcriptomic disruption of gene expression (Gardon et al., 2020b) in the 95 pearl oyster (Pinctada margaritifera). As P. margaritifera is a species of commercial interest 96 97 and the second most important economic resource in French Polynesia, risk assessment using realistic MP (i.e. sourced from local pearl-farming gear debris) is very important. It will form 98 the crucial next step to improving both the simulation of the pearl oyster environment and the 99 realism of results that can support decision making. 100

101 A few recent studies provide protocols for preparing model micro- and nanoplastics (e.g. Cole, 102 2016; Eitzen et al., 2019), some of which present cryomilling as an effective way to obtain reference particles (Kühn et al., 2018). However, the particles thus-obtained from aged 103 polymers were mostly in the range of several hundred µm (Kühn et al., 2018) or nano sized (El 104 105 Hadri et al., 2020). The production of standardized size particles targeting a range of around 1 to 100 µm, which is a typical size range used in most of laboratory studies (de Sá et al., 2018; 106 107 Paul-Pont et al., 2018), remains under-investigated. The present analytical investigation thus proposes to test a cryogrinding and sieving protocol for laboratory MP production from 108 weathered plastic pearl farming equipment as this is a potential source of MP in pearl farming 109

lagoons (Gardon et al., 2021). The objective was to obtain a specific size range of particles 110 included in the P. margaritifera particle size retention range (2 to 200 µm; Pouvreau et al., 111 1999). Thus, in view of our environmental data showing the prevalence of MP 20-200 µm in 112 the cultured pearl oysters (Gardon et al., 2021) and to keep close to the most MP size used in 113 laboratory studies (<50 µm; de Sá et al., 2018), we focused on the obtention of polydisperse 114 particles ranging from 20 to 60 µm. With the aim of questioning difference between the 115 116 expected and the real particle sizes, we hypothesized that cryogrinding and sieving techniques do not make it possible to obtain a specific particle size range regardless of the grinding time. 117 Yet, this approach has already been used in some recent (eco)toxicological studies (e.g. Revel 118 119 et al., 2019; Schür et al., 2020; Carrasco-Navarro et al., 2021). However, the overall particle size distribution of the obtained plastic powder was not always considered, depending on the 120 method used to characterize these "lab MP". A commonly used approach is a Coulter counter 121 equipped with a 100 µm aperture tube, which allows the detection of particles ranging from 2 122 to 100 µm (Revel et al., 2019; Schür et al., 2020; Zimmermann et al., 2020), while the number 123 of particles <2 µm remains unknown if no further analysis is performed. The lack of 124 consideration of the smaller size range is therefore an omission that deserves attention. In our 125 126 study, we examine the potential scale of the error caused by ignoring the nano fraction. This 127 would bias ecotoxicological results interpretation, especially considering that the toxicity of particles increases as their size decreases (Jeong et al., 2016; Ma et al., 2016). We demonstrate 128 the need to improve the standardization of particle concentrations used in exposure experiments 129 130 and highlight the real challenges of producing microplastics with a controlled size range.

131 2. Materials and methods

132 **2.1.** Plastic selection

Several types of plastic pearl farming gear were collected from a pearl farm in Manihi atoll 133 (14°24'10.4"S, 145°57'29.2"W), among which synthetic ropes and spat collectors were the most 134 abundant (Andréfouët et al., 2014). Both ropes and collectors are suspected to be potential 135 sources of polyethylene (PE) and polypropylene (PP) microplastics in the environment of 136 137 cultivated pearl oysters (Gardon et al., 2021). The polymers of the gear were identified by Fourier-transform infrared spectroscopy (FTIR) on both plastic pieces and MP particles 138 produced, confirming that the spat collector (shade-mesh) was made of PP (Figure 1A-B) and 139 the rope was made of PE (Figure 1D–E). 140

141 **2.2.** Microplastic production

The sampled spat collectors and ropes were first washed in saline water (100 g of NaCl L^{-1}) 142 overnight (o/n) to remove as many potentially present microorganisms as possible, then rinsed 143 thoroughly and dried at 60°C for 3 days in a proofer. They were then cut into ≤ 1 cm pieces 144 using clean stainless-steel scissors (Figure 1C and F; Figure 2, step 1). A second washing in 145 146 saline water was performed o/n on the plastic pieces, followed by rinsing with filtered $(1.2 \,\mu m)$ distilled water and drying in a proofer at 60°C for 3 days. Two-gram aliquots of dried plastic 147 148 pieces were packaged in aluminium and immersed in liquid nitrogen for mechanical cryogenic 149 grinding. Steel grinding jars (50 ml) with a steel ball 2 cm in diameter were cooled in liquid 150 nitrogen and filled with an aliquot (2 g of plastic pieces per jar) once all materials were cooled down (Figure 2, step 2). The grinding jars were then placed in a Mixer Mill MM 400 (RetschTM) 151 152 for grinding (Figure 2, step 3). Three running times were tested for each MP type: 1-, 2- and

3-minutes run of grinding. After grinding, the MP from the spat collector (MP_{coll}) and rope
(MP_{rope}) were dried at 60°C o/n before sieving (Figure 2, step 4).

A multi-step sieving phase was carried out to collect the MP 20-60 µm fraction. First, the MP 155 powder was sieved through the 60 µm sieve and rinsed with filtered 70% ethanol from a wash 156 bottle, aiming to avoid MP aggregates as much as possible and facilitate particle passage 157 through the sieve (Figure 2, step 5). The remaining $>60 \,\mu m$ fraction was then suspended in 500 158 ml of filtered distilled water (*i.e.* ~1 g L^{-1}) and the resulting solution sonicated at 30 kHz for 5 159 min to dissociate potential aggregates (Figure 2, step 6) in order to improve the subsequent 160 second sieving through the 60 µm sieve with filtered 70% ethanol (Figure 2, steps 7–8). The 161 162 $60 \,\mu\text{m}$ sieve was then dried at 60°C o/n and the dried >60 μm MP fraction was weighed with a digital precision weighing instrument (RADWAG[®] PS 600.R2; read accuracy = 0.0001 g) by 163 putting the fraction in a tared cup (Figure 2, step 8). The MP 20–60 µm fraction was put through 164 the same liquid sieving described above (Figure 2, steps 9-12) with the addition of Tween- 20° 165 166 (0.1% of the total volume) to the suspended solution before sonication to improve the final sieving phase. The MP 20–60 µm fraction was then rinsed a last time with filtered 70% ethanol 167 and dried at 60°C o/n before recovery and weighing (Figure 2, step 12). The obtained MP 20-168 60 μ m fraction was conserved in stock solution resuspended in filtered ethanol at 1.5 g L⁻¹ for 169 particle size distribution and microstructure characterization (Figure 2, steps 13–14). 170

All the sieving steps were realised under an extractor hood and over a glass dish. All materials
were cleaned and rinsed between each grinding treatment. All wastes, including liquids, were
treated as chemical waste.

174 **2.3.** Quantitative assessment

175 Microplastic fractions were weighed to estimate the relative mass of the >60 μ m and 20–60 μ m 176 fractions as well as the loss of plastic mass following production from an initial 4 g of plastic 177 pieces (*i.e.* 2 g per jar) for each plastic type and grinding condition.

178 **2.4.** Particle characterization

Size distributions of the produced MP were assessed using a MultisizerTM 3 Coulter Counter 179 (Beckman Coulter, Inc., Brea, CA) equipped with a 100 µm aperture tube (detection range of 180 2-100 µm), an approach commonly used to analyse "homemade" microplastics (e.g. Schür et 181 al., 2020). A 1.5 µl MP suspension was added to 15 ml electrolytic solution (0.9% NaCl 182 solution) supplied by the manufacturer (Beckman Coulter, Inc., Brea, CA) and previously 183 184 filtered on a 0.2 µm sterile filter. The solution was shaken before measurement and three repeated measures with the 100 µm capillary (100 µl analytical volume, 300 measured points 185 from 2 to 100 µm size) were performed for each condition. Background measurements were 186 also performed without any MP suspension to quantify contamination in the electrolytic 187 solution. Concentrations and size distribution of microplastics were thus corrected by 188 subtracting the number of particles measured in the electrolytic solution for each of the 189 measured points. 190

191 Laser diffraction analyses were also done, using a Beckman Coulter LS 130 particle laser 192 diffractometer (Beckman Coulter, Inc., Brea, CA) to measure the size distribution of the 193 particles down to $0.4 \mu m$. A few ml of stock solutions were injected until an obturation of 5% 194 was reached.

195 The particle microstructure was observed using a Hitachi TM 3030 scanning electron 196 microscope (SEM) at 15 kV (in charge-up reduction mode) to analyse particle shapes and 197 structures in dry conditions (on the remaining plastic powder) and following slow solvent198 (ethanol) evaporation (from resuspended MP stock solution).

199 2.5. Data analyses

200 The weights of the microplastic fractions gave the distribution between fractions $>60 \,\mu\text{m}$ and 201 20-60 µm, as well as the plastic mass loss caused during the production method, which was 202 calculated by subtracting the weighed MP fractions from the initial weight. Data on particle 203 size distribution obtained by Coulter counter analysis of the 20-60 µm fraction were averaged 204 and plotted on the 300 measured points (from 2 to 100 µm). We determined the proportion of 205 particles really included in the obtained 20-60 µm fraction as well as proportions of particles above and below 60 and 20 µm, respectively. Pairwise comparisons were done to determine 206 significant differences between grinding times regarding frequency distributions of particle 207 count across the size ranges of 2–20 µm and 20–60 µm using Fisher's exact test. Considering 208 no difference, grinding times were then grouped by plastic type and used as replicates (n = 3)209 210 to compare the relative abundance of particle count between both size ranges. Data were therefore transformed by the arcsine square root function. Normality of data distribution and 211 212 homogeneity of variance were tested with Shapiro-Wilk test and Bartlett test, respectively. 213 Means (± standard deviation, SD) were then compared using a two-way ANOVA for plastic type and size range ($\alpha = 0.05$). Tukey's post hoc test was used to determine the significant 214 differences between the averages of each group. Results were considered significant at P < 0.05. 215 Data on the differential volume (%) and number (%) of analysed particles obtained by laser 216 diffraction analysis were plotted on 24 measured points (from 0.375 to 200 µm). The average 217 size (mean \pm SD) and relative abundance of total analysed particles in the sizes <1, <10, <20, 218 <50, <100 and <200 µm were obtained. All analyses were performed and graphics drawn in 219 RStudio v4.0.5 statistics software. 220

221 3. Results and discussion

222 3.1. A microplastic production method adaptable to plastic properties

High mass proportions of MP $>60 \,\mu m$ were recovered for both types of plastic regardless of the 223 grinding time (Table 1). The >60 μ m fraction made from the spat collector reached weights of 224 225 3.96 g (99.0%), 3.94 g (98.4%) and 3.87 g (96.7%) after 1, 2 and 3 min of grinding, respectively; from the rope the weights were 3.64 g (91.0%), 3.10 g (77.6%) and 3.69 g (92.2%), respectively 226 227 (Table 1). Accordingly, low mass proportions were recovered in the spat collector 20-60 µm fraction, reaching only 0.03 g (0.9%), 0.03 g (0.7%) and 0.03 g (0.8%) after 1, 2 and 3 min of 228 grinding, respectively, while the weight of this fraction from rope reached 0.15 g (3.7%), 0.69 229 g (17.2%) and 0.16 g (4.0%) for these grinding times (Table 1). Interestingly, a greater 230 proportion of MP weight was obtained in PE rope following 2 min grinding before decreasing 231 232 after 3 min grinding. Even though those results came from single replicate (and were therefore not tested statistically), it is likely that 2 min grinding reached an intermediate state of particle 233 size improving the sieving phase. Indeed, smaller particle size might have favoured their 234 passage through the 60 µm sieve compared to 1 min grinding. Meanwhile, particle size 235 produced might have decreased following 3 min grinding leading to larger and harder formation 236 of aggregates > 60 μ m (Hotze et al., 2010; Ashraf et al., 2018). Despite a high variability 237 according to grinding time in the weight of the 20-60 µm fraction in MP made from rope, the 238 mass of these particles was from 5 to 25 times greater than those made from spat collector. In 239 240 addition, higher mass losses were observed from the rope than from the spat collector (Table 1). This plastic mass loss may be explained in several ways, including the sticking of particles 241 to lab materials, particle volatility or the production of small MP <20 μ m. In view of these 242 243 results, grinding time seems to have a low influence on the production of 20-60 µm particles and on the loss of plastic mass, and these effects are clearly smaller than the influence of plastic 244

type. Differences in grinding fractions between spat collector and rope could be related to 245 plastic type properties including density, crystallinity and additive content as well as shape and 246 weathering. Indeed, even though liquid nitrogen makes plastic matter more brittle, grinding 247 efficiency may be influenced by plastic density (*i.e.* by taking more or less space in the grinding 248 jar and thus affecting mechanical grinding), which was higher for rope than spat collector (jar 249 filling_{coll} > jar filling_{rope}). It may also be influenced by the shape of the plastic pieces before 250 251 grinding, which was quite flat and thin for spat collector but cylindrical and thicker for rope (Figure 1C and F), favouring fragmentation in the latter (Oyinloye and Yoon, 2020). In 252 addition, the grinding efficiency of plastic types is likely influenced by their intrinsic 253 254 mechanical resistance, which is partly dependent on the additives incorporated during their manufacture (e.g. plasticisers, antioxidants), and their weathering at sea, characterized by the 255 loss of structural integrity induced by biotic (*i.e.* biodegradation) and abiotic (*e.g.* photolysis, 256 257 hydrolysis, thermal degradation) factors (Andrady, 2011), including the leaching of additives (Hahladakis et al., 2018). For example, phthalate esters, such as bis(2-ethylhexyl) phthalate 258 (DEHP), are commonly used as plasticisers to improve the quality and durability of polymers 259 by increasing their flexibility (Rowdhwal and Chen, 2018). A previous study showed DEHP to 260 be one of the most important plastic additives in both plastic types, with a higher concentration 261 quantified in aged rope (95.51 μ g g⁻¹) than spat collector (70.26 μ g g⁻¹) (Gardon et al., 2020a). 262 It is likely that differences in concentrations of DEHP and/or other specific additives might 263 have influenced the mechanical resistance of both plastic types to cryogrinding. Therefore, it 264 265 seems that the mechanical properties of plastic materials, their fate and, probably, their ageing are important factors to consider in the choice of grinding time, both to limit the loss of materials 266 and optimize the yield of the targeted size range fraction. In our study, ageing was probably not 267 a driving variable as the infrared spectra did not show strong oxidation of the collected 268 polymers. Indeed, the carbonyl absorption band in the $1780-1660 \text{ cm}^{-1}$ region, which can be 269

used as a probe to monitor surface oxidation of PE and PP (Rowenczyk et al., 2020), remained
weak (Figure 1A–B).

272 **3.2.** Inconsistency between particle sieving range and actual size distribution

Size distribution analyses of the 20-60 µm fractions revealed an inconsistency between the 273 274 theoretical sieving range and the actual particle sizes, regardless of the plastic type or grinding 275 time. The effectiveness of the protocol was shown by the increased number of MP in the range from 20 μ m (~130–870 MP μ g⁻¹) to 60 μ m (~0–130 MP μ g⁻¹) according to the Coulter counter 276 analyses (Figure 3A–B, focusing on the particle size distribution in the range of 4–60 µm). The 277 278 peak particle number appeared to be mostly centred around 20 µm. However, there was a decrease in particle frequency around 8 µm, and further down, a large increase in the number 279 of particles of smaller size (around 5 µm and below; Figure 3A–B). Coulter counter analyses 280 (only considering particles >2 μ m) showed that the actual 20–60 μ m fractions only reached 281 5.7% (~26,000 MP μ g⁻¹), 17.8% (~28,000 MP μ g⁻¹) and 16.1% (~28,000 MP μ g⁻¹) of the total 282 analysed particles from PP spat collector after 1, 2 and 3 min of grinding, respectively; and 283 3.6% (~17,000 MP μ g⁻¹), 6.1% (~18,000 MP μ g⁻¹) and 8.4% (~18,000 MP μ g⁻¹) from PE rope, 284 respectively (Table 2). No difference occurred between grinding times in the frequency 285 distributions of particles across size ranges of 2–20 μ m and 20–60 μ m (P > 0.05). Using 286 grinding times as replicates (n = 3), the relative abundance of particle count in the 20–60 µm 287 fraction reached $13.2 \pm 6.6\%$ and $6.0 \pm 2.4\%$ for PP spat collector and PE rope, respectively; 288 while averages in the 2–20 μ m fraction reached 86.8 ± 6.6% and 94.0 ± 2.4%, respectively. No 289 significant difference was observed between plastic types according to size range. However, a 290 significant lower number of particles (P < 0.0001) was obtained in the 20–60 µm fraction 291 compared to the 2-20 µm fraction (Figure 3C). Particle size characterization therefore 292 demonstrated that 53–70% (~82,000–333,000 MP μ g⁻¹) of the total analysed particles in the 293 20–60 μ m fractions were in fact <3 μ m (Table 2). Such a result indicates the potential 294

occurrence of the smallest MP and nanoplastics (MNP) in the 20 µm sieved plastic powder 295 296 despite all precautions taken to dispose of MP $< 20 \,\mu m$ (*i.e.* liquid sieving, sonication steps and the use of Tween-20[®] dispersing agent). Considering the similar Coulter counter results among 297 the different grinding times, we focused our laser diffraction analyses on the 1-min grinding 298 treatment, which confirmed and fine-tuned particle size distribution (considering particles >0.4 299 μm; Figure 4). Results showed a high number of particles below the 2 μm threshold, with 300 89.1% (0.70 ± 0.75 µm) and 81.6% (0.82 ± 1.02 µm) of total particles <1 µm from spat collector 301 302 and rope, respectively (Figure 4A and C). It demonstrates the gap between a conventionally used method (i.e. a Coulter counter) to characterize particle size distribution up to the 2 µm 303 304 threshold (e.g. Schür et al., 2020) and a finer analysis including the nano fraction capable of 305 detecting particles up to the 0.4 µm threshold (Balakrishnan et al., 2020). This gap emphasizes the need to be very cautious when assessing particle size distribution on a volume or number 306 307 basis. Considering that small particles will count very little in terms of volume/weight, but a great deal in terms of numbers (Figure 4), it clearly appears that their presence should not be 308 ignored, especially when conducting ecotoxicological studies. Overall, our results highlighted 309 the discrepancy between what is expected from the sieving and what is really obtained in the 310 311 relevant fractions. Such data confirm the need to thoroughly check the size distribution of 312 "homemade" MP using appropriate analytical methods for both micro- and nanosized particles.

313 **3.3.** Particle self-assembly induces biased sieving and size assessment

A plausible explanation for the observed sieving inefficiency is the formation of anisotropic assemblies, in which physical properties of particles differ according to their orientation. Such phenomenon has already been demonstrated by spherical NP uniformly grafted with macroparticles that robustly self-assemble into a variety of anisotropic superstructures when they are dispersed in the corresponding polymer matrix (Akcora et al., 2009; Damasceno et al., 2012). Self-assembly is the process by which individual components arrange themselves into

an ordered structure. Self-assemblies and particle interactions are probably less frequent when 320 321 a polymer matrix is diluted during size characterization (Jain et al., 2004), making it possible to observe these diverging results between quantitative and qualitative assessments. This 322 physical phenomenon is likely illustrated by our results on size distribution obtained with the 323 Coulter counter, which showed totals of 6,800, 2,300 and 2,600 analysed particles from spat 324 collector samples after 1-, 2- and 3-min runs, respectively (Figure 3A), and 7,200, 4,500 and 325 326 3,300 from the rope samples (Figure 3B). Even though those results came from pseudoreplicates, the number of analysed particles was higher after 1 min of grinding than after 2 and 327 3 min with either plastic type, suggesting a large amount of particle self-assembly, possibly 328 329 depending on the size reduction induced by the longer grinding time. The formation of aggregates in the MP 20-60 µm fraction was confirmed by laser diffraction analyses showing 330 4% and 14% of total volume particles >60 µm from spat collector (Figure 4B) and rope (Figure 331 332 4D) samples, respectively. Characteristics such as shape, surface properties, charge, polarizability or mass could determine the degree of self-assembly, producing structures and 333 patterns at all physical scales (Whitesides and Grzybowski, 2002). Molecular mechanisms 334 involved in self-assembly include non-covalent or weak-covalent interactions such as van der 335 336 Waals, electrostatic and hydrophobic interactions (Whitesides and Grzybowski, 2002; Deng et 337 al., 2020). According to our results, these interactions may be plastic type-dependent (Yanar and Kwetkus, 1995; Park et al., 2008) as well as influenced by particle shape and size 338 (Damasceno et al., 2012). Spontaneous MP self-assembly into crystal superstructures could 339 explain why the sieving was not sufficiently effective (Lee et al., 2018; Deng et al., 2020), as 340 illustrated in the SEM images (Figure 5). This physical phenomenon may have occurred 341 342 between the drying phase (Figure 5A–B) and the liquid sieving phase over the 20 µm sieve of which the ethanol efflux was slow. This condition could be compared to the solvent 343 evaporation-driven assembly system developed by Lee et al. (2018) (Figure 5C-I). It seems 344

that the sonicating bath containing Tween-20[®] did not have the expected effect of preventing 345 particle aggregation, as illustrated by the formation of 3D crystals of cuboid shape on all 346 physical scales (Figure 5C-H). Further research and development are needed to reduce these 347 particle interactions in polymer matrices to dispose of more of the MP <20 µm and get as close 348 as possible to the desired size range. A promising investigation way is the introduction of 349 stabiliser/protectant that plays an active part in preventing hard agglomerate formation during 350 351 the drying process (Yeap, 2018). For example, De Jaeghere et al. (1999) examined the redispersibility of suspended polyethylene oxide-grafted nanoparticles previously frozen into ice 352 crystals before subjecting to lyophilization with and without lyoprotectant (trehalose). Results 353 354 showed that lyophilized nanoparticles without trehalose was found to form agglomerates even 355 after sonication for re-dispersion procedure. Meanwhile, the ability of lyophilized nanoparticles with trehalose to be re-dispersed was significantly enhanced. In this study, we have therefore 356 357 demonstrated the necessity of considering size distribution as well as the total number of particles and aggregates, since the aggregates are not dissociated during the measurement 358 359 process.

360 Here, we emphasised the importance to better understand MNP fate and behaviour aiming to 361 control particle size distribution in the corresponding polymer matrix. This constitutes a preliminary step towards the description of more complex aquatic system, such as experimental 362 conditions involving more than two components interacting with one another, such as 363 microalgae (Demir-Yilmaz et al., 2022), and/or by considering natural organic matter as small 364 aggregates already present in the dispersing medium (Clavier et al., 2019). This can result in a 365 complex combination of homo- and heteroaggregates (Praetorius et al., 2020), especially in 366 marine water where all particle contacts are effective due to high ionic strength promoting 367 various aggregation pathways and several possible attachment efficiencies (Clavier et al., 368 2019). These complex interactions make their theoretical and experimental determination 369

challenging (Praetorius et al., 2020), while their influence on exposure parameters remainconcrete on bioavailability in ecotoxicological studies.

372 **3.4.** Implications for ecotoxicological studies

In this study, we attempted to produce MP in a range of 20 to 60 µm in order to match the 373 374 retention size range of P. margaritifera (i.e. 2-200 µm) (Pouvreau et al., 1999), which would 375 enable controlled exposition in future experiments. Particle characterization revealed that the MP produced by our method were $\leq 60 \,\mu$ m, but results demonstrated an uncontrolled production 376 of MP <20 μ m, mainly because of particles smaller than 1 μ m (>80% of the total particle 377 number). This experimental artefact raises important questions for the interpretation of 378 379 previously published result from (eco)toxicological studies that used grinding and sieving methods to produce MP without thoroughly characterizing the size range of the particles in the 380 nanometric range (e.g. Schür et al., 2020). Some authors mention such bias to interpreting their 381 382 toxicological data, as illustrated by Revel et al. (2019), who discussed a possible implication of NP in the observed toxicity with regards to their MP production method. Whenever possible, 383 the proportion of small MP and NP must be characterized and considered in the exposition 384 levels, especially with regard to the hypothesis that particle toxicity increases as size decreases 385 (Jeong et al., 2016; Ma et al., 2016). This is a real problem for assessing the toxicity of MNP 386 387 to obtain relevant data for decision support, but also because no data is available regarding in situ NP contamination (Schwaferts et al., 2019). In addition, the lack of consideration of the 388 smallest particle sizes also raises an ethical issue associated to pollution with the possible 389 390 release of NP in wastewater effluents from experiments. Indeed, NP may pass through most of the filtration devices, therefore entering the natural environment (Paul-Pont et al., 2018). 391

Overall, our study highlights that controlling the size distributions of small MP and NPfollowing laboratory MP production poses some significant challenges since their hierarchical

394	self-assembly remains a physical problem. While waiting for better knowledge of in situ
395	contamination, there is an important need to improve particle production methodology and
396	associated characterization of particle populations.

397 Author information

398 Corresponding Author

*Phone: (+689) 40 54 60 47. Fax: (+689) 40 54 60 99. E-mail: tony.gardon@ifremer.fr

400 **ORCID**

401 Tony Gardon: 0000-0002-5761-0526

402 Notes

403 The authors declare no competing financial interest

404 Acknowledgments

This study was financially supported by the MICROLAG project funded by *Direction des Ressources Marines* (DRM) of French Polynesia and by the European INTERREG France
(Channel) England project "Preventing Plastic Pollution" co-financed by the European
Regional Development Fund. T. Gardon was funded by a doctoral research grant N°09793 from
Ifremer. We would like to thank the *Institut de Radioprotection et de Sûreté Nucléaire* (IRSN)
of French Polynesia for supplying liquid nitrogen, particularly Patrick Bouisset (Laboratory of
Environment Study and Monitoring – IRSN – LESE).

412 **References**

- Akcora, P., Liu, H., Kumar, S.K., Moll, J., Li, Y., Benicewicz, B.C., Schadler, L.S., Acehan,
 D., Panagiotopoulos, A.Z., Pryamitsyn, V., Ganesan, V., Ilavsky, J., Thiyagarajan, P.,
 Colby, R.H., Douglas, J.F., 2009. Anisotropic self-assembly of spherical polymergrafted nanoparticles. Nature Mater 8, 354–359. https://doi.org/10.1038/nmat2404
- 416 graned hanoparticles. Nature Mater 8, 554–559. https://doi.org/10.1058/inhat2404 417 Andrady, A.L., 2011. Microplastics in the marine environment. Marine Pollution Bulletin 62,

418 1596–1605. https://doi.org/10.1016/j.marpolbul.2011.05.030

- Andréfouët, S., Thomas, Y., Lo, C., 2014. Amount and type of derelict gear from the declining
 black pearl oyster aquaculture in Ahe atoll lagoon, French Polynesia. Marine Pollution
 Bulletin 83, 224–230. https://doi.org/10.1016/j.marpolbul.2014.03.048
- Ashraf, M.A., Peng, W., Zare, Y., Rhee, K.Y., 2018. Effects of Size and Aggregation/Agglomeration of Nanoparticles on the Interfacial/Interphase Properties and Tensile Strength of Polymer Nanocomposites. Nanoscale Research Letters 13, 214. https://doi.org/10.1186/s11671-018-2624-0
- Balakrishnan, G., Lagarde, F., Chassenieux, C., Nicolai, T., 2020. Characterisation of Colloidal
 Particles in Seawater by Light Scattering Techniques.
 https://doi.org/10.20944/preprints202003.0189.v1
- Carrasco-Navarro, V., Muñiz-González, A.-B., Sorvari, J., Martínez-Guitarte, J.-L., 2021.
 Altered gene expression in *Chironomus riparius* (insecta) in response to tire rubber and
 polystyrene microplastics. Environmental Pollution 285, 117462.
 https://doi.org/10.1016/j.envpol.2021.117462
- Clavier, A., Praetorius, A., Stoll, S., 2019. Determination of nanoparticle heteroaggregation
 attachment efficiencies and rates in presence of natural organic matter monomers.
 Monte Carlo modelling. Science of The Total Environment 650, 530–540.
 https://doi.org/10.1016/j.scitotenv.2018.09.017
- Cole, M., 2016. A novel method for preparing microplastic fibers. Sci Rep 6, 34519.
 https://doi.org/10.1038/srep34519
- Connors, K.A., Dyer, S.D., Belanger, S.E., 2017. Advancing the quality of environmental microplastic research: Advancing the quality of environmental microplastic research.
 Environ Toxicol Chem 36, 1697–1703. https://doi.org/10.1002/etc.3829
- Cózar, A., Echevarria, F., Gonzalez-Gordillo, J.I., Irigoien, X., Ubeda, B., Hernandez-Leon, S.,
 Palma, A.T., Navarro, S., Garcia-de-Lomas, J., Ruiz, A., Fernandez-de-Puelles, M.L.,
 Duarte, C.M., 2014. Plastic debris in the open ocean. Proceedings of the National
 Academy of Sciences 111, 10239–10244. https://doi.org/10.1073/pnas.1314705111
- Damasceno, P.F., Engel, M., Glotzer, S.C., 2012. Predictive Self-Assembly of Polyhedra into
 Complex Structures. Science 337, 453–457. https://doi.org/10.1126/science.1220869
- 448 De Jaeghere, F., Allémann, E., Leroux, J.C., Stevels, W., Feijen, J., Doelker, E., Gurny, R.,
 449 1999. Formulation and lyoprotection of poly(lactic acid-co-ethylene oxide)
 450 nanoparticles: influence on physical stability and in vitro cell uptake. Pharm Res 16,
 451 859–866. https://doi.org/10.1023/a:1018826103261
- de Sá, L.C., Oliveira, M., Ribeiro, F., Rocha, T.L., Futter, M.N., 2018. Studies of the effects of
 microplastics on aquatic organisms: What do we know and where should we focus our
 efforts in the future? Science of The Total Environment 645, 1029–1039.
 https://doi.org/10.1016/j.scitotenv.2018.07.207
- Demir-Yilmaz, I., Yakovenko, N., Roux, C., Guiraud, P., Collin, F., Coudret, C., ter Halle, A.,
 Formosa-Dague, C., 2022. The role of microplastics in microalgae cells aggregation: A
 study at the molecular scale using atomic force microscopy. Science of The Total
 Environment 832, 155036. https://doi.org/10.1016/j.scitotenv.2022.155036

- 460 Deng, K., Luo, Z., Tan, L., Quan, Z., 2020. Self-assembly of anisotropic nanoparticles into
 461 functional superstructures. Chem. Soc. Rev. 49, 6002–6038.
 462 https://doi.org/10.1039/D0CS00541J
- 463 Eitzen, L., Paul, S., Braun, U., Altmann, K., Jekel, M., Ruhl, A.S., 2019. The challenge in
 464 preparing particle suspensions for aquatic microplastic research. Environ Res 168, 490–
 465 495. https://doi.org/10.1016/j.envres.2018.09.008
- El Hadri, H., Gigault, J., Maxit, B., Grassl, B., Reynaud, S., 2020. Nanoplastic from
 mechanically degraded primary and secondary microplastics for environmental
 assessments. NanoImpact 17, 100206. https://doi.org/10.1016/j.impact.2019.100206
- Eriksen, M., Lebreton, L.C.M., Carson, H.S., Thiel, M., Moore, C.J., Borerro, J.C., Galgani, F.,
 Ryan, P.G., Reisser, J., 2014. Plastic Pollution in the World's Oceans: More than 5
 Trillion Plastic Pieces Weighing over 250,000 Tons Afloat at Sea. PLoS ONE 9,
 e111913. https://doi.org/10.1371/journal.pone.0111913
- Gardon, T., El Rakwe, M., Paul-Pont, I., Le Luyer, J., Thomas, L., Prado, E., Boukerma, K., 473 Cassone, A.-L., Quillien, V., Soyez, C., Costes, L., Crusot, M., Dreanno, C., Le 474 Moullac, G., Huvet, A., 2021. Microplastics contamination in pearl-farming lagoons of 475 476 French Polynesia. Journal of Hazardous Materials 126396. https://doi.org/10.1016/j.jhazmat.2021.126396 477
- Gardon, T., Huvet, A., Paul-Pont, I., Cassone, A.-L., Sham Koua, M., Soyez, C., Jezequel, R.,
 Receveur, J., Le Moullac, G., 2020a. Toxic effects of leachates from plastic pearlfarming gear on embryo-larval development in the pearl oyster *Pinctada margaritifera*.
 Water Research 179, 115890. https://doi.org/10.1016/j.watres.2020.115890
- Gardon, T., Morvan, L., Huvet, A., Quillien, V., Soyez, C., Le Moullac, G., Le Luyer, J., 2020b.
 Microplastics induce dose-specific transcriptomic disruptions in energy metabolism and
 immunity of the pearl oyster *Pinctada margaritifera*. Environmental Pollution 266,
 115180. https://doi.org/10.1016/j.envpol.2020.115180
- 486 Gardon, T., Reisser, C., Soyez, C., Quillien, V., Le Moullac, G., 2018. Microplastics Affect
 487 Energy Balance and Gametogenesis in the Pearl Oyster *Pinctada margaritifera*.
 488 Environmental Science & Technology. https://doi.org/10.1021/acs.est.8b00168
- Hahladakis, J.N., Velis, C.A., Weber, R., Iacovidou, E., Purnell, P., 2018. An overview of
 chemical additives present in plastics: Migration, release, fate and environmental impact
 during their use, disposal and recycling. Journal of Hazardous Materials 344, 179–199.
 https://doi.org/10.1016/j.jhazmat.2017.10.014
- Hotze, E.M., Phenrat, T., Lowry, G.V., 2010. Nanoparticle Aggregation: Challenges to
 Understanding Transport and Reactivity in the Environment. Journal of Environmental
 Quality 39, 1909–1924. https://doi.org/10.2134/jeq2009.0462
- Jahnke, A., Arp, H.P.H., Escher, B.I., Gewert, B., Gorokhova, E., Kühnel, D., Ogonowski, M.,
 Potthoff, A., Rummel, C., Schmitt-Jansen, M., Toorman, E., MacLeod, M., 2017.
 Reducing Uncertainty and Confronting Ignorance about the Possible Impacts of
 Weathering Plastic in the Marine Environment. Environmental Science & Technology
 Letters 4, 85–90. https://doi.org/10.1021/acs.estlett.7b00008
- Jain, N., Trabelsi, S., Guillot, S., McLoughlin, D., Langevin, D., Letellier, P., Turmine, M.,
 2004. Critical Aggregation Concentration in Mixed Solutions of Anionic
 Polyelectrolytes and Cationic Surfactants. Langmuir 20, 8496–8503.
 https://doi.org/10.1021/la0489918
- Jeong, C.-B., Won, E.-J., Kang, H.-M., Lee, M.-C., Hwang, D.-S., Hwang, U.-K., Zhou, B.,
 Souissi, S., Lee, S.-J., Lee, J.-S., 2016. Microplastic Size-Dependent Toxicity,
 Oxidative Stress Induction, and p-JNK and p-p38 Activation in the Monogonont Rotifer
 (*Brachionus koreanus*). Environmental Science & Technology 50, 8849–8857.
 https://doi.org/10.1021/acs.est.6b01441

- Kühn, S., van Oyen, A., Booth, A.M., Meijboom, A., van Franeker, J.A., 2018. Marine
 microplastic: Preparation of relevant test materials for laboratory assessment of
 ecosystem impacts. Chemosphere 213, 103–113.
 https://doi.org/10.1016/j.chemosphere.2018.09.032
- Lee, Y.H., Lay, C.L., Shi, W., Lee, H.K., Yang, Y., Li, S., Ling, X.Y., 2018. Creating two selfassembly micro-environments to achieve supercrystals with dual structures using
 polyhedral nanoparticles. Nat Commun 9, 2769. https://doi.org/10.1038/s41467-01805102-x
- Lenz, R., Enders, K., Nielsen, T.G., 2016. Microplastic exposure studies should be
 environmentally realistic. Proc Natl Acad Sci USA 113, E4121–E4122.
 https://doi.org/10.1073/pnas.1606615113
- Ma, Y., Huang, A., Cao, S., Sun, F., Wang, L., Guo, H., Ji, R., 2016. Effects of nanoplastics and microplastics on toxicity, bioaccumulation, and environmental fate of phenanthrene in fresh water. Environmental Pollution 219, 166–173. https://doi.org/10.1016/j.envpol.2016.10.061
- Oyinloye, T.M., Yoon, W.B., 2020. Effect of Freeze-Drying on Quality and Grinding Process
 of Food Produce: A Review. Processes 8, 354. https://doi.org/10.3390/pr8030354
- Park, C.-H., Jeon, H.-S., Yu, H.-S., Han, O.-H., Park, J.-K., 2008. Application of Electrostatic
 Separation to the Recycling of Plastic Wastes: Separation of PVC, PET, and ABS.
 Environ. Sci. Technol. 42, 249–255. https://doi.org/10.1021/es070698h
- Paul-Pont, I., Tallec, K., Gonzalez-Fernandez, C., Lambert, C., Vincent, D., Mazurais, D., 530 531 Zambonino-Infante, J.-L., Brotons, G., Lagarde, F., Fabioux, C., Soudant, P., Huvet, A., 2018. Constraints and Priorities for Conducting Experimental Exposures of Marine 532 Organisms Microplastics. Front. Mar. Sci. 533 to 5. https://doi.org/10.3389/fmars.2018.00252 534
- Phuong, N.N., Zalouk-Vergnoux, A., Poirier, L., Kamari, A., Châtel, A., Mouneyrac, C.,
 Lagarde, F., 2016. Is there any consistency between the microplastics found in the field
 and those used in laboratory experiments? Environmental Pollution 211, 111–123.
 https://doi.org/10.1016/j.envpol.2015.12.035
- Pouvreau, S., Jonquières, G., Buestel, D., 1999. Filtration by the pearl oyster, Pinctada margaritifera, under conditions of low seston load and small particle size in a tropical lagoon habitat. Aquaculture 176, 295–314. https://doi.org/10.1016/S0044-542 8486(99)00102-7
- Praetorius, A., Badetti, E., Brunelli, A., Clavier, A., Alberto Gallego-Urrea, J., Gondikas, A., 543 544 Hassellöv, M., Hofmann, T., Mackevica, A., Marcomini, A., Peijnenburg, W., K. Quik, J.T., Seijo, M., Stoll, S., Tepe, N., Walch, H., Kammer, F. von der, 2020. Strategies for 545 determining heteroaggregation attachment efficiencies of engineered nanoparticles in 546 547 aquatic environments. Environmental Science: Nano 7. 351-367. https://doi.org/10.1039/C9EN01016E 548
- Revel, M., Lagarde, F., Perrein-Ettajani, H., Bruneau, M., Akcha, F., Sussarellu, R., Rouxel, J.,
 Costil, K., Decottignies, P., Cognie, B., Châtel, A., Mouneyrac, C., 2019. TissueSpecific Biomarker Responses in the Blue Mussel *Mytilus spp*. Exposed to a Mixture of
 Microplastics at Environmentally Relevant Concentrations. Front. Environ. Sci. 7.
 https://doi.org/10.3389/fenvs.2019.00033
- Rochman, C.M., Brookson, C., Bikker, J., Djuric, N., Earn, A., Bucci, K., Athey, S.,
 Huntington, A., McIlwraith, H., Munno, K., Frond, H.D., Kolomijeca, A., Erdle, L.,
 Grbic, J., Bayoumi, M., Borrelle, S.B., Wu, T., Santoro, S., Werbowski, L.M., Zhu, X.,
 Giles, R.K., Hamilton, B.M., Thaysen, C., Kaura, A., Klasios, N., Ead, L., Kim, J.,
 Sherlock, C., Ho, A., Hung, C., 2019. Rethinking microplastics as a diverse contaminant

- suite. Environmental Toxicology and Chemistry 38, 703–711.
 https://doi.org/10.1002/etc.4371
- Rowdhwal, S.S.S., Chen, J., 2018. Toxic Effects of Di-2-ethylhexyl Phthalate: An Overview.
 BioMed Research International 2018, e1750368. https://doi.org/10.1155/2018/1750368
- Schür, C., Zipp, S., Thalau, T., Wagner, M., 2020. Microplastics but not natural particles induce
 multigenerational effects in *Daphnia magna*. Environmental Pollution 260, 113904.
 https://doi.org/10.1016/j.envpol.2019.113904
- Schwaferts, C., Niessner, R., Elsner, M., Ivleva, N.P., 2019. Methods for the analysis of
 submicrometer- and nanoplastic particles in the environment. TrAC Trends in
 Analytical Chemistry 112, 52–65. https://doi.org/10.1016/j.trac.2018.12.014
- Thornton Hampton, L.M., Lowman, H., Coffin, S., Darin, E., De Frond, H., Hermabessiere, L.,
 Miller, E., de Ruijter, V.N., Faltynkova, A., Kotar, S., Monclús, L., Siddiqui, S., Völker,
 J., Brander, S., Koelmans, A.A., Rochman, C.M., Wagner, M., Mehinto, A.C., 2022. A
 living tool for the continued exploration of microplastic toxicity. Microplastics and
 Nanoplastics 2, 13. https://doi.org/10.1186/s43591-022-00032-4
- van Sebille, E., Wilcox, C., Lebreton, L., Maximenko, N., Hardesty, B.D., van Franeker, J.A.,
 Eriksen, M., Siegel, D., Galgani, F., Law, K.L., 2015. A global inventory of small
 floating plastic debris. Environmental Research Letters 10, 124006.
 https://doi.org/10.1088/1748-9326/10/12/124006
- 578 Whitesides, G.M., Grzybowski, B., 2002. Self-assembly at all scales. Science 295, 2418–2421.
 579 https://doi.org/10.1126/science.1070821
- Woodall, L.C., Sanchez-Vidal, A., Canals, M., Paterson, G.L.J., Coppock, R., Sleight, V.,
 Calafat, A., Rogers, A.D., Narayanaswamy, B.E., Thompson, R.C., 2014. The deep sea
 is a major sink for microplastic debris. Royal Society Open Science 1, 140317–140317.
 https://doi.org/10.1098/rsos.140317
- Yanar, D.K., Kwetkus, B.A., 1995. Electrostatic separation of polymer powders. Journal of
 Electrostatics, Selected papers from the special technical session "Electrostatics in
 Polymer Processing and Charge Monitoring", 1993 IEEE Industry Applications Society
 Meeting 35, 257–266. https://doi.org/10.1016/0304-3886(94)00044-W
- 588Yeap, S.P., 2018. Permanent agglomerates in powdered nanoparticles: Formation and future589prospects.PowderTechnology323,51–59.590https://doi.org/10.1016/j.powtec.2017.09.042
- Zimmermann, L., Göttlich, S., Oehlmann, J., Wagner, M., Völker, C., 2020. What are the drivers of microplastic toxicity? Comparing the toxicity of plastic chemicals and particles to *Daphnia magna*. Environmental Pollution 267, 115392.
 https://doi.org/10.1016/j.envpol.2020.115392
- 595



598

Figure 1. Polymer identification in two plastic pearl farming gear types by FTIR. Polypropylene (PP) for the spat collector (A) and polyethylene (PE) for the synthetic rope (B). Photographs show the spat collector (C) and synthetic rope (E) and their associated plastic pieces (D and F, respectively) used for MP production. Spectra of particles produced were identical to those of plastic gears, hence not added here. Adapted from Gardon et al. (2020a).



Figure 2. Synthetic diagram of the microplastic production method tested.

Table 1. Microplastic fractions produced from the two types of plastic pearl farming gearaccording to grinding time.

Grinding time	MP fraction	Plastic type					
		PP spat collector		PE rope			
		Weight (g)	Proportion (%)	Weight (g)	Proportion (%)		
Initial		4.0000	100.0	4.0000	100.0		
1 min	>60 µm	3.9588	99.0	3.6410	91.0		
	20–60 µm	0.0344	0.9	0.1490	3.7		
	Loss*	0.0068	0.2	0.2100	5.2		
2 min	>60 µm	3.9377	98.4	3.1050	77.6		
	20–60 µm	0.0295	0.7	0.6900	17.2		
	Loss*	0.0328	0.8	0.2050	5.1		
3 min	>60 µm	3.8676	96.7	3.6890	92.2		
	20–60 µm	0.0305	0.8	0.1620	4.0		
	Loss*	0.1019	2.5	0.1490	3.7		

611

⁶¹² * The loss of plastic mass was calculated by subtracting the weighed MP fractions from the

613 initial 4.00 g of plastic pieces.



617 Figure 3. Particle size distribution of microplastics obtained in the 20-60 µm fraction as assessed by Coulter counter analyses. Density plots of particle size distribution of MP 20-60 618 619 µm fraction obtained from spat collector (A) and rope (B) samples according to grinding times of 1, 2 and 3 minutes. Bar chart of the relative abundance of particle count across size ranges 620 of 2–20 µm and 20–60 µm according to plastic type (C). The dashed black line on the density 621 plots indicates the minimal 2 µm detection thresholds from the Coulter counter (equipped with 622 a 100 µm aperture tube) analysis. The grey area corresponds to the 20 to 60 µm sieving range 623 used in the present microplastic production method. Bar chart illustrate mean \pm SD with 624 grinding times as replicates (n = 3). Letters indicate statistically significant differences between 625 626 groups.

Table 2. Relative abundance of microplastics produced in the 20–60 μm fraction according to

628 their size distribution above the $2 \mu m$ threshold.

Plastic type	Grinding time	Percentage of particle count (%)					
		2-3 μm	<5 µm	<10 µm	<20 μm	20–60 µm	
PP spat collector	1 min	62	82	88	94	6	
	2 min	53	66	71	82	18	
	3 min	56	69	74	84	16	
PE rope	1 min	70	88	92	96	4	
	2 min	60	80	87	94	6	
	3 min	60	79	84	92	8	

629



Figure 4. Particle size distribution of microplastics obtained in the 20–60 μ m fraction as assessed by laser diffraction analyses. Bar plots (A–D) show the differences in number and volume of particle sizes made from spat collector (A–B) and rope (C–D) by 1 min of grinding. The dashed black line indicates the minimal 2 μ m detection thresholds from the Coulter counter (equipped with a 100 μ m aperture tube). The grey area corresponds to the 20 to 60 μ m sieving range used in the present microplastic production method.





Figure 5. Representative SEM images of microplastics in the 20–60 µm fraction produced in
this study and their spontaneous self-assembly into crystal superstructures through slow solvent

evaporation. Pictures of MP made from spat collector (A) and rope (B) samples taken in dry 644 645 conditions. Pictures of ordered assemblies from colloidal micro- and nanoplastics (MNP) of various shapes into crystalline structures with a cuboid shape at all physical scales (C–H). These 646 spontaneous assemblies are associated with attractive forces among particles (e.g. van der 647 Waals forces, electrostatic, hydrophobic interactions) and ligand-substrate interactions (e.g. 648 chemisorption) responsible for forcing particles to self-arrange into ordered assemblies with 649 650 multi-layered superstructures (F–G). Connective flow during solvent evaporation concentrates plastic particles and 3D crystals near the drying front, giving rise to building blocks that grow 651 to larger dimensions until complete solvent evaporation occurs and supercrystals form at the 652 653 millimetric scale (H). A synthetic scheme adapted and redrawn from Lee et al. (2018) and Deng et al. (2020) illustrates this process (I). 654