

Generating LG modes for atom trapping in a Sr optical lattice clock

Miguel A Cifuentes Marin, Haosen Shang, Yannick Foucault, Rodolphe Le Targat, Jérôme Lodewyck

► To cite this version:

Miguel A Cifuentes Marin, Haosen Shang, Yannick Foucault, Rodolphe Le Targat, Jérôme Lodewyck. Generating LG modes for atom trapping in a Sr optical lattice clock. 2022 Joint conference of the European Frequency and Time Forum & the IEEE International Frequency Control Symposium, Apr 2022, Paris, France. IEEE Xplore, 2022, 10.1109/EFTF/IFCS54560.2022.9850746. hal-04204835

HAL Id: hal-04204835 https://hal.science/hal-04204835

Submitted on 12 Sep 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Generating LG modes for atom trapping in a Sr optical lattice clock

Miguel A. Cifuentes Marin¹, Haosen Shang¹, Yannick Foucault¹, Rodolphe Le Targat¹, Jérôme Lodewyck¹

¹LNE-SYRTE, Observatoire de Paris, Université PSL, CNRS, Sorbonne Université





We propose to increase the number of trapping sites in a magic wavelength optical lattice by using sinusoidal LG_{0l} modes with azimuthal index l, whose transverse profile is composed of 2l identical trapping sites. Consequently, we expect a better accuracy of our clock by reducing the density of atoms per site. The new proposed trapping potential can be modeled by the equation:

$$U_{0l}(r,\varphi,z) = -\alpha_{E_1} I_0 e^{\frac{-2r^2}{w^2(z)}} \cos^2\left[kz - \psi_l(z)\right] \\ \times \left(\frac{-2r^2}{w^2(z)}\right)^{|l|} \cos^2(l\varphi)$$



PSL

Observatoire

I. LG modes implementation

 \Rightarrow **Setup** for the generation and PDH locking of LG modes.



The LG modes are generated using an LCOS-SLM. The SLM displays a computer generated hologram which encode the phase of the LG mode [4] and a diffraction

LG grating. The shape of the desired mode appears in the \Rightarrow Hologram and generated LG_{02} mode first diffraction order.





The cavity filters the shape of the beam diffracted by the SLM when using a blazed grating. The hologram corresponds to a spatial period $T_x = 662.5 \ \mu m$ or a number of grooves $n_x = 24$.

II. SLM diffraction and coupling efficiencies



 \Rightarrow The SLM diffraction efficiency η_{slm} , can be improved by decreasing the number of grooves. The results on the left figure were obtained for $n_x = 70$.

III. Total efficiency

The total efficiency of the setup: $\eta_{tot} \approx \eta_{slm} \eta_c$.

 \Rightarrow Blazed grating presents $\eta^B_{slm} \sim 70\%$ on the first diffraction order. In spite of some similarities the diffracted order exposes a shape other than the LG_{0l} mode.

 \Rightarrow Sinusoidal grating exposes the desired LG_{0l} encoded on the hologram. However, $\eta_{slm}^S < 30\%$.

 \Rightarrow Intermediate grating shows $\eta_{slm}^{I} \sim 40\%$. There was two diffraction orders, where one of them was the LG_{0l} mode.

 $\Rightarrow \textbf{Coupling efficiency: } \eta_c^I > \eta_c^S > \eta_c^B$



 \Rightarrow Blazed grating is the most efficient for the setup along the optical path, so it remains appropriate for the creation of the optical lattice trap.

LG_{0l}	0	1	2	3	4
η_{tot}	0.438	0.317	0.183	0.121	0.080
$U_0 [E_r]$	1095	792	457	302	200

On our Sr clocks the minimum depth required is about $100E_r$ for the clock interrogation stage. However, with the optical drain technique we used to transfer the atoms from the blue MOT to the optical lattice [5], a trapping depth as large as $1000E_r$ is required.

Acknowledgements

IV. LG lattice loading methods

Having generated the LG modes we expect to load the new lattice by two different methods.

LG lattice potential. The challenge is the determination of the best geometry of the drain.



⇒ Method 1: Transfer of atoms from a TEM₀₀ lattice potential to an LG lattice potential. An automatic locking switch between the selected modes is being developed. ⇒ Method 2: Transfer of atoms from the MOT to the



This work was supported by the European Union from the European Metrology Programme for Innovation and Research (EMPIR) project ROCIT 18SIB05. EMPIR projects are co-funded by the European Union's Horizon 2020 research and innovation program and the EM-PIR participating states.

First, we expect to compute the loading efficiencies of the LG lattice by running Montecarlo simulations for the proposed methods, and then we will run experiments for comparing them. Also, future works will focus on studying the systematic uncertainty associated with cold collisions and lattice light shifts effects.

References

- [1] W. F. McGrew, X. Zhang, R. J. Fasano, S. A. Schäffer, K. Beloy, D. Nicolodi, R. C. Brown, N. Hinkley, G. Milani, M. Schioppo, T. H. Yoon, and A. D. Ludlow. Atomic clock performance enabling geodesy below the centimetre level. *Nature*, 564(7734), December 2018.
- [2] Matthew A. Norcia, Aaron W. Young, William J. Eckner, Eric Oelker, Jun Ye, and Adam M. Kaufman. Seconds-scale coherence on an optical clock transition in a tweezer array. Science, 366(6461), October 2019.
- [3] Akatsuka Tomoya, Masao Takamoto, and Katori Hidetoshi. Three-dimensional optical lattice clock with bosonic 88Sr atoms. Physical Review A, February 2010.
- [4] Vincent Carrat, Citlali Cabrera-Gutiérrez, Marion Jacquey, José W. Tabosa, Bruno Viaris de Lesegno, and Laurence Pruvost. Long-distance channeling of cold atoms exiting a 2D magneto-optical trap by a Laguerre-Gaussian laser beam. Optics Letters, 39(3), February 2014.
- [5] Jérôme Lodewyck, Slawomir Bilicki, Eva Bookjans, Jean-Luc Robyr, Chunyan Shi, Grégoire Vallet, Rodolphe Le Targat, Daniele Nicolodi, Yann Le Coq, Jocelyne Guéna, Michel Abgrall, Peter Rosenbusch, and Sébastien Bize. Optical to microwave clock frequency ratios with a nearly continuous strontium optical lattice clock. *Metrologia*, 53(4), July 2016.