

Near-future projections in continuous agent-based models for crowd dynamics: mathematical structures in use and their implications

Iñaki Echeverría-Huarte, Antonin Roge, Olivier Simonin, Alexandre Nicolas

To cite this version:

Iñaki Echeverría-Huarte, Antonin Roge, Olivier Simonin, Alexandre Nicolas. Near-future projections in continuous agent-based models for crowd dynamics: mathematical structures in use and their implications. $2024.$ hal- $04213884v2$

HAL Id: hal-04213884 <https://hal.science/hal-04213884v2>

Preprint submitted on 19 Aug 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Near-future projections in continuous agent-based models for crowd dynamics: mathematical structures in use and their implications

Iñaki ECHEVERRÍA-HUARTE,^{1, 2, *} Antonin ROGE,³ Olivier SIMONIN,⁴ and Alexandre NICOLAS^{3,†}

 1 Centro de Física Teórica e Computacional, Faculdade de Ciências,

Universidade de Lisboa, 1749-016 Lisboa, Portugal.

 2 Depto. de Física y Mat. Apl., Facultad de Ciencias,

 3 Universite Claude Bernard Lyon 1, CNRS, Institut Lumière Matière, 69100 Villeurbanne, France. $\frac{1}{\epsilon}$

⁴CITI lab., INSA de Lyon, Inria, 69621 Villeurbanne, France.

(Dated: August 19, 2024)

This paper addresses the theoretical foundations of pedestrian models for crowd dynamics. While the topic gains momentum, current models differ widely in their mathematical structure, even if we only consider continuous agent-based models. To clarify their underpinning, we first lay mathematical foundations for the common hierarchical decomposition into strategic, tactical, and operational levels and underline the practical interest in preserving the continuity between the latter two levels by working with a floor field, rather than way-points. Turning to local navigation, we clarify how three archetypical approaches, namely, purely reactive models, anticipatory models based on the idea of times to collision, and game theory, differ in the way they extrapolate trajectories in the near future. We also insist on the oft-overlooked distinction between processes pertaining to decision-making and mechanical effects in dense settings. The implications of these differences are illustrated with a comparison of the numerical predictions of these models in the simple scenario of head-on collision avoidance between agents, by varying the walking speed, the reaction times, and the degree of courtesy of the agents, notably.

I. INTRODUCTION

Many breakthroughs in modern science have hinged on a reshuffling of the mathematical framework in use. For instance, the ability of modern statistics to account for the regularities of human anatomical features or social events [1, 2] can hardly be dissociated from the mathematical handling of errors and uncertainties and the thenemerging theories of probabilities [3]. Similarly, the theoretical revisitation of the foundations of economics by von Neumann and Morgenstern [4] has been instrumental for the progress of modern economics. Transportation science has largely benefited from the advances in these two disciplines.

Presently, within the field of transportation, modeling pedestrian dynamics is a topic that gains more and more traction, due to both its practical relevance for crowd safety [5] and flow management, and its theoretical intricacy [6, 7]. But at the same time, little thought has been dedicated to the soundness of its conceptual foundations. In fact, one almost takes for granted that pedestrian models should retain the formal structure in place in the fields that inspired them.

Thus, models originating from the field of algorithmic robotics (or computer graphics) typically rely on the notion of velocity obstacles, i.e., the set of all velocities leading to a collision before a predefined time horizon [8–10], and the idea that the chosen velocity should not belong to this set. What matters most is to reach a target while avoiding collisions at all costs. In this sense, mathematical proofs are often given to guarantee the absence of collisions, at least in some regimes [11].

Shifting the emphasis from global maneuverability to individual choice, economists and econometricians have employed the structure of discrete-choice models to find which step is optimal [12] and adequately calibrate their model [13]; each agent then chooses to make a step which optimizes a utility function depending on various factors. The idea of optimal steps was also taken up in the optimal-step model [14], from a more pragmatic standpoint.

By contrast, physicists have propounded a line of models that keep the formal structure of Newton's second law and handle interactions between pedestrians in the same way as mechanical forces. This is the case for the celebrated social force model [15] and its countless extensions and variants [16–18]. Contacts and collisions between agents are then possible, particularly at high density, so that these models are frequently used to study evacuations; besides, they heavily (arguably, too heavily) rely on these contact forces to reproduce the collective flow of crowds [19]. The equations of motion underlying these models are structurally similar to those used for simple self-propelled particles, such as active Brownian particles [20]. But Moussaid et al. insisted on the more heuristic nature that is actually at play in pedestrians' decisions of motion, thus regarding the desired velocity (or self-propulsion velocity in the terminology of active matter) as the output of some heuristic rules; their model

Universidad de Navarra, E-31080 Pamplona, Spain.

[∗] iehuarte@fc.ul.pt

[†] alexandre.nicolas@cnrs.fr

[‡] École Normale Supérieure Paris-Saclay, 4 Av. des Sciences, 91190 Gif-sur-Yvette, France;

was successfully tested against experimental data in a broad range of situations [21]. Along similar lines, some of us have recently proposed an agent-based model which feeds the output of a decisional layer, consisting of several contributions, into a mechanical equation of motion; the model was validated in an even broader range of situations [22].

The present paper is not aimed at putting forward yet another specific model. Instead, in the continuation of the short report in [23], it aspires to delve into the mathematical structure of agent-based pedestrian models and clarify their implications on the dynamics that the models predict. We will start from a very broad perspective and revisit in Sec. II the hierarchical decomposition into levels of description of pedestrian motion, showing that strictly adhering to the distinction between the tactical level and the operational one can be limiting for practical purposes. Then, focusing on local navigation, we will stress the difference between the influence of the environment (human and built) on walking choices and their mechanical effects in case of contacts. The theoretical discussion will be illustrated using three archetypal models for operational pedestrian dynamics, introduced in Sec. III. Section IV will expose to what extent their numerical predictions differ, with an emphasis on the simple scenario of head-on collision avoidance between agents. We will draw our final conclusions in Sec. V.

II. A DEEP DIVE INTO THE FOUNDATIONS OF PEDESTRIAN AGENT-BASED MODELS

A. Levels of description of pedestrian dynamics

Pedestrian flows can be probed at different scales. Typically, the modeler's task is split into three levels: a strategic level (where do I want to go and when?), a tactical level (what route do I take to reach this goal?) and an operational level (how do I interact with the human and built environment locally, en route?), using the terminology of $[24]$. In this section, we will enquire into this decomposition and see that, depending on how strictly it is enforced and on the extent to which future is anticipated, different branches of models for local navigation arise. With this clarification in mind, we will question the relevance of a stark distinction between the tactical and operational levels.

It makes no doubt that the foregoing levels of description are coupled to some extent. For instance, should I contemplate going to the sea, my ultimate strategic decision may be influenced by my (tactical) knowledge of approximately how much it costs to get there, in human, financial, and environmental terms, while the route choice operated at the tactical level may hinge on lowerlevel features. The decomposition may nonetheless be warranted if each level only depends on a coarse-grained vision of the lower levels.

To grasp the possible limitations of this reasoning,

let us sharpen the definitions in mathematical terms, namely, in space-time $\Omega \times [0,T]$, where $\Omega \subset \mathbb{R}^2$ is the available geometric space and $[0, T]$ is the time window under consideration. The evolution of a crowd of N agents is then represented by a set of N trajectories $r_i(t)$, for $i = 1...N$ and $t \in [0, T]$. From this perspective, for each agent i , a strategic choice consists in selecting a target region \mathcal{T}_i in spacetime:

$$
[\text{stratney}] \text{ Choose } \mathcal{T}_i \subset \Omega \times [0, T] \tag{1}
$$

Multiple path routes \mathcal{R}_i , i.e., classes of 'equivalent' trajectories defined over the time window $[0, T]$, may lead to the target in space, which we assume is reached by time T. Topologically, there are but few possible definitions of such classes of equivalence; two trajectories are equivalent if they belong to the same homotopy class, i.e., if they can be smoothly deformed into one another without crossing an obstacle or a no-go area. The tactical choice comes down to selecting one of these homotopy classes or routes \mathcal{R}_i , that which minimizes a suitably defined generalized cost \mathcal{C}_i :

[TACTICS] Select
$$
\mathcal{R}_i^*
$$

\n $\mathcal{R}_i^* = \underset{\text{ routes } \mathcal{R}_i}{\arg \min} \mathcal{C}_i [\mathcal{R}_i]_0^T.$ (2)

The route cost can be defined operationally as the optimum over all trajectories r_i belonging to that route,

$$
\mathcal{C}_i[\mathcal{R}_i]_0^T = \min_{\mathbf{r}_i \in \mathcal{R}_i} C_i[\mathbf{r}_i]_0^T. \tag{3}
$$

Finally, only one trajectory $r_i^*(t)$ in this class will materialize at the operational level, during navigation,

[OPERATIONAL] Select
$$
\boldsymbol{r}_i^* \in \mathcal{R}_i^*
$$

\n $\boldsymbol{r}_i^* = \underset{\boldsymbol{r}_i \in \mathcal{R}_i^*}{\arg \min} C_i[\boldsymbol{r}_i]_0^T.$ (4)

B. Selection of an optimal path by rationally bounded agents

To make the problem more concrete, we write the (still fairly generic) cost function as

$$
C_i[\mathbf{r}_i]_0^T = \int_0^T \underbrace{c_i[\mathbf{r}_i(t), \mathbf{r}_{-i}(t)]}_{\text{running cost}} dt \tag{5}
$$

Here, the running cost c_i depends on agent i's trajectory as well as the other agents' trajectories r_{-i} = $(r_1, ..., r_{i-1}, r_{i+1}, ..., r_N)$; the minimizer is the trajectory that is selected operationally. For concreteness, below, we will study simple running costs that just penalize large speeds and the spatial proximity to another agent with a repulsive potential.

Noteworthily, the tactical choice of Eq. 2 is fully entangled with the operational selection of Eq. 4. Adding to this complexity is the dependence of the individual costs C_i on the other agents' trajectories r_{-i} , highlighted in Eq. 5. This is why the optimization problem does not boil down to finding the local minimum of a function, but is a game [4] between different players, the agents, each intent on optimizing their cost but unable to control the opponents' decisions. In other words, the minimization should be understood in the sense of a Nash equilibrium $[25]$, i.e., agent i's 'optimal' choice is conditioned on the fact that the the other agents' trajectories $r_j, j \neq i$, are also optimal for them.

Not only does this process make the model computationally complex, but one may also question its realism: Pedestrians are unable to accurately foresee the others' trajectories; at best can they try to predict them, so that r_{-i} in Eq. 4 should be replaced by its prediction $\tilde{r}_{-i}^{(i)}$ by agent i.

Pragmatically, one can assume that at each time t these predictions are accurate for the short-term future $[t, t + \delta t]$, but are blurry beyond $t + \delta t$, so that the agent needs to adjust their plans of motion every so often, based on their estimation of

$$
C_i[\mathbf{r}_i]_t^T = C_i[\mathbf{r}_i]_t^{t+\delta t} + C_i[\mathbf{r}_i]_{t+\delta t}^T
$$

\n
$$
\approx C_i[\mathbf{r}_i]_t^{t+\delta t} + \tilde{C}_i^{t+\delta t}(\mathbf{r}_i(t+\delta t)),
$$
\n(6)

where $\tilde{C}_i^{t + \delta t}[{\bm r}_i(\delta t)]$ is a 'fuzzy estimate' of the future cost beyond $t + \delta t$ (notice the contrast with the exact treatment of the value function in optimal control theory). Assuming that trajectories cannot be planned to any level of detail in the blurry future, $\tilde{C}_i^{t+\delta t}$ will only depend on the position $r_i(t + \delta t)$ reached at that time. Note, in anticipation, that if δt is small the trajectories can be considered linear, i.e., $\forall j \neq i$, $\mathbf{r}_j(t+\delta t) \simeq \mathbf{r}_j(t)+\mathbf{v}_j(t)\delta t$, so that the minimization of Eq. 6 will ultimately reduce to a dynamical equation of motion: at each time t , each agent *i* has to select an optimal velocity v_i^* .

Quite interestingly, these abstract considerations surreptitiously led to the substitution of the remaining cost $C_i[\mathcal{R}]_{t+\delta t}^T$ in the equation of motion by a floor field (also called potential field or distance function [26, 27]) $\tilde{C}_i^{t+\delta t}(\boldsymbol{r}),$

$$
C_i[\mathcal{R}]_{t+\delta t}^T \leadsto \tilde{C}_i^{t+\delta t}\Big(\boldsymbol{r}(t+\delta t)\Big). \tag{7}
$$

The latter is a real-valued function $\Omega \to \mathbb{R}$ that quantifies how attractive a given location r is effectively, for every class of agents. In principle, it should exactly match the cost of the optimal route from that location to the target location over the time window $[t + \delta t, T]$, but in practice this cost may be assessed roughly, notably in view of the shortest-path distance of r to the goal or via an Eikonal equation [26, 27], traditionally used in ray tracing algorithms, in which the cost of walking through a given zone plays the role of an index of refraction [22].

Alternative approaches to split the tactical and operational layers

The use and storage of floor fields presents the major advantage of making the tactical-operational connection seamless, but it is relatively memory-consuming, say around a few megabytes per agent type for a $100 \text{ m} \times$ 100 m space with a 10 cm resolution. This used to be an issue in the past, but this is no longer so with any modern computer.

Perhaps due to this historic reason, floor fields have seldom been used in continuous models, which generally handle the tactical route planning of Eq. 2 separately from, and prior to, the local navigation of Eq. 4 (there are exceptions, though, e.g. [26]). The tactical layer then feeds the operational one with a preferred velocity [28] or intermediate 'way-points' (glocal description) [10, 29, 30]. This articulation, we will argue, is by no means seamless; see Sec. IV A. In this approach, routes $\mathcal R$ are defined as paths in the visibility graph of the environment, in which two areas are linked if they are directly connected and mutually visible. Route planning favors the route with the shortest distance or, in a dynamic approach, the one with the shortest travel time based on current densities. Then, this route is represented as a series of way-points, or intermediate goals, or midway destinations (which notably go around large obstacles). Compared to the floor field, local navigation will then be guided towards the next way-point (e.g., by making the agent's desired velocity point to it), rather than surf on a space-covering map.

We claim that this entails several drawbacks. To start with, it conceptually establishes an arbitrary frontier between various types of obstacles, the larger ones being accounted for in route planning while the smaller ones are only considered for local navigation [Fig. 1(a-b)]. Topologically, this distinction does not exist: Given that a pedestrian can overlap with neither a large obstacle nor a less extended one (nor another pedestrian [Fig. 1(c)]), all these obstacles generate distinct homotopy classes. Local optimizations starting from a trajectory in one class and smoothly adjusting it cannot depart from the initial route.

Setting arbitrary frontiers between obstacles has tangible fallout. If discrete way-points are introduced at the tactical level as milestones along the route, then the preferred route is immediately set in stone, leaving no alternative. This choice between alternatives may be premature. Consider a situation in which an agent faces a dilemma between two almost equivalent paths, one going left and the other going right, the latter being less favorable by a very thin margin. Adhering to the above decomposition, the route planner will select the left path and set intermediate goals along it. Should a counterwalking pedestrian unexpectedly obstruct the left path, the simulated agent will somewhat deviate from their planned local navigation, but still aim to go left, whereas in reality they would opt for the right path in this circumstance. In other words, the degeneracy reflecting the quasi-equivalence of two, or more, options is lifted too early because of the arbitrary decomposition between the tactical level and the operational one.

C. Modeling local navigation

Irrespective of the way in which tactical planning is implemented (via a road-map or a floor field as in Eq. 6), local pedestrian navigation will also require responding to the motion of neighboring pedestrians in the short-term, foreseeable future. Naturally, the reason why these are more difficult to handle than static obstacles is that they are moving. Thus, in spacetime, they are not cylinders (invariant by translation along the time axis), but nonoverlapping winding tubes (or tunnels).

Purely reactive models such as the Social Force Model (SFM) with circular specification [31] overlook this complication. Other agents are handled similarly to static obstacles, as illustrated in Fig. $2(a)$, that is to say, much in the same way as driven passive particles [32] interacting via a configuration-dependent potential, except that the interactions need not be reciprocal.

At the other extreme, in a game-theoretical approach, in order to steer appropriately, each agent i strives to predict the other agents' motion $\tilde{r}_{-i}^{(i)}$ in the near future, i.e., furthers their tubes in spacetime; see Fig. 2. Then, they adjust their own tube to optimize the generalized cost of Eq. 5. Importantly, furthering the other agents' trajectories is not merely a forecasting task, insofar as these trajectories depend on agent i's choice of motion; thus, agent *i* has to anticipate their neighbors' responses. The numerical resolution of these intricacies requires heavy computations (which prompted the development of mean-field versions of this approach [25, 33]).

To keep in check the computational cost, methods based on the anticipated time to collision (TTC) have been put forward and validated empirically [34]. More precisely, the TTC is computed as the first time in the future at which a collision is expected if the neighbouring agents' velocities are constant. An expression for the TTC-based interaction energy was derived by Karamouzas and colleagues [34], in the form of a cutoff power law. In space-time, basing the potential on the TTC (which is a function of current positions and velocities) comes down to prolonging the other agents' past trajectories as cylinders invariant along their velocity vectors v_j [Fig. 2(b)], whereas a full-fledged gametheoretical approach allows any tubular shape extending into the future [Fig. $2(c)$].

Depending on whether v_i are the neighbors' observed velocities or the velocities expected by i, agent i's task will be either mere forecasting, as in [22], or anticipation of the neighborhood's response. Optimizing the generalized cost as a function of the whole set of velocities $\{v_i\}_{1\leq i\leq N}$, as in [11], goes in the latter direction. That being said, the gap between the two options is narrower than it may look, because all agents update their desired velocity at every time step, once they have actually observed their neighbors' responses to their choice of motion. Still, we will see in Sec. IV D that mere forecasting with frequent updates and anticipation are not equivalent, when studying choices made out of courtesy.

D. Mechanics of locomotion and physical contacts

Pedestrian motion occupies a singular position among transport systems in that physical contacts can occur in close-to-normal flows at high densities. Thus, in addition to choices, mechanical effects need to be taken into account. In this respect, the motion of pedestrian i (as a physical body of mass m and position r_i , averaged over a stepping cycle, is governed by Newton's law of motion, as follows,

$$
m\ddot{\boldsymbol{r}}_i = m\frac{\boldsymbol{u}_i^* - \dot{\boldsymbol{r}}_i}{\tau^{\text{mech}}} + \sum_{j \neq i} \boldsymbol{F}_{j \to i}^{\text{c}} + \sum_{w \in \text{walls}} \boldsymbol{F}_{w \to i}^{\text{c}},\qquad(8)
$$

where $\mathbf{F}_{j \to i}^{\text{c}}$ and $\mathbf{F}_{w \to i}^{\text{c}}$ denote contact forces exerted by neighbouring pedestrians and walls, respectively. The first term of Eq. 8, which represents the controllable part of the acceleration [28] or the damped self-propelling force of an active particle, indicates that the desired velocity u_i^* is not reached instantly, but only after characteristic time τ^{mech} (a fraction of a second in free space) due to the cyclic human gait or the limited friction with the substrate. Importantly, τ^{mech} only depends on locomotion and mechanical interactions, but on no account on the reaction time.

To elucidate this distinction between this mechanical relaxation time and the cognitive reaction time, let us consider the example of a pedestrian walking on solid ground versus skating on an ice rink. While the reaction time of the pedestrian in both situations is the same, τ^{mech} will be longer on the ice rink due to the more slippery surface; the skater will thus need more time to adjust their movements accordingly. To extrapolate to an even broader context, one may contrast the mechanical response time of a boat with that of a ground vehicle. Notably, τ^{mech} is substantially higher for the former, reflecting the specifics of moving on water. These two examples from a broader context highlight the relevance of coupling the mechanical layer centred on Eq. 8 with a decision-making layer determining u_i^* , which is consistent with the early insight of [28], but quite generally overlooked in practice [6, 21, 31, 34].

Alternative approaches

Indeed, in conventional force-based models [15, 31, 34], pseudo-forces are additively inserted into Eq. 8 to account for the deviations from u_i^* due to the local environment (other agents and walls). Conceptually, this is not satisfactory, because it puts these cognition-mediated effects on the same footing as mechanical forces, in particular subjecting them to the same relaxation time scale τ mech. The conflation of mechanical and decisional processes is facilitated in practice by the fact that the cognitive reaction time τ_{ψ} involved in walking is of the same order of magnitude as τ^{mech} and that both (cognitive and mechanical) processes take place within the confines of the same physical entity; the pedestrian. The confusion is much more conspicuous, but of the same nature, if one considers, instead of a pedestrian, a remote-controlled boat, for which $\tau_{\psi} \ll \tau^{\text{mech}}$, and the control operator and the system are spatially separated.

III. PRESENTATION OF DIFFERENT TYPES OF MODELS

After clarifying the conceptual foundations of major frameworks for agent-based pedestrian modeling and their differences, we aim to illustrate their implications in simulations and, for that purpose, this Section introduces archetypal examples for each of the three lines of models under consideration.

A. Game-theoretical model

In Sec. II B, we argued that the agent's selection of a path, in interaction with their environment, can be handled as the optimization of a generalized cost function (Eq. 4), subject to the concomitant path choices of other agents, hence a competition between the agents. This defines a 'game' in the mathematical sense [35]. While this assumption did not restrict the generality of the reasoning, here, to put forward a concrete, minimalistic model, we make further simplifications: we assume that all agents have the same type of cost function and that it takes the following simple form

$$
C_i\Big(\boldsymbol{r}_i|\boldsymbol{r}_{-i}\Big) = \int_0^T \Big[\lambda v_i(t')^2 + \sum_{j \neq i} V(r_{ij}(t'))\Big] dt' + C_i^T\Big(\boldsymbol{r}_i(T)\Big),\tag{9}
$$

where the term in the integrand involving the speed $v_i(t') = ||\dot{\mathbf{r}}_i(t')||$ penalizes large speeds, V is a simple repulsive distance-based potential, e.g., an exponential function $V(r) = V_0 \exp(-r/r_c)$ (using the shorthand $r = ||\mathbf{r}||$, and the terminal cost $C_i^T(\mathbf{r}) = \pm Kx$, drives the agent to its goal (here going left or right). As the scale of the cost C_i does not affect the position of its minimum, it can be rescaled so that $\lambda = 1$. Besides, for an isolated agent, $V = 0$, the cost C_i in Eq. 9 is minimized for a speed $v = K/2$; therefore, the parameter K can be set to $2v_d$, where v_d is the agent's preferential speed.

The game-theoretical problem is thus well defined. To find a Nash equilibrium, we solve Eq. 9 by splitting the

 $\cos t C_i$ into a short-term part over a time window $[t, t+dt]$ and the remaining cost, i.e., the value function $U(\mathbf{r}, t + \mathbf{r})$ $dt = \inf_{\mathbf{v}} \int_{t+dt}^T \cdots + C_i^T$ conditional on the position \mathbf{r}_i reached at time $t + dt$. This leads to Hamilton-Jacobi-Bellman equations for U, after neglecting higher-order terms:

$$
0 = \frac{\partial U}{\partial t} + \sum_{j \neq i} V(||\mathbf{r}_{ij}(t)||) - \frac{1}{4} (\nabla U)^2, \qquad (10)
$$

with boundary condition $U(\mathbf{r}, T) = C_i^T(\mathbf{r}_i)$. Equation 10 is solved numerically over space and time. At each time step $(dt = 0.05 s)$, assuming that the other agent's trajectory (hence r_{ij}) is known, the optimal velocity is calculated as $v^* = -\frac{1}{2}\nabla_r U$, after solving for $U(r, t)$ in Eq. 10 using an Euler finite-difference scheme in space and time, and starting from $t = T$; the amplification of numerical instabilities in the computation of derivatives is mitigated by smoothing the U-fields with a Gaussian kernel (with standard deviation 0.05 m). Supposing that no inertia is at play, the agent updates his or her position with $\mathbf{r}(t+dt) = \mathbf{r}(t) + \mathbf{v} \cdot dt.$

We then proceed iteratively, starting from initial guesses of the two agents' trajectories $r_i(t)$ and $r_j(t)$, and then updating i and j alternatively, until convergence. Note that initial guesses help to reach equilibrium trajectories faster but may constrain their shapes, as several Nash equilibria may exist. On the other hand, we have checked that the algorithm is robust to variations of dt and that the aforementioned rescaling of the cost by λ has no impact.

B. ANticipatory Dynamics Algorithm (ANDA)

The above optimization of a full trajectory in relation with the rest of the crowd may become computationally costly for a crowd. To achieve a trade-off between this account of anticipation and numerical tractability, we turn to anticipatory models, and in particular the ANDA algorithm introduced in [22], which consists of a decision-making layer and a mechanical layer (given by Eq. 8). The desired velocity u_i^* entering the mechanical layer is obtained from the decision-making layer as the velocity that minimizes a cost function $E[\boldsymbol{u}]$ comprising several contributions (Eq. 11). We will briefly recall the main features of this function; for a detailed presentation of the model, the reader is referred to [22].

$$
E[\mathbf{u}] = E_{\text{biomech}} + E_{\text{FF}} + E_{\text{inertia}}
$$

+ $E_{\text{pers-space}} + E_{\text{anticipation}}$ (11)

In free space, only three factors are active: the biomechanical contribution E_{biomech} , which measures the empirical physiological cost of walking at a given speed $u = ||u||$ [36]; the static floor field E_{FF} discussed in Section 2, evaluated at the position to be reached at the next time step with the test velocity u ; and the quadratic penalty E_{inertia} for abrupt changes in velocity. In uniform motion (i.e., no inertial effect), the chosen velocity is then directed along the gradient of E_{FF} and its magnitude v^{pref} minimizes the sum of the first two contributions, as illustrated in Fig. 3. Accordingly, if one knows an agent's free-walking speed v^{pref} , the slope of the floor field can directly be obtained and the model contains no adjustable parameter at this point.

On top of these three contributions, for pedestrians walking alone (no groups), interactions with the built environment and the crowd generate two new terms, reflecting two distinct types of repulsive interactions at play in pedestrian dynamics. The first one, $E_{\text{pers-space}}$, is based on the separation distance between an agent and their neighbours, with a short-ranged repulsive strength decaying with distance, which is familiar to physicists; it reflects the desire of people to preserve a personal space around themselves, whose extent may vary between individuals and between cultures (as studied by the field of proxemics [37]). Beyond these concerns for personal space, pedestrians also pay particular attention to the risk of future collisions and adapt their trajectories to avoid them. Karamouzas et al. demonstrated, using empirical data sets, that these effects are much more readily described using a new variable, the anticipated time to collision (TTC), than distances $[34]$.

In the ANDA model, we have kept this TTC-based energy, $E_{\text{anticipation}}$, except that non-physical collisions between personal spaces are also taken into account (which results in a smoother profile) and only the most imminent collision is considered.

This search for an optimal velocity u_i^* minimizing $E[\mathbf{u}_i]$ is done every τ_{ψ} seconds, which corresponds to the aforementioned cognitive reaction time. The actual velocity is then computed using the mechanical equation of motion, Eq. 8. In particular, it may happen that the selected desired velocity \boldsymbol{u}_i^\star leads to a collision within τ_ψ and thus activates repulsive mechanical forces, an issue which is already addressed in [22], but into which we shall not delve here, because the examples provided below do not involve any physical contacts.

Incidentally, the cost $E[\mathbf{u}_i]$ involves not only the test velocity u_i of agent i, but also the velocities u_j of the other agents, in particular i's neighbours. Here, we posit that the velocities to take into account for these other agents are the current ones, i.e., $u_j = v_j(t)$, which comes down to assuming that agent *i* furthers the other agents' trajectories on the basis of the velocities that he or she currently observes. This assumption departs from what is typically done to determine equilibrium points in game theory, where each agent considers a situation in which the other agents' choices are also optimal for them. Nevertheless, to lowest order in $\delta u_i = u_i(t+\delta t) - u_i(t)$, the difference is transparent, insofar as a first-order expansion of $E[\mathbf{u}_i]$ only involves terms in $\boldsymbol{\delta u}_i$ and in $\boldsymbol{\delta u}_j$, $j \neq i$ (no cross terms), and the latter do not affect the minimizer's value u_i^* .

Overall, the model follows the functional diagram outlined in Fig. 4. There are only a few parameters (4 to 6, depending on how they are counted) that can be freely adjusted, including the spatial extent and the strength of the repulsion from the personal space and the penalty for abrupt velocity changes. The predictions of the model have already been validated in a very wide range of scenarios, listed in Table I, generally in a quantitative way [22].

C. Social-force model with circular specification

Finally, going all the way down the scale of complexity, we consider a reactive agent-based model. A classic paradigm of this category of models, the celebrated Social-Force-Model (SFM) in its minimal version, hypothesizes that the local rules of navigation in a crowd system can be formalized by only using a mechanical layer identical to Eq. 8, which combines three different forces $[31]$. Formally, a pedestrian i who wants to move in a particular direction \hat{e}_i at a desired speed v_d , is attracted to this destination by a driving force f_i^D which describes the adaptation of his/her current velocity \dot{r}_i to his/her desired one as:

$$
\boldsymbol{f}_i^D = \frac{\boldsymbol{v}_d - \dot{\boldsymbol{r}}_i}{\tau} \tag{12}
$$

where τ is the time needed for the velocity adjustment $(\tau = 0.4 \text{ s}$ below). Importantly, in this expression both v_d and τ are parameters that remain constant over time, regardless of the conditions in which the pedestrian is found. Herein lies the main difference with the ANDA model, where, as explained above, the decisional layer provides the optimal value for the desired velocity.

As pedestrian i moves through space, s/h e is repelled by other pedestrians j under the effect of a social force $\dot{f}_{ij}^S = -\nabla V_{ij}(r_{ij})$ that mimics the interpersonal distances desired by people when walking. Thus, the ideal path that an isolated pedestrian would follow is permanently modulated by his/her tendency to move away from other individuals. For this purpose, here we use a long-range repulsive function decaying with distance, $V_{ij}(r_{ij}) = V_0 \exp(-r_{ij}/r_c)$, following [31]. This version of the potential, known as the circular specification, is the simplest, as it depends solely on the relative distance between pedestrians. Note that a more sophisticated potential – dubbed elliptical specification – had been proposed in the paper which originally introduced the SFM [15] and accounts for some degree of anticipation of imminent collisions [51, 52]. Finally, physical contacts between agents might happen. To prevent pedestrians from overlapping either with each other or with walls, contact forces \hat{f}_{ij}^C are introduced (but of little use for what follows).

Thus, at each instant t , the acceleration of a pedestrian is given by the sum of the internal and external forces to

which they are subjected, leading to an evolution of their speed as:

$$
m_i \ddot{\boldsymbol{r}}_i = \boldsymbol{f}_i^D + \sum_{j \neq i} \boldsymbol{f}_{ij}^S(t) + \sum_{j \neq i} \boldsymbol{f}_{ij}^C(t) \tag{13}
$$

This ordinary differential equation is solved numerically with time step $dt = 0.05$ s.

IV. NUMERICAL COMPARISON OF THE OUTPUT IN SPECIFIC SETTINGS

After highlighting the conceptual discrepancies between the modeling branches, we will now make use of numerical simulations of the paradigmatic models exposed in the previous section to compare their output. While the scenarios under study could be multiplied ad infinitum, an emphasis will here be put on two simple, but ubiquitous tasks of binary collision avoidance, namely, obstacle avoidance and head-to-head collision between two pedestrians, for which the results are amenable to intuitive interpretation.

A. Local navigation around complex static obstacles

First, consider the avoidance of a static obstacle.

As mentioned above, this avoidance choice has an impact on the homotopy of the trajectory, which likens it to a tactical decision. However, in practice, the avoidance of small obstacles is often deferred to the operational module. In this case, the usual method consisting in first overlooking these small obstacles and prescribing the desired velocity towards an intermediate goal, and then taking the obstacles into account via repulsive pseudo-forces may fail drastically when these obstacles are of complex shape. This is illustrated with the simplified SFM in Fig. $5(a,c)$. Technically speaking, the obstacle was made of adjacent columns, each exerting the same repulsion as a static agent, $|V_{ij}^S| = V_0 \exp(-r/r_c)$, with $V_0 = 10$ and $r_c = 1$ m. We observe that the agent is blocked ahead of the obstacle. Lowering the repulsion to $V_0 = 2$ is not conducive to a more realistic response for concave obstacles: the agent then succeeds in entering the concave shape but gets trapped in it [Fig. $5(c)$]. (In both types of simulations, a small noise was introduced on the initial positions to break the symmetry along the y -axis.) Other agent-based models prescribing desired velocities independently of the obstacles would fail similarly [22].

On the other hand, within ANDA, the recourse to a floor field $V(r)$ (or, more generally, to a value function $u(\mathbf{r}, t)$ in game-theoretical approaches) sweeps away the distinction between local navigation and tactics. The extensive information about the geometry contained in the floor field naturally guides the agent around the obstacle, irrespective of its shape [Fig. 5(b,d)].

B. Frontal collision avoidance

We now turn to collision avoidance between two pedestrians, with a particular interest in the qualitative features obtained when the desired speed is varied from slowly walking agents to people running towards one another. To simulate this scenario, we consider a scenario similar to the experiments of Moussaïd et al. $[38]$, with two agents initially positioned at opposite ends of a corridor, about 10 meters away from one another and intent on reaching the other end of the corridor. Initially, both agents are slightly displaced in the vertical direction following a uniform random distribution centered at 0, with an amplitude of $r/2$, where r is the radius of the pedestrian. This ensures that they will always collide assuming straight trajectories. A total of 100 repetitions were simulated with varying initial conditions. Note that, in the three models under consideration, the increase in the desired speed reflects higher eagerness or hurry to reach the target, rather than a leisurely jogging session.

It has been shown that an SFM with forces spatially tailored in an ad hoc way can replicate the experimentally obtained mean trajectories for casually walking pedestrians [38]. These trajectories are also quantitatively reproduced by the ANDA model $[22]$, as shown in Fig. $6(b)$.

With the simple SFM introduced above, without specific tailoring of the potenial V , the replication of the experiments is of course much poorer [Fig. $6(c)$]. For most parameters that have been tested, collisions are observed when the desired speed is increased. The only way to prevent a collision between the agents at all desired speeds is to impose a strong repulsion, $V_0 = 10$. Then, at moderate speeds, e.g., $v_d = 1.5 \text{m/s}$, this leads to a sharp and strong detouring behavior, represented in Fig. 6(c). More interesting are however the qualitative changes that occur when v_d is further increased. As the interaction is only based on distance, the avoidance maneuver is then undertaken when collision is really imminent, i.e., much later than one would expect. Therefore, despite the repulsion strength, at $v_d = 3m/s$ the agents even fail to avoid one another, even though they started 10 meters away from each other.

The situation differs widely with ANDA: since short TTC (and not only short distances) are heavily penalized in the selection of an optimal velocity, the agents will start interacting farther and farther ahead as v_d is increased, reflecting anticipation of the upcoming colllision. As a matter of fact, the spatial profiles of the trajectories in Fig. $6(b)$ do not change much when v_d is varied: at higher v_d , at a given distance ahead of the collision point, the stronger TTC effect tends to be balanced by the higher eagerness to move forward. In any event, the agents manage to avoid collision in all these circumstances.

This also holds for the game-theoretical model, where the effect of varying v_d is however felt slightly more strongly [Fig. $6(a)$]. This is due to the proportional increase of the cost driving the agent to its goal, which

starts to dominate the repulsion with other agents. Technically speaking, here we considered a repulsive strength $V_0 = 1.1$, which provides acceptable results with respect to the empirical data. This parameter was chosen so as to minimize the distance between the experimental trajectory and the simulated one, measured in terms of the cumulative error between each simulated trajectory point the closest point of the real trajectory, and to reach an inter-agent distance when passing as close as possible to the experiments. Besides, note that we have added to the terminal cost C^T a term $K_y |y|$ (with $K_y = 1.5$), which pulls agents towards the central line, in order to limit their diffusion along the y-axis.

C. Effects of the characteristic times of the problem: distraction and mechanical friction

Let us now underscore the differences between the various timescales characterising pedestrian motion, which are best distinguished in ANDA.

The first timescale is the cognitive reaction time τ_{ψ} , depending on how often the agents refresh their perceptions of the environment (gazing activity) and how long they need to react in accordance; within ANDA, it is the time interval between updates of the desired velocity given by the decisional layer. Obviously, this time is expected to soar if the person is engaged in a discussion or playing with their smartphones (texting or web-browsing, in particular).

The consequences of this are illustrated in Fig. 7 for binary collision avoidance. While already visible at low walking speeds $v_d = 1$ m/s, these consequences get even more striking at $v_d = 2 \text{ m/s}$. It is enlightening to confront these results with the experiments conducted by Murakami and colleagues [50]. In these experiments, a series of binary collision avoidance maneuvers was performed, in which one of the two pedestrians was sometimes asked to perform some complex activity on their smartphone while passing their counterpart. Interestingly, compared to the baseline with no smartphone distraction, the avoidance maneuver by a distracted agent is undertaken later, but with a larger and more sudden reaction, which is qualitatively fully consistent with the numerical output of ANDA. Meanwhile, in the experiments, the non-distracted agent, who could not fully rely on mutual coordination for this avoidance, undertook a larger detour well in advance, so that the distance when passing the distracted agent is ultimately larger on average than with two non-distracted participants. With ANDA, it is also found that the distance when passing tends to increase with τ_{ψ} : By responding with sufficient anticipation, gradual and limited adjustments of the velocity are sufficient, whereas abrupt detours may be needed if a collision is perceived only when it is imminent. Even though the foregoing comparison was limited to a very qualitative level, it can easily be understood that the ability to model digitally distracted pedestrians is vested with special interest in an overly connected society, where accidents due to smartphone-walking are on the surge.

The second timescale is the mechanical relaxation time τ^{mech} . Large τ^{mech} denote a more inertial response, which would be typical of ice-skaters or swimmers, hence a difficulty to hold or recover one's course if the presence of inertia is not internalised enough (bottom of Fig. 7). This echoes the advice given to sailors to steer the wheel smoothly and with anticipation.

D. Priority and courtesy

Finally, one last example will showcase the relevance of establishing formal connections between the different modeling frameworks in Sec. II. It deals with the way in which tacit cultural and behavioral codes, dubbed 'intangible factors' in [10], can be accounted for. Concretely, one is concerned with the priority given to some people, e.g. out of courtesy, when walking. Such effects were rendered by means of $ad-hoc$ proxy agents in [10], that is, virtual 'outgrowths' of an agent's body that neighbours are forced to heed when moving.

We argue that these effects can be described much more naturally (and generally) by suitably modifying the game-theoretical cost functions entering Eqs. 2-4: In most cases, these behavioral rules can be rendered by internalizing a fraction α of the cost (or utility) experienced by the higher-priority agent (j) in the 'courteous' agent's cost C_i :

$$
C_i[\dots] \to (1 - \alpha) C_i[\dots] + \alpha C_j[\dots]. \tag{14}
$$

This is an example of altruistic preferences. Incidentally, as emphasized elsewhere in a more general context [53], this altruism does not result from stiff (Kantian) morality: the homo kantiensis of Alger and Weibull [53], who would strive for the best outcome in would-be encounters with their likes, would not exhibit any form of such courtesy; on the other hand, note the conceptual similarity with the methods put forward by Hoogendoorn et al. in a different context [54]. Naturally, these ideas can straightforwardly be extended to situations with several higher-priority neighbours j.

Now, our success in framing the equations of motion of anticipatory models (such as ANDA) as simplified games in Sec. II straightforwardly paves the way for translating this game-theoretical cost into new pseudo-energies \tilde{E}_i in ANDA (see Eq. 11). The decisional layer of agent i will then consist in minimizing $\tilde{E}_i[\boldsymbol{u}_i]$, where

$$
\tilde{E}_i[\boldsymbol{u}_i] = (1-\alpha) E_i[\boldsymbol{u}_i \,|\, \boldsymbol{v}_j(t)] + \alpha \min_{\boldsymbol{u}_j \in \mathbb{R}^2} E_j[\boldsymbol{u}_j \,|\, \boldsymbol{u}_i]. \tag{15}
$$

To illustrate the outcome of this element, we turn back to our example setup and simulate the head-on collision avoidance between a courteous pedestrian $(\alpha > 0)$ and an elderly person with walking issues $(\alpha = 0)$ and show

the result in Fig. 8. Clearly, with increasing courtesy (or altruism) α , the courteous agent (willingly) takes a larger and larger share of the effort required to avoid a collision. Qualitatively, this bears resemblance with the empirical results of collision avoidance between a young adult and an old one reported in [55].

Interestingly, courtesy could not have been accounted for by simply enhancing the agents' forecasting abilities in ANDA (or any similar model), e.g. by letting them prolong the others' tubes in spacetime on the basis of not only the observed velocities, but also the observed accelerations. Instead, the courteous move hinges on the anticipation of how the other agent might move in response to one's own hypothetical actions. Similarly, a purely selfish strategy, whereby one undertakes no collision avoidance whatsoever, is only viable if one anticipates that the other agent will swerve.

V. CONCLUSION

In summary, we have examined the conceptual foundations of continuous pedestrian dynamics models. Starting from a broad context, we have argued that the articulation between the tactical and operational levels of description, which tends to coincide with the articulation between global path planning and local navigation, raises practical issues for modeling. While it is generally operated by defining intermediate way-points, the storage in memory of a 'tactical' floor field covering all space presents several advantages, particularly in the presence of obstacles or uncomfortable areas on the preferred paths. Our investigation has focused on three major branches of models, here dubbed purely reactive, anticipatory, and game-like; it has shed light on the simplifying assumptions under which a branch reduces to another one: differing in their predictions of the future, reactive agents, anticipatory agents, and game players extrapolate future trajectories in spacetime in the form of time-invariant cylinders, cylinders, and flexible tubes, respectively.

For illustrative purposes, an archetypal example was chosen within each modeling branch: the circular spec9

ification of the SFM, the ANDA model, and a game in which agents interact via a distance-based repulsive potential. While the first one struggles to replicate head-on collision avoidance at various walking speeds, the latter two produce fairly similar collision-avoiding trajectories. Moreover, the distinction between cognitive processes and mechanical contacts was underscored, at odds with the frequent amalgamation of the two notions in existing models. The effect of the timescales associated with these processes on collision avoidance was studied numerically; the trends predicted by ANDA when the reaction time is increased are qualitatively similar to those reported experimentally in [50], opening the door to numerical studies of the crowd dynamics of people distracted by their smartphones, a topic of particular relevance for pedestrian safety.

Finally, the insight gained into the relation between the equation of motion of anticipatory models and generalized costs in games proved helpful to naturally account for courtesy or priority effects in the former, as illustrated numerically by a collision avoidance maneuver involving a courteous agent and a standard one and in which the detour is mostly undertaken by the former one. More generally, the development of theoretically better grounded models is strongly advisable when it comes to exploring emerging situations for which one cannot fully rely on the (still scarce) data at hand.

ACKNOWLEDGMENTS

We thank Matteo BUTANO for his particularly useful help with game theory. We acknowledge partial financial support by the Fédération d'Informatique de Lyon (CROSS project) and by the French National Research Agency (Agence Nationale de la Recherche, grant number ANR-20-CE92-0033) and the German Research Foundation (Deutsche Forschungsgemeinschaft DFG, grant number 446168800), in the frame of the French-German research project MADRAS. I. E. acknowledges Asociación de Amigos de la Universidad de Navarra for his grant.

- $[1]$ L. A. J. Quetelet, Du système social et des lois qui le $régissent$ (Guillaume, 1848).
- [2] L. A. J. Quetelet, Sur l'homme et le développement de ses facultés, ou Essai de physique sociale, Vol. 2 (Bachelier, Imprimeur-libraire, 1869).
- [3] K. Pearson, Contributions to the mathematical theory of evolution, Philosophical Transactions of the Royal Society of London. A 185, 71 (1894).
- [4] J. Von Neumann and O. Morgenstern, Theory of games and economic behavior, in Theory of games and economic behavior (Princeton university press, 1944).
- [5] M. Haghani, M. Coughlan, B. Crabb, A. Dierickx, C. Fe-

liciani, R. van Gelder, P. Geoerg, N. Hocaoglu, S. Laws, R. Lovreglio, et al., A roadmap for the future of crowd safety research and practice: Introducing the swiss cheese model of crowd safety and the imperative of a vision zero target, Safety science 168, 106292 (2023).

- [6] B. Maury and S. Faure, Crowds in Equations: An Introduction to the Microscopic Modeling of Crowds (World Scientific, 2018).
- [7] A. Corbetta and F. Toschi, Physics of human crowds, Annual Review of Condensed Matter Physics 14, 311 (2023).
- [8] J. Van Den Berg, S. Patil, J. Sewall, D. Manocha, and M. Lin, Interactive navigation of multiple agents in

crowded environments, in Proceedings of the 2008 symposium on Interactive 3D graphics and games (2008) pp. 139–147.

- [9] J. Van den Berg, S. J. Guy, M. Lin, and D. Manocha, Reciprocal n-body collision avoidance, in Robotics research (Springer, 2011) pp. 3–19.
- [10] S. Curtis, *Pedestrian velocity obstacles: Pedestrian sim*ulation through reasoning in velocity space, Ph.D. thesis, The University of North Carolina at Chapel Hill (2013).
- [11] I. Karamouzas, N. Sohre, R. Narain, and S. J. Guy, Implicit crowds: Optimization integrator for robust crowd simulation, ACM Transactions on Graphics (TOG) 36, 1 (2017).
- [12] G. Antonini, M. Bierlaire, and M. Weber, Discrete choice models of pedestrian walking behavior, Transportation Research Part B: Methodological 40, 667 (2006).
- [13] T. Robin, G. Antonini, M. Bierlaire, and J. Cruz, Specification, estimation and validation of a pedestrian walking behavior model, Transportation Research Part B: Methodological 43, 36 (2009).
- [14] M. J. Seitz and G. Köster, Natural discretization of pedestrian movement in continuous space, Physical Review E 86, 046108 (2012).
- [15] D. Helbing and P. Molnar, Social force model for pedestrian dynamics, Physical review E 51, 4282 (1995).
- [16] M. Chraibi, A. Seyfried, and A. Schadschneider, Generalized centrifugal-force model for pedestrian dynamics, Physical Review E 82, 046111 (2010).
- [17] S. Seer, C. Rudloff, T. Matyus, and N. Brändle, Validating social force based models with comprehensive real world motion data, Transportation Research Procedia 2, 724 (2014).
- [18] X. Chen, M. Treiber, V. Kanagaraj, and H. Li, Social force models for pedestrian traffic–state of the art, Transport reviews 38, 625 (2018).
- [19] I. M. Sticco, G. A. Frank, F. E. Cornes, and C. O. Dorso, A re-examination of the role of friction in the original social force model, Safety science 121, 42 (2020).
- [20] P. Romanczuk, M. Bär, W. Ebeling, B. Lindner, and L. Schimansky-Geier, Active brownian particles: From individual to collective stochastic dynamics, The European Physical Journal Special Topics 202, 1 (2012).
- [21] M. Moussaïd, D. Helbing, and G. Theraulaz, How simple rules determine pedestrian behavior and crowd disasters, Proceedings of the National Academy of Sciences 108, 6884 (2011).
- [22] I. Echeverría-Huarte and A. Nicolas, Body and mind: Decoding the dynamics of pedestrians and the effect of smartphone distraction by coupling mechanical and decisional processes, Transportation research part C: emerging technologies 157, 104365 (2023).
- [23] I. Echeverría-Huarte and A. Nicolas, Revisiting the theoretical bases of agent-based models for pedestriandynamics, in Proceedings of the 2022 Traffic and Granular Flow Conference (Springer Nature, 2023 (in press)).
- [24] S. P. Hoogendoorn and P. H. Bovy, Pedestrian routechoice and activity scheduling theory and models, Transportation Research Part B: Methodological 38, 169 (2004).
- [25] A. Lachapelle and M.-T. Wolfram, On a mean field game approach modeling congestion and aversion in pedestrian crowds, Transportation research part B: methodological 45, 1572 (2011).
- [26] F. Dietrich and G. Köster, Gradient navigation model

for pedestrian dynamics, Physical Review E 89, 062801 (2014).

- [27] B. Kleinmeier, B. Zönnchen, M. Gödel, and G. Köster, Vadere: An open-source simulation framework to promote interdisciplinary understanding, arXiv preprint arXiv:1907.09520 (2019).
- [28] S. Hoogendoorn and P. HL Bovy, Simulation of pedestrian flows by optimal control and differential games, Optimal control applications and methods 24, 153 (2003).
- [29] N. Pelechano Gómez, K. O'Brien, B. G. Silverman, and N. Badler, Crowd simulation incorporating agent psychological models, roles and communication, in First International Workshop on Crowd Simulation (2005).
- [30] T. Ikeda, Y. Chigodo, D. Rea, F. Zanlungo, M. Shiomi, and T. Kanda, Modeling and prediction of pedestrian behavior based on the sub-goal concept, Robotics 10, 137 (2013).
- [31] D. Helbing, I. Farkas, and T. Vicsek, Simulating dynamical features of escape panic, Nature 407, 487 (2000).
- [32] N. Bain, Hydrodynamics of polarized crowds: experiments and theory, Ph.D. thesis, École Normale Supérieure de Lyon (2018).
- [33] T. Bonnemain, M. Butano, T. Bonnet, I. Echeverría-Huarte, A. Seguin, A. Nicolas, C. Appert-Rolland, and D. Ullmo, Pedestrians in static crowds are not grains, but game players, Physical Review E 107, 024612 (2023).
- [34] I. Karamouzas, B. Skinner, and S. J. Guy, Universal power law governing pedestrian interactions, Physical review letters 113, 238701 (2014).
- [35] B. Maury and F. Al Reda, Game-theoretic and inhibition-based models for crowd motion, Comptes Rendus. Mathématique 359, 1071 (2021).
- [36] L. W. Ludlow and P. G. Weyand, Energy expenditure during level human walking: seeking a simple and accurate predictive solution, Journal of Applied Physiology 120, 481 (2016).
- [37] E. T. Hall, The hidden dimension, Vol. 609 (Anchor, 1969).
- [38] M. Moussaïd, D. Helbing, S. Garnier, A. Johansson, M. Combe, and G. Theraulaz, Experimental study of the behavioural mechanisms underlying self-organization in human crowds, Proceedings of the Royal Society B: Biological Sciences 276, 2755 (2009).
- [39] A. Corbetta, J. A. Meeusen, C. M. Lee, R. Benzi, and F. Toschi, Physics-based modeling and data representation of pairwise interactions among pedestrians, Physical review E 98, 062310 (2018).
- [40] A. Nicolas, M. Kuperman, S. Ibañez, S. Bouzat, and C. Appert-Rolland, Mechanical response of dense pedestrian crowds to the crossing of intruders, Scientific reports 9, 105 (2019).
- [41] S. Older, Movement of pedestrians on footways in shopping streets., Traffic engineering and control 10, 160 (1968).
- [42] M. Mōri and H. Tsukaguchi, A new method for evaluation of level of service in pedestrian facilities, Transportation Research Part A: General 21, 223 (1987).
- [43] U. Weidmann, Transporttechnik der Fussgänger. Transporttechnische Eigenschaften des Fussgängerverkehrs, Literaturauswertung, Tech. Rep. (ETH Zürich, 1992-01).
- [44] J. Zhang, W. Klingsch, A. Schadschneider, and A. Seyfried, Transitions in pedestrian fundamental diagrams of straight corridors and t-junctions, Journal of

Statistical Mechanics: Theory and Experiment 2011, P06004 (2011).

- [45] J. Zhang, W. Klingsch, A. Schadschneider, and A. Seyfried, Ordering in bidirectional pedestrian flows and its influence on the fundamental diagram, Journal of Statistical Mechanics: Theory and Experiment 2012, P02002 (2012).
- [46] C.-J. Jin, R. Jiang, S. Wong, S. Xie, D. Li, N. Guo, and W. Wang, Observational characteristics of pedestrian flows under high-density conditions based on controlled experiments, Transportation research part C: emerging technologies 109, 137 (2019).
- [47] V. Predtechenskii and A. I. Milinskii, Planning for foot traffic flow in buildings (National Bureau of Standards, US Department of Commerce, and the National Science Foundation, Washington, DC, 1978).
- [48] T. Kretz, A. Grünebohm, and M. Schreckenberg, Experimental study of pedestrian flow through a bottleneck, Journal of Statistical Mechanics: Theory and Experiment 2006, P10014 (2006).
- [49] A. Seyfried, O. Passon, B. Steffen, M. Boltes, T. Rupprecht, and W. Klingsch, New insights into pedestrian flow through bottlenecks, Transportation Science 43, 395 (2009).
- [50] H. Murakami, T. Tomaru, C. Feliciani, and Y. Nishiyama, Spontaneous behavioral coordination between avoiding pedestrians requires mutual anticipation rather than mutual gaze, Iscience 25 (2022).
- [51] A. García, D. Hernández-Delfin, D.-J. Lee, and M. Ellero, Limited visual range in the social force model: Effects on macroscopic and microscopic dynamics, Physica A: Statistical Mechanics and its Applications 612, 128461 (2023).
- [52] X. Hu, T. Chen, and Y. Song, Anticipation dynamics of pedestrians based on the elliptical social force model, Chaos: An Interdisciplinary Journal of Nonlinear Science 33 (2023).
- [53] I. Alger and J. W. Weibull, Homo moralis—preference evolution under incomplete information and assortative matching, Econometrica 81, 2269 (2013).
- [54] S. Hoogendoorn, V. Knoop, H. Mahmassani, and S. Hoogendoorn-Lanser, Game-theoretical approach to decentralized multi-drone conflict resolution and emergent traffic flow operations, arXiv preprint arXiv:2308.01069 (2023).
- [55] V. Rapos, M. E. Cinelli, R. Grunberg, S. Bourgaize, A. Cretual, and A.-H. Olivier, Collision avoidance behaviours between older adult and young adult walkers, Gait & Posture 88, 210 (2021).

FIG. 1. Route choice spans a continuum of decisions, from (a) actual routes to (b) obstacle avoidance, or even (c) pedestrian avoidance.

FIG. 2. Schematic differences between different stems of agent-based models, highlighting their distinct extrapolations of the future. In this spacetime depiction, agents' trajectories are represented as tubes.

FIG. 3. Specification of the ANDA model presented in Sec. III B. Variations of the bio-mechanical cost E_{biomech} (based on the data from $[36]$) and of the floor field E_{FF} with the test speed; by definition, the preferential speed v^{pref} minimizes the sum of these two contributions.

FIG. 4. General functional diagram of the ANDA model introduced in Sec. III B.

TABLE I. Overview of empirical and experimental data used to validate the ANDA model.

Description	Type	Reference
Avoidance maneuvers of individual pedestrians Empirical & Experimental Data $[38, 39]$		
Intruder	Experimental Data	33, 40
Speed density relation - Unidirectional Flow	Empirical & Experimental Data $[41-44]$	
Speed density relation - Bidirectional Flow	Experimental Data	$\vert 45 \vert$
Lane Formation	Experimental Data	46
Bottleneck Flow	Experimental Data	$[47 - 49]$
Smartphone Distraction	Experimental Data	50

FIG. 5. Avoidance of a static obstacle of convex square shape or non-convex shape. (a and c) SFM prediction for an agent walking at $v_d = 1.5 \,\mathrm{m/s}$; the obstacle is made of adjacent columns, each generating a potential (a) with high repulsion strength $V_0 = 10$ or (c) low strength $(V_0 = 2)$; (b and d) Predictions of ANDA, for which the floor field integrates the effect of the obstacle.

FIG. 6. Collision avoidance by two counter-walking agents in a straight corridor, as a function of the preferential speed v_d . Numerical predictions based on (a) game theory, (b) ANDA, (c) SFM. The experimental data, drawn in gray, come from [38].

FIG. 7. Effect of the cognitive reaction time τ_{ψ} and the mechanical relaxation time τ^{mech} on the collision avoidance between two agents in a straight corridor. First row (varying time-update) for $v_d = 1.0$ m/s (a) and $v_d = 2.0$ m/s (b). Second row (varying τ^{mech}) for $v_d = 1.0$ m/s (c) and $v_d = 2.0$ m/s (d).

FIG. 8. Effect of courtesy: Binary collision avoidance between a standard agent moving from left to right ($\alpha_{\rightarrow} = 0$) and a courteous agent moving from right to left with different degrees of courtesy $\alpha_{\leftarrow},$ as specified in the legend.