



HAL
open science

Multilingual Audio Captioning using machine translated data

Matéo Cousin, Etienne Labbé, Thomas Pellegrini

► **To cite this version:**

Matéo Cousin, Etienne Labbé, Thomas Pellegrini. Multilingual Audio Captioning using machine translated data. 2023. hal-04220315

HAL Id: hal-04220315

<https://hal.science/hal-04220315>

Preprint submitted on 27 Sep 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution 4.0 International License

MULTILINGUAL AUDIO CAPTIONING USING MACHINE TRANSLATED DATA

Matéo Cousin, Étienne Labbé, Thomas Pellegrini

IRIT, Université Paul Sabatier, CNRS, Toulouse, France

{etienne.labbe,thomas.pellegrini}@irit.fr

ABSTRACT

Automated Audio Captioning (AAC) systems attempt to generate a natural language sentence, a caption, that describes the content of an audio recording, in terms of sound events. Existing datasets provide audio-caption pairs, with captions written in English only. In this work, we explore multilingual AAC, using machine translated captions. We translated automatically two prominent AAC datasets, AudioCaps and Clotho, from English to French, German and Spanish. We trained and evaluated monolingual systems in the four languages, on AudioCaps and Clotho. In all cases, the models achieved similar performance, about 75% CIDEr on AudioCaps and 43% on Clotho. In French, we acquired manual captions of the AudioCaps eval subset. The French system, trained on the machine translated version of AudioCaps, achieved significantly better results on the manual eval subset, compared to the English system for which we automatically translated the outputs to French. This advocates in favor of building systems in a target language instead of simply translating to a target language the English captions from the English system. Finally, we built a multilingual model, which achieved results in each language comparable to each monolingual system, while using much less parameters than using a collection of monolingual systems.

Index Terms— automated audio captioning, multilingual audio captioning, ConvNeXt audio

1. INTRODUCTION

Automated Audio Captioning (AAC) seeks to develop systems with the capability to provide textual descriptions of audio recordings. While most available datasets exclusively offer captions in English, practical applications demand the ability to generate text in multiple languages. Our study is motivated by two fundamental questions: i) Can machine-translated captions effectively be used to build AAC systems in languages other than English? ii) Is it advantageous to construct new systems as opposed to mere translation of captions generated by an English-based system?

To try to address these questions, we investigate the use of machine translation to train and evaluate systems in

French, German and Spanish, using two prominent datasets in AAC: AudioCaps (AC) [1] and Clotho (CL) [2]. We develop monolingual models, building upon our recent ConvNeXt-Transformer architecture [3]. Furthermore, we enhance this architecture to introduce a straightforward multilingual approach, capable of generating captions in all four languages with accuracy akin to a collection of monolingual systems. Finally, we compare the quality of captions produced by a French system with those translated from an English model, employing a French version of the AC test set. This version includes captions crafted by a human annotator for the specific purpose of our evaluation.

2. MONOLINGUAL SYSTEMS

Our AAC baseline model is an encoder-decoder architecture called CNext-trans, proposed in our previous work [3, 4]. Figure 1 shows the model, comprised of an audio encoder, based on the computer vision model ConvNeXt [5], which provides sequences of audio embeddings to a transformer-based language model, responsible for the word level generation of captions.

In previous work, we adapted and pretrained the ConvNeXt encoder on AudioSet [6], for the audio tagging task [7]. It achieved a 0.471 mean average precision on the AudioSet test set, better or on par with recent transformer models, such as AST [8]) and PaSST-S [9]. It gives a list of features of shape 768×31 for a 10-seconds audio clip, which are projected by a sequence of dropout set to 0.5, dense layer, a ReLU activation and another dropout set to 0.5. The decoder is a standard transformer decoder architecture [10] with six decoder layers blocks, four attention heads per block, a feed-forward dimension of 2048, a GELU [11] activation function and a global dropout set to 0.2. Unlike many existing AAC systems, no pretrained language model was used for the decoder/word modelling part. We found that freezing the ConvNeXt encoder leads to lower variances, so we decided to precompute all its embeddings to train only the decoder part.

For each of the four target languages, we used this CNext-trans architecture. The only architectural change needed to build a system for a new language, is adapting the size of the embedding and linear classification layers to cope with




Fig. 1. Overview of our AAC monolingual system: CNext-trans. Highlighted in blue are the two layers that are replicated when building a multilingual system: the embedding and classification dense layers, which are language-specific.

different vocabulary sizes. CNext-trans contains 28M frozen parameters (the ConvNeXt encoder) and 12M trainable parameters. This last value slightly varies according to the target language. For instance, the classification layer is comprised of 1.2M, 1.5M and 2.3M of parameters, for English, French/Spanish, and German, respectively.

3. MULTILINGUAL SYSTEM

We built a multilingual system based on the monolingual one, by adding language-specific embedding and classification layers in parallel, for each target language. All the remaining of the model has been kept identical. Compared to a monolingual system, with a size of about 40M parameters (12M trainable parameters, since the audio encoder is frozen), the multilingual model contains 50.8M parameters (22.8M trainable). If we were to use a collection of four monolingual systems, the total size of such systems would be 160M parameters (48M trainable parameters). Thus, the multilingual system allows to reduce the model size by 70% relative. The main question of the present work was to compare the quality of the captions generated when using the two options.

4. AAC DATA

AudioCaps [1] (AC) contains 51308 audio files from AudioSet [6]. Since YouTube videos are sometimes removed or made unavailable, our version of the train split contains 46230 out of 49838 files, 464 out of 495 in the validation split and 912 out of 975 files in the test split.

Clotho [2] (CL) comprises 6974 audio recordings, with duration ranging from 15 to 30 seconds. The dataset is di-

vided into three splits used respectively for training, validation and testing, containing five captions per audio file. In our experiments, we resampled the audio files from 44.1 kHz to 32 kHz. During training, we randomly select one of five captions for each audio file.

Machine translated versions. AC and CL contain English-only captions. In order to translate the captions of both datasets to French, German, and Spanish, we tested two recent open-source deep learning-based tools: Opus-MT [12], No Language Left Behind (NLLB) [13]. A third option was considered: the paid service offered by the DeepL translation API¹.

We compared their translations manually on a subset of sentences from AC. A number of captions in AC contain spelling mistakes, onomatopoeia and uncommon words, and we observed that both Opus-MT and NLLB failed to deliver satisfactory results in those cases. Given our observations and also benchmarks published in the literature [14, 15], we finally opted for the DeepL translation API.

AC-fr-test-manual. We created a manual set of captions, in French, specifically for the test subset of AC. To do so, we hired a company specialized in data annotation. A single annotator carried out the task of writing the captions. We followed the same annotation methodology as in the seminal AC study [1]: the annotator had access to the audio track to write a caption, and in case he was not sure about the sound events he perceived, he could watch the corresponding video to eventually edit its caption. Due to budget constraints, we have limited the number of manual captions to one per sound file, instead of five in the original dataset.

¹<https://www.deepl.com/translator>

Table 1. Average sentence length and number of unique words in the train and test subsets of AC and CL.

		Sent. length		#Word types	
		Train / Test		Train / Test	
AC	en	8.7 / 10.3	4861 / 1623		
	fr	10.4 / 12.7	5797 / 1973		
	es	9.5 / 11.6	5889 / 1976		
	de	8.5 / 10.1	9391 / 2792		
AC-fr-test-manual	fr	- / 11.3	- / 927		
CL	en	11.3 / 11.3	4366 / 3517		
	fr	12.9 / 12.8	6384 / 3942		
	es	11.6 / 11.6	6635 / 3962		
	de	10.6 / 10.6	9537 / 5069		

In Table 1, we report the average sentence length and number of unique words in the train and test subsets in the four languages. We observe expected findings: German (de) has the smallest sentence length, whilst using much more unique words; French sentences are the longest ones; and the English vocabulary is the smallest one.

Regarding AC-fr-test-manual, the captions are shorter than the translated ones: 11.3 words on average compared to 12.7. They use 927 unique words, which seems much smaller than the translated subset (1973 word types), but this is due to having a single caption per audio file in the manual set instead of five in the translated set.

As a side-note, the total costs involved with automatically translating both AC and CL in three target languages amounted to about 300 euros, whereas the manual captions in French of the test subset of AC alone (one caption per audio) costed around 3,500 euros.

5. EXPERIMENTAL SETUP

To train our systems, we used the same hyperparameters as in our previous work [4]. The models were trained for 100 epochs on AC and 400 on CL, with the AdamW optimizer [16], a $5 \cdot 10^{-4}$ learning rate, a large weight decay value of 2 and a cosine learning rate decay. We used Mixup [17] applied to the audio and word embeddings, label smoothing [18] and SpecAugment [19]. For the multilingual systems, a training epoch consists in using each audio file four times, in order to train the models in the four languages. At inference time, we used a beam search algorithm modified to prevent the models from repeating a same word twice in a caption, except for language-specific lists of stopwords from NLTK.

To evaluate and compare the models, we report the standard metric called CIDEr-D [20]. We also report semantic similarity values between the predicted captions and the reference captions in each language, by using the multilingual model paraphrase-multilingual-mpnet-base-v2. We will refer to this metric as SBERT-sim. For both metrics, the higher, the better.

6. RESULTS USING TRANSLATED CAPTIONS

Table 2 reports the CIDEr-D (%) and SBERT-sim (%) values on AC and CL, achieved by monolingual and multilingual systems. In each configuration, five runs were carried out, with five different random seeds. The reported values were averaged over the five runs. Standard deviation values are not reported but they are below 1.5% in CIDEr and 0.2% in SBERT-sim.

On AC, our English monolingual system achieved 76.1% CIDEr-D, slightly worse than the state-of-the-art Multi-TTA system [22], which does not use external training data. Our multilingual system slightly outperformed Multi-TTA with 77.4% CIDEr-D. On CL, both our mono- and multilingual systems outperformed CNN14-trans [24].

Regarding our results in the four languages, generally speaking, similar CIDEr-D and SBERT-sim values were obtained from one language to another, except in German (de), for which the CIDEr-D values are significantly lower, for both datasets. The multilingual model was better than the monolingual one in AC, with 75.8% CIDEr-D and 73.6% SBERT-sim values averaged over the four languages. In CL, it is the contrary, the monolingual system is better, by 1.4% absolute in CIDEr-D. Table 3 illustrates outputs by our multilingual system for two AC audio files. We chose them to show an example (top four captions in the table) in which the captions in the four languages are identical, and another one (bottom four captions), in which they differ.

To investigate how similar are the output captions in the different languages, we computed SBERT-sim values between them. The paraphrase-multilingual-mpnet-base-v2 model allows to directly compare captions in two different languages. With the monolingual system, the average similarity values between the English system outputs and the French, Spanish and German ones, were 77.7% and 69.4% in AC and CL, respectively. With the multilingual system, we compare its English outputs to its French, Spanish and German ones. We obtained larger values of 78.6 % and 71.3% in AC and CL, which seems to show that the multilingual system tends to produce captions that are more similar from a language to another than in the case of the monolingual models. It may be explained by the weight sharing intrinsic to the multilingual system, but further study is required to investigate this point.

Table 2. Results in CIDEr-D (%) and SBERT-sim (%) on the test subsets of AC and CL in English (en) and French (fr), Spanish (es), German (de), using the machine translated captions for training and testing in the case of fr, es, de.

Test data	System	Language	#params (↓)	CIDEr-D (↑)		SBERT-sim (↑)		
				mono	multi	mono	multi	
AC	HTSAT-BART [21] (uses external training data)	en	171M	78.7	N/A	N/A	N/A	
	Multi-TTA [22]	en	108M	76.9	N/A	N/A	N/A	
	-----		en	40M	76.1	77.4	72.2	72.5
	CNext-trans (ours)	fr	41M	79.9	82.0	75.0	75.1	
		es	41M	75.0	74.0	73.1	73.1	
		de	42M	68.4	69.9	73.5	73.8	
		Avg.	41M	74.8	75.8	73.4	73.6	
CL	BEATs+Conformer [23] (uses external training data)	en	1.5B	50.6	N/A	N/A	N/A	
	CNN14-trans [24]	en	88M	44.1	N/A	N/A	N/A	
	-----		en	40M	46.6	45.6	58.8	58.5
	CNext-trans (ours)	fr	41M	41.8	41.3	63.1	63.1	
		es	41M	47.3	44.6	61.0	60.6	
		de	43M	39.3	38.0	64.0	64.1	
		Avg.	41M	43.8	42.4	61.7	61.6	

Table 3. Captions obtained by our multilingual model, for two AC files, “Pb6MqpdX5Jw”, and “JTHMXLC9YRS”.

Lang.	Predicted captions
en	rain falls and thunder roars in the distance
fr	la pluie tombe et le tonnerre gronde au loin
es	la lluvia cae con fuerza y los truenos retumban a lo lejos
de	regen fällt und der donner grollt
en	a duck quacking
fr	un chien halète et respire
es	los patos graznan y el viento sopla
de	ein hund hechelt und atmet schwer

7. RESULTS ON THE AC MANUAL TEST SET

Table 4 reports CIDEr-D values on AC-fr-test-manual, using the monolingual systems trained in French and in English. We translated the English system outputs to French, using DeepL. We also report the score of the multilingual system. The monolingual and even more the multilingual French systems significantly outperformed the English one.

Table 4. Results in CIDEr-D (%) on AC-fr-test-manual

Monolingual/ multilingual	Training language(s)	Candidates	CIDEr-D (↑, %)
mono	fr	fr	93.2
multi	en, fr, es, de	fr	95.8
mono	en	translated to fr	81.1

8. CONCLUSIONS

To the best of our knowledge, this work is the first one to explore multilingual audio captioning. We demonstrate the viability of automatically translating English captions into French, German, or Spanish, and using them effectively to build proficient systems in these languages. We introduced a multilingual architecture that generates captions in all four languages. A final experiment, conducted on a newly developed iteration of the AudioCaps test set containing human-authored French captions, supports the adoption of a system trained in the target language as opposed to merely translating outputs from an English-based system.

9. REFERENCES

- [1] Chris Dongjoo Kim, Byeongchang Kim, Hyunmin Lee, and Gunhee Kim, “AudioCaps: Generating captions for audios in the wild,” in *Proc. NAACL-HLT*, Minneapolis, June 2019, pp. 119–132.
- [2] Konstantinos Drossos, Samuel Lipping, and Tuomas Virtanen, “Clotho: an Audio Captioning Dataset,” in *Proc. ICASSP*, Barcelona, 2020, pp. 736–740.
- [3] Etienne Labbé, Thomas Pellegrini, and Julien Pinquier, “IRIT-UPS DCASE 2023 audio captioning and retrieval system,” Tech. Rep., DCASE2023 Challenge, May 2023.
- [4] Etienne Labbé, Thomas Pellegrini, and Julien Pinquier, “Killing two birds with a stone: can an audio captioning system also be used for audio-test retrieval?,” in *To appear in Proc. DCASE*, Tampere, 2023.
- [5] Zhuang Liu, Hanzi Mao, Chao-Yuan Wu, Christoph Feichtenhofer, Trevor Darrell, and Saining Xie, “A ConvNet for the 2020s,” in *Proc. CVPR*, 2022, pp. 11966–11976.
- [6] Jort F. Gemmeke, Daniel P. W. Ellis, Dylan Freedman, Aren Jansen, Wade Lawrence, R. Channing Moore, Manoj Plakal, and Marvin Ritter, “Audio Set: An ontology and human-labeled dataset for audio events,” in *Proc. ICASSP*, 2017, pp. 776–780.
- [7] Thomas Pellegrini, Ismail Khalfaoui-Hassani, Etienne Labbé, and Timothée Masquelier, “Adapting a ConvNeXt Model to Audio Classification on AudioSet,” in *Proc. INTERSPEECH 2023*, 2023, pp. 4169–4173.
- [8] Yuan Gong, Yu-An Chung, and James Glass, “AST: Audio Spectrogram Transformer,” in *Proc. INTERSPEECH 2021*, 2021, pp. 571–575.
- [9] Khaled Koutini, Jan Schlüter, Hamid Eghbal-zadeh, and Gerhard Widmer, “Efficient Training of Audio Transformers with Patchout,” in *Proc. INTERSPEECH 2022*, 2022, pp. 2753–2757.
- [10] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, L ukasz Kaiser, and Illia Polosukhin, “Attention is All you Need,” in *Proc. Neurips*, 2017, vol. 30.
- [11] Dan Hendrycks and Kevin Gimpel, “Gaussian Error Linear Units (GELUs),” 2016.
- [12] Jörg Tiedemann and Santhosh Thottingal, “OPUS-MT – building open translation services for the world,” in *Proceedings of the 22nd Annual Conference of the European Association for Machine Translation*, Lisboa, Portugal, Nov. 2020, pp. 479–480.
- [13] Marta R Costa-jussà, James Cross, et al., “No language left behind: Scaling human-centered machine translation,” *arXiv preprint arXiv:2207.04672*, 2022.
- [14] Pierre Isabelle and Roland Kuhn, “A Challenge Set for French → English Machine Translation,” *arXiv preprint arXiv:1806.02725*, 2018.
- [15] Ahmad Yulianto and Rina Supriatnaningsih, “Google Translate vs. DeepL: A quantitative evaluation of close-language pair translation (French to English),” *AJELP: Asian Journal of English Language and Pedagogy*, vol. 9, no. 2, pp. 109–127, Dec. 2021.
- [16] Ilya Loshchilov and Frank Hutter, “Decoupled weight decay regularization,” in *Proc. ICLR 2019*, New Orleans, 2019.
- [17] Hongyi Zhang, Moustapha Cissé, Yann N. Dauphin, and David Lopez-Paz, “mixup: Beyond Empirical Risk Minimization,” in *Proc ICLR*, Vancouver, 2018.
- [18] Christian Szegedy, Vincent Vanhoucke, Sergey Ioffe, Jon Shlens, and Zbigniew Wojna, “Rethinking the Inception Architecture for Computer Vision,” in *Proc. CVPR*, 2016, pp. 2818–2826.
- [19] Daniel S. Park, William Chan, Yu Zhang, Chung-Cheng Chiu, Barret Zoph, Ekin D. Cubuk, and Quoc V. Le, “SpecAugment: A simple data augmentation method for automatic speech recognition,” in *Proc. INTERSPEECH 2019*, sep 2019, ISCA.
- [20] Ramakrishna Vedantam, C. Lawrence Zitnick, and Devi Parikh, “CIDER: Consensus-based image description evaluation,” in *Proc. CVPR*, 2015, pp. 4566–4575.
- [21] Xinhao Mei, Chutong Meng, Haohe Liu, Qiuqiang Kong, Tom Ko, Chengqi Zhao, Mark D. Plumbley, Yuexian Zou, and Wenwu Wang, “WavCaps: A ChatGPT-assisted weakly-labelled audio captioning dataset for audio-language multimodal research,” *arXiv preprint arXiv:2303.17395*, 2023.
- [22] Eungbeom Kim, Jinhee Kim, Yoori Oh, Kyungsu Kim, Minju Park, Jaeheon Sim, Jinwoo Lee, and Kyogu Lee, “Exploring train and test-time augmentations for audio-language learning,” 2023.
- [23] Shih-Lun Wu, Xuankai Chang, Gordon Wichern, Jee-weon Jung, François Germain, Jonathan Le Roux, and Shinji Watanabe, “BEATs-based audio captioning model with INSTRUCTOR embedding supervision and ChatGPT mix-up,” Tech. Rep., DCASE, May 2023.
- [24] Hyejin Won, Baekseung Kim, Il-Youp Kwak, and Changwon Lim, “CAU submission to DCASE 2021 task6: Transformer followed by transfer learning for audio captioning,” Tech. Rep., DCASE, July 2021.