



HAL
open science

Experimental characterisation of the radio propagation channel in the millimetre frequency bands for railway communications -Preliminary results

Nicholas Attwood, Marion Berbineau, François Gallée, Patrice Pajusco

► To cite this version:

Nicholas Attwood, Marion Berbineau, François Gallée, Patrice Pajusco. Experimental characterisation of the radio propagation channel in the millimetre frequency bands for railway communications - Preliminary results. XXXVth URSI General Assembly and Scientific Symposium, URSI, Aug 2023, Sapporo, Japan. hal-04222937

HAL Id: hal-04222937

<https://hal.science/hal-04222937>

Submitted on 2 Oct 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Experimental characterisation of the radio propagation channel in the millimetre frequency bands for railway communications - Preliminary results

Nicholas Attwood⁽¹⁾, Marion Berbineau⁽²⁾, François Gallee⁽¹⁾, and Patrice Pajusco⁽¹⁾

(1) IMT-Atlantique - Lab-STICC, Brest, France,

[nicholas.attwood, francois.gallee, patrice.pajusco]@imt-atlantique.fr

(2) Université Gustave Eiffel, COSYS/LEOST, Lille, France, marion.berbineau@univ-eiffel.fr

A new 5G based system called FRMCS (Future Railway Mobile Communication Systems) is under development at European level to replace GSM-R that will be obsolete in 2030. This new system will be deployed in very narrow frequency bands allocated for railway critical applications: 4 MHz in the actual GSM-R band and 10 MHz in the 1900 MHz band. To overcome frequency scarcity, millimeter frequency bands are explored. Radio channel characterization and modelling in the millimeter frequency bands is a very active field of research for 5G and beyond system developments [1]. Only some works deal with the railway case. Static measurements at 60 GHz for in train propagation are presented in [2]. Some measurements at 60 GHz with moving trains are reported in [3] using a modified RUSK channel sounder.

The objective of our work is to develop millimeter wave radio channel models for dynamic railway scenarios (moving transmitters, receivers and scatterers) for specific use cases such as virtual coupling of trains, platooning, remote driving of trains and specific areas (train stations, shunting yards, high-speed lines, secondary lines). To this aim, the IMT Atlantique / Lab-STICC research laboratory has developed a Single Input Single Output millimetre-band chirp channel sounder based on Software Defined Radio boards (SDR). In order to perform the baseband conversion to 60 GHz, a development board from Analog Device is used. This digitally controllable board allows to obtain a millimetre band transmission and reception chain with variable gains, separated in two different modules synchronised by the GPS. A 25 dB amplifier on transmitter side is used for longer measurement distances. The excitation signal is a chirp. We measure the complex transfer function of the channel to obtain the complex impulse response. A classical "back to back" calibration stage allows to take into account the antenna gains as well as the transfer functions of the transmitting and receiving chains. The bandwidth used is 160 MHz (SDR available band).



Figure 1. Environnement of the first measurements campaign

A first measurements campaign in a railway trial site (Figure 1.) was performed in SISO mode to validate the global operating mode of the channel sounder. Dynamic measurements at low speed were done. In the final paper, we will present and comment the evolution of the Power Density Profile (PDP) along the distance, the Doppler for the main path and a statistical analysis of the results. The work is performed in the framework of the French ANR (Agence Nationale de la Recherche) project mmW4Rail (Wireless mmW communications for Railway).

References

- [1] S. Salous & Al., "Wideband MIMO Channel Sounder for Radio Measurements in the 60 GHz Band," IEEE Transactions on Wireless Communications, vol. 15, no. 4, pp. 2825–2832, Apr. 2016. doi: 10.1109/TWC.2015.2511006
- [2] K. Yang & Al., "Propagation measurements with regional train at 60 GHz for virtual coupling application", in 2017 11th EUCAP. Paris, France: IEEE, Mar. 2017, pp. 126–130. doi: 10.23919/EuCAP.2017.7928494.
- [3] M. Soliman & Al., "Design and Evaluation of a Millimeter Wave Channel Sounder for Dynamic Propagation Measurements," 2018 IEEE 88th VTC-Fall, Chicago, IL, USA, 2018, pp. 1-5, doi: 10.1109/VTC-Fall.2018.8690620.