



HAL
open science

Automatic Molecular Tour Creation: a Study

Vincent Larroque, Maxime Maria, Stéphane Mérillou, Matthieu Montes

► **To cite this version:**

Vincent Larroque, Maxime Maria, Stéphane Mérillou, Matthieu Montes. Automatic Molecular Tour Creation: a Study. 44th Annual Conference of the European Association for Computer Graphics (Eurographics 2023), May 2023, Saarbrücken, Germany. The Eurographics Association, Eurographics 2023 - Posters, pp.7-8, 2023, 10.2312/egp.20231024 . hal-04225143

HAL Id: hal-04225143

<https://hal.science/hal-04225143>

Submitted on 18 Dec 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

PROBLEM

- Computer simulations are essential for progress in drug design. For example, they allow rapid selection of potential drug candidates, according to their inhibitory effect on the target.
- Biochemists all over the world use molecular visualization software to explore molecular systems with millions of atoms in real-time.
- Molecules can be represented in various ways as described in Kozlíková *et al.* [KKF*17] overview of molecular visualization and must be considered when looking for interesting features.
- The geometric complexity of molecules makes exploration difficult, even for experts: we aim to provide a tool that will help the preliminary study of molecules by automatically creating a tour of the interesting viewpoints around it.

RELATED WORK

- Viewpoint selection for molecular visualization has been discussed in three specific papers:
 - Vázquez *et al.* [VFSLO6] proposed an information theory-based method to select viewpoints of molecules.
 - Doulamis *et al.* [DCMP10] used input from domain experts to train a non-linear classifier to search for interesting viewpoints.
 - Heinrich *et al.* [HVV*16] expended [VFSLO6] for another *molecular* representation and provided a study about viewpoint preferences.
- Vázquez and Heinrich defined two types of good viewpoints:
 - A viewpoint showing a lot of atoms and bonds, exposing most of the molecule (*figure 1, down*).
 - A viewpoint showing a geometrical configuration of the molecule (*figure 1, up*).
- Due to limited research specific to molecular visualization, our work consisted in finding and adapting general methods based on the surveys of Secord [SLF*11] and Bonaventura [BFS*18].




Figure 1: Examples of molecular configurations (up) and another view of the same molecule (down).

CONCLUSION

Our preliminary study exposes that our tool can generate molecular tours of interesting points of view around the molecule but cannot find specific geometrical configurations when requested. A larger study could provide more insight into our tool's true capabilities, but it is certain that new metrics specific to molecular visualization could provide benefits.

METHODOLOGY

The goal is to find the best viewpoints around a molecule: we must, at first, select the candidate viewpoints around it. To do so, we use the recursive discretization of an icosahedron, as shown in *figure 2.a*, to select regularly spaced points around the molecule.

The camera is placed on each of these points, looking at the molecule center, to compute an image. This image will then be analyzed by several metrics to compute a score based on its various visible properties. Finally, this score allows us to choose the best viewpoints, which have either the lowest or highest scores. Metrics are defined as $VQ(v) = F_m(v)$ where $VQ(v)$ is the quality score of a viewpoint v computed with the $F_m(v)$ metric function.




Figure 2: Pipeline of the molecular tour creation. (a) the icosahedron used to select viewpoints. (b) the corresponding viewpoint sphere. (c) the created molecular tour path.

RESULTS

We conducted a preliminary study with 10 molecules on the ability of metrics to detect a geometrical configuration: the "tunnel". Our results have shown that the molecule tour is able, for most measures, to show both a viewpoint exposing most of the molecule and a "tunnel" exposing viewpoint. *Figure 3.b* shows the resulting best viewpoint for a molecule. The metric used was the viewpoint entropy [VFSLO6] with an icosahedron of 642 vertices. *Figures 3.b-1* and *3.b-3*, of low scores, are exposing the geometrical configuration "tunnel" while the high scores in *figures 3.b-2* and *3.b-4* are viewpoints exposing most atoms of the molecule.

Our study also showed that most metrics are unreliable: *figure 4* features a plot of the precision of some measures. The precision is calculated as the ability of a measure to reliably detect the "tunnel" geometrical configuration either on its highest (red) or lowest score (blue) or not at all. Precision goes from reliable (± 1) to unreliable or unable to detect the feature at all (0).




Figure 3: Result of the molecular tour with key viewpoints (1, 2, 3 and 4) and their intermediary viewpoints.

REFERENCES

- [BFS*18] BONAVENTURA X., FEIXAS M., SBERT M., CHUANG L., ALLRAVEN C.: A Survey of Viewpoint Selection Methods for Polygonal Models. *Entropy* 20, 5 (2018), 370.
- [DCMP10] DOULAMIS N., CHRONIS E., MIAOULIS G., PLEMENOS D.: Personalized View Selection of 3D Molecular Proteins. In *Intelligent Computer Graphics 2010*. Springer Berlin Heidelberg, 2010, pp. 211–227.
- [KKF*17] KOZLÍKOVÁ B., KRONE M., FALK M., LINDOW N., BAADEN M., BAUM D., VIOLA I., PARULEK J., HEGE H.-C.: Visualization of Biomolecular Structures: State of the Art Revisited. *Computer Graphics Forum* 36, 8 (2017), 178–204.
- [SLF*11] SECORD A., LU J., FINKELSTEIN A., SINGH M., NEALEN A.: Perceptual Models of Viewpoint Preference. *ACM Trans. Graph.* 30, 5 (Oct. 2011), 1–12.
- [VFSLO6] VÁZQUEZ P.-P., FEIXAS M., SBERT M., LLOBET A.: Realtime automatic selection of good molecular views. *Computers & Graphics* 30, 1 (2006), 98–110.
- [PPB*05] POLONSKY O., PATANÉ G., BIASOTTI S., GOTSMAN C., PAGNUOLO M.: What's in an image? *The Visual Computer* 21, 8 (Sept. 2005), 840–847.
- [FSG09] FEIXAS M., SBERT M., GONZÁLEZ F.: A Unified Information-Theoretic Framework for Viewpoint Selection and Mesh Saliency. *ACM Trans. Appl. Percept.* 6, 1 (Feb. 2009).
- [HVV*16] HEINRICH J., VUONG J., HAMMANG C. J., WU A., RITTENBRUCH M., HOGAN J., BRERETON M., O'DONOGHUE S. I.: Evaluating Viewpoint Entropy for Ribbon Representation of Protein Structure. *Computer Graphics Forum* 35, 3 (June 2016), 181–190.