

# Sustainable and cost-effective MAS DNP-NMR at 30 K with cryogenic sample exchange

Subhradip Paul, Eric Bouleau, Quentin Reynard-Feytis, Jean-Pierre Arnaud, Florian Bancel, Bertrand Rollet, Pierre Dalban-Moreynas, Christian Reiter, Armin Purea, Frank Engelke, et al.

#### ▶ To cite this version:

Subhradip Paul, Eric Bouleau, Quentin Reynard-Feytis, Jean-Pierre Arnaud, Florian Bancel, et al.. Sustainable and cost-effective MAS DNP-NMR at 30 K with cryogenic sample exchange. Journal of Magnetic Resonance, 2023, pp.107561. 10.1016/j.jmr.2023.107561. hal-04234910

### HAL Id: hal-04234910 https://hal.science/hal-04234910v1

Submitted on 10 Oct 2023

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# Sustainable and cost-effective MAS DNP-NMR at 30 K with cryogenic sample exchange

3	Subhradip Paul <sup>a</sup> , Eric Bouleau <sup>b</sup> , Quentin Reynard-Feytis <sup>a</sup> , Jean-Pierre Arnaud <sup>b</sup> , Florian
4	Bancel <sup>b</sup> , Bertrand Rollet <sup>b</sup> , Pierre Dalban-Moreynas <sup>b</sup> , Christian Reiter <sup>c</sup> , Armin Purea <sup>c</sup> , Frank
5	Engelke <sup>c</sup> , Sabine Hediger <sup>a</sup> , Gaël De Paëpe <sup>a</sup> *
6	<sup>a</sup> Univ. Grenoble. Alpes, CEA, CNRS, IRIG, MEM, 38000 Grenoble, France
7	<sup>b</sup> Univ. Grenoble Alpes, CEA, IRIG, DSBT, 38000 Grenoble, France
8	° Bruker Biospin 76275 Ettlingen, Germany

9

10 Abstract We report here instrumental developments to achieve sustainable, cost-effective 11 cryogenic Helium sample spinning in order to conduct dynamic nuclear polarisation (DNP) and 12 solid-state NMR (ssNMR) at ultra-low temperatures (< 30 K). More specifically, we describe an 13 efficient closed-loop helium system composed of a powerful heat exchanger (95% efficient), a 14 single cryocooler and a single helium compressor to power the sample spinning and cooling. The 15 system is integrated with a newly designed triple-channel NMR probe that minimizes thermal 16 losses without compromising the RF performance and spinning stability (+/- 0.05%). The probe 17 is equipped with an innovative cryogenic sample exchange system that allows swapping samples

in minutes without introducing impurities in the close-loop system. We report that significant gain
in sensitivity can be obtained at 30-40 K on large micro-crystalline molecules, with unfavorable
relaxation timescales, making them difficult or impossible to polarize at 100 K. We also report
rotor-synchronized 2D experiments to demonstrate the stability of the system.

Magic angle spinning (MAS) solid-state NMR at high magnetic field has developed as a key spectroscopy to study the structure and dynamics of a wide array of systems including bio-solids, catalysts, drugs, and energy materials [1–5]. Nevertheless, there are still emerging applications, both for biomolecules (*in vitro* and *in cell* NMR), small molecules and materials (bulk and especially surfaces), where NMR still suffers from its relatively limited sensitivity[6–9].

28 Besides the access to stronger magnetic field, such limitations can be strongly attenuated by 29 cooling the electronics of the probe [10] and/or the sample to cryogenic temperatures [11,12], but 30 also by hyperpolarizing the sample by Dynamic Nuclear Polarization (DNP) through microwave 31  $(\mu w)$  irradiation. The latter involves the transfer of polarization from unpaired electrons to the 32 nuclei of interest and is driven by the application of a suitable microwave irradiation [13-15]. The 33 recent renaissance of DNP and its combination with high magnetic field and sample spinning is a 34 direct consequence of the groundbreaking research undertaken by the Griffin group at 35 Massachusetts Institute of Technology (MIT) [16–18]. Since then, a growing community of DNP 36 practitioners has reported a large range of previously infeasible applications, further increasing the 37 impact of DNP and revolutionizing the scope of solid-state NMR [19-27]. These advances are 38 supported by theoretical insights [28–37], as well as the development of innovative hardware 39 [18,38–41] and biradical polarizing agents [42–45].

The last decade has witnessed the introduction of new polarizing agents (PAs), in particular for high field and fast MAS experiments [46–55]. The last generation of PAs have improved significantly the sensitivity, with <sup>1</sup>H DNP enhancement factors (compared to Boltzmann polarization) at 100 K typically around 50 to 200 (depending on the rotor diameter) and buildup times between 1s to 10 s depending on the magnetic field and the system to polarize. To improve things further, the development of new PAs can be combined with performing DNP experiments 46 at temperatures much lower than 100 K. Several initiatives aiming at developing ultra-low
47 temperature MAS experiments have been reported and have recently been reviewed
48 [11,12,39,40,56]

Except for the system built at NIH in Tycko's group [56] that uses cold nitrogen gas (N<sub>2</sub>) to spin the sample and cold helium gas to cool the sample down to 20 K, most of the recent reports relied on the use of Helium for both spinning and cooling the sample. The approach was pioneered by Yannoni and coworkers, and more recently implemented in the Barnes group that showed the possibility to spin the sample down to 5 K [57,58] using nitrogen-cooled helium gas and liquid He blowing on the center of the rotor. In 2012 – 2013, the group of Fujiwara [59] and Levitt [12] showed results down to < 25 K using pressurized LHe dewar for spinning and cooling.

56 In 2015, a milestone was achieved by the Osaka and Grenoble groups, demonstrating the use of 57 helium closed-loop systems based on the use of gas compressors and counter-flow heat exchangers 58 to achieve stable sample rotation and cooling [60,61]. The Grenoble group could demonstrate a 59 factor of ~30-50 in time-savings on self-assembled peptide nanocrystals using TOTAPOL by 60 lowering the sample temperature from 100-110 K to the 40-50 K range under DNP condition [61]. 61 Also, using a 3.2 mm rotor, faster sample spinning was demonstrated with He (17.5 kHz at 50 K) 62 than N<sub>2</sub> (12.5 kHz at 108 K). Finally, 100 kHz <sup>1</sup>H decoupling was reported over 50 ms acquisition 63 without arcing. This first experimental setup (called NUMOC) used LHe to cool the Bearing, 64 Drive, and VT (variable temperature) gas flows, using a single compressor and powerful heat 65 exchanger for all three lines. On the other hand, the Osaka group was able to fully remove the use 66 of LHe and to reach 4 kHz MAS at 35 K and 4.7 kHz at 40 K using two GM cryo-coolers (one for the Bearing and one for the Drive) [60]. Afterwards, they were able to combine this setup with 67

DNP and access faster MAS and lower temperature (10 kHz at 22 K) by adding three additional
cryo-coolers [40].

70 In recent years, we have continued developing our system in Grenoble with the goal to make it 71 sustainable, in terms of Helium consumption, and cost-effective, in terms of hardware and cooling 72 power requirement, without compromising on the RF, µw, and MAS capabilities. To reach this 73 goal, we have designed an improved cryostat that relies on the use of a single cryocooler and a 74 single compressor for all three Bearing, Drive, and VT lines, and a new generation of triple channel 75 DNP probe that truly acts as a helium-tight cryostat providing excellent thermal insulation. The 76 latter is also equipped with a cryogenic sample exchanger that allows switching samples in minutes 77 without warming up and opening of the probe. Beyond the convenience for day-to-day usage, this 78 is also an extremely important point for setting reliably the stator at the magic angle once the probe 79 is cold (30-40 K). Indeed, the angle may need to be slightly readjusted between temperature cycles, 80 although this is not always the case with the current probe. A nutation frequency of 100 kHz on the <sup>1</sup>H channel is achieved using 76.3 W of power at 40 K, whereas 62.5 kHz <sup>13</sup>C using 50 W. 81 82 Combined with cAsymPol-POK, one of the latest generation of PA that we have recently 83 introduced, we can improve the signal-to-noise ratio for proton-dense methyl-containing organic 84 powdered sample [50,54] by a factor 5 to 23 by lowering the sample temperature from 100 K to 85 40 K. We also illustrate the reliability of the setup regarding RF performance and sample spinning stability, by showing 2D DQ-<sup>13</sup>C<sup>13</sup>C-<sup>13</sup>C SR26 and <sup>15</sup>N-<sup>13</sup>C TEDOR experiments performed on 86 diluted <sup>13</sup>C,<sup>15</sup>N-*f*-MLF. 87

88

#### **89 MATERIALS AND METHODS**

90 Sample preparation for DNP

6

The ampicillin and indomethacin samples were purchased from Sigma-Aldrich and used as is
for the preparation of DNP sample. 37 mg of each were ground to a fine powder and impregnated
with 10 µl of 20 mM cAsymPol-POK in d8-Glycerol/D<sub>2</sub>O/H<sub>2</sub>O 60:30:10 (v:v:v) (GDH matrix).
For the *f*-MLF tripeptide, one part of <sup>13</sup>C-<sup>15</sup>N isotopically labelled tripeptide (4 mg) and four
parts of unlabeled peptide (16 mg) were co-dissolved in isopropanol and recrystallized following

97 [63]. The sample was impregnated with 15  $\mu$ l of 10 mM cAsymPol-POK in GDH matrix.

the protocol in Ref [62]. KBr (10 mg) was added to the sample to be used as internal thermometer

98

96

#### 99 DNP-enhanced solid-state NMR experiments

100 Solid-state NMR experiments were recorded using a Bruker DNP-NMR AVANCE III 400 MHz 101 (9.4 T) spectrometer equipped with a gyrotron (operating at its fundamental mode) and a 102 corrugated transmission line. For all the DNP experiments, the µw power was about ~15-21 W, 103 measured at the probe base using a water load (before the taper). All the DNP-NMR measurements 104 were performed with a home-built 3.2 mm HXY triple-resonance MAS probe that can be operated 105 at cryogenic temperature and is suitable for Helium spinning. The field of the 9.4 T magnet was 106 slightly adjusted such that the microwave irradiation at 263.7 GHz was matching the maximum intensity in the AsymPol-POK's field profile, resulting in <sup>1</sup>H resonating at 400.2 MHz, <sup>13</sup>C at 100.6 107 MHz on the X-channel, and <sup>15</sup>N at 40.6 MHz on the Y channel of the probe (set in triple channel 108 109 configuration).

110

- 111 NMR parameters
- 112 Cross Polarization experiments

113 The 1D experiments at 100 K and 40 K were carried out at a spinning frequency ( $\nu_r$ ) of 8 kHz.

114 For each experiment, 15 ms of free induction decay and 128 transients were acquired. The spectra

115 were processed with Topspin without any apodisation and plotted using Nmrglue [64] and Python.

116 The referencing was done indirectly with respect to TMS using adamantane at room temperature.

117 All the experimental parameters are tabulated in Table 1 of the supplementary information.

118

119 **DARR** 

The DARR [65] experiment was carried out at 40 K with  $v_r = 7.5$  kHz. 25 ms of acquisition time was employed in the direct dimension with 2.6 s of recycle delay between the 4 transients of each indirect time increment. 256 slices (128 complex points) were collected in the indirect dimension. The slices were collected using STATES-TPPI for quadrature detection, with a spectral width of 250 ppm. For DARR, the mixing time was set to 20 ms with an RF field strength on <sup>1</sup>H matching the spinning frequency. The experimental parameters are tabulated in Table 2 of the supporting information.

127

128 *z*-filtered TEDOR

The z-filtered TEDOR experiment was carried out at 40 K with  $v_r = 7$  kHz. The REDOR mixing period was set at 1.14 ms to favour polarization transfer over distances corresponding to one-bond. A z-filter of one rotor period was used to obtain purely absorptive peaks [66]. 16 transients were collected with 2.6 s recycle delay for each increment. 96 slices (48 complex points) were collected in the indirect dimension using STATES-TPPI with a spectral width of 40 ppm. The experimental parameters are tabulated in Table 2 of the supporting information.

135

#### 136 DQ-SQ correlation

The experiment was carried out at 40 K at  $v_r = 6.7$  kHz. Modified SR26 recoupling [67] with STiC phase-shift [68] was used for 4.77 ms total mixing time (double-quantum excitation and reconversion). During the recoupling periods, 100 kHz Lee-Goldburg continuous wave decoupling was applied to remove both <sup>1</sup>H-<sup>13</sup>C and <sup>1</sup>H-<sup>1</sup>H couplings. For each increment, 16 scans were recorded with 2.6 s recycle delay. 128 slices (64 complex points) were recorded in the indirect dimension using STATES-TPPI with a spectral width 400 ppm. The experimental parameters are tabulated in Table 2 of the supporting information.

144

#### 145 **RESULTS AND DISCUSSION**

Compared to the results reported earlier [39,61], our 3.2 mm MAS-DNP probe (called PAVLOT) was completely re-designed to make it suitable for operation at ultra-low temperature in a sustainable and cost-effective fashion. With the same purpose, our closed-loop cooling system was upgraded for better performances and to fully eliminate helium consumption. The key modifications made to the different parts of the system as well as specifications and results obtained are delineated below.

152

#### 153 **Probe dewar architecture**

The probe was designed as a small cryostat and consists of two main parts, a probe base and a cylindrical part (probe tube) that goes inside the magnet (Fig. 1). The interior of the probe tube, which includes the stator, the RF capacitors and the internal waveguide, is maintained in a cold helium atmosphere. The latter space is thermally isolated from the laboratory thanks to a doublewalled tubular envelope maintained under vacuum. To minimize thermal losses, the outer tube can be clamped to the probe base housing without any contact with the inner tube, which contains the cold gas. The inner tube can withstand a pressure of 4 bar on the inside while a vacuum is applied on its outside ( $2 \times 10^{-5}$  mbar), between the two walls.

162 The base of the probe is also under vacuum, to minimize thermal loss ( $5 \times 10^{-6}$  mbar). This is 163 mandatory if one wants to minimize the number of cryocoolers needed to cool the closed-loop He 164 cycle. This is very different from a conventional 100 K DNP probe, where the probe base is 165 deliberately kept at higher temperature using flush gas to avoid freezing and condensation. This 166 latter approach is compatible with reaching 100 to 110 K at the sample using liquid nitrogen 167 cooling. This is obviously no longer suitable at helium temperatures, and for that reason we 168 designed our probe base as a small cryostat with the inner part protected from ambient temperature 169 by vacuum.

170



171

Figure 1. (a) Schematic of the closed-loop helium spinning system built at CEA Grenoble (b) Correspondingphotograph of the system, the probe being in the NMR magnet bore.

#### 174 Closed-loop He cycle for Bearing/Drive/VT gas powered with a single compressor

As described previously [39,60,61], the rotation and cooling of the sample is achieved via a closed-loop helium cycle. In our case, the system is built around a single water-cooled screw compressor (Quantum systems – L x W x H =  $0.8 \times 0.6 \times 1$  m; Power rating = 11 kW) which can deliver a gas flow rate up to 1286 l/min (mass flow rate of 3.4 g/s) and create a pressure up to 11 bar. The compressor is equipped with two 100-litre buffer gas tanks on the high- and low-pressure inlets respectively. Helium gas is compressed to a pressure of 9 bar and then fed into a cabinet that 181 controls the flow of four independent streams. The first two lines are used for sample spinning (i.e. 182 bearing and drive). The third line can be used for sample cooling (VT line) or, in the future, as a 183 Venturi line for 1.3 or 0.7 mm diameter rotor. The fourth line cools the radiation shield of the 184 cryostat, which contains the heat exchanger. We use additional 10 l buffer tanks (located before 185 the exchanger) on the bearing and drive lines to minimize fluctuations in sample spinning and to 186 act as a damper in case of compressor failure. The set up allows us to achieve a sample spinning 187 stability of 0.05 % (see Fig. 2a). The spinning detection is done using fiber optics and a home-built 188 spinning detection module. Currently the sample spinning is performed by setting manually the 189 Bearing and Drive flowmeter target values, which are regulated by feedback control. Automated 190 control of the spinning frequency using feedback loops on the drive and bearing flows will be 191 implemented soon.

The low-pressure tank on the compressor is maintained at 1.1 bar. Since we are working with a closed-loop He cycle, this pressure corresponds also to the pressure inside the probe, which is maintained above atmospheric pressure. After passing through the stator to spin the rotor, the helium gas is deflected down the probe using a Kapton wrap, generating a persistent gas flow around the capacitors. The high flow and high pressure inside the probe helps to prevent arcing [60,61].

198

#### 199 Coupling the probe to the cryostat

Cold He gas streams are delivered to the probe using a flexible cryogenic line, which is both under vacuum ( $10^{-5}$  mbar) and thermally shielded (< 110 K). The connection ports to the probe are Johnston bayonet type fittings. The five pairs of insulated tubes (bearing, drive, VT, radiation

203 shield, venturi) are equipped with a specific gasket to obtain a very good cold seal. The clamp can 204 withstand pressures up to several bars and is easily installed in less than a minute with toggle locks. 205 The initial cooling time of the entire setup, the cryostat and the probe, from RT to 30 K, measured 206 at the sample, is less than 24 h. We typically use < 500 L of He (under Normal Temperature and 207 Pressure) to flush the system before cooling. During normal system operation (i.e. under MAS), 208 there is virtually no helium consumption. The probe can be detached from the main cryostat within 209 30 minutes. While the probe is disconnected, the cryostat can be isolated and kept cold using a 210 flexible 5-line isolation loop. The probe can be reconnected and cooled down in 30 minutes due to 211 its low heat capacity and good thermal insulation. Overall, this procedure consumes < 100 L of He 212 (under Normal Temperature and Pressure). This is particularly convenient for changing the probe 213 configuration without warming up the entire system.

214

#### 215 Powerful heat exchanger equipped with a single cryocooler for cost-effective He spinning

As previously reported, we use a counter-flow heat exchanger that has been designed to achieve a perfect balance. The length of the helical coil-in-coil multi-tubes of the exchanger is calculated so that the counter-flow heat exchange process takes most of the energy out of the gas entering the exchanger, which implies that the out-going gas at the inlet point of the exchanger has temperature close to that of the incoming gas. The efficiency of the heat exchanger can be expressed as follows:

221 
$$E \approx \frac{T_{1,in} - T_{1,out}}{T_{1,in} - T_{2,in}}$$

where,  $T_{1,in}$  and  $T_{2,in}$  are the temperatures of the two incoming gas flow,  $T_{1,out}$  is the temperature of the gas flow 1 at the outlet of the tube-in-tube architecture. When the mass flow rates of the two gases are equal, the efficiency of the counter-flow heat exchange process can be conveniently related to the Number of Transferrable Units (NTU):

226 
$$NTU = \frac{E}{1 - E}$$

227 NTU is a dimensionless constant which depends on the surface area available for exchange. Three 228 configurations of heat exchanger were tested corresponding to NTU of 19, 24, and 32, which translate into 95 %, 96 %, and 97 % of transfer efficiency. The 96 % and 97 % configurations 229 230 allow reducing the sample temperature by 4 K and 7 K, respectively, with respect to the 95 % one. 231 However, they both result in a significant drop in pressure that is detrimental for fast sample 232 spinning. Therefore, we chose to work with 95 % efficiency in this study. The design of the 233 exchanger was guided by numerical calculations with three aims in mind: (a) to transfer most of 234 the enthalpy from the outgoing to the incoming gas, (b) to minimize the pressure drop through the 235 heat exchanger to favor high spinning frequencies while minimizing frictional heat inside the 236 tubes, (c) to minimize longitudinal conduction along the tubes to produce a thermal by-pass, which 237 prevents heat conduction from the warm to the cold end.

238 After passing through the heat exchanger, the He gas goes through a two-stage CRYOMECH PT 239 cooler that can reach 10 K in one hour. The first stage produces 80 W of cooling power at 55 K 240 while the second stage provides 22 W of cooling power at 18 K. The compressor of the PT requires 241 9.2 kW and can be stored easily because of the relatively small footprint (L x W x H =  $0.6 \times 0.6 \times 0$ 242 0.6 m). Each of the cryocoolers used in the OSAKA setup (i.e. 3 to 5 GM) have similar 243 performance as the unique PT cryocooler used here, highlighting both the excellent performance 244 of our heat exchanger and the minimal losses of the system (cryostat and probe). The CRYOMECH 245 cryocooler is mechanically connected to 2 regenerative heat exchangers, also known as capacitive 246 heat exchangers, which consist of a single flow path inside a copper block to temper the fluid. The 247 capacitive heat exchangers are mounted with the goal to minimize thermal resistance (0.01 K/W). 248 Three heat exchanger configurations were tested for cryogenic Helium spinning:

249	1. Drive, bearing, and VT gas lines going through the first stage of the cryocooler and only
250	the VT line further through the second stage. In this configuration, we could reach abou
251	50 K at the sample.

- Drive, bearing, and VT gas lines all going through the first stage of the cryocooler and both
   bearing and VT lines further through the second stage. With this configuration, we could
   reach 40 K at the sample.
- 255 3. Drive and bearing gas lines going through the first stage of the cryocooler and only the
  256 bearing line further through the second stage. No VT gas is used. With this configuration,
  257 we could reach 30 K on the sample.

We conclude that for 3.2 mm rotor and our current setup, there is no need to use a VT line. The sample temperature was measured using a rotor filled with KBr and spinning the sample at 8 kHz [63]. Note that 20 W  $\mu$ w irradiation (measured at the probe base) increases the sample temperature by ~5 K for a zirconia rotor filled with KBr.

262

#### 263 Probe performances: spinning stability, noise figure, and RF field strengths

The spinning stability of our system was monitored by following the position of the first sideband of a series of <sup>79</sup>Br spectra. As each spectrum can be recorded with only one scan, it provides a direct access to frequency fluctuations of our system. As shown in Fig. 2a, we monitored the position of the sideband every 2 s, over a period of about 45 min. The variation in spinning frequency is about 0.05% of the nominal value, indicating an excellent stability, which is important for conducting experiments that demand rotor synchronization and spinning stability.

The current setup allows reaching 27 K at low spinning speed (~5 kHz) and in absence of microwave irradiation. The rotors can be spun up reliably up to 10 kHz at 30-35 K in absence of microwave irradiation. The latter increases the temperature of standard samples by 5-7 K using thefull power of the gyrotron (about 22 W at the base of the probe).

274 In order to provide best sensitivity, it is mandatory to investigate the noise level of the probe. At 275 helium temperature, the probe circuit can act as a good receiver to pick up RF signals from 276 surrounding electromagnetic waves and from other electronic circuits in proximity (temperature 277 sensors, MAS detection, etc.). In Fig. 2b, the blue trace shows the initial noise spectrum obtained 278 for PAVLOT at 40 K with the X channel tuned to <sup>13</sup>C. It clearly demonstrates the undesirable RF 279 pickup of FM radio broadcasting. After shielding and grounding of the probe connectors and 280 internal components (mainly the Cernox sensor used for the detection of the sample temperature), 281 the noise spectrum was significantly improved at 40 K (orange trace). Considering the specific 282 frequency region of the carbon spectra (0 - 200 ppm), the noise is reduced by a factor of 1.5 going 283 from 298 K to 40 K (comparison between green and orange data). With an electronic circuit (probe 284 and preamplifier) entirely cooled, one would expect the thermal noise to improve by a factor of 285  $\sim 2.8$  by going from 298 to 40K. We ascribe the discrepancy to the fact that the pre-amplifier is not 286 cooled here. This strongly support the development of cold preamplifier for NMR experiments run 287 at ultra-low temperature, as recently demonstrated by Matsuki et al.[69].

As mentioned previously, we maintain high flow and pressure in the probe to avoid any arcing. This approach seems so far successful as demonstrated in Fig. 2c, which shows the free induction decay (FID) of a CP experiment acquired with 25 ms of <sup>1</sup>H decoupling at 100 kHz rf field strength. Nutation curves on both <sup>1</sup>H and <sup>13</sup>C channels are given in Fig. 2d at RF field strengths of 78.1 kHz (at 60 W) and 62.5 kHz (at 50 W), respectively. The <sup>1</sup>H nutation curve was recorded indirectly through CP by detecting <sup>13</sup>C while increasing the length of the <sup>1</sup>H excitation pulse, giving maximum signal intensity for a 90° pulse. The carbon nutation curve was recorded by increasing



295 the length of a flip-back pulse after the CP, resulting in a zero-crossing of the signal intensity for

the  $90^{\circ}$  pulse.



Figure 2 (a) Position of the 1<sup>st</sup> sideband, with respect to the centerband, in a <sup>79</sup>Br spectrum of KBr. The spectrum was recorded with 1 scan every 2 s. The nominal spinning frequency was 7589 Hz, and the maximum variation observed was 0.05% of the nominal frequency as indicated. (b) Noise spectra acquired with a large spectral window at 40 K before shielding and grounding (blue) and at 298 K (green) / 40 K (orange) after shielding of the probe components. (c) <sup>13</sup>C FID acquired for 25 ms with 100 kHz <sup>1</sup>H decoupling. (d) Nutation experiments performed indirectly via CP on <sup>1</sup>H (top panel), and <sup>13</sup>C (bottom panel). The corresponding nutation frequency are 78.1 kHz at 60 W for <sup>1</sup>H, and 62.5 kHz at 50 W for <sup>13</sup>C (3.2 and 4 µs 90° pulse for <sup>1</sup>H and <sup>13</sup>C, respectively).

305

#### 306 **RF circuit and matching/tuning capability**

The RF part of the probe is a commonly used triple resonance configuration, consisting of a transmission line in the 1H channel and lumped elements such as variable capacitors and inductances for tuning, matching and providing isolation between channels. The variable 310 capacitors consist of two coaxial sapphire cylinders with variable overlap. Using the same material 311 for the inner and outer part of the capacitor allows for tuning in a wide temperature range, 312 preventing any mechanical jamming due to different thermal expansion coefficients. Hence, the 313 coil and the RF capacitors are placed in the cold He environment consistent with our previous 314 design, which also leads to an improvement in signal-to-noise ratio due to lower thermal noise.

315 The X and Y tuning capacitors feature a capacitance range of 2 to 50 pF, giving both channels 316 broadband capabilities. By adding shunt capacitors in parallel to the tuning capacitors, the range 317 can be further extended towards lower frequencies, whereas a serial capacitor can be connected to 318 increase the X and Y frequencies, and the XY stop circuit can be changed to implement various 319 triple resonance configurations. The RF circuit is not optimized for one fixed set of nuclei but is 320 kept flexible to enable tuning to multiple nuclei. A proper isolation between the different RF 321 channels is done by LC stop circuits and grounding at the zero voltage crossing along the 322 transmission line.

It is important to stress that the probe behaves like a small helium-tight cryostat, which imposes new constraints, such as the design of helium-tight cryogenic feedthroughs that control the cold RF capacitors and the magic angle setting. The probe shown in Fig. 3 is equipped with 7 cryogenic feedthroughs corresponding to the tuning/matching capacitors for the three HXY channels and the magic angle adjustment system.

328

329



330

Figure 3. (a) Profile of our re-designed probe. (b) and (c) Photograph of the probe being inserted in a wide-bore 9.4
 T magnet. (d) Top view of the RF circuits with (e) zoom on the tuning and matching rod feedthroughs.

333

#### 334 Cryogenic sample exchange compatible with a helium closed loop cycle

335 To prevent any pollution of the closed-loop He cycle, e.g. seeping moisture, which would cause 336 spinning problems or rotor blockage in the transfer line, we conceived an antechamber fixed at the 337 sample insert/eject point of the probe. Before inserting a sample, the rotor is placed in a home-338 built sample-catcher acting as antechamber, and three cycles of helium gas flushing and 339 subsequent pumping (two minutes) are performed. To our knowledge, this is the first example of 340 an insert-eject system that is compatible with a closed-loop He-spinning system. This is an 341 important step towards routine use of such a technology. Indeed, the absence of cryogenic sample 342 exchange implies to warm up, disconnect, and open up the probe before the sample can be 343 exchanged. Then, the probe needs to be reconnected and cooled down again. The cooling of the 344 probe is then done while spinning the sample from RT to cryogenic temperature (20 to 40 K

345 typically) [60]. Overall, such a procedure is time-consuming, tedious and has a high probability of 346 introducing impurities into the probe and therefore into the recirculated closed-loop system. With 347 the cryogenic insert-eject system described here, the sample is inserted into the cold probe within 348 minutes, ready to be spun and measured. Overall, inserting/ejecting a sample requires about 1 L of 349 He gas (at Normal Temperature and pressure).

Furthermore, this insert-eject system enables refining the magic angle (if needed) at the experimental cryogenic temperature prior to start experiments. Without this system, one needs to warm up the entire probe after magic-angle setting, e.g. using KBr, to insert the sample of interest before cooling back again. Such important temperature cycles of ~250 K can sometimes slightly change the magic angle settings, making it unreliable.

355

#### 356 Sensitivity considerations at 100 K and below

357 As reported in the literature, there is a clear interest in performing MAS NMR at cryogenic 358 temperatures of 100 K and below, and combining it with DNP, when possible. In addition to 359 increasing the spin polarization, cooling the sample and probe electronics also reduces noise 360 [60,61,70], both improving the signal-to-noise ratio (SNR). Additionally, cooling the sample to 361 cryogenic temperatures also lengthens nuclear coherence dephasing times, which allows for 362 significantly increased polarization transfer. This has proven particularly useful in the case of quadrupolar nuclei and to record long-distance <sup>13</sup>C-<sup>13</sup>C and <sup>15</sup>N-<sup>13</sup>C transfer at natural isotopic 363 364 abundance [20,71–76].

Recently, several groups have combined DNP at temperature much lower than 100 K. In all cases, these reports have pointed towards a systematic gain in sensitivity, typically up to one order of magnitude, by reducing the sample temperature from 100 K to 30 K, depending on the 368 systems and PA used [39,56,61,69,77,78]. This was also tested with our new probe and is discussed
369 in the next paragraph (see also Fig. 4).

370

#### **Polarizing protonated microcrystals with DNP at << 100 K**

372 As recently reported by our group [54], it is important to report the performance in sensitivity of 373 polarizing agents on protonated systems and not simply on deuterated frozen solutions. Therefore, 374 we chose two proton-dense microcrystalline solids impregnated with cAsymPol-POK, one of the 375 latest polarizing agents reported so far [50]. Organic microcrystals are non-porous micrometer-376 size particles. Polarizing microcrystals with DNP is challenging but can be facilitated if one of the 377 crystal dimensions (or more) is smaller than a micron, or if the <sup>1</sup>H bulk longitudinal relaxation 378 time constant  $T_{1n}$  of the undoped system is much longer than the time needed to propagate the 379 hyperpolarization from the outer shell to the core of the system [79–81].

To illustrate the benefits in lowering the sample temperature down to 30-40 K, we chose to polarize two organic microcrystals, ampicillin and indomethacin, that have an inherent bulk <sup>1</sup>H  $T_{1n}$ (undoped) of > 70 s and ~ 3s, respectively, at 100 K. Since it typically takes a few seconds (or more) to polarize microcrystals with DNP at 100 K and 9.4 T, the very short bulk <sup>1</sup>H  $T_{1n}$  of indomethacin makes it extremely difficult to polarize compared to ampicillin, which has a longer bulk <sup>1</sup>H  $T_{1n}$  of > 70 s.

The results are reported in Fig. 4, which shows the <sup>13</sup>C signal-to-noise (SNR) as a function of the hyperpolarization time, at 100 K and 40 K. The <sup>13</sup>C signal is measured through <sup>1</sup>H to <sup>13</sup>C CPMAS. The obtained buildup curves can be fitted using one or two exponential functions. For the build ups requiring two components, the shorter of the two is directly related to the efficiency of the PA to polarize the outer shell of the particles (about hundreds of nm)[79], whereas the longer

component can be seen as the ability to polarize the nuclei at the core which are more distant fromthe polarizing agent [46,54,73,73,76,81].



393

394 Figure 4. (a) and (c) Signal to noise (SNR) ratio as a function of the hyperpolarization time (DNP build up experiments) 395 at 100 K (orange circles) and 40 K (blue circles) of (a) the C11 resonance of ampicillin at 172 ppm and (c) the C10' 396 of indomethacin at 155.1 ppm. SNR was measured from <sup>1</sup>H-<sup>13</sup>C CP spectra. The samples were impregnated with 20 397 mM cAsymPol-POK in GDH matrix (see Materials and Methods). The polarization buildups were fitted with a sum 398 of two exponentials as described in the text, except for the indomethacin one at 100 K, which is mono-exponential. 399 (b) and (d) Microwave on (blue) and microwave (off) (black and scaled vertically by a factor 5) CPMAS spectra at 40 400 K of (b) ampicillin with a recycle delay of 11.2 s and (d) indomethacin with a recycle delay of 5 s. The recycle delay 401 was calculated in each case to obtain the best sensitivity [54]. The apparent DNP enhancement factor  $\varepsilon_{on/off}$  is about 402 98 for ampicillin and 23 for indomethacin. For the CP experiments, 81 kHz of <sup>1</sup>H decoupling using SW<sub>t</sub>-TPPM [82,83] 403 was applied during detection. Ramped CP of 2 ms contact time was used to transfer the polarization from the <sup>1</sup>H to 404 <sup>13</sup>C [84]. Pre-saturation pulses were used on both channels and an echo of two rotor-periods in all was applied prior 405 to detection.

406

407 For the ampicillin sample, we first notice that the SNR at the plateau is increased by a factor of
408 4.8 by lowering the temperature from 100 K to 40 K. For a better understanding, it is interesting

here to rationalize this signal-to-noise improvement factor in order to disentangle the different contributions. On one hand, comparing the noise level at 40 K versus 100 K, we observe a reduction of about x1.2. On the other hand, lowering the temperature from 100 K to 40 K leads to an increase of the electron Boltzmann polarization by ~2.5. Considering these two factors, it suggests that the DNP efficiency is roughly improved by a factor of ~1.6 in this case.

414 The polarization buildup shown in Fig. 4 (a) had to be fitted with a sum of two exponential 415 functions at both temperatures. The short and the long components are 5.7 s (50 %), and 62 s (50 416 %) at 100 K, and 8.5 s (55 %) and 96 s (45 %) at 40 K. The requirement of a two-components fit 417 is consistent with the hyperpolarization of a core-shell structure. Interestingly, both the short and 418 long components of the buildup get slightly longer upon cooling from 100 to 40 K, while their 419 respective weight is roughly preserved (about 1:1). Note that the long component is limited by 420 bulk <sup>1</sup>H  $T_{1n}$  (undoped). Fig. 4 (b) shows the <sup>13</sup>C CPMAS spectrum with and without microwave 421 irradiation for a recycling time that maximizes the sensitivity with microwave. The corresponding 422 DNP enhancement factor is 98 at 40 K and 62 at 100 K, with 11.5 s and 8.2 s recycling time, 423 respectively. Comparing the sensitivity, a factor of ~2.7 of improvement is observed when 424 lowering the temperature from 100 K to 40 K. In terms of resolution, the full width at half height 425 (FWHH) of the CO resonance is roughly identical at both temperatures. This is therefore a nice 426 example where sensitivity is improved without compromising the resolution. Another striking 427 observation is the large x35 of signal enhancement of the methyl groups at 40 K compared to 100 428 K. It is well established that the methyl rotation at 100 K makes the <sup>1</sup>H hyperpolarization by DNP 429 challenging, and that it can also potentially interfere with CP and <sup>1</sup>H decoupling spin dynamics, 430 resulting usually in low intensities for CH<sub>3</sub> signals. As suggested in Ref [85], the reduced methyl 431 rotation below 75 K is likely to help recovering more favorable relaxation properties, which is

432 confirmed by our data. Lowering the sample temperature at 40 K should definitely help probing433 methyl-methyl long-range constraints as suggested in Ref [85].

434 The case of indomethacin microcrystals is very different. Indeed, the time required to 435 hyperpolarize the particles (up to 10 s or more) is typically longer than the bulk <sup>1</sup>H  $T_{1n}$  of ~3 s at 436 100 K, making them difficult to polarize at 100 K, as shown in Fig. 4 (c). Interestingly, the <sup>1</sup>H 437 polarization buildup at 100 K can be fitted using only one component of about 1.3 s. This makes 438 sense considering the bulk <sup>1</sup>H bulk  $T_{1n}$  (undoped). In this case, we only start polarizing the outer 439 shell of the microcrystals but diffusion of the hyperpolarization within the particle is limited by 440 the bulk  ${}^{1}\text{H}$   $T_{1n}$ , which brings the polarization back to Boltzmann equilibrium. Remarkably, as we 441 cool the sample down to 40 K, the <sup>1</sup>H buildup (Fig. 4 (c)) becomes bi-exponential, with a short 442 component at 3.3 s and a longer one at 47 s (weights of 41 % and 59 %, respectively). This clearly 443 highlights that hyperpolarization can now be transferred beyond the outer shell of the particles, as a direct consequence of a longer bulk  ${}^{1}\text{H}$   $T_{1n}$  of indomethacin microcrystals at 40 K. Finally, Fig. 444 4 (d) shows the <sup>13</sup>C CPMAS spectrum of indomethacin with and without microwave irradiation at 445 446 40 K for a recycling time of 5 s that maximizes the sensitivity with microwave. The corresponding 447 DNP enhancement factor is 23, to be compared to the DNP enhancement factor of 3 at 100 K with 448 1.8 s recycling. Overall, this translates into an improvement in sensitivity of x5 and or in time-449 savings of x25 when going from 100 K to 40 K, using cAsymPol-POK as polarizing agent.

450

#### 451 Multidimensional experiments at 40 K

452 After discussing the improved sensitivity that is achieved on organic microcrystals, we also show 453 that our closed-loop He cycle can be used to record multidimensional experiments that requires 454 stable spinning, double/triple channel irradiation and high power H/X/Y pulses. The experiments shown in Fig. 5 were performed on diluted tri-peptide U-<sup>13</sup>C,<sup>15</sup>N-N-Formylmethionyl-leucyl-455 phenylalanine (f-MLF). With a bulk <sup>1</sup>H  $T_{1n}$  of ~3 s at 100 K, this microcrystalline system is also 456 457 challenging to polarize. Similarly, to the indomethacin case, a drastic improvement in SNR of a 458 factor of 6 is obtained by hyperpolarizing this sample at 40 K compared to 100 K, using cAsymPol-459 POK as polarizing agents. The polarization buildup at 40 K is bi-exponential with components at 460 3.6 s (40 %) and 20 s (60 %).



Figure 5. Different 2D experiments on the *f*-MLF sample. (a) 2D <sup>13</sup>C-<sup>13</sup>C DARR spectrum obtained in 49 minutes with 20 ms of mixing time. The inset shows intra- (labelled) and inter-residue cross peaks. (b) DQ-SQ spectrum using SR26 with STiC phase shifts. It was acquired in 1 hr 42 min with 4.77 ms of total mixing time. (c) Triple-resonance z-filtered TEDOR experiment with excellent sensitivity obtained in 1 h 14 min, with a mixing time of 2.2 ms.

465

466 Fig. 5 (a) shows a 2D <sup>13</sup>C-<sup>13</sup>C DARR correlation spectrum obtained with 20 ms of mixing time. 467 As shown in the inset, the spectrum is dominated by intra-molecular cross peaks (e.g.  $C_M' - C_M^{\alpha}$  468 ,  $C_{F'} - C_{M}^{\alpha}$ , and  $C_{L'} - C_{L}^{\alpha}$  for the region considered in the inset), but inter-residue cross peaks (e.g. 469  $C_{M'} - C_{L}^{\alpha}$  and  $C_{L'} - C_{F}^{\alpha}$ ) are also visible at smaller intensity because of the isotopic dilution of the 470 sample. The well-resolved data stresses two important points: (a) the magic angle can be set very 471 accurately given the resolution of the carbonyl lines, (b) high power <sup>1</sup>H decoupling can be applied 472 during 30 ms (or more) without any sign of arcing, enabling the good resolution achieved in both 473 dimensions.

474 To further highlight the excellent spinning stability and RF performance of the probe, we report in 475 Fig. 5 (b) a 2D DQ-SQ correlation experiment required at 6.7 kHz MAS using SR26 [67] combined 476 with STiC phase shift [68]. The latter alleviates the need to rotor-synchronize evolution in the 477 indirect dimension. This yields clean 2D data, where the spectral width in the indirect dimension 478 can be chosen sufficiently large to avoid signal folding. The very good quality of the 2D spectrum 479 and the absence of artefact are the direct consequence of the excellent spinning stability and RF 480 performance of the probe. Finally, we report a triple resonance zf-TEDOR experiments in Fig. 5 (c) employing 15 ms of 75 kHz <sup>1</sup>H decoupling. The correlations seen in the 2D correspond to N-481 482 Ca and N-C' transfer over one-bond.

483

#### 484 **CONCLUSIONS**

In this work, we have described a sustainable and cost-effective approach to cryogenic Helium spinning. The system is based around a new He spinning MAS-DNP probe, a powerful counterflow heat exchanger (95 % efficient), a single cryo-cooler and a single He compressor. The current setup allows reaching 27 K at low spinning speed (~5 kHz), and about 30-35 K at 10 kHz (in absence of microwave irradiation). Faster spinning frequencies can be achieved (up to 15 kHz at 40 K) but not reliably. Indeed, at such spinning frequencies, the drive caps often come off due to the differential thermal contraction of the rotor (zirconia) and the caps (vespel), but we are 492 currently working on this problem with the design of new rotor caps for faster spinning. In addition, 493 the system is equipped with a cryogenic sample exchange capability, which allows swapping 494 samples in minutes. Tested on organic microcrystals, we report large SNR improvements by 495 decreasing the sample temperature from 100 to 40 K. The improvements are particularly 496 pronounced for systems that are difficult to polarize because of their intrinsic short <sup>1</sup>H  $T_{1n}$  at 100 497 K. The excellent MAS stability and RF performance of the probe are illustrated with double/triple 498 resonance 2D experiments.

499 Beyond the goal of performing NMR/DNP in the < 50 K regime, the Grenoble setup has been 500 developed with a clear commitment towards cost-effectiveness and sustainability, with 501 considerable attention paid to thermal isolation and heat transfer efficiency, to minimize cooling 502 power requirements, footprint, power consumption and maintenance cost. The Grenoble setup has 503 now an efficient sample insert-eject capability and will be upgraded in a next future with a second 504 cryocooler to reach < 15 K. Overall, the Grenoble setup paves the way to a cost-effective solution 505 for sustainable fast MAS He spinning. These advances will be combined with the development of 506 tailored polarizing agents and should prove particularly useful for the development of very high 507 field DNP combined for instance with cheaper solid-state sources.

508

#### 509 AUTHOR INFORMATION

- 510 **Corresponding Author**
- 511 \*E-mail: gael.depaepe@cea.fr

512

#### 513 ACKNOWLEDGEMENTS

- 514 This work was supported by the French National Research Agency through CBH-EUR-GS and
- 515 the Labex ARCANE (ANR-17-EURE-0003), the CDP Glyco@Alps (ANR15-IDEX-02), the

516 project TOGETHER (ANR 19-CE29-0021), and the European Research Council (ERC-CoG-

517 2015, No. 682895). GDP thanks Frédéric Mentink-Vigier and Daniel Lee for stimulating

- 518 discussions. GDP thanks Snorri Sigurdsson for providing the cAsymPol-POK polarizing agents
- 519 used in this work.
- 520

#### 521 **REFERENCES**

- R. Tycko, BIOMOLECULAR SOLID STATE NMR: Advances in Structural Methodology
   and Applications to Peptide and Protein Fibrils, Annu. Rev. Phys. Chem. 52 (2001) 575–606.
- J.V. Hanna, M.E. Smith, Recent technique developments and applications of solid state NMR
   in characterising inorganic materials, Solid State Nucl. Magn. Reson. 38 (2010) 1–18.
- 526 [3] O. Pecher, J. Carretero-González, K.J. Griffith, C.P. Grey, Materials' Methods: NMR in
   527 Battery Research, Chem. Mater. 29 (2017) 213–242.
- 528 [4] S.E. Ashbrook, J.M. Griffin, K.E. Johnston, Recent Advances in Solid-State Nuclear
   529 Magnetic Resonance Spectroscopy, Annu. Rev. Anal. Chem. 11 (2018) 485–508.
- 530 [5] D.D. Laws, H.-M.L. Bitter, A. Jerschow, Solid-State NMR Spectroscopic Methods in
   531 Chemistry, Angew. Chem. Int. Ed. 41 (2002) 3096–3129.
- 532 [6] B. Reif, S.E. Ashbrook, L. Emsley, M. Hong, Solid-state NMR spectroscopy, Nat. Rev.
  533 Methods Primer. 1 (2021) 1–23.
- A.A. Shcherbakov, J. Medeiros-Silva, N. Tran, M.D. Gelenter, M. Hong, From Angstroms
   to Nanometers: Measuring Interatomic Distances by Solid-State NMR, Chem. Rev. 122
   (2022) 9848–9879.
- 537 [8] F.-X. Theillet, In-Cell Structural Biology by NMR: The Benefits of the Atomic Scale, Chem.
  538 Rev. 122 (2022) 9497–9570.
- 539 [9] A.J. Pell, G. Pintacuda, C.P. Grey, Paramagnetic NMR in solution and the solid state, Prog.
  540 Nucl. Magn. Reson. Spectrosc. 111 (2019) 1–271.
- [10] A. Hassan, C.M. Quinn, J. Struppe, I.V. Sergeyev, C. Zhang, C. Guo, B. Runge, T. Theint,
  H.H. Dao, C.P. Jaroniec, M. Berbon, A. Lends, B. Habenstein, A. Loquet, R. Kuemmerle, B.
  Perrone, A.M. Gronenborn, T. Polenova, Sensitivity boosts by the CPMAS CryoProbe for
  challenging biological assemblies, J. Magn. Reson. 311 (2020) 106680.
- 545 [11] R. Tycko, NMR at Low and Ultra-Low Temperatures, Acc. Chem. Res. 46 (2013) 1923–
   546 1932.
- 547 [12] M. Concistrè, O.G. Johannessen, E. Carignani, M. Geppi, M.H. Levitt, Magic-Angle
  548 Spinning NMR of Cold Samples, Acc. Chem. Res. 46 (2013) 1914–1922.
- 549 [13] A.W. Overhauser, Polarization of Nuclei in Metals, Phys. Rev. 92 (1953) 411–415.
- [14] J.I. Kaplan, Spin Resonance in Metals as a Function of the Overhauser Effect, Phys. Rev. 99
   (1955) 1322–1323.

- 552 [15] T.R. Carver, C.P. Slichter, Experimental Verification of the Overhauser Nuclear Polarization
   553 Effect, Phys. Rev. 102 (1956) 975–980.
- [16] D.A. Hall, D.C. Maus, G.J. Gerfen, S.J. Inati, L.R. Becerra, F.W. Dahlquist, R.G. Griffin,
   Polarization-Enhanced NMR Spectroscopy of Biomolecules in Frozen Solution, Science. 276
   (1997) 930–932.
- [17] R.G. Griffin, T.F. Prisner, High field dynamic nuclear polarization—the renaissance, Phys.
   Chem. Chem. Phys. 12 (2010) 5737–5740.
- [18] A.B. Barnes, G. De Paëpe, P.C.A. van der Wel, K.-N. Hu, C.-G. Joo, V.S. Bajaj, M.L. MakJurkauskas, J.R. Sirigiri, J. Herzfeld, R.J. Temkin, R.G. Griffin, High-Field Dynamic Nuclear
  Polarization for Solid and Solution Biological NMR, Appl. Magn. Reson. 34 (2008) 237–
  263.
- 563 [19] A. Lesage, M. Lelli, D. Gajan, M.A. Caporini, V. Vitzthum, P. Miéville, J. Alauzun, A.
  564 Roussey, C. Thieuleux, A. Mehdi, G. Bodenhausen, C. Copéret, L. Emsley, Surface enhanced
  565 NMR spectroscopy by dynamic nuclear polarization, J. Am. Chem. Soc. 132 (2010) 15459–
  566 15461.
- 567 [20] D. Lee, H. Takahashi, A.S.L. Thankamony, J.-P. Dacquin, M. Bardet, O. Lafon, G.D. Paëpe,
   568 Enhanced Solid-State NMR Correlation Spectroscopy of Quadrupolar Nuclei Using
   569 Dynamic Nuclear Polarization, J. Am. Chem. Soc. 134 (2012) 18491–18494.
- [21] A.J. Rossini, A. Zagdoun, M. Lelli, A. Lesage, C. Copéret, L. Emsley, C. Coperet, L. Emsley,
   Dynamic Nuclear Polarization Surface Enhanced NMR Spectroscopy, Acc. Chem. Res. 46
   (2013) 1942–1951.
- [22] Q.Z. Ni, E. Daviso, T.V. Can, E. Markhasin, S.K. Jawla, T.M. Swager, R.J. Temkin, J.
  Herzfeld, R.G. Griffin, High Frequency Dynamic Nuclear Polarization, Acc. Chem. Res. 46
  (2013) 1933–1941.
- 576 [23] D. Lee, S. Hediger, G. De Paëpe, Is solid-state NMR enhanced by dynamic nuclear
   577 polarization?, Solid State Nucl. Magn. Reson. 66–67 (2015) 6–20.
- 578 [24] D. Gauto, O. Dakhlaoui, I. Marin-Montesinos, S. Hediger, G. De Paëpe, Targeted DNP for
   579 biomolecular solid-state NMR, Chem. Sci. 12 (2021) 6223–6237.
- [25] R.W. Hooper, B.A. Klein, V.K. Michaelis, Dynamic Nuclear Polarization (DNP) 101: A New
   Era for Materials, Chem. Mater. 32 (2020) 4425–4430.
- [26] W.Y. Chow, G. De Paëpe, S. Hediger, Biomolecular and Biological Applications of Solid State NMR with Dynamic Nuclear Polarization Enhancement, Chem. Rev. 122 (2022) 9795–
   9847.
- 585 [27] T. Biedenbänder, V. Aladin, S. Saeidpour, B. Corzilius, Dynamic Nuclear Polarization for
   586 Sensitivity Enhancement in Biomolecular Solid-State NMR, Chem. Rev. 122 (2022) 9738–
   587 9794.
- [28] K.-N. Hu, G.T. Debelouchina, A.A. Smith, R.G. Griffin, Quantum mechanical theory of
   dynamic nuclear polarization in solid dielectrics., J. Chem. Phys. 134 (2011) 125105.
- [29] K.R. Thurber, R. Tycko, Theory for cross effect dynamic nuclear polarization under magic angle spinning in solid state nuclear magnetic resonance: The importance of level crossings,
   J. Chem. Phys. 137 (2012) 084508.
- 593 [30] Y. Hovav, A. Feintuch, S. Vega, Theoretical aspects of Dynamic Nuclear Polarization in the
   594 solid state the cross effect., J Magn Reson. 214 (2012) 29–41.
- [31] A. Karabanov, G. Kwiatkowski, W. Köckenberger, Spin dynamic simulations of solid effect
   DNP: the role of the relaxation superoperator, Mol. Phys. 112 (2014) 1838–1854.

- [32] K.R. Thurber, R. Tycko, Perturbation of nuclear spin polarizations in solid state NMR of
   nitroxide-doped samples by magic-angle spinning without microwaves., J. Chem. Phys. 140
   (2014) 184201.
- [33] F. Mentink-Vigier, Ü. Akbey, H. Oschkinat, S. Vega, A. Feintuch, Theoretical aspects of
   Magic Angle Spinning Dynamic Nuclear Polarization, J. Magn. Reson. 258 (2015) 102–
   120.
- [34] F. Mentink-Vigier, S. Paul, D. Lee, A. Feintuch, S. Hediger, S. Vega, G. De Paëpe, Nuclear
   depolarization and absolute sensitivity in magic-angle spinning cross effect dynamic nuclear
   polarization, Phys. Chem. Chem. Phys. 17 (2015) 21824–21836.
- [35] F. Mentink-Vigier, S. Vega, G. De Paëpe, Fast and accurate MAS–DNP simulations of large
   spin ensembles, Phys. Chem. Chem. Phys. 19 (2017) 3506–3522.
- [36] F. Mentink Vigier, A.-L. Barra, J. van Tol, S. Hediger, D. Lee, G. De Paëpe, De novo
   prediction of cross-effect efficiency for magic angle spinning dynamic nuclear polarization,
   Phys. Chem. Chem. Phys. 18 (2019) 1–636.
- [37] F.A. Perras, M. Pruski, Large-scale ab initio simulations of MAS DNP enhancements using
  a Monte Carlo optimization strategy, J. Chem. Phys. 149 (2018) 154202.
- [38] M. Rosay, M. Blank, F. Engelke, Instrumentation for solid-state dynamic nuclear polarization
  with magic angle spinning NMR, J. Magn. Reson. 264 (2016) 88–98.
- [39] D. Lee, E. Bouleau, P. Saint-Bonnet, S. Hediger, G. De Paëpe, Ultra-low temperature MASDNP, J. Magn. Reson. 264 (2016) 116–124.
- [40] Y. Matsuki, T. Fujiwara, Cryogenic Platforms and Optimized DNP Sensitivity, in: eMagRes,
  John Wiley & Sons, Ltd, 2018: pp. 9–24.
- [41] F.J. Scott, E.P. Saliba, B.J. Albert, N. Alaniva, E.L. Sesti, C. Gao, N.C. Golota, E.J. Choi,
  A.P. Jagtap, J.J. Wittmann, M. Eckardt, W. Harneit, B. Corzilius, S. Th. Sigurdsson, A.B.
  Barnes, Frequency-agile gyrotron for electron decoupling and pulsed dynamic nuclear
  polarization, J. Magn. Reson. 289 (2018) 45–54.
- [42] K.-N. Hu, Polarizing agents and mechanisms for high-field dynamic nuclear polarization of
   frozen dielectric solids, Solid State Nucl. Magn. Reson. 40 (2011) 31–41.
- [43] K.-N. Hu, H. Yu, T.M. Swager, R.G. Griffin, Dynamic Nuclear Polarization with Biradicals,
  J. Am. Chem. Soc. 126 (2004) 10844–10845.
- [44] S. Hediger, D. Lee, F. Mentink-Vigier, G. De Paëpe, MAS-DNP Enhancements:
   Hyperpolarization, Depolarization, and Absolute Sensitivity, eMagRes. 7 (2018) 105–116.
- [45] G. Menzildjian, J. Schlagnitweit, G. Casano, O. Ouari, D. Gajan, A. Lesage, Polarizing agents
   for efficient high field DNP solid-state NMR spectroscopy under magic-angle spinning: from
   design principles to formulation strategies, Chem. Sci. 14 (2023) 6120–6148.
- [46] A. Zagdoun, G. Casano, O. Ouari, G. Lapadula, A.J. Rossini, M. Lelli, M. Baffert, D. Gajan,
  L. Veyre, W.E. Maas, M. Rosay, R.T. Weber, C. Thieuleux, C. Coperet, A. Lesage, P. Tordo,
  L. Emsley, A Slowly Relaxing Rigid Biradical for Efficient Dynamic Nuclear Polarization
  Surface-Enhanced NMR Spectroscopy: Expeditious Characterization of Functional Group
  Manipulation in Hybrid Materials, J. Am. Chem. Soc. 134 (2012) 2284–2291.
- [47] C. Sauvée, M. Rosay, G. Casano, F. Aussenac, R.T. Weber, O. Ouari, P. Tordo, Highly
  Efficient, Water-Soluble Polarizing Agents for Dynamic Nuclear Polarization at High
  Frequency, Angew. Chem. Int. Ed. 52 (2013) 10858–10861.
- [48] G. Mathies, M.A. Caporini, V.K. Michaelis, Y. Liu, K.-N. Hu, D. Mance, J.L. Zweier, M.
  Rosay, M. Baldus, R.G. Griffin, Efficient Dynamic Nuclear Polarization at 800 MHz / 527
  GHz with Trityl-nitroxide Biradicals, Angew. Chem. Int. Ed Engl. 54 (2015) 11770–11774.

- [49] D. Wisser, G. Karthikeyan, A. Lund, Alicia Lund, G. Casano, Hakim Karoui, H. Karoui, M.
  Yulikov, G. Menzildjian, A.C. Pinon, A. Purea, F. Engelke, S.R. Chaudhari, D.J. Kubicki,
  A.J. Rossini, I.B. Moroz, D. Gajan, C. Copéret, G. Jeschke, M. Lelli, L. Emsley, A. Lesage,
  O. Ouari, O. Ouari, BDPA-Nitroxide Biradicals Tailored for Efficient Dynamic Nuclear
  Polarization Enhanced Solid-State NMR at Magnetic Fields up to 21.1 T., J. Am. Chem. Soc.
  140 (2018) 13340–13349.
- [50] F. Mentink-Vigier, I. Marin-Montesinos, A.P. Jagtap, T. Halbritter, J. Van Tol, S. Hediger,
  D. Lee, S.T. Sigurdsson, G. De Paëpe, Computationally Assisted Design of Polarizing Agents
  for Dynamic Nuclear Polarization Enhanced NMR: The AsymPol Family, J. Am. Chem. Soc.
  140 (2018) 11013–11019.
- [51] A. Lund, G. Casano, G. Menzildjian, M. Kaushik, G. Stevanato, M. Yulikov, R. Jabbour, D.
  Wisser, M. Renom-Carrasco, C. Thieuleux, F. Bernada, H. Karoui, D. Siri, M. Rosay, I.V.
  Sergeyev, D. Gajan, M. Lelli, L. Emsley, O. Ouari, A. Lesage, TinyPols: a family of watersoluble binitroxides tailored for dynamic nuclear polarization enhanced NMR spectroscopy
  at 18.8 and 21.1 T, Chem. Sci. 68 (2020) 42–61.
- [52] X. Cai, A. Lucini Paioni, A. Adler, R. Yao, W. Zhang, D. Beriashvili, A. Safeer, A. Gurinov,
  A. Rockenbauer, Y. Song, M. Baldus, Y. Liu, Highly Efficient Trityl-Nitroxide Biradicals
  for Biomolecular High-Field Dynamic Nuclear Polarization, Chem. Weinh. Bergstr. Ger. 27
  (2021) 12758–12762.
- [53] R. Yao, D. Beriashvili, W. Zhang, S. Li, A. Safeer, A. Gurinov, A. Rockenbauer, Y. Yang,
  Y. Song, M. Baldus, Y. Liu, Highly bioresistant, hydrophilic and rigidly linked tritylnitroxide biradicals for cellular high-field dynamic nuclear polarization, Chem. Sci. 13
  (2022) 14157–14164.
- [54] R. Harrabi, T. Halbritter, F. Aussenac, O. Dakhlaoui, J. Van Tol, K.K. Damodaran, D. Lee,
  S. Paul, S. Hediger, F. Mentink-Vigier, S.Th. Sigurdsson, G. De Paëpe, Highly Efficient
  Polarizing Agents for MAS-DNP of Proton-Dense Molecular Solids, Angew. Chem. Int. Ed.
  669 61 (2022) e202114103.
- [55] T. Halbritter, R. Harrabi, S. Paul, J. Van Tol, D. Lee, S. Hediger, S.Th. Sigurdsson, F.
  Mentink-Vigier, G. De Paëpe, PyrroTriPol: a semi-rigid trityl-nitroxide for high field dynamic nuclear polarization, Chem. Sci. 14 (2023) 3852–3864.
- [56] K. Thurber, R. Tycko, Low-temperature dynamic nuclear polarization with helium-cooled
   samples and nitrogen-driven magic-angle spinning, J. Magn. Reson. 264 (2016) 99–106.
- [57] A. Hackmann, H. Seidel, R.D. Kendrick, P.C. Myhre, C.S. Yannoni, Magic-angle spinning
   NMR at near-liquid-helium temperatures, J. Magn. Reson. 1969. 79 (1988) 148–153.
- [58] E.L. Sesti, N. Alaniva, P.W. Rand, E.J. Choi, B.J. Albert, E.P. Saliba, F.J. Scott, A.B. Barnes,
  Magic angle spinning NMR below 6 K with a computational fluid dynamics analysis of fluid
  flow and temperature gradients, J. Magn. Reson. 286 (2018) 1–9.
- [59] Y. Matsuki, K. Ueda, T. Idehara, R. Ikeda, I. Ogawa, S. Nakamura, M. Toda, T. Anai, T.
  Fujiwara, Helium-cooling and -spinning dynamic nuclear polarization for sensitivityenhanced solid-state NMR at 14T and 30K, J. Magn. Reson. 225 (2012) 1–9.
- [60] Y. Matsuki, S. Nakamura, S. Fukui, H. Suematsu, T. Fujiwara, Closed-cycle cold helium
   magic-angle spinning for sensitivity-enhanced multi-dimensional solid-state NMR, J. Magn.
   Reson. 259 (2015) 76–81.
- [61] E. Bouleau, P. Saint-Bonnet, F. Mentink-Vigier, H. Takahashi, J.-F. Jacquot, M. Bardet, F.
   Aussenac, A. Purea, F. Engelke, S. Hediger, D. Lee, G. De Paëpe, Pushing NMR sensitivity

- limits using dynamic nuclear polarization with closed-loop cryogenic helium sample
  spinning, Chem. Sci. 6 (2015) 6806–6812.
- 690 [62] C.M. Rienstra, M. Hohwy, M. Hong, R.G. Griffin, 2D and 3D 15N-13C-13C NMR
  691 Chemical Shift Correlation Spectroscopy of Solids: Assignment of MAS Spectra of Peptides,
  692 J. Am. Chem. Soc. 122 (2000) 10979-10990.
- [63] K.R. Thurber, R. Tycko, Measurement of sample temperatures under magic-angle spinning
  from the chemical shift and spin-lattice relaxation rate of 79Br in KBr powder, J. Magn.
  Reson. 196 (2009) 84–87.
- [64] J.J. Helmus, C.P. Jaroniec, Nmrglue: an open source Python package for the analysis of
   multidimensional NMR data, J. Biomol. NMR. 55 (2013) 355–367.
- [65] K. Takegoshi, S. Nakamura, T. Terao, 13C–1H dipolar-assisted rotational resonance in magic-angle spinning NMR, Chem. Phys. Lett. 344 (2001) 631–637.
- [66] C.P. Jaroniec, C. Filip, R.G. Griffin, 3D TEDOR NMR Experiments for the Simultaneous
   Measurement of Multiple Carbon-Nitrogen Distances in Uniformly 13 C, 15 N-Labeled
   Solids, J. Am. Chem. Soc. 124 (2002) 10728-10742.
- [67] D.H. Brouwer, P.E. Kristiansen, C.A. Fyfe, M.H. Levitt, Symmetry-Based 29 Si Dipolar
   Recoupling Magic Angle Spinning NMR Spectroscopy: A New Method for Investigating
   Three-Dimensional Structures of Zeolite Frameworks, J. Am. Chem. Soc. 127 (2005) 542–
   543.
- [68] K. Märker, S. Hediger, G. De Paëpe, Efficient 2D double-quantum solid-state NMR
   spectroscopy with large spectral widths, Chem. Commun. 53 (2017) 9155–9158.
- [69] Y. Matsuki, S. Nakamura, F. Hobo, Y. Endo, H. Takahashi, H. Suematsu, T. Fujiwara,
  Cryogenic signal amplification combined with helium-temperature MAS DNP toward
  ultimate NMR sensitivity at high field conditions, J. Magn. Reson. 335 (2022) 107139.
- [70] M. Rosay, L. Tometich, S. Pawsey, R. Bader, R. Schauwecker, M. Blank, P.M. Borchard,
  S.R. Cauffman, K.L. Felch, R.T. Weber, R.J. Temkin, R.G. Griffin, W.E. Maas, Solid-state
  dynamic nuclear polarization at 263 GHz: spectrometer design and experimental results,
  Phys. Chem. Chem. Phys. 12 (2010) 5850.
- [71] H. Takahashi, S. Hediger, G. De Paëpe, Matrix-free dynamic nuclear polarization enables
   solid-state NMR 13C–13C correlation spectroscopy of proteins at natural isotopic abundance,
   Chem. Commun. 49 (2013) 9479.
- [72] K. Märker, S. Paul, C. Fernández-De-Alba, D. Lee, J.-M. Mouesca, S. Hediger, G. De Paëpe,
  Welcoming natural isotopic abundance in solid-state NMR: probing π-stacking and
  supramolecular structure of organic nanoassemblies using DNP, Chem. Sci. 8 (2017) 974–
  987.
- [73] K. Märker, M. Pingret, J.-M. Mouesca, D. Gasparutto, S. Hediger, G. De Paëpe, A New Tool for NMR Crystallography: Complete <sup>13</sup> C/ <sup>15</sup> N Assignment of Organic Molecules at Natural Isotopic Abundance Using DNP-Enhanced Solid-State NMR, J. Am. Chem. Soc. 137 (2015) 13796–13799.
- [74] D. Lee, N.T. Duong, O. Lafon, G. De Paëpe, Primostrato solid-state NMR enhanced by
   dynamic nuclear polarization: Pentacoordinated Al3+ ions are only located at the surface of
   hydrated γ-alumina, J. Phys. Chem. C. 118 (2014) 25065–25076.
- 730 [75] M. Dekhil, G. Mollica, T.T. Bonniot, F. Ziarelli, P. Thureau, S. Viel, Determining carbon-
- carbon connectivities in natural abundance organic powders using dipolar couplings, Chem.
  Commun. 52 (2016) 8565–8568.

- [76] G. Mollica, M. Dekhil, F. Ziarelli, P. Thureau, S. Viel, Quantitative Structural Constraints
  for Organic Powders at Natural Isotopic Abundance Using Dynamic Nuclear Polarization
  Solid-State NMR Spectroscopy, Angew. Chem. Int. Ed. 54 (2015) 6028–6031.
- [77] Y. Matsuki, T. Sugishita, T. Fujiwara, Surface-Only Spectroscopy for Diffusion-Limited
   Systems Using Ultra-Low-Temperature DNP MAS NMR at 16.4 T, J. Phys. Chem. C. 124
   (2020) 18609–18614.
- [78] K.R. Thurber, A. Potapov, W.-M. Yau, R. Tycko, Solid state nuclear magnetic resonance
  with magic-angle spinning and dynamic nuclear polarization below 25K, J. Magn. Reson.
  226 (2013) 100–106.
- [79] P.C.A. van der Wel, K.-N. Hu, J. Lewandowski, R.G. Griffin, Dynamic Nuclear Polarization
  of Amyloidogenic Peptide Nanocrystals: GNNQQNY, a Core Segment of the Yeast Prion
  Protein Sup35p, J. Am. Chem. Soc. 128 (2006) 10840–10846.
- [80] A.J. Rossini, A. Zagdoun, F. Hegner, M. Schwarzwälder, D. Gajan, C. Copéret, A. Lesage,
  L. Emsley, Dynamic Nuclear Polarization NMR Spectroscopy of Microcrystalline Solids, J.
  Am. Chem. Soc. 134 (2012) 16899–16908.
- [81] H. Takahashi, B. Viverge, D. Lee, P. Rannou, G. De Paëpe, Towards Structure Determination
  of Self-Assembled Peptides Using Dynamic Nuclear Polarization Enhanced Solid-State
  NMR Spectroscopy, Angew. Chem. Int. Ed. 52 (2013) 6979–6982.
- [82] R. Thakur, N. Kurur, P. Madhu, Swept-frequency two-pulse phase modulation for
  heteronuclear dipolar decoupling in solid-state NMR, Chem. Phys. Lett. 426 (2006) 459–
  463.
- [83] S. Paul, N.D. Kurur, P.K. Madhu, On the choice of heteronuclear dipolar decoupling scheme
   in solid-state NMR, J. Magn. Reson. 207 (2010) 140–148.
- [84] G. Metz, X.L. Wu, S.O. Smith, Ramped-Amplitude Cross Polarization in Magic-Angle Spinning NMR, J. Magn. Reson. A. 110 (1994) 219–227.
- [85] Q.Z. Ni, E. Markhasin, T.V. Can, B. Corzilius, K.O. Tan, A.B. Barnes, E. Daviso, Y. Su, J.
  Herzfeld, R.G. Griffin, Peptide and Protein Dynamics and Low-Temperature/DNP Magic
  Angle Spinning NMR, J. Phys. Chem. B. 121 (2017) 4997–5006.
- 761

762		
763		
764		
765		
766		
767		

## 770 For Table of Contents Only



- //0