



Approaching second-strain gradient elasticity with soft X-rays diffraction

Amar Chaalane, Frédéric Cherioux, Vincent Luzet, Eric Joseph, Nicolas Jaouen, Horia Popescu, Bruno Fabre, Fabien Amiot

► To cite this version:

Amar Chaalane, Frédéric Cherioux, Vincent Luzet, Eric Joseph, Nicolas Jaouen, et al.. Approaching second-strain gradient elasticity with soft X-rays diffraction. MecaNano General Meeting 2023, Apr 2023, Madrid, Spain. hal-04238208

HAL Id: hal-04238208
<https://hal.science/hal-04238208v1>

Submitted on 21 Nov 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Approaching second-strain gradient elasticity with soft X-rays diffraction

Amar Chaalane¹, Frédéric Cherioux², Vincent Luzet², Eric Joseph¹, Nicolas Jaouen³, Horia Popescu³, Bruno Fabre⁴, and Fabien Amiot^{*1}

¹femto-st – Institute Femto-st – 24 rue de l'épitaphe 25000 Besançon, France

²Franche-Comté Électronique Mécanique, Thermique et Optique - Sciences et Technologies (UMR 6174) (FEMTO-ST) – Université de Technologie de Belfort-Montbeliard, Ecole Nationale Supérieure de Mécanique et des Microtechniques, Centre National de la Recherche Scientifique, Université de Franche-Comté – 32 avenue de l'Observatoire 25044 BESANCON CEDEX, France

³Synchrotron SOLEIL (SSOLEIL) – Centre National de la Recherche Scientifique – L'Orme des Merisiers Saint-Aubin - BP 48 91192 GIF-sur-YVETTE CEDEX, France

⁴Institut des Sciences Chimiques de Rennes (ISCR) – Université de Rennes 1, Institut National des Sciences Appliquées - Rennes, Ecole Nationale Supérieure de Chimie de Rennes, Institut de Chimie du CNRS, Centre National de la Recherche Scientifique – Campus de Beaulieu - Bât. 10 Avenue du Général Leclerc 35042 Rennes Cedex, France

Abstract

It is well established that downsizing mechanical structures make their surface-over-volume ratio much larger than for usual objects, so that their ability to interact with their environment is significantly augmented. This has been particularly used in the development of cantilever sensors, where a surface energy change on one side induces the cantilever's bending. Even though this phenomenon has been implemented for a wide range of molecules, the modeling the mechanical response of a micromechanical structure to a surface energy change has been scarcely investigated. Second-strain gradient elasticity has been shown to naturally involve the equivalent of surface tension for solids, and thus seems particularly suited to model the deformation of solids subjected to a surface energy change.

A toy model is first used to demonstrate the key role of the material in the chemo-mechanical transduction, thereby stressing the need for an adequate experimental identification procedure.

First results from an original approach are reported herein. Beams made of a material driven by second-strain gradient elasticity are expected to display short-wavelength sinusoidal components in their displacement field. In order to experimentally validate this prediction, silicon nitride cantilevers of different thicknesses have been functionalized so that the surface energy is controlled by UV illumination. The resulting deformation has been probed using a simultaneous illumination in the soft X-rays range in transmission. The sinusoidal components of the displacement are shown to act as a diffraction grating and the observed diffraction peaks yield key information on the higher-grade elastic parameters, in line with theoretical predictions.

^{*}Speaker