



HAL
open science

Dielectric response of confined water films from a classical density functional theory perspective

D. Borgis, Damien Laage, Luc Belloni, Guillaume Jeanmairet

► **To cite this version:**

D. Borgis, Damien Laage, Luc Belloni, Guillaume Jeanmairet. Dielectric response of confined water films from a classical density functional theory perspective. *Chemical Science*, 2023, 2023 (14), pp.11141-11150. 10.1039/D3SC01267K . hal-04241385v2

HAL Id: hal-04241385

<https://hal.science/hal-04241385v2>

Submitted on 16 Oct 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Dielectric response of confined water films from a classical density functional theory perspective

Daniel Borgis,^{1,2, a)} Damien Laage,² Luc Belloni,³ and Guillaume Jeanmairet⁴

¹⁾ *Maison de la Simulation, USR 3441 CNRS-CEA-Université Paris-Saclay, 91191 Gif-sur-Yvette, France*

²⁾ *PASTEUR, Département de chimie, École normale supérieure, PSL University, Sorbonne Université, CNRS, 75005 Paris, France*

³⁾ *LIONS, NIMBE, CEA, CNRS, Université Paris-Saclay, 91191 Gif-sur-Yvette, France*

⁴⁾ *Sorbonne Université, CNRS, Physico-Chimie des Électrolytes et Nanosystèmes Interfaciaux, PHENIX, F-75005 Paris, France*

We re-examine the problem of the dielectric response of highly polar liquids such as water in confinement between two walls using a simple two-variable density functional theory involving number and polarisation densities. In the longitudinal polarisation case where a perturbing field is applied perpendicularly to the walls, we show that the notion of local dielectric constant, although ill-defined at a microscopic level, makes sense when a coarse-graining over the typical size of a particle is introduced. The approach makes it possible to study the effective dielectric response of thin liquid films of various thicknesses in connection to the recent experiments of [Fumagalli *et al.*, *Science*, 2018, 360, 1339-1342], and to discuss the notion interfacial dielectric constant. We argue that the observed properties as function of slab dimension, in particular the very low dielectric constants of the order of 2-3 measured for thin slabs of ~ 1 nm thickness do not highlight any special property of water but can be recovered for a generic polar solvent having similar particle size and the same high dielectric constant. Regarding the transverse polarisation case where the perturbing field is parallel to the walls, the associated effective dielectric constant as a function of the slab dimension reaches bulk-like values at much shorter widths than in the longitudinal case. In both cases, we find an oscillatory behaviour for slab thicknesses in the one nanometer range due to packing effects.

I. INTRODUCTION

The dielectric constant is a macroscopic concept that relates the linear response of the polarisation vector to the Maxwell electric field¹. The derivation of the dielectric constant of bulk fluids from statistical mechanics principles has a long history starting from the early works of Debye, Onsager and Kirkwood²⁻⁴, with major advances leading to its modern formulation in the 1970s⁵⁻⁸. The extension to inhomogeneous liquids and the necessary conditions to define a local, space-dependent dielectric constant $\epsilon(\mathbf{r})$ were given by Nienhuis and Deutch⁵ and re-examined thirty years later by Ballenegger and Hansen⁹. Such clear definition is crucial for the implicit solvent models used, *e.g.*, in biomolecular simulations to represent the aqueous surrounding medium or for deriving effective electrostatic interaction models based on space-dependent dielectric constants¹⁰. That question led to a number of early works trying to characterise $\epsilon(\mathbf{r})$ in the vicinity of biomolecules or membranes using molecular dynamics (MD) simulations¹⁰⁻¹². In 2005, Ballenegger and Hansen presented the first MD simulations of a model polar solvent in confinement between two repulsive walls in order to define a local $\epsilon(z)$ rigorously using either linear response or a small perturbing electric field.¹³ For a perturbation perpendicular to the walls, they were led to conclude that such $\epsilon(z)$ is ill-defined and "is not a useful quantity near the walls". This pioneering work has initiated a number of subsequent MD studies of water in confinement or at interfaces using a realistic atomistic representation

of both the solvent and the confining surfaces¹⁴⁻¹⁹. This interest was revived recently by the experimental studies of Fumagalli *et al.*²⁰ who reported local capacitance measurements for water confined between two atomically flat walls separated by various distances down to 1 nanometer. Their experiments were interpreted as revealing "the presence of an interfacial layer with vanishingly small polarisation", that translates into an "anomalously low dielectric constant of confined water". Historically, the question of the nature of the hydration layer close to an electrified interface goes back to the early theories of Helmholtz and Stern and has plagued the theory of electric double layers for electrolytes at charged interfaces⁷. Already almost a century ago, by analysing surface capacitance data, Stern demonstrated that a thin interfacial layer exists at a solid-water interface with a dielectric constant much reduced compared to bulk water.⁷ To our knowledge, there is no clear consensus yet on the precise microscopic definition of this Stern layer and on the value of the dielectric constant that should be attributed to it. A proposed experimental reference for aqueous solutions at ambient conditions is $\epsilon \simeq 7$ instead of $\epsilon \simeq 80$ for the bulk⁷, an already small value in the absence of extreme confinement.

The dielectric properties of interfacial and confined water have been the subject of many recent simulation studies, including, *e.g.*, refs.^{18,19,21-32}. However, as already stressed in the early work of ref.¹³, the convergence of confined water dielectric properties by MD simulations is very difficult to achieve. Recent developments have been devoted to more efficient methods to compute the dielectric constant³², or to analytical theoretical approaches based on a dielectric continuum theory (DCT)³³ or a nonlocal field theoretical approach³⁴. Different explanations have

^{a)} Electronic mail: daniel.borgis@ens.fr

been proposed for the observed reduction in the perpendicular dielectric constant of confined water²⁰. These include a dielectrically 'dead' interfacial water layer caused by orientational constraints imposed by the interface^{20,26,27}, the disruption of the water hydrogen-bond network at the interface³¹, a dielectric boundary effect³³, and an excluded volume effect^{19,35}.

Classical density functional theory (DFT) is a well-founded, efficient theoretical approach to describe atomic and molecular fluids at interfaces or in confinement; See ,e.g., Refs^{36? -41}. In this article, we re-examine the problem of the dielectric response of highly polar liquids such as water in confinement between two walls using a two-variable density functional theory, in terms of number and polarisation densities, that we have derived and used previously for either a generic dipolar fluid^{42,43} or for water^{44,45}. It is a simplified version of the full molecular density functional theory (MDFT) formalism that three of us have been developing for a number of years⁴⁶⁻⁴⁹. This simplicity (combined with accuracy as will be seen) makes it possible first to sort out the important physical variables, secondly to derive analytical solutions and/or to provide instantaneous numerical solutions that are exempted from the statistical noise inherent to molecular simulations, and this for as many physical situations as desired. We note that a connected DFT approach was recently applied to the study of polarisation fluctuations in confined water; the coupling of number and polarisation densities was not considered explicitly, however, with an abrupt number density profile introduced as input.³⁵ Our goal is three-fold: 1) To reproduce at a much simpler level and to re-examine previous MD results concerning the definition of a local (ill-defined) longitudinal dielectric constant close to a wall or in confinement and to extend this definition to that of a (well-defined) locally coarse-grained dielectric constant. 2) To contribute to the understanding of the experiments of Fumagalli *et al.* and of the notion of "anomalously low dielectric constant" of water in confinement. 3) More generally to provide a theoretical foundation for describing quantitatively, at a fully molecular level, surface-induced solvent structures, as a consequence of the coupling between solvent density and solvent polarisation, and in a form that can be incorporated into commonly used mean field dielectric theories¹⁰.

The outline of the paper is as follows. Sec. II introduces our two-variable, number and polarisation density free energy functional. It is applied in Sec. III to the microscopic structure and longitudinal dielectric response of a model Stockmayer fluid, having the same bulk dielectric constant as water at similar density, in one-dimensional confinement between two graphene-like surfaces. The response is studied as function of slab thickness from less than a nanometer to micrometers. Sec. IV extends the study to a dipolar representation of SPC/E water and to the transverse response in addition to the longitudinal one. Sec. V concludes.

II. FREE-ENERGY FUNCTIONAL FOR A DIPOLAR LIQUID

Before discussing a more complete model of water later on, and in order to distinguish generic dielectric proper-

ties from the specific water properties emerging from its special H-bond structure, we start with an ersatz of water, namely a Stockmayer fluid composed of Lennard-Jones (LJ) particles embedding a permanent dipole μ , and whose density and dielectric constant at ambient temperature are similar to those of water. We take the parameters from the early studies of Pollock and Alder⁵⁰: $\sigma_{LJ} = 3.024 \text{ \AA}$, $\epsilon_{LJ} = 1.87 \text{ kJ/mol}$, $\mu = 1.835 D$, $\rho = 0.0289 \text{ \AA}^{-3}$ or, in dimensionless units, $T^* = k_B T / \epsilon_{LJ} = 1.35$, $\rho^* = \rho \sigma_{LJ}^3 = 0.8$, $\mu^* = \sqrt{\mu^2 / \epsilon_{LJ} \sigma_{LJ}^3} = 2$. Those parameters yield a dielectric constant $\epsilon = 80$. They also correspond to a state point considered by Ballenegger and Hansen when studying the dielectric properties of the closely related dipolar-soft-sphere model in confinement¹³. As shown in Refs^{42-45,51}, such dipolar liquid submitted to an external potential can be described accurately by a grand-potential functional depending on the local number density $n(\mathbf{r})$ and local polarisation density $\mathbf{P}(\mathbf{r})$. This functional is fixed by the chemical potential of the bulk fluid at density n_0 . It can be decomposed into density and polarisation terms, $\mathcal{F} = \mathcal{F}_n + \mathcal{F}_P$, with the density term given by

$$\mathcal{F}_n[n] = k_B T \int d\mathbf{r} \left[n(\mathbf{r}) \ln \left(\frac{n(\mathbf{r})}{n_0} \right) - n(\mathbf{r}) + n_0 \right] + \int d\mathbf{r} n(\mathbf{r}) V_0(\mathbf{r}) - \frac{k_B T}{2} \int d\mathbf{r}_1 d\mathbf{r}_2 \Delta n(\mathbf{r}_1) c_s(r_{12}) \Delta n(\mathbf{r}_2) + \mathcal{F}_B[n(\mathbf{r})] \quad (1)$$

where $\Delta n(\mathbf{r}) = n(\mathbf{r}) - n_0$. $V_0(\mathbf{r})$ represents the external LJ potential exerted at point \mathbf{r} . $\mathcal{F}_B[n(\mathbf{r})]$ is the so called bridge potential, that we take here as a hard-sphere (HS) bridge functional based on fundamental measure theory⁵²⁻⁵⁴, using the Kierlik-Rosinberg scalar version^{55,56} and a reference HS diameter defined conventionally as $d_{HS} = \sigma_{LJ}(1 + 0.298T^*) / (1 + 0.3316T^* + 0.001048T^{*2})^{57}$. The polarization part of the functional reads

$$\mathcal{F}_P[n, \mathbf{P}] = k_B T \int d\mathbf{r} n(\mathbf{r}) \times \left(\ln \left[\frac{\mathcal{L}^{-1}(\Omega(\mathbf{r}))}{\sinh(\mathcal{L}^{-1}(\Omega(\mathbf{r})))} \right] + \Omega(\mathbf{r}) \mathcal{L}^{-1}(\Omega(\mathbf{r})) \right) - \int d\mathbf{r} \mathbf{P}(\mathbf{r}) \cdot \mathbf{E}_0(\mathbf{r}) - \int d\mathbf{r}_1 \mathbf{P}(\mathbf{r}_1) \cdot \mathbf{E}_{exc}(\mathbf{r}_1) \quad (2)$$

with $\Omega(\mathbf{r}) = P(\mathbf{r}) / \mu n(\mathbf{r})$ and $P(\mathbf{r}) = |\mathbf{P}(\mathbf{r})|$. The first term represents the ideal free energy for an ensemble of non interacting dipoles submitted to an external electric field; there \mathcal{L} designates the Langevin function and \mathcal{L}^{-1} its inverse. $\mathbf{E}_0(\mathbf{r})$ is the external electric field at point \mathbf{r} . The excess electric field $\mathbf{E}_{exc}(\mathbf{r}_1)$ is defined by

$$\mathbf{E}_{exc}(\mathbf{r}_1) = \frac{1}{2} \frac{k_B T}{\mu^2} \int d\mathbf{r}_2 [c_\Delta(r_{12}) \mathbf{P}(\mathbf{r}_2) + c_D(r_{12}) (3\hat{\mathbf{r}}_{12} (\mathbf{P}(\mathbf{r}_2) \cdot \hat{\mathbf{r}}_{12}) - \mathbf{P}(\mathbf{r}_2))] \quad (3)$$

where $\hat{\mathbf{r}}_{12} = \mathbf{r}_{12} / r_{12}$. In eqs 1 and 3, $c_S(r)$, $c_\Delta(r)$, $c_D(r)$ represent the spherical and dipolar spherical-invariant projections of the angular-dependent direct correlation function of the bulk liquid at density n_0 . Those functions are inputs in the theory and are obtained from a preliminary simulation of the bulk fluid. See Ref.^{42,45} for their behaviour in direct and Fourier space.

The equilibrium number density and polarisation density are obtained by minimisation of the functional with respect to both $n(\mathbf{r})$ and $\mathbf{P}(\mathbf{r})$. Minimisation of \mathcal{F}_P with respect to $\mathbf{P}(\mathbf{r})$ for a given $n(\mathbf{r})$ gives

$$P(\mathbf{r}) = \mu n(\mathbf{r}) \mathcal{L}(\beta \mu |\mathbf{E}_0(\mathbf{r}) + \mathbf{E}_{exc}(\mathbf{r})|) \quad (4)$$

This accounts for dipolar saturation at high local electric fields. It does so at a fully microscopic level compared to the coarse-grained dipolar Poisson approach of Berthoumieux *et al.*⁵⁸. For small external fields, the ideal free energy in eq. 3 can be developed at dominant order in polarisation

$$\mathcal{F}_P^{id}[n, \mathbf{P}] = \frac{1}{2} \int d\mathbf{r} \frac{\mathbf{P}(\mathbf{r})^2}{\alpha_d n(\mathbf{r})} \quad (5)$$

where $\alpha_d = \mu^2/3k_B T$ is the orientational polarizability of a permanent dipole in a field. In that case, minimisation yields a linear relation between $\mathbf{P}(\mathbf{r})$ and $\mathbf{E}_0(\mathbf{r})$, with indeed a nonlocal response function.

III. CONFINEMENT IN A ONE-DIMENSIONAL SLIT PORE

In order to mimic the experimental setup of Ref.²⁰, as well as to follow the simulation conditions of Ballenegger and Hansen¹³, we consider a model of one-dimensional slit pore composed of 2 graphene-like plates in the x - y plane separated by a distance h along z . As in Ref.¹³, the external potential $V_0(z)$ exerted by the two walls results from the x - y integration of a 3D-Lennard-Jones potential. It is of the 9-3 type, with parameters pertinent to carbon-water interactions

$$V_0(z) = \frac{4\pi}{3} \epsilon_w \left[\frac{\sigma_w^9}{15z^9} + \frac{\sigma_w^9}{15(h-z)^9} - \frac{\sigma_w^3}{2z^3} - \frac{\sigma_w^3}{2(h-z)^3} \right] \quad (6)$$

with $\sigma_w = 3.9 \text{ \AA}$ and $\epsilon_w = 2.6 \text{ kJ/mol}$. An external electric field $E_0(z)$ is applied along the perpendicular z -direction. For such a 1D-geometry, the polarisation field is so-called longitudinal (*i.e.*, aligned with the electric field in q -space), and the two direct correlation functions $c_\Delta(q), c_D(q)$ (zeroth- and second-order Hankel transform of $c_\Delta(r), c_D(r)$, respectively) reduce in q -space to a single longitudinal function $c_L(q) = c_\Delta(q) + 2c_D(q)$ ⁴⁵. The two components of the functional $\mathcal{F} = \mathcal{F}_n + \mathcal{F}_P$ of eqs 1-3 can be written per surface area in the form

$$\begin{aligned} \mathcal{F}_n[n] = & k_B T \int dz \left[n(z) \ln\left(\frac{n(z)}{n_0}\right) - n(z) + n_0 \right] \\ & - \frac{k_B T}{2} \int dz_1 dz_2 \Delta n(z_1) c_S(z_{12}) \Delta n(z_2) \\ & + \int dz n(z) V_0(z) + \mathcal{F}_B[n(z)] \end{aligned} \quad (7)$$

$$\begin{aligned} \mathcal{F}_P[n, P] = & k_B T \int dz n(z) \times \\ & \left[\ln\left(\frac{\mathcal{L}^{-1}(\Omega(z))}{\sinh(\mathcal{L}^{-1}(\Omega(z)))}\right) + \Omega(z) \mathcal{L}^{-1}(\Omega(z)) \right] \\ & - \frac{1}{6\alpha_d} \int dz_1 dz_2 c_L(z_{12}) P(z_1) P(z_2) \\ & - \int dz P(z) E_0(z) \end{aligned} \quad (8)$$

$c_S(z), c_L(z)$ are defined here as the inverse 1D Fourier transforms of the 3D functions $c_S(q), c_L(q)$. They are plotted in Fig. 1. It should be noted that both are short range and vanish beyond $r \simeq 6 \text{ \AA}$. This might be surprising for the polarisation-polarisation contribution $c_L(z)$ since dipole-dipole interactions are a-priori long-range. It is a well-known fact, however, that for a longitudinal polarisation field, the long-range $1/r^3$ part of the dipolar tensor disappears, and the Maxwell field is rigorously defined by the local relation $\mathbf{E}(\mathbf{r}) = \mathbf{E}_0(\mathbf{r}) - 4\pi\mathbf{P}(\mathbf{r})$. In other words the dielectric displacement is equal to the external field, $\mathbf{D}(\mathbf{r}) = \mathbf{E}_0(\mathbf{r})$.




Figure 1. One-dimensional direct correlation functions for the Stockmayer fluid model described in the text, and entering in eqs 7-8

For a small perturbing field $E_0(z)$ and when $n(z)$ is provided independently through the minimisation of eq. 7 only (which amounts to neglecting the n - P coupling appearing in the ideal term of eq. 8), the quadratic form of eq. 5 can be used, turning the minimisation in $P(z)$ to a linear algebra problem that can be solved through matrix inversion. In this linear regime, the nonlocal response can be written in terms of the susceptibility $\chi_0(z_1, z_2)$

$$P(z_1) = \int dz_2 \chi_0(z_1, z_2) \alpha_d E_0(z_2) \quad (9)$$

with

$$\chi_0(z_1, z_2) = n(z_1) \delta(z_{12}) + \frac{h_L(z_1, z_2)}{3} n(z_1) n(z_2) \quad (10)$$

where the longitudinal, inhomogeneous pair distribution function $h_L(z_1, z_2)$ relates to the bulk direct correlation function $c_L(z_{12})$ through an inhomogeneous Ornstein-Zernike (OZ) relation. See the supplementary information (SI) for details. For a constant electric field $E_0(z) \equiv E_0$,

the integration upon the second variable can be performed and a local response function can be defined as

$$f(z) = 4\pi P(z)/E_0 = 1 - \frac{1}{\epsilon_{\perp}(z)} \quad (11)$$

where $\epsilon_{\perp}(z)$ stands for a local *longitudinal* dielectric constant and formally

$$f(z_1) = 4\pi\alpha_d n(z_1) \left(1 + \int dz_2 \frac{h_L(z_1, z_2)}{3} n(z_2) \right) \quad (12)$$

Variants of this formula can be readily found in the literature⁹, It explains how a local dielectric constant can be defined even though the dielectric response function itself, given by χ_0 or h_L , is intrinsically non-local⁷. It is seen that the inhomogeneous fluid density $n(z)$ enters at two places; the first one indicates that the local response function should be zero where there is no particle, $n(z) = 0$. The second one excludes the nonlocal contribution to the polarisation response coming from region where the density is zero, $n(z_2) = 0$. This nonlocal cut-off effect on the polarisation response near the boundaries was pointed out recently by Olivieri *et al.*¹⁹. Among several other worthy remarks, it is justified in the SI that, since $h_L(z_1, z_2)$ is short-ranged, the influence of the walls is expected to be short-ranged too, and the bulk value of $f(z)$ and $\epsilon_{\perp}(z)$ should be reached after only a few particle diameters from the walls.

From now on, we depart from this linear algebra formulation that implies matrix inversion. The results presented next were obtained numerically by the joint minimisation of the functional with respect to $n(z)$ and $P(z)$ in the presence of a small and constant external field $E_0 = 0.1$ V/nm. We have written a simple, dedicated Python code for that purpose. For a discretisation of the fields over typically $N = 1024$ points, the minimisation procedure is instantaneous on a laptop (less than a second).

Following the simulations of Ref.¹³, we first consider a relatively wide slit of width $h = 50 \text{ \AA}$ ($16.5 \sigma_{LJ}$). We plot the equilibrium density field $n(z)$ as well as the response function $f(z)$ in reduced units in Fig. 2. Both present strong structural oscillations up to 6 sigma from the walls. These two curves appear very similar to the ones obtained by Ballenegger and Hansen¹³ via MD— although their study was mainly focused on the less polar case $\mu^* = 1.2$, the simulations for $\mu^* = 2$ proving very hard to converge. In Fig. 3-top, we plot the resulting inverse dielectric constant $1/\epsilon_{\perp}(z)$ that presents oscillations that span unphysical negative values up to $\sim 6 \sigma_{LJ}$ from the walls. That leads Ballenegger and Hansen to conclude that " $\epsilon_{\perp}(z)$ is not a useful quantity near the walls". Here we modulate that judgement by recalling that standard electrostatics is by essence a coarse grained theory, and that one should rather look at a coarse-grained $\tilde{\epsilon}_{\perp}(z)$ with a coarse-graining length of at least the size of a particle (this approach was used in ref.¹³ to smoothen the dipolar fluctuations). Here, this can be formalised by looking at a coarse-grained polarisation field, defined for example using

$$\tilde{P}(z) = \int dz' w(|z - z'|) P(z') \quad (13)$$




Figure 2. Top: Reduced density $n^*(z) = n(z)\sigma_{LJ}^3$ for a slab of width $h = 50 \text{ \AA}$ ($16.5\sigma_{LJ}$). Bottom: Local response function $f(z) = 4\pi P(z)/E_0$.

where the weight function $w(z)$ is taken as a normalized Gaussian function with standard deviation $\sigma_P = \lambda\sigma_{LJ}$, λ of order 1. A coarse-grained dielectric constant $\tilde{\epsilon}_{\perp}(z)$ can be defined from $\tilde{P}(z)$ exactly as in eq. 11. The inverse, coarse-grained, dielectric constant $1/\tilde{\epsilon}_{\perp}(\mathbf{r})$ corresponding to $\lambda = 0.7$ is plotted as function of distance in Fig. 3-top together with the bare microscopic results. This quantity now appears as a smooth curve that does remain strictly positive, so that $\tilde{\epsilon}(\mathbf{r})$ itself is well defined and well behaved; see Fig. 3-bottom. It presents two peaks at values higher than in the bulk close to the walls; the main feature to be retained, however, is that the bulk value is reached after a few particle diameters, at a distance where the microscopic polarisation still presents microscopic oscillations ($z \sim 4 - 5 \sigma_{LJ}$), and that there are no long-range effects induced by the walls on the local dielectric constant. We note that the coarse-graining length σ_P should not be considered as fundamental quantity, but rather as an observation length scale. It might be linked also to the resolution of the experiment that is realised. As soon as this observation/resolution becomes comparable to the particle size, $1/\tilde{\epsilon}_{\perp}(z)$ and $\tilde{\epsilon}_{\perp}(z)$ appear as locally well-defined, positive quantities. As a rule of thumb, to keep a microscopic character in our analysis, we choose σ_P large enough to smooth the spurious behaviour of $1/\epsilon(z)$ (or $f(z)$), but small enough to have its overall microscopic behaviour unchanged, in particular keeping a limited penetration into the walls and an unaltered distance at which the bulk value is reached. We find both conditions typically fulfilled for $0.6 \leq \lambda \leq 1$; $\lambda = 0.7$ appears as a good compromise. The variation of the results of Fig. 3 with the parameter λ is illustrated in the SI. Increasing λ from 0.7 to 1 and beyond




Figure 3. Top: Local inverse dielectric constant $1/\epsilon_{\perp}(z)$ in a slab of width $h = 50 \text{ \AA}$ (blue curve) and its coarse-grained version $1/\tilde{\epsilon}_{\perp}(z)$ obtained through eq. 13 with a coarse-graining length $\sigma_P = 0.7\sigma_{LJ}$ (violet curve). Bottom: Coarse-grained dielectric constant $\tilde{\epsilon}_{\perp}(z)$ whereas the corresponding microscopic $\epsilon_{\perp}(z)$ is ill-defined.

gives a more regular behaviour for $\tilde{\epsilon}_{\perp}(z)$ but indeed a more important smoothing of the boundaries. We argue in the SI that, for modelling purposes, the fundamental quantity to consider is rather the coarse-grained response $f(z)$ that is less sensitive to the choice of λ and can be modelled with two inverted sigmoid-like curves, yielding smooth curves when converted to $\tilde{\epsilon}_{\perp}(z)$.

In Fig. 4 and 5, we plot the results corresponding to a much narrower slab with $h = 10 \text{ \AA}$ ($\sim 3\sigma_{LJ}$). It can be seen that only two solvent layers are allowed in-between the plates and that the density $n(z)$ and the polarisation density $P(z)$ remain everywhere far from their bulk values. The coarse-grained dielectric constant $\tilde{\epsilon}_{\perp}(z)$ displayed in Fig. 5 has a nice and smooth hat shape that reaches a maximum value around 10 in the middle of the slab, again far below the bulk value.

From the above findings, one can state that the very long range effect, up to a micrometer, observed for the measured ϵ_{\perp} as function of slab thickness in Ref.²⁰ cannot be attributed to any long-range effect of the walls on the local dielectric constant of the liquid. One should look rather at some effective dielectric response of the whole slab to the applied potential difference. For our slab model submitted to a constant external field (the so-called dielectric box model of Ref.¹⁸) this can be measured by relating the average polarisation in the slab to the field

$$\bar{P}(h) = \frac{1}{h} \int_0^h P(z) dz = \frac{1}{4\pi} \left(1 - \frac{1}{\bar{\epsilon}_{\perp}(h)} \right) E_0 \quad (14)$$




Figure 4. Same as Fig. 2 for a slab of width $h = 10 \text{ \AA}$.




Figure 5. Same as Fig. 3 for a slab of width $h = 10 \text{ \AA}$.

which yields according to eq. 11

$$\frac{1}{\bar{\epsilon}_{\perp}(h)} = \frac{1}{h} \int_0^h dz \frac{1}{\epsilon_{\perp}(z)} \quad (15)$$

$$\simeq \frac{1}{h} \int_0^h dz \frac{1}{\tilde{\epsilon}_{\perp}(z)} \quad (16)$$

The second equality holds for the coarse-grained dielectric constant instead of the microscopic one if the coarse-graining length is such that $\tilde{P}(0) = \tilde{P}(h) \simeq 0$. The mi-

macroscopic expressions 14-15 remain the ones to be used in the following. Expressing the total electrostatic energy of the device, which includes the self-energy of the electric field between the plates, writing the potential difference between them as

$$\Delta\Phi(h) = - \int_0^h dz E(z) = - \int_0^h dz \frac{1}{\epsilon_{\perp}(z)} E_0 \quad (17)$$

and equating this energy to $1/2 C(h)\Delta\phi(h)^2$ yields the effective capacitance

$$C(h) = \frac{\bar{\epsilon}_T(h)}{4\pi h} \quad (18)$$

with $\bar{\epsilon}_T(h)$ having the same definition as in eq. 15. Measuring the average polarisation in the slab or the effective slab capacitance are thus equivalent. When the plate-to-plate distance h is large enough as in Fig. 3, one can divide the device in three regions, two interfacial regions of width h_i and an intermediate bulk region of width $h - 2h_i$ where $\epsilon_{\perp}(z) \simeq \epsilon_{bulk}$. In that case, the choice of h_i results in the definition of an effective dielectric constant ϵ_i for the interfacial region through

$$\frac{1}{\epsilon_i} = \frac{1}{h_i} \int_0^{h_i} dz \frac{1}{\epsilon_{\perp}(z)} \quad (19)$$

and the resulting dielectric constant of the whole slab can be written as

$$\frac{1}{\bar{\epsilon}_{\perp}(h)} = 2 \frac{h_i}{h} \frac{1}{\epsilon_i} + \left(1 - 2 \frac{h_i}{h}\right) \frac{1}{\epsilon_{bulk}} \quad (20)$$

or alternatively

$$\bar{\epsilon}_{\perp}(h) \simeq \frac{\epsilon_{bulk}}{1 + \frac{2h_i}{h} \left(\frac{\epsilon_{bulk}}{\epsilon_i} - 1\right)} \quad (21)$$

Visual inspection of Fig. 3 leads to the choice $h_i \simeq 6\sigma_{LJ}$ when looking at the bare $1/\epsilon_{\perp}(z)$, or $h_i \simeq 3\sigma_{LJ}$ when looking at the coarse-grained curve $1/\bar{\epsilon}_{\perp}(z)$. Here we can define h_i unambiguously as the value under which we find that the approximation in eq. 20 departs from the exact integral in eq. 15. This criterion gives us $h_i \simeq 9 \text{ \AA}$, and $\epsilon_i \simeq 5$. The approximated formulas 20-21 match completely the model of 3 capacitors in series that was used in Ref.²⁰ to interpret the experimental results, except that here h_i, ϵ_i are not fitting parameters but follow from a microscopic analysis. We note that the final formulas proposed in the dielectric continuum theory approach of Cox and Geissler³³ or in the dividing surface model of Loche *et al.*²⁵ amount in eq. 21 to reduce the interfacial width h_i to the depletion length where the fluid density is zero (roughly $h_i = 2 \text{ \AA}$ by inspection of Fig. 3) and to fix accordingly $\epsilon_i = 1$.

The three separated capacitor picture expressed by eq. 20-21 should not apply when $h < 2h_i$, *i.e.*, below $\sim 20 \text{ \AA}$. In that case one has to resort merely to numerical integration in eq. 15. For the $h = 10 \text{ \AA}$ case, illustrated in Figs 4-5, the numerical integral yields a slab-averaged dielectric constant of $\bar{\epsilon}_{\perp} = 2.3$; this is a surprisingly small

value compared to the bulk, that is in line with the experimental findings for water. In Fig. 6, we have plotted $\bar{\epsilon}_{\perp}(h)$ computed over the range $0 - 10 \text{ nm}$, together with the asymptotic formula 21 starting from the same microscopic/nanoscale distances up to the micrometer range. We use the same log-log representation as in Ref.²⁰ for direct comparison. Although our curves correspond to a simplified water model embedded in a simplified slab (no H-bonds, no electronic polarisation), the similarities with the experimental results are striking. In particular we recover the main feature pointed out by the experimental work: the effective dielectric constant measured in slabs with a thickness in the 1 nm range is found around 2; this was quoted as an "anomalously low dielectric constant of confined water". Our theoretical work makes it possible to bring some insight to the interpretation of the experimental results. Indeed the long range behaviour observed for $\bar{\epsilon}_{\perp}(h)$ has no mystery since, in longitudinal conditions, the measure of the average polarisation or capacitance yields the integral of $1/\epsilon_{\perp}(z)$ which, since $1/\epsilon_{bulk} \ll 1$, gets its main contribution from the boundaries. Very thick slabs are required for the bulk to contribute. This is clear from the slow h_i/h convergence appearing in eq. 21. It should be noted that this asymptotic formula using the values h_i, ϵ_i derived above works extremely well even in the $h = 1 \text{ nm}$ range, *i.e.*, down to separation distances $h < 2h_i$ where it should not! We can only attribute this to continuity that allows the extrapolation of the curve on a limited range below its validity. Note also that since $\epsilon_{bulk}/\epsilon_i \gg 1$, the results essentially depend on the ratio h_i/ϵ_i so that, on an empirical ground, other choices of those parameters are possible to reproduce the average slab dielectric constant. In particular one can take $\epsilon_i = 1$ and $h_i = 9/5 = 1.8$, a value very close to the one suggested in the dielectric continuum theory (DCT) of Cox and Geissler³³; see Fig. 6. There is in fact much more in their analysis than considering this limit, that amounts to model the solid-liquid interface as a step-function. Their study points out the importance, as well as the ambiguity, of locating the dielectric boundaries and of defining properly the volume of the device, which contains a molecular exclusion volume portion and one filled by the liquid. Such ambiguity is present in our definition of the device polarisation that involves its thickness h (eq. 14). We have taken as a natural microscopic definition of h the distance between the center of the surface atoms of each plates, so that the integrated Lennard-Jones potential can be defined as in eq. 6. Other experimental choices for h are possible and the measure of the device thickness is also submitted to experimental uncertainties. The influence of this uncertainty is illustrated in the SI. The observed trends are in clear agreement with Ref.³³. Although based on a simplified, step-wise, molecular representation of the solid-liquid interface, the DCT approach does capture the essential balance between low and high dielectric constant volumes.

Finally, our results show a structuration due to molecular stacking for thicknesses in the $0.6 - 1.2 \text{ nm}$ range, with two clear peaks at $h = 0.6$ and 1 nm and damped oscillations beyond. This is in agreement with the sub-nanometer oscillatory behaviour observed by simulations by Jalali *et al.*²⁸ for SPC/E water in tight confinement. The overall flat-

tening of the curve around a value of 2 seems reminiscent, within the error bars, of the plateau detected experimentally in the 1 nm region.




Figure 6. Effective dielectric constant computed using cDFT for the model Stockmayer fluid embedded in a slab of width h as function of h . The red solid curve corresponds to the asymptotic formula 21 with the parameters determined in the text; it starts at $h = h_i$. The red dashed curve corresponds to the dielectric continuum theory of Cox and Geissler³³ or dividing surface model of Loche *et al.*²⁵ with $\epsilon_i = 1$ and $h_i = 9/5 = 1.8$. These curves can be compared with the experimental results reported in Ref.²⁰ for water in nano- to micrometric hBN slits.

IV. EXTENSION TO SPC/E WATER

To get even closer to water, although still at a dipolar level, we extend the previous theory by introducing in the functional the parameters and the $c_S(z), c_L(z)$ direct correlation functions corresponding to SPC/E water. We take the simple weighted density approximation of Ref.^{49,59} for the bridge functional. Since the symmetry of water is beyond that of a simple dipole, at least a supplementary density-polarisation coupling has to be introduced in the functional in the form⁴⁵

$$\mathcal{F}[n, P] = \mathcal{F}_n[n] + \mathcal{F}_P[n, P] + \mathcal{F}_{nP}[n, P] \quad (22)$$

with

$$\mathcal{F}_{nP}[n, P] = -\frac{k_B T}{\mu} \int dz_1 dz_2 c_{nL}(z_{12}) \Delta n(z_1) P(z_2) \quad (23)$$

This introduces the fact that a spontaneous polarisation exists even in the slab with zero applied field. The corresponding polarisation profile is anti-symmetrical with respect to the two walls and the integrated polarisation of the sample is zero, as it should. This spontaneous polarisation remains prominent when a small to moderate external field is applied. See Fig. 7 for a large slab with $h = 50 \text{ \AA}$ and also Ref.⁴⁸ where molecular density functional theory calculations were performed with a molecular representation of the electrodes and a constant voltage applied between the electrodes rather than an external electric field.

On the other hand, the dielectric response $f(z) = 4\pi(P(z) - P_0(z))/E_0$, represented in Fig. 7, is perfectly




Figure 7. Top: Polarisation in a slab of width $h = 50$ with and without an applied external electric field. A spontaneous polarisation exists due to the density/polarisation coupling of eq. 23 which remains the dominant contribution at the interfaces when a field is applied. Bottom: The resulting response function $f(z) = 4\pi(P(z) - P_0(z))/E_0$ which appears perfectly symmetrical.

symmetrical. It appears less oscillatory and reaches the bulk value more rapidly than in the Stockmayer case of Fig. 3; this is a sign that the damping of spatial correlations occurs more quickly in water than in a purely dipolar liquid. In Fig. 8 this response is plotted in terms of the ill-defined, local microscopic constant and of its well-defined coarse-grained version.

We present in Fig. 9 the curve for $\bar{\epsilon}_\perp(h)$ which is very similar to the one obtained for the Stockmayer solvent, so that identical conclusions can be drawn. No specific property of water emerges, beyond being a polar, molecular fluid of high dielectric constant. This result is consistent with the observation by MD simulations²⁶ that confined polar liquids like methanol, acetonitrile and dichloromethane exhibit a dielectric constant reduction similar to that of water. We further note that in our results the dielectric constant reduction of confined water is reproduced by considering exclusively the number and polarisation densities, without requiring orientational constraints imposed by the interface on the water molecules. We find an interfacial width $h_i = 7.5 \text{ \AA}$ and an associated effective interfacial dielectric constant $\epsilon_i = 3.9$, to be compared to $h_i = 7.4$ and $\epsilon_i = 2.1$ determined experimentally by Fumagalli *et al.*²⁰. h_i appears slightly smaller for SPC/E than for the purely dipolar fluid since, as we mentioned, the spatial correlations in water are shorter range. Concordingly, we do observe oscil-




Figure 8. Top: (Ill-defined) microscopic perpendicular dielectric constant for SPC/E water in a slab of width $h = 50 \text{ \AA}$ (in cyan) and its coarse-grained version with a coarse-graining length $\sigma_P = 2 \text{ \AA}$ (in violet). Bottom: Same for the parallel dielectric constant when the field is applied parallel to the plates ($\sigma_P = 1.5 \text{ \AA}$).

lations of $\bar{\epsilon}_\perp(h)$ around the value of 2 in the 0.6-1 nm range with a first minimum at 1.8 around $h = 0.75 \text{ nm}$ and a second higher minimum around $h = 1 \text{ nm}$; this is in agreement with the simulation results of Ref.²⁸. Indeed, those oscillations are damped more quickly than in the Stockmayer case.

Finally, although we are not aware of any experimental results to compare with, we take the opportunity here to study the transverse polarisation case, *i.e.*, applying an external electric field in the transverse direction x parallel to the plates. All the DFT formalism developed above remains valid if the longitudinal direct correlation function $c_L(z)$ in eq. 8 is replaced by the transverse one, $c_T(z)$ defined as the inverse, 1D Fourier transform of $c_\Delta(q) - c_D(q)$ ⁴⁵. The density-polarisation coupling of eq. 23 vanishes in this case and one resorts to the joint minimisation of the equivalent of the functional in eqs.7-8 using $c_T(z)$. The response function to a constant field E_0 is defined in this case using

$$f(z) = 4\pi P(z)/E_0 = \epsilon_\parallel(z) - 1 \quad (24)$$

The picture is different from that in the longitudinal case since the measure now concerns ϵ instead of $1/\epsilon$. As seen in Fig. 8 for a 50 Å-slab, the resulting $\epsilon_\parallel(z)$ does present oscillations close to the boundaries but remains everywhere positive and well-defined. This simple fact was emphasised in the early studies of Ballenegger and Hansen¹³

and confirmed by subsequent MD studies using molecular solvents^{14,18,19,23-25}. For a slab of thickness h , an effective dielectric constant can be defined as

$$\bar{\epsilon}_\parallel(h) = \frac{1}{h} \int_0^h dz \epsilon_\parallel(z) \quad (25)$$

If the slab is thick enough to distinguish two interfacial regions from an intermediate bulk buffer, as illustrated in Fig. 8, the following simple formula pertinent to 3 capacitors in parallel can be inferred by decomposing the integral

$$\bar{\epsilon}_\parallel(h) = \epsilon_{bulk} \left[1 - 2 \frac{h_i}{h} \left(1 - \frac{\epsilon_i}{\epsilon_{bulk}} \right) \right] \quad (26)$$

with


$$\epsilon_i = \frac{1}{h_i} \int_0^{h_i} dz \epsilon_\parallel(z) \quad (27)$$

Again ϵ_i is fixed by the choice of a reasonable h_i . Using the same unambiguous selection criterion as before (the minimal h_i that fulfil the asymptotic equation 26), we find $h_i = 10 \text{ \AA}$ and $\epsilon_i \simeq 50$, *i.e.*, a much larger interfacial, effective value than in the perpendicular case. Besides it can be seen in Fig. 9 that the bulk value is reached for slabs of thickness $h \simeq 10 \text{ nm}$, thus much narrower rather than $\sim 500 \text{ nm}$ necessary for the perpendicular dielectric constant. As for the out-of-plan polarisation case, a slight oscillatory behaviour of the in-plane dielectric constant $\bar{\epsilon}_\parallel(h)$ is observed for thicknesses between 0.6 and 1 nm but we do not detect the drastic drop by two orders of magnitude that Hamid *et al.* found in their simulations around $h = 0.75 \text{ nm}$, that they attribute to a freezing transition occurring at that particular packing condition²⁹.

Finally, let us mention that our DFT results are in overall agreement with previous MD simulations^{14,16,18,19,23,25,26}. In particular Itoh and Sakuma¹⁶ have computed by MD simulations the perpendicular and parallel effective dielectric constants of three-dimensional graphite/SPCE-water/graphite slabs of various sizes. In spite of our different, simplified modelling of water and of the surface-water interactions, the DFT results in Fig. 8 are in quantitative agreement with theirs for the few slab geometries that they explored.

V. CONCLUSIONS

In this work, we presented a simple two-variable, number/polarisation density functional theory describing the microscopic structure of polar fluids at interfaces or in confinement, as well as their microscopic dielectric response to external fields. For a given system geometry the numerical solution is obtained instantaneously with a laptop and compares very well with previous MD simulations of closely related systems^{9,19}. It provides at modest numerical cost locally coarse-grained quantities that can further nourish continuum Poisson-Boltzmann models. The approach made it possible to model thin water films of various thicknesses and to mimic the experimental setup of Ref²⁰. Our



(h)

Figure 9. Effective dielectric constant for SPC/E water embedded in a slab of width h as function of h . The blue dots are the cDFT results for $\bar{\epsilon}_{\perp}(h)$ and the solid curve correspond to the asymptotic formula 21 with the parameters determined in the text and down to $h = h_i$. The blue triangles and cyan solid curve are the same for $\bar{\epsilon}_{\parallel}(h)$.

modelling is indeed incomplete and neglects physical features such as the precise chemical nature of the interface, its three-dimensional roughness, and the electronic polarisability of both the solid surfaces and the solvent. A main conclusion, however, is that finding very low effective longitudinal dielectric constants of the order of 2-3 for water in slabs of nanometer size through capacitance measurements should not be a special property of water but is true for any generic polar solvent having a high bulk dielectric constant. Fig. 6 obtained for the Stockmayer solvent or Fig. 9 for a dipolar representation of water present close similarities with the experimental curve in Ref²⁰. A similar conclusion is reached in Ref.³³ which follows a purely macroscopic, electrostatics route. On the other hand the definition of a local, space-dependent longitudinal dielectric constant is found irrelevant at a microscopic level close to the walls but can be inferred at a molecular coarse-grained level with a smoothing length of the order of the size of a solvent particle. This local dielectric constant is shown to reach its bulk value after a short distance h_i from the slab walls, typically 10 \AA for water. This clearly defines a short-range interfacial solvent region with an effectively low dielectric constant ϵ_i . Since in the longitudinal polarisation case the response concerns $1/\epsilon$ rather than directly ϵ , incorporating the intermediate bulk region with a $1/\epsilon_{bulk}$ contribution turns rigorously to a three-capacitors-in-series model described by formula 20. Since the $1/\epsilon_{bulk}$ is small, the low dielectric constant interfacial regions dominate and it requires large slab thicknesses for the bulk to contribute; this explains the very slow increase of ϵ with slab thickness. Our theoretical approach brings additional insight to this simple, phenomenological capacitor model. 1) Although it should not apply to slab width below $2h_i$, twice the interfacial thickness, it does hold for shorter distances down to h_i . We take this as a continuity effect. 2) In our microscopic analysis, the parameters h_i can be defined unambiguously from the microscopic structure and it fixes also the value of the second parameter ϵ_i . Phenomenologically, since the

behaviour in eq. 20 depend essentially on the ratio h_i/ϵ_i , other choices of parameter couples are possible including the extreme choice $\epsilon_i = 1$ (See Fig. 6). 3) We do observe an oscillatory behaviour, leading to an effective flattening of the dielectric response around $\bar{\epsilon}_{\perp}(h) = 2$ for slabs below 1 nm , a saturation effect that is reminiscent of the one detected experimentally. In our case, we can relate this non-monotonic behaviour to the interplay between polarisation response and hard-sphere packing when only one or two layers of solvent particles are allowed in the slab.

We have also studied the complementary case of the transverse response when the perturbing field is applied parallel to the walls instead of perpendicular. In that case the microscopic dielectric constant $\epsilon_{\parallel}(z)$ is well-defined although presenting some structural oscillations close to the walls; those are smoothed out by coarse-graining over a particle dimension. A three-capacitors-in-parallel model described by eq. 26 is found to apply for slabs above 1 nm and the overall, slab capacitance is found to reach the bulk value for slab thickness on the order of 10 nm , *i.e.*, much narrower than in the perpendicular case. The inferred interfacial effective dielectric constant is also much higher.

Finally, let us mention that water in confinement can be described at a much more refined molecular density functional theory level using the full MDFT formalism and its associated MDFT software that includes not only the dipolar symmetry but all the higher multipolar symmetries and makes it possible also to represent the surface-water interaction at a fully atomistic, 3D level⁴⁸. Such calculations are underway and will be presented in a forthcoming publication.

ACKNOWLEDGEMENTS

This work was supported by the Agence Nationale de la Recherche, projet ANR BRIDGE AAP CE29.

REFERENCES

- ¹W. D. JACKSON, *Classical Electrodynamics*, Wiley, New York, third edition, 1999.
- ²L. ONSAGER, *J. Am. Chem. Soc.* **58**, 1486 (1936).
- ³J. KIRKWOOD, *J. Chem. Phys.* **7**, 911 (1939).
- ⁴F. BOOTH, *J. Chem. Phys.* **19**, 391 (1951).
- ⁵G. NIENHUIS and J. M. DEUTCH, *J. Chem. Phys.* **55**, 4213 (1971).
- ⁶J. D. RAMSHAW, *J. Chem. Phys.* **55**, 1763 (1971).
- ⁷J. D. RAMSHAW, *J. Chem. Phys.* **66**, 3134 (1977).
- ⁸J.-P. HANSEN and I. R. McDONALD, *Theory of Simple Liquids: With Applications to Soft Matter*, Academic Press, Amstersdam, 4th edition, 2013.
- ⁹V. BALLENEGGER and J. P. HANSEN, *Europhys. Lett.* **63**, 381 (2003).
- ¹⁰B. ROUX and T. SIMONSON, *Biophys. Chem.* **78**, 1 (1999).
- ¹¹T. SIMONSON and D. PERAHIA, *Proc. Natl. Acad. Sci. U.S.A.* **92**, 1082 (1995).
- ¹²T. SIMONSON and C. L. BROOKS, *J. Am. Chem. Soc.* **118**, 8452 (1996).
- ¹³V. BALLENEGGER and J. P. HANSEN, *J. Chem. Phys.* **122**, 114711 (2005).
- ¹⁴D. J. BONTHUIS, S. GEKLE, and R. R. NETZ, *Phys. Rev. Lett.* **107**, 1 (2011).

- ¹⁵A. GHOULI, A. SZYMZYK, R. RENOU, and M. DING, *Epl* **99**, 37008 (2012).
- ¹⁶H. ITOH and H. SAKUMA, *J. Chem. Phys.* **142**, 184703 (2015).
- ¹⁷C. SCHAAF and S. GEKLE, *Phys. Rev. E - Stat. Nonlinear, Soft Matter Phys.* **92**, 1 (2015).
- ¹⁸A. SCHLAICH, E. W. KNAPP, and R. R. NETZ, *Phys. Rev. Lett.* **117**, 1 (2016).
- ¹⁹J. F. OLIVIERI, J. T. HYNES, and D. LAAGE, *J. Phys. Chem. Lett.* **12**, 4319 (2021).
- ²⁰L. FUMAGALLI, A. ESFANDIAR, R. FABREGAS, S. HU, P. ARES, A. JANARDANAN, Q. YANG, B. RADHA, T. TANIGUCHI, K. WATANABE, G. GOMILA, K. S. NOVOSELOV, and A. K. GEIM, *Science* (80-.). **360**, 1339 (2018).
- ²¹C. ZHANG, F. GYGI, and G. GALLI, *J Phys Chem Lett* **4**, 2477 (2013).
- ²²C. ZHANG, *J Chem Phys* **148**, 156101 (2018).
- ²³M. MOTEVASELIAN and N. ALURU, *J Phys Chem Lett* **11**, 10532 (2020).
- ²⁴S. RUIZ-BARRAGAN, D. MUNOZ-SANTIBURCIO, S. KORNING, and D. MARX, *Phys Chem Chem Phys* **22**, 10833 (2020).
- ²⁵P. LOCHE, C. AYAZ, A. WOLDE-KIDAN, A. SCHLAICH, and R. R. NETZ, *J Phys Chem B* **124**, 4365 (2020).
- ²⁶M. H. MOTEVASELIAN and N. R. ALURU, *ACS Nano* **14**, 12761 (2020).
- ²⁷S. MONDAL and B. BAGCHI, *Nano Letters* **20**, 8959 (2020).
- ²⁸H. JALALI, H. GHORBANFEKR, I. HAMID, M. NEEK-AMAL, R. RASHIDI, and F. M. PEETERS, *Phys. Rev. E* **102**, 1 (2020).
- ²⁹I. HAMID, H. JALALI, , F. M. PEETERS, and M. NEEK-AMAL, *J. Chem. Phys.* **154**, 114503 (2021).
- ³⁰C. QI, Z. ZHU, C. WANG, and Y. ZHENG, *J Phys Chem Lett* **12**, 931 (2021).
- ³¹I. AHMADABADI, A. ESFANDIAR, A. HASSANALI, and M. R. EJTEHADI, *Phys Rev Mat* **5**, 024008 (2021).
- ³²F. DEISSENBECK and S. WIPPERMANN, *J Chem Theory Comput* (2023).
- ³³S. J. COX and P. L. GEISSLER, *Chem. Sci.* **13**, 9102 (2022).
- ³⁴G. MONET, H. BERTHOUMIEUX, F. BRESME, and A. KORNYSHEV, *Phys. Rev. Lett.* **126**, 216001 (2021).
- ³⁵J. NOJI, A. YOSHIMORI, J. OHNUKI, and M. TAKANO, *J Phys Soc Jpn* **9**, 114602 (2022).
- ³⁶R. EVANS, *Advances in Physics* **28**, 143 (1979).
- ³⁷R. EVANS, *Fundamentals of Inhomogeneous Fluids*, Marcel Dekker, Incorporated, 1992.
- ³⁸P. FRODL and S. DIETRICH, *Phys. Rev. A* **45**, 7330 (1992).
- ³⁹T. BIBEN, J. P. HANSEN, and Y. ROSENFELD, *Phys. Rev. E* **57**, R3727 (1998).
- ⁴⁰A. OLEKSY and J. P. HANSEN, *J. Chem. Phys.* **132**, 204702 (2010).
- ⁴¹J. WU and Z. LI, *Annual Review of Physical Chemistry* **58**, 85 (2007).
- ⁴²R. RAMIREZ, R. GEBAUER, M. MARESCHAL, and D. BORGIS, *Physical Review E* **66**, 031206 (2002).
- ⁴³R. RAMIREZ and D. BORGIS, *J. Phys. Chem. B* **109**, 6754 (2005).
- ⁴⁴G. JEANMAIRET, M. LEVESQUE, R. VUILLEUMIER, and D. BORGIS, *J. Phys. Chem. Lett.* **4**, 619 (2013).
- ⁴⁵G. JEANMAIRET, N. LEVY, M. LEVESQUE, and D. BORGIS, *J. Phys. Condens. Matter* **28**, 244005 (2016).
- ⁴⁶D. BORGIS, L. GENDRE, and R. RAMIREZ, *J. Phys. Chem. B* **116**, 2504 (2012).
- ⁴⁷L. DING, M. LEVESQUE, D. BORGIS, and L. BELLONI, *J. Chem. Phys.* **147**, 094107 (2017).
- ⁴⁸G. JEANMAIRET, B. ROTENBERG, D. BORGIS, and M. SALANNE, *J. Chem. Phys.* **151**, 124111 (2019).
- ⁴⁹D. BORGIS, S. LUUKKONEN, L. BELLONI, and G. JEANMAIRET, *J. Chem. Phys.* **155**, 024117 (2021).
- ⁵⁰E. L. POLLOCK and B. J. ALDER, *Phys. A Stat. Mech. its Appl.* **102**, 1 (1980).
- ⁵¹M. LEVESQUE, V. MARRY, B. ROTENBERG, G. JEANMAIRET, R. VUILLEUMIER, and D. BORGIS, *J. Chem. Phys.* **137**, 224107 (2012).
- ⁵²Y. ROSENFELD, *Phys. Rev. Lett.* **63**, 980 (1989).
- ⁵³R. ROTH, R. EVANS, A. LANG, and G. KAHL, *J. Phys. Condens. Matter* **14**, 12063 (2002).
- ⁵⁴R. ROTH, *J. Phys.: Condens. Matter* **22**, 063102 (2010).
- ⁵⁵E. KIERLIK and M. L. ROSINBERG, *Phys. Rev. A* **42**, 3382 (1990).
- ⁵⁶M. LEVESQUE, R. VUILLEUMIER, and D. BORGIS, *J. Chem. Phys.* **137**, 034115 (2012).
- ⁵⁷J. FU, Y. LIU, Y. TIAN, and J. WU, *J. Phys. Chem. C* **119**, 5374 (2015).
- ⁵⁸H. BERTHOUMIEUX, G. MONET, and R. BLOSSEY, *J. Chem. Phys.* **155**, 024112 (2021).
- ⁵⁹D. BORGIS, S. LUUKKONEN, L. BELLONI, and G. JEANMAIRET, *J. Phys. Chem. B* **124**, 6885 (2020).