

Domain Wall Dynamics in Notched Ferromagnetic Nanowires

Gilles Carbou

Université de Pau et des Pays de l'Adour
Laboratoire de Mathématiques et de leurs Applications,
UMR CNRS 5142

Joint works with David Sanchez (INSA-Toulouse) and Mouna Kassan (UPPA)

ANR MOSICOF

**Conference in honour of Prof. Frédéric Hélein
"Analyse des EDP, géométrie et physique"
5-9 june 2023 - Toulouse**

Plan

1 Physical Context

2 Ferromagnetic Nanowires

3 DW in infinite nanowire of constant cross-section



4 DW in infinite nanowire with one notch

- Without applied field
- Pinning and depinning
- After depinning

Ferromagnetic materials

Properties

- Spontaneous magnetization
- Magnetic field generated by the magnetization
- Formation of domains and domain walls



A. Aharoni, Introduction to the Theory of Ferromagnetism,
Oxford University Press, 1996

Industrial Applications

- Electromagnets
- Transformers
- Radar absorbing paints
- Mobile phones
- Modern Recording Devices

Magnetic Moment

- Volume occupied by the ferromagnetic material: $\Omega \subset \mathbb{R}^3$
- Magnetization described by the magnetic moment $m : \Omega_x \rightarrow \mathbb{R}^3$

$$|m(x)| = 1 \text{ p. p.}$$

- Constitutive Relation: $B = H + m$
- Static configurations: critical points of \mathcal{E} under the constraint $|m| = 1$

Micromagnetism energy

$$\mathcal{E}(m) = \frac{A}{2} \int_{\Omega} |\nabla m|^2 + \frac{1}{2} \int_{\mathbb{R}^3} |h_d(m)|^2 + \int_{\Omega} \Psi(m) - \int_{\Omega} m \cdot H_a$$

Magnetic Moment

- Volume occupied by the ferromagnetic material: $\Omega \subset \mathbb{R}^3$
- Magnetization described by the magnetic moment $m : \Omega_x \rightarrow \mathbb{R}^3$

$$|m(x)| = 1 \text{ p. p.}$$

- Constitutive Relation: $B = H + m$
- Static configurations: critical points of \mathcal{E} under the constraint $|m| = 1$

Micromagnetism energy

$$\mathcal{E}(m) = \frac{A}{2} \int_{\Omega} |\nabla m|^2 + \frac{1}{2} \int_{\mathbb{R}^3} |h_d(m)|^2 + \int_{\Omega} \Psi(m) - \int_{\Omega} m \cdot H_a$$

Magnetic Moment


- Volume occupied by the ferromagnetic material: $\Omega \subset \mathbb{R}^3$
- Magnetization described by the magnetic moment $m : \Omega_x \rightarrow \mathbb{R}^3$

$$|m(x)| = 1 \text{ p. p.}$$

- Constitutive Relation: $B = H + m$
- Static configurations: critical points of \mathcal{E} under the constraint $|m| = 1$

Micromagnetism energy

$$\mathcal{E}(m) = \frac{A}{2} \int_{\Omega} |\nabla m|^2 + \frac{1}{2} \int_{\mathbb{R}^3} |h_d(m)|^2 + \int_{\Omega} \Psi(m) - \int_{\Omega} m \cdot H_a$$



$$\operatorname{curl} h_d(m) = 0, \quad \operatorname{div} (h_d(m) + \bar{m}) = 0$$

Magnetic Moment

- Volume occupied by the ferromagnetic material: $\Omega \subset \mathbb{R}^3$
- Magnetization described by the magnetic moment $m : \Omega_x \rightarrow \mathbb{R}^3$

$$|m(x)| = 1 \text{ p. p.}$$

- Constitutive Relation: $B = H + m$
- Static configurations: critical points of \mathcal{E} under the constraint $|m| = 1$

Micromagnetism energy

$$\mathcal{E}(m) = \frac{A}{2} \int_{\Omega} |\nabla m|^2 + \frac{1}{2} \int_{\mathbb{R}^3} |h_d(m)|^2 + \int_{\Omega} \Psi(m) - \int_{\Omega} m \cdot H_a$$

Uniaxial Anisotropy: $\Psi(m) = -\frac{1}{2}(m \cdot \xi)^2$ or Planar Anisotropy: $\Psi(m) = +\frac{1}{2}(m \cdot \xi)^2$

Magnetic Moment

- Volume occupied by the ferromagnetic material: $\Omega \subset \mathbb{R}^3$
- Magnetization described by the magnetic moment $m : \Omega_x \rightarrow \mathbb{R}^3$

$$|m(x)| = 1 \text{ p. p.}$$

- Constitutive Relation: $B = H + m$
- Static configurations: critical points of \mathcal{E} under the constraint $|m| = 1$

Micromagnetism energy

$$\mathcal{E}(m) = \frac{A}{2} \int_{\Omega} |\nabla m|^2 + \frac{1}{2} \int_{\mathbb{R}^3} |h_d(m)|^2 + \int_{\Omega} \Psi(m) - \int_{\Omega} m \cdot H_a$$

Applied magnetic field: H_a

Magnetic Moment

- Magnetic domain : $\Omega \subset \mathbb{R}^3$
 - Magnetization described by the magnetic moment $m : \mathbb{R}_t^+ \times \Omega_x \rightarrow \mathbb{R}^3$
- $|m(t, x)| = 1 \text{ p. p.}$
- Constitutive Relation: $B = H + m$

Landau-Lifschitz Equation

$$\frac{\partial m}{\partial t} = -m \times \mathcal{H} - m \times (m \times \mathcal{H}), \quad \mathcal{H} = -\partial_m \mathcal{E}(m) = A\Delta m + h_d(m) + \nabla\Psi(m) + H_a$$

$$m(0, \cdot) = m_0 \text{ on } \Omega, \quad \frac{\partial m}{\partial n} = 0 \text{ on } \mathbb{R}^+ \times \partial\Omega,$$

$$\mathcal{E}(m) = \frac{A}{2} \int_{\Omega} |\nabla m|^2 + \frac{1}{2} \int_{\mathbb{R}^3} |h_d(m)|^2 + \int_{\Omega} \Psi(m) - \int_{\Omega} m \cdot H_a$$

$$\mathcal{E}(m(t, \cdot)) + \int_0^t \left\| \frac{\partial m}{\partial t}(s, \cdot) \right\|_{L^2}^2 ds = \mathcal{E}(m_0)$$

Magnetic Moment

- Magnetic domain : $\Omega \subset \mathbb{R}^3$
 - Magnetization described by the magnetic moment $m : \mathbb{R}_t^+ \times \Omega_x \rightarrow \mathbb{R}^3$
- $|m(t, x)| = 1$ p. p.
- Constitutive Relation: $B = H + m$

Landau-Lifschitz-Gilberg Equation

$$\frac{\partial m}{\partial t} - m \times \frac{\partial m}{\partial t} = -2m \times \mathcal{H} \quad m \times \Delta m = \sum_i \partial_{x_i} (m \times \partial_{x_i} m)$$

$$\mathcal{H} = -\partial_m \mathcal{E}(m) = A \Delta m + h_d(m) + \psi(m) + H_a$$

$$\mathcal{E}(m) = \frac{A}{2} \int_{\Omega} |\nabla m|^2 + \frac{1}{2} \int_{\mathbb{R}^3} |h_d(m)|^2 + \int_{\Omega} \Psi(m) - \int_{\Omega} m \cdot H_a$$

$$\mathcal{E}(m(t, \cdot)) + \int_0^t \left\| \frac{\partial m}{\partial t}(s, \cdot) \right\|_{L^2}^2 ds = \mathcal{E}(m_0)$$

References: Static Case


$$\mathcal{E}(m) = \frac{A}{2} \int_{\Omega} |\nabla m|^2 + \frac{1}{2} \int_{\mathbb{R}^3} |h_d(m)|^2 + \int_{\Omega} \Psi(m) - \int_{\Omega} m \cdot H_a$$

Visintin (1985); C. (1997); Hardt, Kinderlherer (2000)

Desimone, Kohn, Müller, Otto (2002)

Rivi  re, Serfaty (2001)

Ignat, Moser (2022)



A. Aharoni, Introduction to the Theory of Ferromagnetism, Oxford University Press, 1996

References: Landau-Lifschitz equation

$$\frac{\partial m}{\partial t} = -m \times \mathcal{H} - m \times (m \times \mathcal{H})$$

$$\mathcal{H} = -\partial_m \mathcal{E}(m) = A \Delta m + h_d(m) + \nabla \Psi(m) + H_a$$

Existence Results

- Joly, Métivier, Rauch (LL-Maxwell without exchange field)
- Visintin; Alouges, Soyeur; C., Fabrie; Ding, Guo (Global in time weak solutions)
- C., Fabrie, Guès (Local in time strong solutions)

Numerical Simulations

- Joly, Haddar (without exchange field)
- Labbé; Garcia-Cervera; Alouges; Bartels, Pröhl; Praetorius;... (with exchange field)

Plan

1 Physical Context


2 Ferromagnetic Nanowires

3 DW in infinite nanowire of constant cross-section

4 DW in infinite nanowire with one notch

- Without applied field
- Pinning and depinning
- After depinning

Data storage in ferromagnetic nanowires



S. Parkin, M. Hayashi, L. Thomas, *Magnetic Domain-Wall Racetrack Memory*, Science 320 (2008)


Stuart S. P. Parkin, Masamitsu Hayashi, Luc Thomas, *Magnetic Domain-Wall Racetrack Memory*, Science 320 (2008)

- 3d devices for the storage of numerical data
- Fast access

- Bits encoded by the sense of the magnetization
- Stabilization of walls positions by notches



G. Hrkac, J. Dean and D. A. Allwood, *Nanowire spintronics for storage class memories and logic*, Phil. Trans. R. Soc. A (2011)
369



Data Storage in Ferromagnetic nanowires: **key points**

For data storage:

- DW are pinned by the notches (reliability of the storage)
- DW depinning by magnetic field: data recording
- DW depinning by application of an electric current: data reading

Goals

- Obtention and justification of equivalent simpler 1d-models for nanowires
- Description of walls configurations and walls dynamics
- Effects of notches on walls stability
- DW depinning

Data Storage in Ferromagnetic nanowires: **key points**


For data storage:

- DW are pinned by the notches (reliability of the storage)
- DW depinning by magnetic field: data recording
- DW depinning by application of an electric current: data reading

Goals

- Obtention and justification of equivalent simpler 1d-models for nanowires
- Description of walls configurations and walls dynamics
- Effects of notches on walls stability
- DW depinning

1d-model of wire



$$\Omega_\eta = \{(x_1, x_2, x_3), x_1 \in \mathbb{I}, (x_2)^2 + (x_3)^2 < \eta^2(\rho(x_1))^2\}$$

Radius of the cross section: ρ

- $\rho : \mathbb{I} \rightarrow \mathbb{R}^{*+}, \mathcal{C}^\infty,$
- $0 < \rho_{min} \leq \rho(x_1) \leq 1$
- $\mathbf{s}(x_1) = \pi(\rho(x_1))^2$


Weak Formulation:

$$\int_{[0,T] \times \Omega_\eta} \left(\frac{\partial m}{\partial t} - m \times \frac{\partial m}{\partial t} \right) \chi = 2 \int_{[0,T] \times \Omega_\eta} \sum_{i=1}^3 m \times \frac{\partial m}{\partial x_i} \cdot \frac{\partial \chi}{\partial x_i}$$

$$- 2 \int_{[0,T] \times \Omega_\eta} m \times H_d(m) \cdot \chi.$$

- rescaling: fix domain $\Omega_1 = \{(x_1, \tilde{x}_2, \tilde{x}_3), x \in \mathbb{I}, (\tilde{x}_2)^2 + (\tilde{x}_3)^2 < (\rho(x_1))^2\}$
- $\eta \rightarrow 0$ in the weak formulation with $\chi(t, x_1, \tilde{x}_2, \tilde{x}_3) = \varphi(t, x_1)$

1d-model of wire



$$\Omega_\eta = \{(x_1, x_2, x_3), x_1 \in \mathbb{I}, (x_2)^2 + (x_3)^2 < \eta^2(\rho(x_1))^2\}$$

Radius of the cross section: ρ


- $\rho : \mathbb{I} \rightarrow \mathbb{R}^{*+}, \mathcal{C}^\infty,$
- $0 < \rho_{min} \leq \rho(x_1) \leq 1$
- $\mathbf{s}(x_1) = \pi(\rho(x_1))^2$

Weak Formulation:

$$\int_{[0, T] \times \Omega_\eta} \left(\frac{\partial m}{\partial t} - m \times \frac{\partial m}{\partial t} \right) \chi = 2 \int_{[0, T] \times \Omega_\eta} \sum_{i=1}^3 m \times \frac{\partial m}{\partial x_i} \cdot \frac{\partial \chi}{\partial x_i}$$
$$- 2 \int_{[0, T] \times \Omega_\eta} m \times H_d(m) \cdot \chi.$$

- rescaling: fix domain $\Omega_1 = \{(x_1, \tilde{x}_2, \tilde{x}_3), x \in \mathbb{I}, (\tilde{x}_2)^2 + (\tilde{x}_3)^2 < (\rho(x_1))^2\}$
- $\eta \rightarrow 0$ in the weak formulation with $\chi(t, x_1, \tilde{x}_2, \tilde{x}_3) = \varphi(t, x_1)$

1d-model of wire



$$\Omega_\eta = \{(x_1, x_2, x_3), x_1 \in I, (x_2)^2 + (x_3)^2 < \eta^2(\rho(x_1))^2\}$$

Radius of the cross section: ρ

- $\rho : I \rightarrow \mathbb{R}^{*+}, C^\infty,$
- $0 < \rho_{min} \leq \rho(x_1) \leq 1$
- $\mathbf{s}(x_1) = \pi(\rho(x_1))^2$


$$m : \mathbb{R}_t^+ \times I_x \rightarrow S^2, \quad m \text{ is constant in the cross-section}$$

$$\int_{[0, T] \times I} \mathbf{s}(x) \left(\frac{\partial m}{\partial t} - m \times \frac{\partial m}{\partial t} \right) \varphi = 2 \int_{[0, T] \times I} \mathbf{s}(x) m \times \frac{\partial m}{\partial x} \cdot \frac{\partial \varphi}{\partial x}$$
$$- 2 \int_{[0, T] \times \Omega_\eta} \mathbf{s}(x) m \times (m_2 \mathbf{e}_2 + m_3 \mathbf{e}_3) \cdot \varphi.$$

$$\mathbf{s}(x) \frac{\partial m}{\partial t} = -m \times H_{eff} - m \times (m \times H_{eff})$$

$$H_{eff} = \partial_x (\mathbf{s}(x) \partial_x m) - \mathbf{s}(x) (m_2 \vec{\mathbf{e}}_2 + m_3 \vec{\mathbf{e}}_3)$$

1d-model of wire



$$\Omega_\eta = \{(x_1, x_2, x_3), x_1 \in I, (x_2)^2 + (x_3)^2 < \eta^2(\rho(x_1))^2\}$$

Radius of the cross section: ρ

- $\rho : I \rightarrow \mathbb{R}^{*+}, C^\infty,$
- $0 < \rho_{min} \leq \rho(x_1) \leq 1$
- $\mathbf{s}(x_1) = \pi(\rho(x_1))^2$

Model of ferromagnetic nanowire

$$\frac{\partial m}{\partial t} = -m \times \mathcal{H}_{eff} - m \times (m \times \mathcal{H}_{eff})$$

$$\mathcal{H}_{eff} = \partial_{xx} m + \frac{\mathbf{s}'}{\mathbf{s}} \partial_x \mathbf{m} - (m_2 \vec{e}_2 + m_3 \vec{e}_3)$$

1d Ferromagnetism Energy

$$E(m) = \frac{1}{2} \int_I \mathbf{s}(x) |\partial_x m|^2 dx + \frac{1}{2} \int_I \mathbf{s}(x) (|m_2|^2 + |m_3|^2) dx$$

Plan

1 Physical Context

2 Ferromagnetic Nanowires

3 DW in infinite nanowire of constant cross-section

4 DW in infinite nanowire with one notch

- Without applied field
- Pinning and depinning
- After depinning

Infinite nanowire of constant cross-section

$$m : \mathbb{R}_t^+ \times \mathbb{R}_x \rightarrow S^2, \mathbf{s} \equiv \pi$$

$$\frac{\partial m}{\partial t} = -m \times H_{\text{eff}} - m \times (m \times H_{\text{eff}})$$

$$H_{\text{eff}} = m_{xx} - (m_2 \vec{e}_2 + m_3 \vec{e}_3)$$

- φ is constant
- $\theta'' + \cos \theta \sin \theta = 0$
- $\theta \rightarrow \pm \pi/2$ when $x \rightarrow \pm \infty$

Static Solutions: Walls

$$\bullet M(x) = R_{\varphi(x)} \begin{pmatrix} \sin \theta(x) \\ \cos \theta(x) \\ 0 \end{pmatrix} = R_{\varphi} \begin{pmatrix} \tanh x \\ \frac{1}{\cosh x} \\ 0 \end{pmatrix}.$$

$$R_{\varphi} = \begin{pmatrix} 1 & 0 & 0 \\ 0 & \cos \varphi & -\sin \varphi \\ 0 & \sin \varphi & \cos \varphi \end{pmatrix}$$

$$\bullet \theta \rightarrow \pm \pi/2 \text{ when } x \rightarrow \pm \infty$$

Exact Static Solutions


Infinite nanowire of constant cross-section

$$m : \mathbb{R}_t^+ \times \mathbb{R}_x \rightarrow S^2, \mathbf{s} \equiv \pi$$

$$\frac{\partial m}{\partial t} = -m \times H_{\text{eff}} - m \times (m \times H_{\text{eff}})$$

$$H_{\text{eff}} = m_{xx} - (m_2 \vec{e}_2 + m_3 \vec{e}_3)$$

- φ is constant
- $\theta'' + \cos \theta \sin \theta = 0$
- $\theta \rightarrow \pm \pi/2$ when $x \rightarrow \pm \infty$



Static Solutions: Walls

$$\bullet M(x) = R_{\varphi(x)} \begin{pmatrix} \sin \theta(x) \\ \cos \theta(x) \\ 0 \end{pmatrix} = R_{\varphi} \begin{pmatrix} \tanh x \\ \frac{1}{\cosh x} \\ 0 \end{pmatrix}.$$

$$R_{\varphi} = \begin{pmatrix} 1 & 0 & 0 \\ 0 & \cos \varphi & -\sin \varphi \\ 0 & \sin \varphi & \cos \varphi \end{pmatrix}$$

- $\theta \rightarrow \pm \pi/2$ when $x \rightarrow \pm \infty$



Exact Static Solutions

Infinite nanowire of constant cross-section

$$m : \mathbb{R}_t^+ \times \mathbb{R}_x \rightarrow S^2, \mathbf{s} \equiv \pi$$

$$\frac{\partial m}{\partial t} = -m \times H_{\text{eff}} - m \times (m \times H_{\text{eff}})$$

$$H_{\text{eff}} = m_{xx} - (m_2 \vec{e}_2 + m_3 \vec{e}_3)$$

- φ is constant
- $\theta'' + \cos \theta \sin \theta = 0$
- $\theta \rightarrow \pm \pi/2$ when $x \rightarrow \pm \infty$

Static Solutions: Walls

$$\bullet M(x) = R_{\varphi(x)} \begin{pmatrix} \sin \theta(x) \\ \cos \theta(x) \\ 0 \end{pmatrix} = R_{\varphi} \begin{pmatrix} \tanh x \\ \frac{1}{\cosh x} \\ 0 \end{pmatrix}.$$

$$R_{\varphi} = \begin{pmatrix} 1 & 0 & 0 \\ 0 & \cos \varphi & -\sin \varphi \\ 0 & \sin \varphi & \cos \varphi \end{pmatrix}$$

$$\bullet \theta \rightarrow \pm \pi/2 \text{ when } x \rightarrow \pm \infty$$

Stability for Static Profiles

G.C. S. Labb   (2006):

Stability of the constant profiles but not asymptotic stability

$$m(t, x) \rightarrow R_{\varphi_\infty} M_0(x - \sigma_\infty) \text{ when } t \rightarrow \infty$$

Infinite nanowire of constant cross-section

$$m : \mathbb{R}_t^+ \times \mathbb{R}_x \rightarrow S^2$$

$$\frac{\partial m}{\partial t} = -m \times H_{\text{eff}} - m \times (m \times H_{\text{eff}})$$

$$H_{\text{eff}} = m_{xx} - (m_2 \vec{e}_2 + m_3 \vec{e}_3) + h_a \vec{e}_1$$

Moving DW

$$M_0(x) = \begin{pmatrix} \tanh x \\ 1/\cosh x \\ 0 \end{pmatrix}$$

$$R_\varphi = \begin{pmatrix} 1 & 0 & 0 \\ 0 & \cos \varphi & -\sin \varphi \\ 0 & \sin \varphi & \cos \varphi \end{pmatrix}$$

$$m(t, x) = R_{h_a t} (M_0(x + h_a t))$$

Stability results

Moving DW with constant small applied field: K. Takasao (2011)

Stability threshold for constant applied field: R. Jizzini (2011)

Controlability results: G.C., S. Labbé, E. Trélat (2008); Y. Privat, E. Trélat (2015).

Non constant applied field: R. Côte, R. Ignat

Infinite nanowire of constant cross-section

$$m : \mathbb{R}_t^+ \times \mathbb{R}_x \rightarrow S^2$$

$$\frac{\partial m}{\partial t} = -m \times H_{\text{eff}} - m \times (m \times H_{\text{eff}})$$

$$H_{\text{eff}} = m_{xx} - (m_2 \vec{e}_2 + m_3 \vec{e}_3) + h_a \vec{e}_1$$

Moving DW

$$M_0(x) = \begin{pmatrix} \tanh x \\ 1/\cosh x \\ 0 \end{pmatrix}$$

$$R_\varphi = \begin{pmatrix} 1 & 0 & 0 \\ 0 & \cos \varphi & -\sin \varphi \\ 0 & \sin \varphi & \cos \varphi \end{pmatrix}$$

$$m(t, x) = R_{h_a t} (M_0(x + h_a t))$$

Stability results

Moving DW with constant small applied field: K. Takasao (2011)

Stability threshold for constant applied field: R. Jizzini (2011)

Controllability results: G.C., S. Labbé, E. Trélat (2008); Y. Privat, E. Trélat (2015).

Non constant applied field: R. Côte, R. Ignat

Plan

1

Physical Context

2

Ferromagnetic Nanowires

3


DW in infinite nanowire of constant cross-section

4

DW in infinite nanowire with one notch

- Without applied field
- Pinning and depinning
- After depinning

Model of infinite wire with one notch



$$\Omega_\eta = \{(x, y, z), x \in \mathbb{R}, y^2 + z^2 < \eta^2(\rho(x))^2\}$$

Radius of the section: ρ


- $\rho : \mathbb{R} \rightarrow \mathbb{R}^+, \mathcal{C}^\infty,$
- $\rho = 1$ outside $[-a, a],$
- $\rho(-x) = \rho(x),$
- ρ non decreasing on $[0, a]$
- $\mathbf{s}(x) = \pi(\rho(x))^2$

Model of infinite wire with notch

$$m : \mathbb{R}_t^+ \times \mathbb{R}_x \rightarrow S^2$$

$$\frac{\partial m}{\partial t} = -m \times \mathcal{H}_{\text{eff}} - m \times (m \times \mathcal{H}_{\text{eff}})$$

$$\mathcal{H}_{\text{eff}} = \partial_{xx} m + \frac{\mathbf{s}'}{\mathbf{s}} \partial_x \mathbf{m} - (m_2 \vec{e}_2 + m_3 \vec{e}_3) + h_a \vec{e}_1$$



Area of the cross
section: $\mathbf{s}(x)$

Plan

1 Physical Context

2 Ferromagnetic Nanowires

3 DW in infinite nanowire of constant cross-section

4 DW in infinite nanowire with one notch

- Without applied field
- Pinning and depinning
- After depinning



Existence of profiles

- $M(x) = R_{\varphi(x)} \begin{pmatrix} \sin \bar{\theta}(x) \\ \cos \bar{\theta}(x) \\ 0 \end{pmatrix}$
- $R_{\varphi} = \begin{pmatrix} 1 & 0 & 0 \\ 0 & \cos \varphi & -\sin \varphi \\ 0 & \sin \varphi & \cos \varphi \end{pmatrix}$
- $\bar{\theta} \rightarrow \pm\pi/2$ when $x \rightarrow \pm\infty$

• φ is constant

$$\bullet \bar{\theta}'' + \frac{\mathbf{s}'}{\mathbf{s}} \partial_x \bar{\theta} + \cos \bar{\theta} \sin \bar{\theta} = 0$$

$$\bullet ((\bar{\theta}')^2 - \cos^2 \bar{\theta})' = -2 \frac{\mathbf{s}'}{\mathbf{s}} (\bar{\theta}')^2$$



Shooting method to reach the separatrix after the notch



Existence of profiles

- $M(x) = R_{\varphi(x)} \begin{pmatrix} \sin \bar{\theta}(x) \\ \cos \bar{\theta}(x) \\ 0 \end{pmatrix}$
- $R_{\varphi} = \begin{pmatrix} 1 & 0 & 0 \\ 0 & \cos \varphi & -\sin \varphi \\ 0 & \sin \varphi & \cos \varphi \end{pmatrix}$
- $\bar{\theta} \rightarrow \pm\pi/2$ when $x \rightarrow \pm\infty$

• φ is constant

$$\bullet \bar{\theta}'' + \frac{\mathbf{s}'}{\mathbf{s}} \partial_x \bar{\theta} + \cos \bar{\theta} \sin \bar{\theta} = 0$$

$$\bullet ((\bar{\theta}')^2 - \cos^2 \bar{\theta})' = -2 \frac{\mathbf{s}'}{\mathbf{s}} (\bar{\theta}')^2$$



Shooting method to reach the separatrix after the notch

Infinite Nanowire with one notch

$$m : \mathbb{R}_t^+ \times \mathbb{R}_x \rightarrow S^2$$

$$\frac{\partial m}{\partial t} = -m \times H_{\text{eff}} - m \times (m \times H_{\text{eff}})$$

$$H_{\text{eff}} = m_{xx} + \frac{\mathbf{s}'}{\mathbf{s}} m_x - m_2 \vec{e}_2 - m_3 \vec{e}_3$$

$m \rightarrow \pm e_1$ when $x \rightarrow \pm \infty$

Wall Profile

$$M_0(x) = \begin{pmatrix} \sin \bar{\theta}(x) \\ \cos \bar{\theta}(x) \\ 0 \end{pmatrix}$$

$$\bar{\theta}'' + \frac{\mathbf{s}'}{\mathbf{s}} \bar{\theta}' + \cos \bar{\theta} \sin \bar{\theta} = 0$$

BC : $\bar{\theta} \rightarrow \pm \pi/2$ when $x \rightarrow \pm \infty$

Thm 1 (with D. Sanchez)

Existence and stability of M_0 , asymptotic stability for the position of the wall

If $\|m(t=0) - M_0\|_{H^1(\mathbb{R})}$ is small, then

- for all time, $\|m(t) - M_0\|_{H^1(\mathbb{R})}$ remains small,
- $m(t)$ tends to $R_{\theta_\infty}(M_0)$ when t tends to $+\infty$.

Mobile frame

Geometrical constraint $|m| = 1$

We describe the perturbations in the mobile frame

$$m(t, x) = \sqrt{1 - |r(t, x)|^2} M_0(x) + r_1(t, x) M_1(x) + r_2(t, x) M_2$$

$$M_0(x) = \begin{pmatrix} \sin \bar{\theta}(x) \\ \cos \bar{\theta}(x) \\ 0 \end{pmatrix} \quad M_1(x) = \begin{pmatrix} -\cos \bar{\theta}(x) \\ \sin \bar{\theta}(x) \\ 0 \end{pmatrix} \quad M_2 = \begin{pmatrix} 0 \\ 0 \\ 1 \end{pmatrix}$$

New Equations for r

$$r : \mathbb{R}_t^+ \times \mathbb{R}_x \rightarrow \mathbb{R}^2$$

$$\partial_t r_1 = -L_1(r_1) - L_2(r_2) + \text{non linear}$$

$$\partial_t r_2 = -L_1(r_1) - L_2(r_2) + \text{non linear}$$

$$L_1(r) = -\partial_{xx} r - \frac{\mathbf{s}'}{\mathbf{s}} \partial_x r + (\sin^2 \bar{\theta} - \cos^2 \bar{\theta}) r$$

$$L_2(r) = -\partial_{xx} r - \frac{\mathbf{s}'}{\mathbf{s}} \partial_x r + (\sin^2 \bar{\theta} - (\bar{\theta}')^2) r$$

Exact Solution

M_0 for $LL \sim 0$ for the new system

Stability of 0 ?

Mobile frame

Geometrical constraint $|m| = 1$

We describe the perturbations in the mobile frame

$$m(t, x) = \sqrt{1 - |r(t, x)|^2} M_0(x) + r_1(t, x) M_1(x) + r_2(t, x) M_2$$

$$M_0(x) = \begin{pmatrix} \sin \bar{\theta}(x) \\ \cos \bar{\theta}(x) \\ 0 \end{pmatrix} \quad M_1(x) = \begin{pmatrix} -\cos \bar{\theta}(x) \\ \sin \bar{\theta}(x) \\ 0 \end{pmatrix} \quad M_2 = \begin{pmatrix} 0 \\ 0 \\ 1 \end{pmatrix}$$

New Equations for r

$$r : \mathbb{R}_t^+ \times \mathbb{R}_x \rightarrow \mathbb{R}^2$$

$$\partial_t r_1 = -L_1(r_1) - L_2(r_2) + \text{non linear}$$

$$\partial_t r_2 = L_1(r_1) - L_2(r_2) + \text{non linear}$$

$$L_1(r) = -\partial_{xx} r - \frac{\mathbf{s}'}{\mathbf{s}} \partial_x r + (\sin^2 \bar{\theta} - \cos^2 \bar{\theta}) r$$

$$L_2(r) = -\partial_{xx} r - \frac{\mathbf{s}'}{\mathbf{s}} \partial_x r + (\sin^2 \bar{\theta} - (\bar{\theta}')^2) r$$

Exact Solution

M_0 for $LL \sim 0$ for the new system

Stability of 0 ?

Properties of the linearized: L_2

On $L^2(\mathbb{R})$, weighted scalar product:

$$\langle u | v \rangle_{\mathbf{s}} = \int_{\mathbb{R}} \mathbf{s}(x) u(x) v(x) dx,$$

$$L_2 = -\frac{1}{\mathbf{s}} \partial_x (\mathbf{s} \partial_x) + (\sin^2 \bar{\theta} - (\bar{\theta}')^2) \implies L_2 \text{ is self-adjoint for } \langle | \rangle_{\mathbf{s}}.$$


$$\langle L_2 u | v \rangle_{\mathbf{s}} = \langle \ell u | \ell v \rangle_{\mathbf{s}}, \quad \text{with } \ell = \partial_x + \bar{\theta}' \tan \bar{\theta}$$

$$L_2 \geq 0, \quad \text{Ker } L_2 = \mathbb{R}(\cos \bar{\theta})$$

- Valid whatever the configurations of the wire (several pinched zones)
- for one wall, on $(\cos \bar{\theta})^\perp$, $L_2 \geq \alpha_2 > 0$
- **Invariance by rotation** $\implies 0$ is an eigenvalue of the linearized

Properties of the linearized: L_1

$$L_1 = L_2 + (\bar{\theta}')^2 - \cos^2 \bar{\theta}$$




Key point : $L_1 \geq 0$?

Infinite nanowire without pinching: $L_1 = L_2$, $L_1 \geq 0$. **Stability**

Properties of the linearized: L_1

$$L_1 = L_2 + (\bar{\theta}')^2 - \cos^2 \bar{\theta}$$



$$(\bar{\theta}')^2 - \cos^2 \bar{\theta} > 0 \text{ on } \text{Ker } L_2 \implies L_1 > 0$$

Plan

1

Physical Context

2

Ferromagnetic Nanowires

3

DW in infinite nanowire of constant cross-section

4

DW in infinite nanowire with one notch


- Without applied field
- **Pinning and depinning**
- After depinning

Notched Nanowire

$$m : \mathbb{R}_t^+ \times \mathbb{R}_x \rightarrow S^2$$

$$\frac{\partial m}{\partial t} = -m \times H_{\text{eff}} - m \times (m \times H_{\text{eff}})$$

$$\mathcal{H}_{\text{eff}} = m_{xx} + \frac{\mathbf{s}'}{\mathbf{s}} m_x - m_2 \vec{e}_2 - m_3 \vec{e}_3 + h_a \vec{e}_1$$



Area of the cross section: $\mathbf{s}(x)$

Constant-cross-section wire: precessional regime

$$m(t, x) = R_{+h_a t} M_0(x + h_a t)$$


Small applied field

Notched Nanowire

$$m : \mathbb{R}_t^+ \times \mathbb{R}_x \rightarrow S^2$$

$$\frac{\partial m}{\partial t} = -m \times H_{\text{eff}} - m \times (m \times H_{\text{eff}})$$

$$\mathcal{H}_{\text{eff}} = m_{xx} + \frac{\mathbf{s}'}{\mathbf{s}} m_x - m_2 \vec{e}_2 - m_3 \vec{e}_3 + h_a \vec{e}_1$$



Area of the cross section: $\mathbf{s}(x)$

Notched wire:

Thm 2, with D. Sanchez

Pinning effects: for small h_a : the wall remains in the notch (static solution), its profile is planar.

Depinning: for $|h_a| \geq \frac{\pi - \mathbf{s}(0)}{\pi + \mathbf{s}(0)}$, there is no static solution with one DW


Pinning and depinning

Notched Nanowire

$$m : \mathbb{R}_t^+ \times \mathbb{R}_x \rightarrow S^2$$

$$\frac{\partial m}{\partial t} = -m \times H_{\text{eff}} - m \times (m \times H_{\text{eff}})$$

$$\mathcal{H}_{\text{eff}} = m_{xx} + \frac{\mathbf{s}'}{\mathbf{s}} m_x - m_2 \vec{e}_2 - m_3 \vec{e}_3 + h_a \vec{e}_1$$




Area of the cross section: $\mathbf{s}(x)$


$$\theta'' + \frac{\mathbf{s}'}{\mathbf{s}} \theta' + \cos \theta \sin \theta + h_a \cos \theta = 0$$

Left side: $(\theta')^2 = -\sin^2 \theta - 2h_a \sin \theta + 1 - 2h_a$,


Right side: $(\theta')^2 = -\sin^2 \theta - 2h_a \sin \theta + 1 + 2h_a$



$$h_a = 0.2$$



$$h_a = 0.2$$



$$h_a = 0.5$$

Plan

1 Physical Context

2 Ferromagnetic Nanowires

3 DW in infinite nanowire of constant cross-section


4 DW in infinite nanowire with one notch

- Without applied field
- Pinning and depinning
- After depinning

$$m : \mathbb{R}_t^+ \times \mathbb{R}_x \rightarrow S^2$$

$$\frac{\partial m}{\partial t} = -m \times H_{\text{eff}} - m \times (m \times H_{\text{eff}})$$

$$\mathcal{H}_{\text{eff}} = m_{xx} + \frac{\mathbf{s}'}{\mathbf{s}} m_x - m_2 \vec{e}_2 - m_3 \vec{e}_3 - h_a \vec{e}_1$$



Area of the cross section: $\mathbf{s}(x)$

Solution without notch:

$$\mathcal{M}_{\sigma_0}(t, x) = R_{-H(t)} M_0(x - \sigma_0 - H(t)), \quad H(t) = \int_0^t h_a(s) ds.$$

Thm 3 (with M. Kassan)

There exists $0 < h^- < h^+$ such that if $h_a \in C^0(\mathbb{R}^+)$ with $\forall t, 0 < h^- \leq h(t) \leq h^+$, then for all $\varepsilon > 0$, there exists σ^* and $\eta > 0$ such that:

for all $\sigma_0 \geq \sigma^*$, for all m , solution of LL, with $\|m(0, \cdot) - \mathcal{M}_{\sigma_0}(0, \cdot)\|_{H^1} \leq \eta$,

$$\forall t > 0, \|m(t, \cdot) - \mathcal{M}_{\sigma_0}(t, \cdot)\|_{H^1} \leq \varepsilon,$$

$$\exists \varphi_\infty, \exists \sigma_\infty, \|m(t, \cdot) - R_{\varphi_\infty} \mathcal{M}_{\sigma_0}(t, \cdot + \sigma_\infty)\|_{H^1} \rightarrow 0$$

First step: mobile frame

$$\mathcal{M}_{\sigma_0}(t, x) = R_{-H(t)} M_0(x - \sigma_0 - H(t)), \quad H(t) = \int_0^t h_a(s) ds.$$

We rewrite m as:

$$m(t, x) = R_{-H(t)} M(t, x - \sigma_0 - H(t)), \quad H(t) = \int_0^t h_a(s) ds.$$

$m(t, x)$ close to $\mathcal{M}_{\sigma_0}(t, x) \iff M(t, \tilde{x})$ close to $M_0(\tilde{x})$, with $\tilde{x} = x - \sigma_0 - H(t)$

Equation for M

$$\partial_t M = -M \times \tilde{H}_{\text{eff}}(M) - M \times (M \times \tilde{H}_{\text{eff}}(M)) + h_a(t)(\partial_x M + M \times (M \times \vec{e}_1)),$$

$$\tilde{H}_{\text{eff}}(M) = \partial_{xx} M + \frac{\mathbf{s}'}{\mathbf{s}}(x + \sigma_0 + H(t))\partial_x M + (M \cdot \vec{e}_1)\vec{e}_1.$$

$$M : \mathbb{R} \times \mathbb{R} \longrightarrow S^2$$

Mobile frame and new unknown

$$M(t, \tilde{x}) = r_1(t, \tilde{x})M_1(\tilde{x}) + r_2(t, \tilde{x})M_2 + \sqrt{1 - |r|^2}M_0(\tilde{x})$$

$$M_0 = \begin{pmatrix} \tanh \tilde{x} \\ \frac{1}{\cosh \tilde{x}} \\ 0 \end{pmatrix}, \quad M_1 = \begin{pmatrix} -\frac{1}{\cosh \tilde{x}} \\ \tanh \tilde{x} \\ 0 \end{pmatrix}, \quad M_2 = \begin{pmatrix} 0 \\ 0 \\ 1 \end{pmatrix}$$

First step: mobile frame

$m(t, x)$ close to $\mathcal{M}_{\sigma_0}(t, x) \iff M(t, \tilde{x})$ close to $M_0(\tilde{x})$, with $\tilde{x} = x - \sigma_0 - H(t)$

Equation for M

$$\partial_t M = -M \times \tilde{H}_{\text{eff}}(M) - M \times (M \times \tilde{H}_{\text{eff}}(M)) + h_a(t)(\partial_x M + M \times (M \times \vec{e}_1)),$$

$$\tilde{H}_{\text{eff}}(M) = \partial_{xx} M + \frac{\mathbf{s}'}{\mathbf{s}}(x + \sigma_0 + H(t))\partial_x M + (M \cdot \vec{e}_1)\vec{e}_1.$$

$$M : \mathbb{R} \times \mathbb{R} \longrightarrow S^2$$

Mobile frame and new unknown

$$M(t, \tilde{x}) = r_1(t, \tilde{x})M_1(\tilde{x}) + r_2(t, \tilde{x})M_2 + \sqrt{1 - |r|^2}M_0(\tilde{x})$$

$$M_0 = \begin{pmatrix} \tanh \tilde{x} \\ \frac{1}{\cosh \tilde{x}} \\ 0 \end{pmatrix}, \quad M_1 = \begin{pmatrix} -\frac{1}{\cosh \tilde{x}} \\ \tanh \tilde{x} \\ 0 \end{pmatrix}, \quad M_2 = \begin{pmatrix} 0 \\ 0 \\ 1 \end{pmatrix}$$

$M(t, \cdot)$ close to $M_0 \iff r$ close to 0

Equation in r

$$\partial_t r = \mathcal{V}_{\sigma_0}(t, x) + (J\mathcal{L} + h_a(t)\ell)r + \text{non linear terms}$$

First step: mobile frame

Mobile frame and new unknown

$$M(t, \tilde{x}) = r_1(t, \tilde{x})M_1(\tilde{x}) + r_2(t, \tilde{x})M_2 + \sqrt{1 - |r|^2}M_0(\tilde{x})$$

$$M_0 = \begin{pmatrix} \tanh \tilde{x} \\ \frac{1}{\cosh \tilde{x}} \\ 0 \end{pmatrix}, \quad M_1 = \begin{pmatrix} -\frac{1}{\cosh \tilde{x}} \\ \tanh \tilde{x} \\ 0 \end{pmatrix}, \quad M_2 = \begin{pmatrix} 0 \\ 0 \\ 1 \end{pmatrix}$$

$M(t, \cdot)$ close to $M_0 \iff r$ close to 0

Equation in r

$$\partial_t r = \mathcal{V}_{\sigma_0}(t, x) + (J\mathcal{L} + h_a(t)\ell)r + \text{non linear terms}$$

$$\mathcal{V}(t, x) = \frac{1}{\cosh x} \frac{\mathbf{s}'}{\mathbf{s}} (x + \sigma_0 + H(t)) \vec{e}_1, \quad |\mathcal{V}(t, x)| \leq K e^{-\gamma(\sigma_0 + H(t))},$$

$$J = \begin{pmatrix} -1 & -1 \\ 1 & -1 \end{pmatrix},$$

$$\mathcal{L}r = -\partial_{xx}r - \frac{\mathbf{s}'}{\mathbf{s}}(x + \sigma_0 + H(t))\partial_xr + (2\tanh^2 x - 1)r, \quad \ell r = \partial_xr + \tanh(x)r$$

Equivalent problem

Equation in r

$$\partial_t r = \mathcal{V}_{\sigma_0}(t, x) + (J\mathcal{L} + h_a(t)\ell)r + \text{non linear terms}$$

$$\mathcal{V}(t, x) = \frac{1}{\cosh x} \frac{\mathbf{s}'}{\mathbf{s}} (x + \sigma_0 + H(t)) \vec{e}_1, \quad |\mathcal{V}(t, x)| \leq K e^{-\gamma(\sigma_0 + H(t))},$$

$$J = \begin{pmatrix} -1 & -1 \\ 1 & -1 \end{pmatrix},$$

$$\mathcal{L}r = -\partial_{xx}r - \frac{\mathbf{s}'}{\mathbf{s}}(x + \sigma_0 + H(t))\partial_xr + (2\tanh^2 x - 1)r, \quad \ell r = \partial_xr + \tanh(x)r$$

To be proved

If σ_0 is large enough, if $r(t=0)$ is small enough, then $r(t, \cdot)$ remains small.

LL without notch ($s \equiv 1$)

$$\frac{\partial m}{\partial t} = -m \times H_{\text{eff}} - m \times (m \times H_{\text{eff}})$$

$$H_{\text{eff}} = m_{xx} - (m_2 \vec{e}_2 + m_3 \vec{e}_3)$$

Invariance by rotation and translation

\implies existence of a 2-parameter family of solutions for LL:

$$(t, x) \mapsto R_\theta M_0(x + \sigma)$$

\implies existence of a 2-parameter family of solutions in the mobile frame

$\implies 0 \in \text{Ker } L$, with $L = -\partial_{xx} + (2 \tanh^2 x - 1)$ associated to $x \mapsto \frac{1}{\cosh x}$ and $L = \ell^* \circ \ell$.

Quasi invariances

LL with notch and applied field

$$\frac{\partial m}{\partial t} = -m \times H_{\text{eff}} - m \times (m \times H_{\text{eff}})$$

$$H_{\text{eff}} = m_{xx} + \frac{\mathbf{s}'}{\mathbf{s}} m_x - (m_2 \vec{e}_2 + m_3 \vec{e}_3) - h_a \vec{e}_1$$

m close to

$$\mathcal{M}_{\sigma_0}(t, x) = R_{-H(t)} M_0(x - \sigma_0 - H(t))$$

Invariance by rotation,
quasi-invariance by translation

2-parameter family of quasi-solutions
close to \mathcal{M}_{σ_0} :

$$(t, x) \mapsto R_\theta \mathcal{M}_{\sigma_0}(t, x + \sigma)$$

2-parameter family of quasi solutions
for Eq. in r :

$$(t, x) \mapsto \mathcal{R}_\Lambda(t, x), \quad \Lambda = (\theta, \sigma)$$

New unknowns: Λ and W

$$r(t, \cdot) = \mathcal{R}_\Lambda(t)(\cdot) + W(t, \cdot), \quad \text{with } \int_{\mathbb{R}} W_i(t, x) \frac{1}{\cosh x} dx = 0.$$

Equations in Λ and W

$$\partial_t W = \mathcal{V}_{\sigma_0}(t, x) + (J\mathcal{L} + h_a(t)\ell)W + F(t, x, \sigma_0, \Lambda, W)$$

$$\frac{d\Lambda}{dt} = \mathcal{G}(t, x, \sigma_0, \Lambda, W)$$

$$\|\mathcal{V}_{\sigma_0}(t, \cdot)\|_{L_t^2} \leq C \exp(-c(\sigma_0 + H(t))), \quad J = \begin{pmatrix} -1 & -1 \\ 1 & -1 \end{pmatrix},$$

$$\mathcal{L}W = -\partial_{xx}W - \frac{\mathbf{s}'}{\mathbf{s}}(x + \sigma_0 + H(t))\partial_xW + (2\tanh^2 x - 1)W, \quad \ell W = \partial_xW + \tanh(x)W$$

$$\|F\|_{L^2} \leq C\|W\|_{H^2}(|\Lambda| + \|W\|_{H^1}) + C \exp(-c(\sigma_0 + H(t)))$$

$$|G| \leq C\|W\|_{H^1} + C \exp(-c(\sigma_0 + H(t)))$$

To be proved:

If $W(0)$ and $\Lambda(0)$ are small, then

- $W(t)$ and $\Lambda(t)$ remain small
- $W \rightarrow 0$ in H^1 and $\Lambda(t) \rightarrow \Lambda_\infty$

Coercivity for W

$$\left\langle W_i \left| \frac{1}{\cosh x} \right. \right\rangle = 0 \implies W \in (\text{Ker } L)^\perp, \text{ with } L = -\partial_{xx} + 2 \tanh^2 x - 1.$$

$$\|W\|_{L^2}^2 \leq \left\langle LW \left| W \right. \right\rangle = \|\ell W\|_{L^2}^2 \leq \|LW\|_{L^2}^2$$

We deal with:

$$\mathcal{L}W = -\partial_{xx}W - \frac{\mathbf{s}'}{\mathbf{s}}(x + \sigma_0 + H(t))\partial_xW + (2\tanh^2 x - 1)W$$

We use a scalar product with time-depending weight:

$$\left\langle u \left| v \right. \right\rangle_t = \int_{\mathbb{R}} \mathbf{s}(x + \sigma_0 + H(t))u(x)v(x)dx$$

for which \mathcal{L} is self-adjoint and coercive, so that:

$$\|W\|_{H^1} \sim \left\langle \mathcal{L}W \left| W \right. \right\rangle_t^{\frac{1}{2}} \text{ and } \|W\|_{H^2} \sim \|LW\|_{L_t^2}.$$

Variational estimates

$$\partial_t W = \mathcal{V}_{\sigma_0}(t, x) + J\mathcal{L}W + h_a(t)\ell W + F(t, x, \sigma_0, \Lambda, W)$$

$$\|\mathcal{V}_{\sigma_0}(t, \cdot)\|_{L_t^2} \leq C \exp(-c(\sigma_0 + H(t))), \quad J = \begin{pmatrix} -1 & -1 \\ 1 & -1 \end{pmatrix},$$

$$\mathcal{L}W = -\partial_{xx}W - \frac{\mathbf{s}'}{\mathbf{s}}(x + \sigma_0 + H(t))\partial_xW + (2\tanh^2 x - 1)W, \quad \ell W = \partial_xW + \tanh(x)W$$

$$\|F\|_{L^2} \leq C\|W\|_{H^2}(|\Lambda| + \|W\|_{H^1}) + C \exp(-c(\sigma_0 + H(t)))$$

$$\frac{d}{dt} \langle \mathcal{L}W | W \rangle_t \leq -\|\mathcal{L}W\|_{L_t^2}^2 + c(|h| + |\Lambda| + \|W\|_{H^1})\|\mathcal{L}W\|_{L_t^2}^2 + C \exp(-c(\sigma_0 + H(t)))\|\mathcal{L}W\|_{L_t^2}$$

Assumption: $|h| \leq \frac{1}{8c}$

While $|\Lambda| \leq \frac{1}{8c}$ and $\|W\|_{H^1} \leq \frac{1}{8c}$, then

$$\frac{d}{dt} \langle \mathcal{L}W | W \rangle_t + \frac{1}{2}\|\mathcal{L}W\|_{L_t^2}^2 \leq C \exp(-2c(\sigma_0 + H(t)))$$

$$\frac{d}{dt} \langle \mathcal{L}W | W \rangle_t + \alpha \langle \mathcal{L}W | W \rangle_t \leq C \exp(-2c(\sigma_0 + H(t)))$$

Comparison lemma

Assumption: $c|h| \leq \frac{1}{8c}$

While $|\Lambda| \leq \frac{1}{8c}$ and $\|W\|_{H^1} \leq \frac{1}{8c}$, then

$$\frac{d}{dt} \langle \mathcal{L}W | W \rangle_t + \alpha \langle \mathcal{L}W | W \rangle_t \leq C \exp(-2c(\sigma_0 + H(t))),$$

so $\langle \mathcal{L}W | W \rangle_t \leq Y(t)$ where Y satisfies $Y' + \alpha Y = C \exp(-2c(\sigma_0 + H(t)))$.

$$Y(t) = Y_0 \exp(-\alpha t) + \exp(-2c\sigma_0) \int_0^t C \exp(-\alpha(t-s)) \exp(-2cH(s)) ds.$$

We need:

- $Y(t)$ small for all time if $Y(0)$ is small and σ_0 large enough,
- $Y(t) \rightarrow 0$
- to control Λ , $\sqrt{Y(t)}$ integrable and its integral can be as small as necessary.

Assumption on h

- $|h(t)|$ small enough
- $t \mapsto \left(\int_0^t \exp(-\alpha(t-s) - 2cH(s)) ds \right)^{\frac{1}{2}}$ tends to zero when $t \rightarrow +\infty$ and integrable on \mathbb{R}^+ .

Example: if $0 < h^- \leq h(t) \leq \frac{1}{8c}$

Conclusion

Done

- Static solution for small constant h_a
- Static solution for multiply notched wire
- Dynamics far from the notch

- Stability threshold for h_a ?
- Dynamics of the walls for wires with several notches?
- Dynamics induced by electric current?

Thank you for your attention

Conclusion

Done

- Static solution for small constant h_a
- Static solution for multiply notched wire
- Dynamics far from the notch

- Stability threshold for h_a ?
- Dynamics of the walls for wires with several notches?
- Dynamics induced by electric current?

Thank you for your attention