

Influence of elastic anisotropy on measured sound velocities of cubic solids

Andreas Zerr, Feng Xu, Philippe Djemia, Y. Roussigné

▶ To cite this version:

Andreas Zerr, Feng Xu, Philippe Djemia, Y. Roussigné. Influence of elastic anisotropy on measured sound velocities of cubic solids. The Joint 28th AIRAPT and 60th EHPRG International Conference 2023, Jul 2023, Edinburgh, Scotland, United Kingdom. pp.157. hal-04241739

HAL Id: hal-04241739 https://hal.science/hal-04241739v1

Submitted on 13 Oct 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Public Domain

Influence of elastic anisotropy on measured sound velocities of cubic solids

<u>Dr. Andreas Zerr</u>¹, Dr. Feng Xu², Prof. Philippe Djemia¹, Prof. Yves Roussigné¹

Laboratoire des Sciences des Procédés et des Matériaux – CNRS, Villetaneuse, France, ²School of Science, Wuhan University of Technology, Wuhan, China

Instrumentation and Techniques 4, July 26, 2023, 16:30–18:30

Pressure dependences of the longitudinal sound velocities, VL(P), single-crystal elastic moduli, Cij(P), and elastic anisotropy, described through the Zener anisotropy ratio $A=2C_{44}/(C_{11} C_{12}$)= C_{44} /C', of three simple cubic solids, namely, sold argon, cubic H_2O ice and NaCl (B1-phase) were recently measured using the technique of the picosecond laser ultrasonics (ps-LU) [1-4]. These experiments revealed growing with pressure elastic anisotropy: A≈6 for argon at P=49 GPa, A≈6.5 for H₂O-ice VII at 62 GPa, A≈0.27 for NaCl-B1 at P=28 GPa. The latter manifested itself in diverging of the VL-extremes in single crystals corresponding, in cubic crystals, to the crystallographic directions <111> and <100>, while $VL_{111}>VL_{100}$ if A>1 and vice-versa if A<1. Moreover, the VLav(P) dependences measured for polycrystalline samples of these solids using Brillouin light scattering (BLS) e.g.[5-7] were found to approach VL₁₁₀(P), independent of the A(P) value, and to deviate from the VLH(P) dependences calculated applying the experimental Cij(P) and the Hill approximation. Here, we show that the latter inconsistency is caused by the elastic anisotropy and that the BLS provides overestimated longitudinal and transversal sound velocities of polycrystalline cubic solids, VLav(P) and VTav(P), respectively, if A>1 and underestimated VLav(P) and VTav(P) if A<1. However, the chance to recognise BLS-peaks of transversal waves in the polycrystalline solids decreases with increasing elastic anisotropy due to the peak broadening and splitting [3]. Distortion of the peaks of the longitudinal waves is less pronounced but still significant.

We evaluated the influence of such distortion on the aggregate shear modulus, Gav(P), derived from the VLav(P) and the bulk modulus, B(P), obtained from an EOS. For solid Ar at P=49 GPa, we found that Gav deviates from GH by ~50%. Furthermore, our LU- and BLS-measurements on polycrystalline γ -Ge₃N₄ having spinel structure [8] confirmed that the elastic anisotropy also influenced position and shape of the Rayleigh peak in the BLS measurements. In general, VRav is underestimated if A>1 and overestimated if A<1. Our evaluation of the influence of anisotropy on the BLS-peaks of γ -Ge₃N₄, with calculated A=2.1 [9], resulted in G underestimated by ~9% and B overestimated by ~29%.

However, similar limitations are relevant for any technique measuring sound velocities with probes having sizes comparable with those of the sample grains. The most reliable approach remains measurement of Cij(P) and extraction of the values of interest using the Hill (or similar) approximation. The ps-LU meets well this requirement at high pressures, also in excess of 100 GPa, because its high 3D-resolution makes use of single crystals unnecessary.

- [1] Kuriakose M., et al., Phys. Rev. B 96, 134122 (2017)
- [2] Raetz S., et al., Phys. Rev. B 99, 224102 (2019)
- [3] Xu F., et al., J. Appl. Phys. 130, 035903 (2021)
- [4] Xu F., et al., arXiv, 2209.10899 (2022)
- [5] Ahart M., et al., J. Chem. Phys. 134, 124517 (2011)
- [6] Grimsditch M., et al., Phys. Rev. B 33, 7192-7200 (1986)
- [7] Campbell A.J. and Heinz D.L., Science 257, 66-68 (1992)
- [8] Feldbach E., et al., Electron. Mater. Lett. 17, 315-323 (2021)
- [9] Li C., et al., (submitted, 2023)

28th AIRAPT and 60th EHPRG

23-28 July 2023

Edinburgh International Conference Centre, Edinburgh, UK



