



HAL
open science

Effect of Scalping on the Mechanical Behavior of Coarse Soils

Nadine Ali-Hassan, Ngoc-Son Nguyen, Didier Marot, Fateh Bendahmane

► **To cite this version:**

Nadine Ali-Hassan, Ngoc-Son Nguyen, Didier Marot, Fateh Bendahmane. Effect of Scalping on the Mechanical Behavior of Coarse Soils. *International Journal of Geotechnical and Geological Engineering*, 2021, 15 (1), pp.64-74. hal-04244439

HAL Id: hal-04244439

<https://hal.science/hal-04244439>

Submitted on 16 Oct 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Effect of Scalping on the Mechanical Behavior of Coarse Soils

Nadine ALI HASSAN, Ngoc Son NGUYEN, Didier MAROT, Fateh BENDAHMANE

Abstract—This paper aims at presenting a study of the effect of scalping methods on the mechanical properties of coarse soils by resorting to numerical simulations based on the discrete element method (DEM) and experimental triaxial tests. Two reconstitution methods are used, designated as scalping method and substitution method. Triaxial compression tests are first simulated on a granular materials with a gap graded particle size distribution by using the DEM. We study the effect of these reconstitution methods on the stress-strain behavior of coarse soils with different fine contents and with different ways to control the densities of the scalped and substituted materials. Experimental triaxial tests are performed on original mixtures of sands and gravels with different fine contents and on their corresponding scalped and substituted samples. Numerical results are qualitatively compared to experimental ones. Agreements and discrepancies between these results are also discussed.

Keywords—Coarse soils, scalping, substitution, discrete element method, triaxial test.

I. INTRODUCTION

COARSE soils are natural materials often used as construction materials for dams, dikes, embankments. They are characterized by a wide grain size gradation where particle diameters vary largely from a few microns up to several decimeters. It is difficult to determine mechanical properties of coarse soils by using the classical laboratory devices such as triaxial apparatuses or shear boxes due to the presence of large elements. Indeed, to obtain accurate mechanical properties of a soil, the diameter of the experimental device is usually required to be 10 times bigger than the maximum diameter of grains.

Hence, it is necessary to remove from the soil all these oversized particles by a scalping or substitution method. The scalping method consists in removing from the soil all the oversized particles and then testing the reconstituted sample. For the substitution method (scalping/replacement), the oversized particles are replaced by an equal mass of smaller ones. However, it is not clear yet how to choose the material for this replacement.

The results of experimental studies on the consequences of scalping and substitution methods on the shear strength of coarse soils are contradictory. Different ways for controlling the density of scalped and substituted samples were proposed. Reiffsteck et al. [12] and WG Holtz [18], [19] controlled the dry density γ_d of scalped and substituted soils to be equal to

that of the original soil, while Torrey et al. [10] controlled the ratio of the dry density γ_d to the maximum dry density $\gamma_{d,max}$ obtained by the Proctor compaction test to be the same for the original, scalped and substituted soils. For cohesionless soils, Dano [13] controlled the relative density (D_R), Dupla et al. [16] controlled the dry density of the fine fraction for all the samples, while Seif El Dine [3] compacted the scalped soil in order to reach the void ratio of the retained fraction in the original soil. The conclusions about consequences of scalping and substitution methods are divergent. It was shown that the scalping method can lead to a good estimation (Leslie [14] and Post [20]), an over-estimation (Dano [13] and Dendani [21]) or an under-estimation (Seif El Dine [3]) of the shear strength. The substitution method can also lead to a good estimation (Pedro et al. [11]), an over-estimation (Reiffsteck et al. [12]) or an under-estimation (Torrey et al. [10] and Valle [15]) of the shear strength. The divergence between these conclusions is related to the fact that the behavior of scalped and substituted soils depends on many factors such as the scalping technique used, the scalping diameter, the compaction parameter to be controlled and the material under consideration.

This paper presents a numerical study followed by an experimental one to get a better understanding of consequences of the scalping and substitution methods on the shear strength of coarse soils. First, triaxial compression tests were simulated on granular materials with gap-graded particle size distribution using the discrete element method (DEM). Both scalping and substitution methods mentioned above are used. It is also crucial to select the parameter to be controlled for the original sample and the scalped (or substituted) one so that they can be considered to be equivalent in terms of compactness. For the numerical study, we control three parameters : the void ratio of the retained fraction ($e_{retained}$), the relative density (D_R) and the global void ratio (e). Experimental tests are performed on mixtures of sand and gravel by using triaxial apparatuses of diameters 50 mm and 100 mm. Numerical results are qualitatively compared to experimental ones.

II. NUMERICAL STUDY

The DEM based on the molecular dynamic (MD) approach is used in order to model a dry cohesionless granular soil which is implemented in the open-source software YADE [22]. The DEM uses Newton-Euler dynamic equations to describe the translational and rotational motions for each rigid particle. The interaction forces at the contact between two particles are calculated by using a contact model that consists of two linear springs in the normal and tangential directions with

GeM Institute, University of Nantes, 58 rue Michel Ange, BP 420, 44606 Saint Nazaire Cedex, France.
nadine.ali-hassan@etu.univ-nantes.fr
ngocson.nguyen@univ-nantes.fr
didier.marot@univ-nantes.fr
fateh.bendahmane@univ-nantes.fr

respective stiffnesses K_n and K_t . The contact normal and tangential stiffnesses are calculated from the respective particle stiffnesses, k_n and k_t , by assuming that the latter ones are connected in series in each direction. They are expressed as follows :

$$K_n = \frac{k_n^i k_n^j}{k_n^i + k_n^j} \text{ and } K_t = \frac{k_t^i k_t^j}{k_t^i + k_t^j} \quad (1)$$

where the superscripts i and j denote two particles at the contact point. The tangential force f_t is limited by Coulomb friction law as $|f_t| \leq f_n \tan(\varphi)$, where f_n is the normal force and φ is the friction angle. The microscopic parameters used in our simulations are identical to those used in [1] where the normal particle stiffness $k_n/D = 250$ MPa, stiffness ratio $k_t/k_n = 0.5$, friction angle $\varphi = 35^\circ$ and mass density $\rho = 2600$ kg/m³.

The simulated samples are mixtures of fine and coarse particles with a gap-graded particle size distribution with different fine contents f_f . Figure 1 shows the particle size distribution (PSD) of the original soil with $f_f = 30\%$ (black curve). The gap ratio $G_r = D_{\min}/d_{\max}$ is chosen to be equal to 3 in order to keep the computation time reasonable because a higher value of G_r leads to a large number of particles and thus, a very long computation time. Each original soil is then scalped by removing all the particles of diameters greater than a scalping diameter d_{scalping} which depends on the removed fraction defined as the ratio of the removed mass to the total mass of the original soil. In our simulations, all the soils are scalped to have a removed fraction of 35%. For the substituted soil, the removed mass is replaced by an equal mass of particles of diameters d between D_{\min} of the coarse fraction and d_{scalping} . The scalped and substituted PSDs are presented in Figure 1 for the original soil of $f_f = 30\%$. It can be seen that the fine content f_f remains constant for the substitution method, while its value is increased to a value f'_f by the scalping method. The values of fine content f_f and D_{\max} for all simulated samples are presented in Table I.




Fig. 1: Particle size distribution of the original soil with $f_f = 30\%$ and those of the scalped and substituted samples.

Three density parameters are considered:

- (i) The global void ratio e

TABLE I: Fine content f_f and maximum diameter D_{\max} of the simulated samples.

Sample	f_f (%)	D_{\max} (mm)
Original	20	12
Scalped	30	9.375
Substituted	20	9.375
Original	30	12
Scalped	46	9
Substituted	30	9
Original	60	12
Scalped	95	6.75
Substituted	60	6.75

- (ii) Void ratio e_{retained} of the retained fraction ($d < d_{\text{scalping}}$) in the original soil

$$e_{\text{retained}} = \frac{V_v}{V_{s,\text{retained}}} = \frac{e}{f_{\text{retained}}}, \quad (2)$$

where V_v is the total void volume, $V_{s,\text{retained}}$ is the solid volume of the retained fraction and $f_{\text{retained}} = V_{s,\text{retained}}/V_s$ with total solid volume V_s .

- (iii) The relative density D_R defined as

$$D_R = \frac{e_{\max} - e}{e_{\max} - e_{\min}}, \quad (3)$$

where e_{\max} and e_{\min} are the maximum and minimum void ratios of the material under consideration.

When a density parameter is chosen, its value for the scalped or substituted soil is controlled to be equal to the value for the original soil.

To study the behavior of a gap-graded soil, it is convenient to use two other void ratios: intergranular void ratio e_c for the coarse-grained fraction and the interfine void ratio e_f for the fine-grained fraction as proposed by Thevanayagam et al. [2]:

$$e_c = \frac{V_v + V_s^f}{V_s^c} = \frac{e + f_f}{1 - f_f} \text{ and } e_f = \frac{V_v}{V_s^f} = \frac{e}{f_f}, \quad (4)$$

where V_s^f and V_s^c are the respective solid volumes of the fine and coarse fractions.

Particles are first generated into a cube composed of six rigid walls according to a given PSD. At this stage, particle diameters are reduced by a factor of 2.0. Next, they are progressively expanded to reach the target PSD. After that, the box dimensions are reduced until the stresses σ_i ($i = 1, 2, 3$) reach 100 kPa. This value of the confining pressure is often used when performing experimental triaxial tests on granular soils such as Thevanayagam et al. [2], [25], Salgado et al. [24] and Murthy et al. [23]. To obtain the loosest state (maximum void ratio e_{\max}), the friction angle between particles is set to the value of 35° used for the triaxial test and a small confining pressure of 1 kPa is applied. The densest state (minimum void ratio e_{\min}) is obtained by setting the friction angle to zero to facilitate rearrangement of particles and by applying a confining pressure of 100 kPa. At the end of the compaction process, the friction angle is then reset to its original value

(35°) used for the triaxial test. It is worth mentioning that these numerical procedures to obtain e_{\min} and e_{\max} are different from the experimental ones for which particles are deposited under gravity from a given height to obtain the loosest state and then vibrated with a given frequency to reach the densest state. These standard procedures have been established for narrowly graded and fine soils. For strongly gap-graded soils, particle segregation might occur when depositing particles under gravity or when vibrating them. A target value of the global void ratio e can be also reached by setting the friction angle to zero value during the compaction to reach around 98% of the target value of e . After that, the friction angle is reset to its original value and compaction continues until the confining pressure is reached. Once the compaction finishes, triaxial compression tests are then performed by prescribing a small strain rate $\dot{\epsilon}_1 = 0.01 \text{ s}^{-1}$ in one direction, while keeping the lateral stresses σ_2 and σ_3 constant in the two other directions. Each sample is loaded until the axial strain ϵ_{11} reaches 10%.

In the following, the mechanical behavior of scalped and substituted soils is presented in comparison with the behavior of the original soils. The densities of scalped and substituted soils are controlled by considering the void ratio e_{retained} of the retained fraction, the relative density D_R and the global void ratio e .

A. Controlling the void ratio e_{retained} of the retained fraction

The original material with fine content of $f_f = 60\%$ is scalped with 35% of the removed fraction and the global void ratio e of the scalped sample is controlled to be equal to the value of e_{retained} that the retained fraction has in the original sample. The original sample has $e = 0.39$ and $e_{\text{retained}} = 0.6$ so the void ratio e of the scalped sample is equal to 0.6. It should be noted that when the original sample is scalped, its fine content increases as shown in the equation below:

$$\begin{aligned} f'_f &= \frac{V_f}{V'_s} = \frac{V_f}{V_s - V_{s,\text{removed}}} = \frac{V_f}{V_s - (1 - f_{\text{retained}})V_s} \\ &= \frac{V_f}{f_{\text{retained}}V_s} = \frac{f_f}{f_{\text{retained}}}, \end{aligned} \quad (5)$$

where symbol ($'$) is used to depict characteristics for the scalped sample. However, by controlling e_{retained} , the interline void ratio e_f is preserved as demonstrated in the equation below:

$$e'_f = \frac{e'}{f'_f} = \frac{e_{\text{retained}}}{f'_f} = \frac{e}{f_{\text{retained}} \cdot f_f} = \frac{e}{f_f} = e_f \quad (6)$$

Figure 2 presents the stress ratio q/p and the volumetric strain ϵ_v versus the axial strain ϵ_{11} for the original sample with $f_f = 60\%$ and of the scalped sample. It can be seen that the shear resistance and the dilatancy of the scalped sample are significantly lower than those for the original soil. This result means that the scalping method leads to an under-estimation of the shear strength of coarse soils when the global void ratio e of the scalped sample is equal to the void ratio e_{retained} of the retained fraction. This numerical result is in good agreement with the experimental finding presented in [3]. The reason for

this under-estimation is that the shear strength of the original soil results from the contributions of the retained fraction, of the removed fraction and of the interface between them. When controlling the void ratio e_{retained} of the retained fraction, we preserve the contribution of the retained fraction. However, we lose the contributions of the removed fraction and the interface between the retained and removed fractions. Therefore, the shear strength of the scalped sample is lower than that of the original soil. The scalping method with e_{retained} controlled would work if the removed particles are fully dispersed by the retained particles and then have no significant contribution to the shear strength of the soil.




Fig. 2: Stress ratio q/p and volumetric strain ϵ_v versus axial strain ϵ_{11} for the original sample with $f_f = 60\%$ and the scalped one. The void ratio e_{retained} of the retained fraction is controlled.

B. Controlling the relative density D_R

Three original soils with fine contents $f_f = 20\%$, 30% and 60% are scalped and substituted. The relative densities D_R for all the original, scalped and substituted samples are controlled to be equal to 50%. Table II presents some characteristics of these samples. Their mechanical behaviors are shown in Figures 3, 4 and 5. As shown in Table II, the scalping method leads to a decrease in the void ratio e for the original fine content $f_f = 20\%$ when the relative density D_R is controlled. As a result, the scalped sample becomes denser and stronger than the original one as shown in Figure 3. It is clear that the scalping method greatly over-estimates the shear strength and dilativeness of the soil with $f_f = 20\%$. On the hand, the scalping method used for the soil with $f_f = 30\%$ leads to an

TABLE II: Fine content f_f , void ratios e_{\max} , e_{\min} , e and maximum stress ratio $(q/p)_{\max}$ for original, scalped and substituted samples.

Sample	f_c	e_{\max}	e_{\min}	e	e_f	e_c	$(q/p)_{\max}$
Original	20%	0.46	0.33	0.39	1.93	0.73	1.04
Scalped	30%	0.36	0.29	0.32	1.03	0.9	1.44
Substituted	20%	0.46	0.32	0.39	1.94	0.74	1.02
Original	30%	0.34	0.28	0.3	1.02	0.86	1.43
Scalped	46%	0.41	0.35	0.37	0.81	1.55	1.25
Substituted	30%	0.37	0.3	0.33	1.09	0.89	1.4
Original	60%	0.46	0.39	0.42	0.69	2.5	1.17
Scalped	92%	0.64	0.54	0.58	0.63	19.5	1.0
Substituted	60%	0.49	0.41	0.45	0.74	2.6	1.04

increase in void ratio e ; as a consequence the scalped sample is less resistant and less dilatant than the original one as shown in Figure 4. The same result is found for the fine content of 60%. For fine contents of 30% and 60%, the scalping method leads to an under-estimation of the shear strength of the original soils.




Fig. 3: Stress ratio q/p and volumetric strain ε_v versus axial strain ε_{11} for original sample with $f_f = 20\%$ and for the scalped and substituted samples. $D_R = 50\%$ is controlled for all the samples.

As mentioned previously, scalping a coarse soil causes an increase in fine content f_f that leads, in turn, to a change in the soil's microstructure and mechanical behavior. Taha et al. [1], [26] studied the role of fine content f_f on the mechanical behavior of gap-graded materials by performing numerical simulations with the DEM. The numerical model and materials




Fig. 4: Stress ratio q/p and volumetric strain ε_v versus axial strain ε_{11} for original samples with $f_f = 30\%$ and for the scalped and substituted samples. $D_R = 50\%$ is controlled for all the samples.

considered in this study are identical to those considered here. Gap-graded samples with different fine contents were compacted to reach the densest state ($D_R = 100\%$). Figure 6 shows the dependence of the void ratio e and the maximum stress ratio $(q/p)_{\max}$ upon fine content f_f . It can be seen that by increasing fine content f_f , the void ratio e decreases, reaches the lowest value at $f_f = 30\%$ and then increases with fine content. Fine content of 30% is the optimum fine content at which the fine particles fill the best the void space between the coarse particles without separating the latter ones; therefore, the material density is highest. Lade et al. [27] found also an optimum fine content around 30% for mixtures of




Fig. 5: Stress ratio q/p and volumetric strain ε_v versus axial strain ε_{11} for original sample with $f_f = 60\%$ and for the scalped and substituted samples. $D_R = 50\%$ is controlled for all the samples.

coarse and fine sands. It is clear from Figure 6.b that when fine content is smaller than the optimum value of 30%, the shear strength increases with the fine content. The shear strength is the best at the optimum fine content. Above this optimum value, the shear strength decreases with fine content. By using these results, we can explain why the scalping method over-estimates the shear strength for $f_f = 20\%$ but under-estimates for $f_f = 30\%$ and 60% as shown in Table II. Indeed, scalping the soil with fine content of 20% causes an increase of its fine content to 30% which is the optimum fine content; therefore, the shear resistance of the scalped sample is higher than that of the original sample. Conversely, scalping the soils of $f_f = 30\%$ and 60% displace their fine contents further away from the optimum fine content; as a result, the shear strengths of the scalped samples are lower than those of the original samples. These results indicate that over-estimation or under-estimation of the scalping method depends on the value of fine content of the scalped soil in comparison with the optimum fine content. If the fine content gets closer to the optimum value, the scalping method over-estimates the shear strength. If the fine content moves further away from the optimum value, the shear strength is under-estimated.

Regarding the substitution method, it leads to a slight increase of e_{\min} , e_{\max} and e in comparison with those of the original samples. As shown in Figures 3, 4 and 5, the substitution method leads to a good estimation of the shear strength of the original soil except for the sample with fine




Fig. 6: (a) Void ratio e and (b) maximum stress ratio $(q/p)_{\max}$ versus fine content f_f for gap-graded samples with $D_R = 100\%$ [1], [27].

content of 60% for which the substituted sample has a lower shear strength than the original one. It is worth mentioning that the materials considered here are not widely graded. The substitution method might have stronger effect for more widely graded soils. Further studies need to be carried out to confirm these results and to interpret them.

C. Controlling the global void ratio e

In this section, we analyze the behavior of scalped and substituted samples in comparison with that of the original one when the global void ratio e is controlled to be the same for all the samples. It should be noted that controlling the global void ratio e is equivalent to controlling the dry density γ_d of samples as proposed in [12], [19] if the solid density γ_s is the same for fine and coarse particles. The scalping method leads to an increase in fine content f_f , hence a decrease in interfine void ratio e_f but an increase in the intergranular void ratio e_c , while the substitution method preserves the latter ones. Table III shows the fine content f_f and the void ratios e , e_f and e_c for the original sample of 30% of fine content and its corresponding scalped and substituted samples.

The behaviors of the original, scalped and substituted samples are shown in Figure 7 for the original fine content $f_f = 30\%$ and $e = 0.36$, and in Figure 8 for $f_f = 60\%$ and $e = 0.49$. It can be seen that for the original fine content

TABLE III: Fine content and void ratios for the original sample of 30% of fine content and its corresponding scalped and substituted samples.

Soil	f_f	e	e_f	e_c
Original	30	0.36	1.18	0.94
Scalped	46	0.36	0.79	1.54
Substituted	30	0.36	1.18	0.94

$f_f = 30\%$, the scalped and substituted samples show much higher shear strength and dilativeness than those of the original sample, particularly for the scalped sample. For the original fine content of 60%, the scalped sample is much stronger than the original one, while the substitution method results in almost the same behavior as that of the original sample.




Fig. 7: Stress ratio q/p and volumetric strain ε_v versus axial strain ε_{11} for original samples with $f_f = 30\%$ and its scalped and substituted samples. $e = 0.36$ is controlled for all the samples.

As mentioned previously, the scalping method results in primarily an increase in fine content and secondly a decrease in the particle size gradation of the coarse fraction, while the substitution method results only in the second effect. In the following, we show how the fine content f_f and the particle size gradation of the coarse fraction influence the mechanical behavior of gap-graded soils when the global void ratio e is controlled. This understanding is needed to explain the consequences of the scalping and substitution methods shown above.

1) *Effect of fine content f_f :* Let us analyze here the effect of the fine content on the mechanical behavior of mixtures of




Fig. 8: Stress ratio q/p and volumetric strain ε_v versus axial strain ε_{11} for the original sample with $f_f = 60\%$ and its scalped and substituted samples. $e = 0.49$ is controlled for all the samples.

fine and coarse particles when their global void ratios e are controlled to be the same. Two series of numerical simulations are performed on samples with gap-graded PSDs shown in Figure 1. Fine content f_f is varied from 20% to 50%, and the global void ratio e is controlled to be around 0.32 for the first series, while f_f is varied from 50% to 75% and e is controlled to be around 0.47 for the second series (see Figure 9). It is worth mentioning that as the maximum and minimum void ratios depend on the fine content, the global void ratio e cannot be controlled to be the same for all fine contents. Figure 10 presents the behavior of different mixtures with fine contents of 20, 30, 40 and 50%. The maximum stress ratio $(q/p)_{\max}$ is plotted versus fine content f_f in Figure 11 for the two series of tests. It can be seen that the effect of fine content f_f when e is controlled is opposite to that found when the relative density D_R is controlled (Figure 6). Indeed, mixtures become weaker and less dilative with an increase in fine content f_f smaller than the optimum value of 30%, while they become stronger and more dilative with an increase in fine content above 30%. At the optimum fine content of 30%, the shear resistance is the highest when the relative density D_R is controlled, while it is the lowest when the global void ratio e is controlled. This result can be explained by comparing value of e to that of the minimum void ratio e_{\min} of each mixture in Figure 9. At the same value of e , the mixture with the optimum fine content of 30% is quite far away from the densest state; as a result, it behaves as a loose material. On the contrary, the mixture

with $f_f = 20\%$ is quite close to its densest state; therefore, it behaves as a dense material with a stronger dilativeness and higher resistance than those of the mixture with $f_f = 30\%$. The difference $e - e_{\min}$ increases with fine content $f_f < 30\%$ but decreases with fine content $f_f > 30\%$. This explains why the shear strength decreases with fine content $f_f < 30\%$ but increases with fine content $f_f > 30\%$. Thevanayagam et al. [25] studies experimentally the effect of fine content on undrained shear strength of mixtures of silt and sand by controlling the global void ratio e as close to 0.6 as possible. The authors found that the undrained shear strength decreases with fine content $< 25\%$ but increases with fine content $> 25\%$. The numerical result obtained in our study is in good agreement with the experimental finding of Thevanayagam et al. Moreover, this experimental study reveals that the optimum fine content for the considered silt-sand mixtures is around 30% (the value of 30% was not considered in this study).




Fig. 9: Global void ratio e of mixtures for the first and second series of tests, in comparison with the minimum void ratio e_{\min} .

2) *Effect of the grain size gradation of the coarse fraction:* Three samples of fine content f_f of 30% were simulated with three different gradation ratios $D_{\max}/D_{\min} = 1.5, 2$ and 3 for the coarse fraction. The values of e are controlled to be equal to 0.33 for all the samples as shown in Figure 12. Figure 13 shows the stress ratio q/p and the volumetric strain ε_v versus axial strain ε_{11} for these three samples. This figure shows clearly a decrease in the shear strength with an increase in the ratio D_{\max}/D_{\min} for the coarse fraction. This numerical result is in good agreement with the experimental finding presented in [3], [28] where the shear strength of mixtures of sands and gravels of the same void ratio e was found to decrease as the gradation of the gravel fraction increases. The decrease of the shear strength with the ratio D_{\max}/D_{\min} can be attributed to a decrease of the minimum void ratio e_{\min} with D_{\max}/D_{\min} as shown in Figure 12. Indeed, at the same value of e , the sample with $D_{\max}/D_{\min} = 3$ is looser than that with $D_{\max}/D_{\min} = 1.5$ in comparison with their respective values of e_{\min} . As a result, the former is less resistant and less dilatative than the latter.

Following the above numerical finding, the over-estimation of the shear strength of the original sample with $f_f = 30\%$ by the substitution method when the global void ratio e is




Fig. 10: Stress ratio q/p and volumetric strain ε_v versus axial strain ε_{11} for different fine contents f_f when the global fine content e is controlled to be almost the same.

controlled is due to the fact that it reduces the particle size gradation of the coarse fraction. For the original sample with $f_f = 60\%$, as its microstructure is primarily governed by the fine fraction, a reduction in the gradation of the coarse fraction has little effect on its shear strength.

Regarding the scalping method, its over-estimation of the shear strength for the original samples with $f_f = 30\%$ and 60% is primarily due to the increase in fine content f_f further away from the optimum value of 30% and secondly due to the reduction in the gradation of the coarse fraction. It could be expected that the scalping method leads to an under-estimation or good estimation of the shear strength for the original sample with $f_f = 20\%$ as the increase in fine content f_f to 30% leads to the loss in shear strength which might be greater or equal to the gain in shear strength caused by the reduction of the gradation of the coarse fraction.

D. Summary

A numerical study of consequences of the scalping and substitution methods on the shear strength of gap-graded materials has been presented. Three different parameters have been considered to control the compactness state of scalped and substituted samples in comparison with that of the original soil: the void ratio e_{retained} of the retained fraction, the relative density D_R and the global void ratio e . If e_{retained} is controlled, the scalping method under-estimates significantly the original shear strength. This method can either under-estimate or over-estimate the original shear strength when D_R or e is controlled depending on the original fine content in comparison with the optimum value. Regarding the substitution method, it could work if the relative density D_R is controlled. When the global void ratio e is controlled, it over-estimates the shear strength for original fine content $f_f < 60\%$ and




Fig. 11: Maximum stress ratio $(q/p)_{max}$ versus fine content f_f when the global void ratio e is controlled.




Fig. 12: Global void ratios e and e_{min} for three mixtures of $D_{max}/D_{min} = 1.5, 2$ and 3 , and with $f_f = 30\%$.

gives a good estimation for $f_f > 60\%$. It is worth mentioning that controlling the relative density D_R requires values of the maximum and minimum void ratios e_{max} and e_{min} for each original, scaled and substituted soil, which are difficult to obtain for coarse soils by using the experimental standard compaction procedures because of particle segregation. This is the reason why only the global void ratio e is controlled for the experimental study that will be presented in the following.

III. EXPERIMENTAL STUDY

Experimental tests were carried out by using two triaxial devices with diameters $\Phi 100$ mm and $\Phi 50$ mm. The ratio $\Phi/D_{max} = 10$ (D_{max} is the maximum particle diameter) is





Fig. 13: Stress ratio q/p and volumetric strain ϵ_v versus axial strain ϵ_{11} with different grading D_{max}/D_{min} and $f_f = 30\%$.

kept for all performed tests in order to respect experimental standards. Coarse soils considered in this study are mixtures of Fontainebleau sand, representing the fine fraction, and Palvadeau and natural gravels, representing the coarse fraction. The names of Fontainebleau sand, Palvadeau and natural gravels are abbreviated as FS, PG and NG, respectively. Table IV presents some characteristics of these elementary materials. It should be noted that the internal friction angle of a soil depend on its void ratio e ; therefore, the values of the drained friction angle φ' shown in this table are only valid for the corresponding values of the void ratio e . As the coefficient of uniformity C_u and the void ratio e are almost the same for both Palvadeau and natural gravels, Palvadeau gravels appear to be more resistant than natural gravels. Two coarse soils with fine contents of 30% and 60%, namely FS30PG40NG30_10 (30% Fontainebleau sand + 40% Palvadeau gravel + 30% natural gravel) and FS60PG10NG30_10 (60% Fontainebleau sand + 10% Palvadeau gravel + 30% natural gravel), were used. Their samples have a diameter of 10 mm and they were tested by using the triaxial device of $\Phi 100$ mm.

Each original soil is then scalped at a particle diameter of 5 mm: the finer fraction (Fontainebleau sand and Palvadeau gravels) is retained, while the coarser fraction (natural gravels) is removed. The original soil is also substituted, where the fraction of naturel gravels is removed and replaced by an equal mass of Palvadeau gravels. The particle size gradation of the replacement material is chosen to be the same as that of Palvadeau gravels in the original sample. Figure 14 shows the PSDs of the original soil with fine content f_f of 30% and

TABLE IV: Characteristics of the elementary materials to compose coarse soils.


Materials	Abbrev.	d_{\min} (mm)	d_{\max} (mm)	C_u	e	φ'
Fontainebleau Sand	FS	0.01	0.6	2.32	0.54	40.6°
Palvadeau Gravels	PG	1.6	5.0	1.57	0.54	42°
Natural Gravels	NG	5.0	10.0	1.45	0.55	47.8°

**Fig. 14:** PSDs for the original soil with $f_f = 30\%$ and its scalped and substituted ones.

its corresponding the scalped and substituted soils. Scalped and substituted samples are named by the name of their corresponding original soil followed by letter S for scalping and SR for scalping/replacement, respectively, and the number 5 indicating their maximum particle diameter of 5 mm. For example, FS30PG40NG30_S_5 and FS30PG40NG30_SR_5 are the respective scalped and substituted samples of the original soil FS30PG40NG30_10. The global void ratio e is controlled such that it is almost the same for all the original, scalped and substituted samples. Samples were compacted by the moist tamping to achieve the target void ratio and then saturated. Afterwards, they are consolidated and then sheared under drained conditions with an effective confining pressure of 100 kPa.

Table V shows the characteristics of the tested samples: composition of each sample, global, interfine and intercoarse void ratios e , e_f and e_c , and the undrained friction angle φ' obtained from the triaxial test. Figures 15 and 16 present the stress ratio q/p and the volumetric strain ε_v versus axial strain ε_{11} for original, scalped and substituted samples with original fine contents of 30% and 60%, respectively. It can be seen that the scalping method results in a friction angle significantly higher than that of the original soil of $f_f = 30\%$ (40.3° for the scalped sample compared to 37.4° for the original sample), while it gives a good friction angle for the original soil of $f_f = 60\%$ (40.5° for the scalped sample compared to 40.7° for the original soil). Regarding the substitution method, it gives friction angles close to those of the original samples for both fine contents of 30% and 60%. One can also remark in Figures 15 and 16 that it is difficult to get a clear effect of the scalping and substitution methods on the volumetric behavior of soils.


Seif El Dine et al. [28] also found that studying the volumetric behavior of gap-graded samples is particularly complicated as they are no longer homogeneous because of shear bands.

**Fig. 15:** Stress ratio q/p and volumetric strain ε_v versus axial strain ε_{11} with original $f_f = 30\%$.

By qualitatively comparing the numerical results presented previously to the experimental ones shown here, we find some agreements between them. Both studies show an over-estimation of the shear strength by the scalping method for the original soil with 30% of fine content, and a good estimation by the substitution method for the original soil with 60% of fine content. However, we find some divergences between the numerical and experimental results. Firstly, the numerical simulation predicts an over-estimation of the shear strength by the scalping method for the original soil of 60% of fine content, while the experimental study shows a good estimation of the shear strength of this soil. Secondly, the substitution method over-estimates the shear strength of soil with 30% of fine content according to the numerical study, while it results in a good estimation according to the experimental study. These divergences are certainly due to the fact that the numerical simulations considered only spherical particles with the same surface friction angle so the effect of particle properties such as shape, roughness were not taken into

TABLE V: Characteristics of the original coarse soils and there corresponding scalped and substituted soils.

Soils	%FS	%PG	%NG	e	e_f	e_c	φ' ($^\circ$)
FS30PG40NG30_10	30	40	30	0.33	1.09	0.89	37.1
FS30PG40NG30_S_5	44	56	0	0.333	0.74	1.37	40.0
FS30PG40NG30_SR_5	30	70	0	0.32	1.08	0.89	37.95
FS60PG10NG30_10	60	10	30	0.39	0.65	2.48	40.35
FS60PG10NG30_S_5	84	16	0	0.39	0.47	7.70	40
FS60PG10NG30_SR_5	60	40	0	0.40	0.67	2.51	39.8

**Fig. 16:** Stress ratio q/p and volumetric strain ε_v versus axial strain ε_{11} with original $f_f = 60\%$.

consideration. For physical soils, particle properties of fine particles might be strongly different from those of coarse particles and these properties might be different for particles in the same fraction. For the soils tested in our experimental study, the coarse fraction (Palvadeau and natural gravels) is more resistant than the fine fraction (Fontainebleau sand). For the coarse fraction, natural gravels are more resistant than Palvadeau gravels as shown in Table IV. It should be noted that scalping a coarse soil leads to a gain in shear resistance due to the increase in fine content but to a loss in shear resistance due to the decrease in coarse content. For numerical materials where the particle properties are the same for both fine and coarse fractions, the gain is bigger than the loss; therefore the scalping method over-estimates the shear resistance when the global void ratio e is controlled. However, for the considered physical coarse soils, the natural gravels are significantly stronger than Fontainebleau sands and Palvadeau gravels; as a result, removing them from the soils causes a significant loss in shear strength which might be equal to the gain. This

would be the reason why the shear strength of the soils with 60% of fine content is well estimated by the scalping method. For the substitution method, we gain the shear resistance due to the reduction in particle size gradation of the coarse fraction but we gain or loss the shear resistance depending on the resistance of the replacement material compared to that of the replaced material. For numerical materials, there is no loss since the particle properties are the same for both replacement and replaced materials. For the considered physical soils, the replacement material (Palvadeau gravels) is less resistant than the replaced material (natural gravels), leading to a loss in the shear strength of the substituted soils; and this loss might be equal to the gain. This would be the reason why the substitution method gives a good estimation of the shear strength for the soils with 30% of fine content. Further numerical and experimental studies need to be carried out to understand the effect of particle properties when using the scalping and substitution methods.

IV. CONCLUSIONS

In this paper, we have presented a study on the effect of the scalping and substitution methods on the mechanical behavior of gap-graded soils by performing numerical simulations with the DEM and experimental triaxial tests. Numerical original samples are composed of fine and coarse spherical particles with different fine contents. They are scalped and substituted, and their compactness states are controlled by considering three different parameters: void ratio e_{retained} of the retained fraction, the relative density D_R and the global void ratio e . The numerical study has shown that the scalping method leads to a significant under-estimation of the shear strength when e_{retained} is controlled. It can lead to an under-estimation or an over-estimation of the shear strength depending on whether D_R or e is controlled and on the original fine content with respect to the optimum fine content. Its consequences are mainly due to the increase in fine content. Whereas, the substitution method leads to an over-estimation of the shear strength for the soil with 30% of fine content if the global void ratio e is controlled to be the same for both original and substituted soils, but it gives a good estimation for the soil with 60% of fine content. Its consequences are mainly due to the reduction in the particle size grading of the coarse fraction. Coarse soils were composed of Fontainebleau sands, Palvadeau and natural gravels with different fine contents were considered in the experimental study. The global void ratio e was controlled to be the same for all original, scalped and substituted samples. It was found that the scalping method gives an over-estimation

of the shear strength of the original soil with 30% of fine content but it gives a good estimation for the soil with 60% of fine content. The substitution method gives a good estimation of the shear strength for both soils. By making a qualitative comparison between the numerical and experimental results, we found some agreements but also disagreements between these results. The disagreements are certainly due to the fact that particle properties such as shape and surface roughness were not taken into consideration in the numerical study. For physical coarse soils, particle properties have a great influence on the mechanical behavior of original, scalped and substituted soils. The influence of particle properties need to be addressed in the upcoming study.

LIST OF SYMBOLS

f_f	Fine content
f_n, f_t	Normal and tangential contact forces
k_n, k_t	Normal and tangential particle stiffnesses
K_n, K_t	Normal and tangential contact stiffnesses
E_m	Young's modulus of the particle material
φ	Contact friction angle
D_{\min}, D_{\max}	Minimum and maximum diameters of coarse particles
d_{\min}, d_{\max}	Minimum and maximum diameters of fine particles
G_r	Gap ratio
e	Global void ratio
e_f	Interfine void ratio
e_c	Intergranular void ratio
e_{retained}	Void ratio of retained particles
D_R	Relative density
V_v, V_s	Void and solid volumes
σ	Stress tensor
p	Mean stress
q	Deviatoric stress
ε	Strain tensor
ε_{11}	Axial strain
ε_v	Volumetric strain

REFERENCES

- [1] H. Taha, N.S. Nguyen, D. Marot, A. Hijazi and K. Abou-Saleh, *Micro-scale investigation of the role of finer grains in the behavior of bidisperse granular materials*. Granular Matter 21.2 (2019): 28.
- [2] S. Thevanayagam and S. Mohan, *Intergranular state variables and stress-strain behaviour of silty sands*. Geotechnique 50.1 (2000): 1-23.
- [3] B. Seif El Dine, *Etude du comportement mécanique des sols grossiers à matrice*. Diss. Ecole nationale des ponts et chaussées (France), 2007.
- [4] D.M. Wood Muir and K. Maeda, *Changing grading of soil: effect on critical states*. Acta Geotechnica 3.1 (2008): 3-14.
- [5] C. Salot, P. Gotteland, and P. Villard, *Influence of relative density on granular materials behavior: DEM simulations of triaxial tests*. Granular matter 11.4 (2009): 221-236.
- [6] C.O.R. Abbireddy and C.R.I. Clayton, *Varying initial void ratios for DEM simulations*. Geotechnique 60 (6) (2010) 497-502.
- [7] Y.J. Liu, G. Li, Z.Y. Yin, C. Dano, P.Y. Hicher, X.H. Xia and J.H. Wang, *Influence of grading on the undrained behavior of granular materials*. Comptes Rendus Mécanique 342.2 (2014): 85-95.
- [8] R. Deluzarche, B. Cambou and J. Fry, *Modeling of rockfill behavior with crushable particles*. Numerical Modeling in Micromechanics via Particle Methods. Routledge, 2017. 219-224.
- [9] U.S Army Corps of Engineers (1970), *Laboratory soils testing*. Engineer Manual EM (1110 - 2 - 1906).
- [10] V.H. Torrey and R.T. Donagh, *Strength parameters of earth-rock mixtures*. Proceedings of the eleventh International Conference on Soil Mechanics and Foundation Engineering. San Francisco (1985), Vol. 2, pp. 1073-1076.
- [11] L.S. Pedro, J.C Dupla, J. Canou, L. Dormieux and Y. Kazan. *Comportement mécanique d'un sol grossier à matrice sous cisaillement monotone*. Revue française de géotechnique 112 (2005): 35-42.
- [12] P. Reiffsteck, J. Arbault, N. Sagnard, M. Khay, D. Subrin, C. Chapeau and D. Levacher, *Mesures en laboratoire du comportement mécanique des sols hétérogènes*. Bulletin des laboratoires des ponts et chaussées 268-269 (2007).
- [13] C. Dano, *Comportement mécanique des sols injectés*. Diss. Ecole Centrale de Nantes (ECN), 2001.
- [14] D. Leslie, *Large scale triaxial tests on gravelly soils*. In Proc. of the 2nd Pan-American Conf. on SMFE, Brazil, volume 1, pages 181-202, 1963.
- [15] N. Valle, *Comportement mécanique d'un sol grossier d'une terrasse alluvionnaire de la Seine*. PhD thesis, Caen, 2001.
- [16] J.C. Dupla, L.S. Pedro, J. Canou and L. Dormieux, *Comportement mécanique des sols grossiers de référence*. Bulletin des laboratoires des ponts et chaussées, (268) :31-58, 2007.
- [17] N.L. Andrianatrehina, H. Souli, J.J. Fry, J.M. Fleureau and J. Rech, *Effet des fines sur les paramètres mécaniques consolidés non drainés de matériaux granulaires*. Congrès français de mécanique. AFM, Association Française de Mécanique, 2015.
- [18] W.G. Holtz and H.J. Gibbs, *Triaxial shear tests on pervious gravelly soils*. Journal of the Soil Mechanics and Foundations Division, 82(1) :1-22, 1956.
- [19] W.G. Holtz, *Triaxial shear characteristics of clayey gravel soils*. US Bureau of Reclamation, 1961.
- [20] G. Post, *Design parameters for fills*, in 7th European Conference on Soil Mechanics and Foundations Engineering, Vol. 4, London (1979).
- [21] H. Dendani, *Comportement de matériaux de barrages en terre : étude expérimentale et modélisation*. PhD thesis, Grenoble INPG, 1988.
- [22] V. Šmilauer et al., *Yade Documentation 2nd ed. The YadeProject (2015)*. DOI10.5281/zenodo.34073. <http://yade-dem.org/doc/>.
- [23] T. Murthy, D. Loukidis, J. Carraro, M. Prezzi and R. Salgado, *Undrained monotonic response of clean and silty sands*. Géotechnique57(3), 273-288 (2007).
- [24] R. Salgado, P. Bandini and A. Karim, A., *Shear strength and stiffness of silty sand*. J.Geotech. Geoenviron. Eng.126(5), 451-462 (2000).
- [25] S. Thevanayagam, T. Shenthan, S. Mohan and J. Liang, *Undrained fragility of cleansands, silty sands, and sandy silts*. J. Geotech. Geoenviron. Eng.128(10), 849-859(2002).
- [26] H. Taha, *Mechanical behavior of eroded soils: numerical study based on the DEM*. PhD dissertation, Université de Nantes, 2019.
- [27] P.V. Lade, C.D. Liggio and J.A. Yamamuro, *Effects of non-plastic fines on minimum and maximum void ratios of sand*. Geotechnical testing journal 21 (1998): 336-347.
- [28] B. Seif El Dine, J.C. Dupla, R. Frank, J. Canou and Y. Kazan, *Mechanical characterization of matrix coarse-grained soils with a large-sized triaxial device*. Canadian Geotechnical Journal 47, no. 4 (2010): 425-438.