

Development and validation of a THermAL Regulated AtMOspheric Simulation Chamber (THALAMOS)

Noureddin Osseiran, Manolis N. Romanias, Alexandre Tomas, Vassileios C Papadimitriou, Frederic Thevenet, Patrice Coddeville

▶ To cite this version:

Noureddin Osseiran, Manolis N. Romanias, Alexandre Tomas, Vassileios C Papadimitriou, Frederic Thevenet, et al.. Development and validation of a THermAL Regulated AtMOspheric Simulation Chamber (THALAMOS). 25th International Symposium on Gas Kinetics and Related Phenomena, Jul 2018, Lille, France. hal-04250537

HAL Id: hal-04250537 https://hal.science/hal-04250537v1

Submitted on 20 Oct 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés. **IMT Lille Douai** École Mines-Télécom

IMT-Université de Lille

Development and validation of a THermAL regulated AtMOspheric Simulation Chamber (THALAMOS)

General Context - Objectives

se; they out any out any ok to the ned and a wide

Smog chambers, are unique tools for investigating crucial atmospheric processes in both gas and heterogeneous phase; they are supposed to provide a controlled, but realistic environment, aiming to simulate atmospheric conditions without any meteorological or emissive impact that occurs in real Atmosphere. Since environmental chambers first designing, back to the mid-1980s, several small- to large-scale facilities have been developed worldwide.

In the framework of the current study, a multi-purpose, medium size, Teflon atmospheric simulation chamber was designed and constructed, **THALAMOS** (**THermAL regulated AtMOSpheric simulation chamber**), that can be operated in a wide

temperature range (-40° to 100° C), at atmospheric pressure (760 Torr). THALAMOS is a unique experimental tool aiming to simulate both extreme outdoor and indoor processes and provide with both kinetic and mechanistic information with regard indoor and outdoor VOCs' Atmospheric degradation. To the best of our knowledge, **THALAMOS** is the first simulation chamber that can be operated in wide temperature range, at least in national level.



Authors

Noureddin Osseiran¹ <u>Manolis N. Romanias¹</u> Alexandre Tomas¹ Vassileios C. Papadimitriou² Frederic Thevenet¹ Patrice Coddeville¹

1: IMT Lille Douai, Université de Lille, Département SAGE, F-59000 Lille, France
2: LAPKIN, University of Crete, 71003 Heraklion, Crete, Greece



THALAMOS: General Description

Parameters	Values
Volume	600 L (Titrated)
Temperature range	235 – 373 K
Light sources	 10 to 20 UV-A (Philips PL-L 24W/10/4P), λ_{max} 365nm 10 to 20 UV-C (OSRAM HNS-L 24W 2G11), λ = 254 nm
Mixing efficiency	< 1 min after reactants injection
Operational conditions	Static (dilution rate <10 ⁻⁷ s ⁻¹) or slow flow
Bath gas	 Zero Air (RH ca. 2% at 293 K) Extra pure zero air (RH < 2ppm, CO, CO₂ < 80 ppb

Temperature response



