



HAL
open science

Transparent electrodes based on GaAs/Au subwavelength gratings for VCSEL applications

Guilhem Almuneau

► **To cite this version:**

Guilhem Almuneau. Transparent electrodes based on GaAs/Au subwavelength gratings for VCSEL applications. VCSEL Day 2023, Sep 2023, Turin (Italie), Italy. 2023. hal-04251127

HAL Id: hal-04251127

<https://hal.science/hal-04251127>

Submitted on 20 Oct 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Transparent electrodes based on GaAs/Au subwavelength gratings for VCSEL applications



N. Monvoisin¹, F. Carcenac¹, A. Lecestre¹, B. Reig¹, S. Calvez¹, O. Gauthier-Lafaye¹, W. Glowadzka², T. Czyszanowski², G. Almuneau¹

1. LAAS-CNRS, Université de Toulouse, CNRS, Toulouse, France

2. Photonics Group, Institute of Physics, Łódź University of Technology, Poland

E-mail: almuneau@laas.fr

We will present the fabrication of a novel approach for transparent electrodes based on a semiconductor deep-subwavelength monolithic high-contrast grating (MHCG) integrated with metal stripes [1]. Two types of combination between GaAs-based MHCG and Au stripes within a deep sub-wavelength grating enable high transmission (>80%), associated with a low sheet resistance, have been measured for TE and TM polarizations respectively in the near-infrared (around 940nm). These structures, that mainly rely on the high refractive index of the employed semiconductor, can be optically designed as highly transparent or highly reflective, in a broad spectral range below the semiconductor band-gap. Electrical injection uniformity in optoelectronics devices such as LED or VCSEL could strongly benefit from this new approach.






Fig. 1 Fabrication and optical characterization of semiconductor-metal deep-subwavelength gratings. (a,c) TE configuration with metal stripes in the grating grooves. (b,d) TM configuration with metal stripes above the grating ridges.

The authors acknowledge the support of the ANR M-ERANET TRAVEL project (ANR-20-MERA-0002), and the LAAS cleanroom facilities part of the French RENATECH network.

References

- [1] T. Czystanowski, A.K. Sokół, et al. "Transparent Electrode Employing Deep-Subwavelength Monolithic High-Contrast Grating Integrated with Metal", *Optics Express* **28.19**, 28383 (2020).