

Polypropylene cracking on embryonic and ZSM-5 catalysts – An operando study

Karolina Tarach, Mariame Akouche, Kamila Pyra, Valentin Valtchev,

Gabriela Jajko, Jean-Pierre Gilson, Kinga Góra-Marek

▶ To cite this version:

Karolina Tarach, Mariame Akouche, Kamila Pyra, Valentin Valtchev, Gabriela Jajko, et al.. Polypropylene cracking on embryonic and ZSM-5 catalysts – An operando study. Applied Catalysis B: Environmental, 2023, 334, pp.122871. 10.1016/j.apcatb.2023.122871. hal-04270575

HAL Id: hal-04270575 https://hal.science/hal-04270575

Submitted on 4 Nov 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

1	POLYPROPYLENE CRACKING ON EMBRYONIC AND ZSM-5 CATALYSTS – AN
2	OPERANDO STUDY
3 4	Karolina A. Tarach ¹ , Mariame Akouche ² , Kamila Pyra ¹ , Valentin Valtchev ² , Gabriela Jajko ^{1,3} , Jean-Pierre Gilson ² , Kinga Góra-Marek ^{1*}
5	¹ Faculty of Chemistry, Jagiellonian University in Krakow, Gronostajowa 2, 30-387 Krakow
6 7	² Normandie Université, ENSICAEN, UNICAEN, CNRS, Laboratoire Catalyse & Spectrochimie, 14000, Caen, France
8 9 10	³ Doctoral School of Exact and Natural Sciences, Jagiellonian University in Krakow, Łojasiewicza 11, 30- 348 Krakow
11	ABSTRACT
12 13 14 15 16	A series of ZSM-5 zeolites (embryonic, microporous, hierarchical) is studied in the catalytic cracking of polypropylene in the framework of its chemical recycling. Two important zeolite features impact their catalytic performances and allow their design as efficient catalysts: their porosity and acidity. They also play a key role in catalyst deactivation and regeneration. A detailed thermogravimetric and spectroscopic (<i>operando</i> FT-IR) analysis of the reaction, including catalyst coking and regeneration,
17 18	shows the emergence of rules to design fit-for-purpose catalysts to be used in existing or grass-roots FCC units.
19 20	
21	
22	
23	
24	
25	
26	
27	

28 1 INTRODUCTION

29 A wide variety of plastics meet the requirements of many segments of the economy in a cost-30 competitive way. Polypropylene (PP) and polyethylene (PE) are the most common type of polyolefins, 31 and their 2022 market size is nearly USD 300 billion with a predicted 5% CAGR (Compound Annual 32 Growth Rate) till 2030 [1]; they account for more than 2/3 of the annual plastics production. One 33 application, consumer product packaging, is in direct daily contact with people, *i.e.*, each of us. A so 34 far inefficient collection of these and all non-biodegradable plastics generates an unsustainable 35 amount of severe pollution, marine plastics being the highly visible tip of this iceberg. Currently, only 36 16 % of plastic waste is reused to make new plastics, with less than 1% chemically reprocessed to provide the original building blocks, i.e., a true circular economy. So, a large proportion of plastics is 37 38 either left scattered in nature, landfilled, mechanically (down)recycled, or incinerated [1]. 39 Depolymerization back to the original monomers is ideally the best approach to chemical recycling and 40 is already taking place for some polyamides and polyesters. It is not yet the case for polyolefins, 41 although they contribute significantly to plastic waste. Their thermal cracking produces a broad range 42 of hydrocarbons requiring further processing to meet the requirements of transportation fuels or 43 higher value (petro)chemicals [2]. Catalysis has a role to play in solving such an important societal 44 challenge. Catalytic cracking, for instance, could bring a combination of higher activity and better 45 selectivity control (narrower product distribution requiring less downstream processing) while working 46 under milder operating conditions (e.g., temperature). All these features indicate potential economic 47 benefits; moreover, catalytic solutions could benefit from the vast experience of existing processes 48 (e.g., FCC [Fluid Catalytic Cracking]), practiced and optimized over at least 70 years on a large scale. 49 Catalytic cracking of polyolefins (polyethylene PE, polypropylene PP) to produce their olefinic 50 monomers has already received attention in previous studies using zeolites [3]. They deserve special 51 attention as their acid sites located in well-defined micropores (~ 0.5-1.0 nm) contribute greatly to the 52 upgrading of heavy oil fractions (atmospheric and vacuum residues) to gasoline (C₅₋₁₁) and/or lower olefins (C₃₋₅) [4]. Polyolefins are intrinsically a less complex feedstock than heavy oil fractions as they 53 54 are made mostly of C-C and C-H bonds while heavy oil fractions contain significant amounts of S, N, 55 metals (Fe, Ni, V...) spread between many high molecular weight hydrocarbons with high C/H ratios (e.g., polyaromatics) poisoning many catalysts. The downside of zeolites is the presence of severe 56 57 diffusion limitations resulting in limited use of all their potential "active" sites when bulky molecules are involved. One of the earliest explored remedies is the design of hierarchical zeolites where 58 59 connected mesopores are added post-synthesis to the pristine micropores, a so-called top-down 60 route. An alternative bottom-up strategy is to synthesize small zeolite crystals, the so-called nano-61 zeolites [5]. Another promising approach could be based on the so-called embryonic zeolites (EZ) [6,7]; 62 these X-Ray amorphous materials, harvested in the early stages of zeolite synthesis, lack the long-range order of zeolites, but their active sites are more accessible enabling the conversion of bulky molecules 63 64 such as 1,3,5 – triisopropylbenzene (TiPBz, kinetic diameter: 1.1 nm) as their pore size can be 65 engineered in a wider range (1-2.5 nm) [8]. While TiPBz can also be dealkylated on μ m-sized ZSM-5, 66 this can only occur on the very few acid sites present on the external surface of the crystals. EZ also possess an advantage over amorphous Silica-Aluminas (ASA) as their tetrahedral Al is more resilient to 67 thermal treatments and therefore keep more of their original acidity due to a reduced dealumination. 68 69 EZ could therefore extend the range of applications of current zeolites in the processing of polyolefins 70 [9].

The present work investigates for the first time the potential use of these acidic X-ray amorphous EZ to deconstruct polypropylene into useful lower molecular weight molecules. They are compared to a purely microporous ZSM-5 and hierarchical zeolites produced by caustic leaching biased towards desilication [8]. Particular attention is paid to the effect of acid site strength (related to the confined environment) and pore dimensions.

76 2 EXPERIMENTAL

77 2.1 Materials

78 EZ-ZSM-5 and H-ZSM-5

The embryonic zeolite was prepared according to the procedure described in ref. 7, using a gel with a Si:Al ratio of 50 and tetrapropylammonium (TPA) as a structure-directing agent. This embryonic zeolite is hereinafter referred to as EZ-ZSM-5. The fully crystalline counterpart of EZ, herein denoted as H-ZSM-5, was obtained from the same initial system after crystallization at 150°C for 2 days.

83 Hierarchical zeolites

84 Two hierarchical zeolites are derived from a common ZSM-5 (CBV 28014, Si/Al = 150, Zeolyst 85 International) by leaching it with 0.2 M and 0.5 M NaOH solutions at 65 °C for half an hour [10]. 86 Typically, 100 ml of the alkaline solutions are added to 3.0 g of zeolite. After each treatment, the 87 suspension is cooled in an ice-bath and filtered. The resulting hierarchical zeolites are washed with 88 deionized water until neutral pH, ion-exchanged four times with a 0.5 M NH₄NO₃ solution at 60 °C for 89 1 h then filtered, washed, and dried at room temperature. The two resulting materials are referred to 90 as deSi-0.2-ZSM-5 and deSi-0.5-ZSM-5, where x in deSi-x-ZSM-5 indicates the NaOH concentration in 91 solution; deSi reminds us that during such an hierarchization, Si is preferentially extracted from the 92 zeolite framework.

93 2.2 Characterization

94 The chemical composition of the catalysts is determined by inductively coupled plasma optical
95 emission spectrometry (ICP-OES, Optima 2100DV, PerkinElmer).

96 The powder X-ray diffractions are recorded on a Rigaku Multiflex diffractometer using the Cu Kα
97 radiation (40 kV, 40 mA).

98 Transmission Electron Microscopy (TEM) of the materials is done on a JEOL-2011F with an acceleration
 99 voltage of 200 kV. Prior to characterization, all samples are dispersed in isopropanol and ultrasonicated
 100 for 30 min and then dropped onto a carbon film on a copper grid.

101 The porosity is measured by nitrogen adsorption/desorption isotherms on a Quantachrome 102 Autosorb–1-MP volumetric analyser. All samples are degassed under 10^{-5} mbar at 350 °C for 24 h 103 before measurement. The specific surface area, S_{BET}, is calculated using the Brunauer-Emmett-Teller 104 method, and the total pore volume (V_{total}) is taken from the nitrogen volume adsorbed at p/p₀ = 0.985. 105 The micropore volume (V_{micro}) is calculated using the *t*-plot method and the mesopore volume (V_{meso}) 106 is BJH adsorption cumulative volume of pores between 1.7 – 30 nm diameter. By anology, the S_{meso} is 107 BJH adsorption cumulative surface area.

The acidic features of the catalysts are assessed by IR monitoring of adsorbed probes (CO and Pyridine). All IR spectra are recorded with a resolution of 2 cm⁻¹ on a Bruker Invenio X FTIR spectrometer fitted with an MCT detector in the range 4000–400 cm⁻¹. The samples are pressed into self-supported wafers (10 mg per 1cm²), placed in an IR cell connected to a vacuum line, activated under vacuum (10⁻⁶ torr) at 500 °C for 1 h and then cooled down to acquire the spectra at room temperature.

113 CO (Linde Gas Poland, 99.95%) is adsorbed at -140 °C up to saturation of the Lewis acidic sites (bands
114 at 2230, 2225 cm⁻¹ and 2190 cm⁻¹) and the appearance of hydrogen-bonded CO to Brønsted Si(OH)Al
115 sites (band at 2175 cm⁻¹).

Pyridine (Py) (Avantor) is adsorbed at 170 °C. Each sample is saturated with Py and the cell evacuated at 170 °C to remove gaseous and physisorbed Py. The Brønsted (BAS) and Lewis (LAS) acid sites concentration are obtained from the integrated area of the adsorbed pyridine bands at 1560–1535 (pyridinium ions, PyH⁺) and 1440–1460 cm⁻¹ (Py-Lewis site adduct) by using extinction coefficients reported earlier [11]. The acid strength is assessed by Py thermodesorption, where all samples are heated to 350 °C, kept there for 10 min, cooled to 170 °C where IR spectra are recorded. The ratio between Py adsorbed at 350 °C and 170 °C describes the acid strength of the various catalysts.

The Brønsted acid sites located on the external and mesoporous surfaces of ZSM-5 are quantified by IR monitoring of the adsorption at 200 °C of 2,6-di-tert-butylpyridine (di-TBPy, Sigma–Aldrich, >97 %, kinetic diameter: 0.8 nm), desorption under vacuum at 200°C (15 min) and cooling down to room temperature. The 1615 cm⁻¹ band intensities of di-TBPyH⁺ (molar extension coefficient 0.50 cm²·µmol⁻¹) are used to quantify the number of di-TBPy-accessible acid sites [12]. The intensity of di-TBPyH⁺ band is calculated from the spectra recorded after di-TBPy adsorption at 200 °C for 15 min, subsequently cooled down to room temperature. All spectra are normalized to a 10 mg weight.

130 **2.3 Catalytic cracking of polypropylene**

131 Low density polypropylene, PP, (Alfa Aesar, Product No.: 42607, Lot No.: P28D047) is crushed, sieved 132 and the ≤250 microns fraction retained for testing. The catalytic cracking of PP takes place in a thermobalance (TGA/SDTA Mettler Toledo). 10 mg of zeolite power is mixed for 10 min with PP (30 133 134 mg) in an agate mortar, 10 mg are transferred to an α -Al₂O₃ crucible in the thermobalance. The polymer cracking takes place within the 30 °C - 600 °C temperature range under a heating rate of 5 135 136 $^{\circ}$ C/min under N₂ flow (80 mL·min⁻¹). The catalyst weight and adsorbed moisture are considered to 137 calculate the degree of conversion and level of coke left on the catalysts. After the reaction, all samples 138 are cooled to 30 °C and then flushed with dry synthetic air (80 mL·min⁻¹). The coke content is the mass 139 change after heating to 800 °C at a rate 30 °C·min⁻¹. For comparative purposes, pure PP is cracked 140 thermally, *i.e.*, without any catalyst. The TGA was connected with GC-MS setup to follow the eluted 141 products.

142 2.4 FT-IR & GC&MS operando

An operando setup is used to study the PP degradation. A self-supporting disc (ca. 5.5-6 mg·cm⁻²) of 143 144 the catalyst and PP in 1:1 ratio is placed in a 2 cm³-volume quartz IR cell (MeasLine, 145 www.measline.com, patent PL232633, Poland). The homogeneity of the zeolite/catalyst mixtures is 146 identical to the TGA setup and the room temperature IR spectra are normalized to the same intensity 147 of the overtone bands ($2050-1800 \text{ cm}^{-1}$). As in each spectrum, the intensity of the 2960 cm⁻¹ (–CH₃) and 2925 cm⁻¹ (–CH₂) bands are similar, an equal amount of catalyst can be assumed. During the 148 149 reaction, the catalyst surface as well as the gas phase are monitored simultaneously, Figure 1. N_2 , the 150 carrier gas (flowrate = 30 ml/min, 110°C) is introduced along Teflon lines (1/16") and the operando IR 151 cell with the catalyst/PP wafer heated from room temperature to 250 °C (ramp of 10 °C ·s⁻¹) till full 152 polymer conversion. Time-resolved spectra are collected on the FT-IR spectrometer and the products simultaneously analysed by mass spectrometry (MeasLine, www.measline.com, RGA200) and gas 153 154 chromatography (Agilent Technologies 7890B). Coke and tars are included to compute catalyst 155 selectivity.





Figure 1. Operando IR cell fed by independently controlled flowing gases (1), coupled to four detectors: IR
spectrometer (2), IR gas cell (3), GC-MS (4).

159 2.5 2D COS analysis of FT-IR spectroscopy results

160 Due to the complexity of the polymer cracking, a two-dimensional correlation analysis (2D COS IR) is 161 helpful to monitor both the PP cracking and the subsequent coke combustion on a catalytically active 162 surface. 2D maps with contour plots along two axes (wavenumbers and correlation intensity) enable 163 better monitoring of the reaction as a function of time on stream than conventional 1D spectra with 164 numerous overlapping bands. Typically, a synchronous 2D correlation map highlights simultaneous or coincident events identified by two separate bands (v_1 and v_2) upon an externally triggered 165 166 perturbation, a chemical reaction in this case. A positive v_1 - v_2 correlation indicates a simultaneous 167 increase or decrease in the intensity of these bands, while a negative correlation indicates that the 168 intensity of one band (*e.g.*, v_1) changes at the expense of the other (*e.g.*, v_2).

169

156

170 3 RESULTS AND DISCUSSION

171 **3.1** Characterization of the catalysts: structure, texture & acidity

The catalysts used in PP cracking possess similar or different structural, textural, and acidic properties to better assign their performances to specific features. Figure 2A highlights that EZ-ZSM-5 with a bulk Si/Al ratio of 50 is X-ray amorphous while the purely microporous H-ZSM-5 and hierarchical samples (deSi-0.2-ZSM-5 and deSi-0.5-ZSM-5) all display the MFI-type structure. The deSi-0.5-ZSM-5 hierarchical zeolite and EZ-ZSM-5 have close Si/Al while deSi-0.2-ZSM-5 is less desilicated. The H-ZSM-5 exhibits a type I N₂ adsorption isotherm with a steep nitrogen uptake at low relative pressure, indicating the presence of micropores (< ~1 nm) (Fig. 2 B). Textural mesopores are evidenced by a 179 second uptake at higher relative pressures. EZ-ZSM-5 displays a type I(b) N₂ adsorption isotherm 180 characteristic of larger micropores and/or smaller mesopores (< \sim 2.5 nm) [13]. The micropores in H-181 ZSM-5 and hierarchical zeolites are, as expected, in the 0.50-0.60 nm range. EZ-ZSM-5 has supermicropores (> 0.7 nm), as well as ultra-microporosity (Fig. 2C). The two hierarchical catalysts, 182 183 deSi-0.5-ZSM-5 and deSi-0.2-ZSM-5, display type IV isotherms with mixed H2 and H4 hysteresis loops 184 [14] in the P/P° range 0.5–0.9 indicative of intracrystalline bottlenecked mesopores and mesopores 185 connected to the outer surface. Mesoporosity is more important in the two deSi-x-ZSM-5 and centred 186 around 18 nm (Fig. 2D). No mesoporous characteristic is visible for EZ-ZSM-5. The indexed hierarchy 187 factor (IHF, see Table 1) is helpful as it measures the alteration of textural properties [10], *i.e.* higher 188 IHF indicates a greater share of mesopores while microporosity is preserved and lower IHF witness 189 either an excess in microporosity or mesoporosity. In our case, a high hierarchization degree with 190 preserved microporosity occurs only for deSi-0.5-ZSM-5 (IHF = 0.50).



191

192 Figure 2. A) XRD powder patterns. B) N₂ adsorption–desorption isotherms. C) Micropore size distributions. D) BJH

193 *pore size distributions.*

196

Table 1. Chemical composition (ICP) and textural properties (N₂ physisorption) data.

	. ,		<u> </u>		<u> </u>	,			
Sample	Si/Alª	V _{total} cm ³ g ⁻¹	V _{micro} b cm³g⁻¹	V _{meso} c cm³g⁻¹	S _{BET} m²g⁻¹	S _{micro} m²g ⁻¹	S _{meso} m²g ⁻¹	IHF ^d	
EZ-ZSM-5	50	0.30	0.26	0.05	601	575	78	0.34	
H-ZSM-5	65	0.62	0.19	0.11	535	447	78	0.25	
deSi-0.2-ZSM-5	124	0.40	0.15	0.15	433	335	98	0.25	
deSi-0.5-ZSM-5	48	0.49	0.13	0.34	393	278	156	0.36	

197 b: t-plot method with thickness between 4 and 9.2Å, P/P° (0.05, 0.8)

198 c: DFT

a: ICP

199 d: IHF (index hierarchy factor) calculated as $(V_{micro}/V_{micro,max}) \times (S_{meso}/S_{meso,max})$ [10].

TEM micrographs are gathered in Figure 3. H-ZSM-5 consists of 400 nm aggregates, while EZ-ZSM-5 shows *ca.* 3-8 nm featureless aggregates. The mildly desilicated deSi-0.2-ZSM-5 shows uniform mesopores from the external surface to the interior of the zeolite microporosity. The more severely leached deSi-0.5-ZSM-5 consists of core–shell particles with macropores on its external shell and zeolite mesoporosity elsewhere. The presence of Al-rich external layer can be anticipated form dense shell displayed in deSi-0.5-ZSM-5. These features are consistent with N₂ physisorption indicating the presence of macro- and meso-porosity in deSi-0.5-ZSM-5.



207

208 Figure 3. Transmission electron microscopy images.

Figure 4A shows the IR spectra of silanols and bridged hydroxyls on all catalysts. EZ-ZSM-5 stands out with the highest population of isolated (SiO)₃Si-OH (3756 cm⁻¹) and internal (3715 cm⁻¹) silanols together with many hydrogen-bonded silanols (broad band around 3510 cm⁻¹). As expected, the silanol population in the two desilicated zeolites is higher than their parent and the increased intensity of isolated Si-OH follows the increasing mesoporous area of deSi-0.5-ZSM-5 and deSi-0.2-ZSM-5 [15]. The bridging hydroxyls, Si(OH)Al, located between 3615-3605 cm⁻¹ on the three crystalline zeolites are absent on EZ-ZSM-5, a common feature on amorphous aluminosilicates where a wider spread of T-O-

- 216 T angle leads to negligible intensities of the corresponding Si(OH)Al bands [16]. A more precise analysis
- of the surface acidity is worth exploring as silanols can sometimes display acidity in the range of
- 218 bridged hydroxyls and therefore promote hydrocarbon transformation as cracking and coking [17].



226

Figure 4. IR spectra: (A) pristine O-H groups (25 °C) and (B) CO adsorbed on acid sites (-100 °C).

221 *Table 2.* Acidity parameters of the catalysts.

Sample	Si/Al	C _{BAS} ª µmol g⁻¹	C _{LAS} ^a µmol g⁻¹	$C_{BAS} + C_{LAS}^a$ $\mu mol \ g^{-1}$	AF _{BAS} b %	^V OH ^C cm ⁻¹	BAS ^d A ₃₅₀ /A ₁₇₀	LAS ^d A ₃₅₀ /A ₁₇₀
EZ-ZSM-5	50	40	30	70	69	-	0.25	0.30
H-ZSM-5	65	115	25	140	3	3610	0.42	0.80
deSi-0.2-ZSM-5	124	95	32	127	50	3605	0.61	0.65
deSi-0.5-ZSM-5	48	140	140	280	33	3615	0.15	0.75

a: Brønsted (C_{BAS}) and Lewis (C_{LAS}) sites concentration determined by FTIR (Py adsorption)

b: Brønsted acid sites accessibility factor (AF_{BAS}), i.e., % of acid sites accessible to di-TBPy vs. C_{BAS} accessible to Py

227 Acid site concentration and strength is measured by FTIR monitoring of Py adsorption (Table 2). The 228 EZ-ZSM-5 and highly mesoporous deSi-0.5-ZSM-5 possess the highest number of LAS, namely 43-50% 229 of the total acidity. The origin of this important Lewis acidity on the embryonic and hierarchical zeolites is further examined by CO adsorption monitored by FT-IR (Fig. 4B). The CO spectra on EZ-ZSM-5 shows 230 a band at 2190 cm⁻¹ indicative of its interaction with minor fraction of LAS of weak and/or moderate 231 232 strength, *i.e.*, extra-framework aluminium species (EFAL species). We showed earlier that after 233 calcination (refs 6, 7), only a minor quantity of Al is octahedrally coordinated, in contrast to what happens to conventional ASA's (amorphous silica alumina's) [18]. On deSi-0.5-ZSM-5, bands at 2225-234 235 2220 cm⁻¹ witness the presence of coordinatively unsaturated of alumina clusters (EFAL species, LAS) with high strength formed after dehydroxylation of two neighbouring Si(OH)Al species [19,20]. On H-236

c: strength of the acidic Si(OH)AI measured by the band shift upon hydrogen bonding with CO at -100 °C (spectra not shown)
 d: Brønsted and Lewis sites strength (A₃₅₀/A₁₇₀) determined by FTIR (Py adsorption)

237 ZSM-5 and deSi-0.2-ZSM-5, both with lower mesoporosity, Brønsted acidity is prevalent as the relative 238 share of LAS does not exceed 25% (Table 2); they could affect accessibility to the microporous acidity. 239 2,6-di-tert-butylpyridine (di-TBPy) adsorption monitored by FTIR, widely used to measure the Brønsted 240 acidity of the external/mesoporous surface of zeolites [12,21] is reported in Table 2 with the 241 Accessibility Factor (AF_{BAS} = percentage of BAS concentration measured by di-TBPy vs. Py adsorption). 242 As expected, on H-ZSM-5 very few BAS are located on its external surface ($AF_{BAS} = 3\%$) while on deSi-243 0.2-ZSM-5 (high intracrystalline mesoporosity) and EZ-ZSM-5 (high intercrystalline mesoporosity) at 244 least half of the BAS protonate di-TBPy ($AF_{BAS} = 50-69\%$). DeSi-0.5-ZSM-5, with the highest IHF (Table 245 1) has the lowest AF_{BAS} of the 3 mesoporous catalysts. Realumination followed by dehydroxylation is 246 the most common explanation of the alteration of acid sites in alkaline leached zeolites [10,19]. The 247 high concentration of LAS on deSi-0.5-ZSM-5 is responsible for micropores clogging and limited 248 accessibility of its BAS.

249 Acid strength is another parameter to consider in zeolitic catalysts. Pyridine thermal desorption, TPD, 250 (A₃₅₀/A₁₇₀, Table 2) indicates a potentially higher acid strength of the BAS in H-ZSM-5. The introduction 251 of mesoporosity in ZSM-5 zeolites reduces the apparent acid strength of protonic sites; they appear 252 "weaker" due to differences in confinement between meso- and micropores [22]. The strength of 253 protonic site can also be influenced by close proximity with extraframework Al and silanols [9,23]. The 254 defect-rich EZ-ZSM-5 follows this rule as a lower protonic acid strength appears. The desilicated 255 zeolites can be also considered less perfect with partially extracted Al near framework atoms. It is the 256 case of deSi-0.5-ZSM-5 with a BAS strength similar to EZ-ZSM-5 while deSi-0.2-ZSM-5 possesses the 257 highest protonic strength due to its higher Si/Al as often reported [24,25]. These trends are also 258 aligned with the stretching frequencies of the Si(OH)Al (v_{OH} , Table 2, Fig. 4A), *i.e.*, the lower v_{OH} , the 259 longer O-H bond, thus higher the acidity of the corresponding proton. As usual, TPD of basic molecules 260 on hierarchical zeolites should be taken with some caution as differences in diffusion pathlengths could 261 affect diffusion/adsorption ratios of the probe and therefore the maximum temperature in the TPD profile of the basic probe [26]. 262

263 3.2 Polypropylene cracking: thermogravimetry and operando FT-IR-GC-MS

The effects of the different textural and acidic properties of the above "ZSM-5 catalysts" are tested in the catalytic cracking of PP (polypropylene). Figure 5A highlights PP conversion (weight loss measured in a thermobalance) as a function of temperature in a typical "Light-off" diagram, along with the thermal cracking of pure PP as a reference. T_{10} and T_{80} (temperature for 10% and 80 % conversion, Fig. 5D) are used as descriptors. The selectivities of the catalysts are measured in an *operando* FT-IR cell fitted with a GC-MS detector (Fig. 5B).



270

271

Figure 5. (A) PP cracking (light-off diagrams) on EZ-ZSM-5, H-ZSM-5 and its two hierarchical zeolites (deSi-0.2ZSM-5 and deSi-0.5-ZSM-5, an "inert" SiO₂ (grey) and thermal cracking (dotted curve). (B) Product distribution
from the catalytic PP cracking. C) T₈₀ variation with BAS (A₃₅₀/A₁₇₀ ratio). (D) Temperature for 10% and 80 %
conversion, T₁₀ and T₈₀, respectively.

276 In the low-temperature range, EZ-ZSM-5 is the most active catalyst, although it has the lowest 277 concentration of acid sites highlighting their higher accessibility coupled with a faster diffusion of 278 reactants and products. Moreover, it cannot be excluded that a portion of the non-bridging silanols 279 could participate in the reaction as their acidity may not be negligible [27]. Indeed, internal H-bonded 280 silanols were already found to be more active and selective compared to external silanols in the 281 Beckmann rearrangement [28]. The EZ sample exhibits the most intense bands at the region typical of hydrogen bonded silanols $(3670 - 3100 \text{ cm}^{-1})$, the involvement of the medium and high acidity silanols 282 283 in cracking process should not be neglected. In line with above, the highest contribution of non-acidic 284 isolated Si-OH (3745 cm⁻¹) in deSi-0.5-ZSM-5 does not offer the significant advancement. [29,30]

285 The presence of an Al-rich layer with many Lewis acid sites in deSi-0.5-ZSM-5, Figures 3 and 4, hampers 286 the diffusion of reactants to the micropores. On deSi-0.2-ZSM-5, with a moderately developed 287 mesopore surface area and low BAS density, the conversion above 350 °C is higher than for other 288 catalysts. A similar critical role of LAS was previously reported by Tarach et al. [19]; a mild 289 dealumination and redistribution of AI on the mesopore surface produces a more open hierarchical 290 porosity. As a result, micropore mouths, free of LAS residues increase BAS accessibility as well as 291 polymer cracking. Verboekend at al. [31] also reported inhibition of LDPE cracking on desilicated ITQ-292 4 at low conversion (10%) due to the presence of excessive amounts of Lewis acid sites.

293 At about 320 °C, PP conversion on EZ-ZSM-5 increases slower than on H-ZSM-5, indicating that BAS 294 accessibility is not the only factor influencing catalyst performance. The linear dependence of T₈₀ PP 295 cracking and BAS strength (A₃₅₀/A₁₇₀) of crystalline zeolites highlights the influence of acidic strength 296 on cracking activity at higher temperature range. On EZ-ZSM-5, the reduced acidic strength due to 297 lower confinement is not compensated by a higher BAS accessibility. For instance, in n-decane cracking 298 on zeolite Beta, BAS strength is the key factor determining catalytic activity [22]. In LDPE cracking, the 299 porosity of hierarchical Beta zeolites helps when their BAS strength is above 80% of their pristine 300 parent [32,33]. Figs 5 C and D therefore highlight that at low temperature, i.e. at low conversions, 301 where the feedstock is mainly composed of very bulky molecules, active site accessibility is critical 302 while at higher temperatures where reactants are less bulky molecules, "apparent acid strength" will 303 play an increasing role.

304 The quantitative analysis of the PP cracking products by GC-MS shows that on the EZ-ZSM-5 catalyst 305 less C₃-C₄ (gas) and C₅-C₆ (liquid), but more C₇₊ are produced compared to H-ZSM-5 and the two 306 hierarchical deSi-x-ZSM-5. It is therefore expected that a catalyst with a higher but less confined 307 microporosity populated with BAS with lower strength will not favor secondary cracking. Moreover, 308 on EZ-ZSM-5 more bimolecular reactions are expected due to the closer proximity of bulky reactants 309 in larger cavities [34]. These observations are in line with literature reports [34,35] on the applicability 310 of medium and wide pore zeolites in the catalytic degradation of polyethylene and polypropylene. The 311 influence of the micropore volume, also impacts the side and sequential reactions and will appear later 312 (Fig. 7).





Figure 6. Cracking products distribution in C_4 and C_5 fractions: paraffinic (green), olefinic (blue), branched (hatched), and linear (filled).

316 The C₄₋₅ product distribution highlights how the structural/textural and acidic properties influence PP 317 cracking selectivity (Fig. 6). The hydrogen-transfer (HT) ability of zeolites is known to increase with 318 micropore voids size and BAS density, in turn influencing the paraffin/olefin (p/o) ratio of the products 319 [36,37] . DeSi-0.2-ZSM-5 and deSi-0.5-ZSM-5 zeolites display a lower HT and therefore produce more 320 olefins in PP cracking. The large external surface and better acid sites accessibility in hierarchical 321 catalysts limit the extent of secondary HT reactions as those are favoured by long reactions paths. This 322 is the case for deSi-0.2-ZSM-5 producing the highest level of olefins. However, for deSi-0.5-ZSM-5, 323 despite more macro- and meso-porosities, its higher BAS and LAS density promotes HT [38], therefore 324 producing more paraffins. Moreover, LAS are also reported to interact with BAS to increase the acid strength of the latter (Table 2) [39,40]. 325

EZ-ZSM-5 also increases isomerization (C4 and C5 fractions) following a bimolecular mechanism (HT 326 reactions) in the more spacious voids of its partially formed unit cells. The high silanols population, 327 which could possess some non-negligible acidity, vide supra, can also favor high iso-paraffin 328 329 production. The inhibition of isomerization (an HT reaction) by shortening the reaction pathlength 330 upon secondary intercrystalline or intracrystalline mesoporosity addition is observed on H-ZSM-5 and 331 hierarchical samples. Corma et al. [41] reported that the Si/Al ratio determines the extent of 332 bimolecular reactions by regulating carbenium ion residence times on the surface. The higher 333 production of iso-C₄ and iso-C₅ paraffins in EZ-ZSM-5 could be ascribed to such a feature. Another source for higher p/o ratio is dehydrogenation reactions to aromatics all the way to coke [42], as the 334 hydrogen produced can saturate olefins, albeit to a minor extent, as little hydrogen is available from 335 336 such a route [38].

In PP cracking, EZ-ZSM-5 behaves more like a FAU than an MFI structure. In addition, some EZ-ZSM-5
 acidic silanols could also play a role as already reported in zeolites for C₈-olefins and polypropylene

[37]. The hierarchical deSi-0.2-ZSM-5 behaves as a zeolite with high acid strength, low acid site density,
and microporous confinement leading to low initial conversions (low T) and limited HT. This results in
lower p/o ratio and limited coke formation.

342 **3.3** Polypropylene cracking and catalyst coking: 2D COS operando FT-IR spectroscopy

The above results are classically produced by relating catalyst characterization to their performances without inspecting the catalyst surface during the reaction. An *operando* study allows to go further and closer to the catalyst surface while in action under realistic conditions of temperature and pressure. The 2D-COS IR technique is particularly suited as it correlates events taking place on the catalyst surface by looking simultaneously at active sites on the catalyst and reactants/products.

348 Time-resolved FT-IR, already proven helpful in hydrocarbon transformations [43,44] is applied here to 349 monitor simultaneously PP cracking and the catalyst surface (Fig. 7). By following the Av(-CH₃)/Av(-350 CH_2) PP ratio evolution during reaction, where $Av(-CH_3)$ and $Av(-CH_2)$ represent the intensities of the 351 of $-CH_3$ (2960 cm⁻¹) and $-CH_2-$ (2925 cm⁻¹) bands characteristic for the surface adsorbed species, the 352 influence of the different catalysts is evidenced. The CH₂/CH₃ intensity ratio is widely used to estimate 353 the length and degree of branching of the aliphatic side-chains; the larger this ratio, the longer the 354 aliphatic chain [45–47]. EZ-ZSM-5 is the most active in end-chain cracking at the earliest stages of the 355 reaction (0-3 min), goes through a maximum before decreasing rapidly due to the formation and 356 retention of heavy by-products (coke precursors), leading to deactivation. Such a deactivation step is 357 not observed on deSi-0.2-ZSM-5 where the $Av(-CH_3)/Av(-CH_2)$ ratio decrease is minimal, and a high 358 proportion of light hydrocarbons is produced.

359 The cracking efficiency is easily seen on 2D COS maps (Figure 8A). The positive cross-peaks on 2D COS 360 maps, spreading from 1475–1425 cm⁻¹ and 1383–1345 cm⁻¹ are more intense on the X-Ray amorphous 361 EZ-ZSM-5 than on the other crystalline catalysts where cross-peaks are centered at 1461 and 1383 cm^{-1} . The positive correlation between the CH₃ and CH₂ deformation bands at *ca.* 1461 and 1383 cm^{-1} 362 363 evidence PP decomposition on the catalysts. A single band developing at 1383 cm⁻¹ is associated with the δ_s (CH₃) mode, whereas the peaks at 1360 and 1345 cm⁻¹ witness the appearance of branched – 364 $CH(CH_3)_2$ and $-C(CH_3)_3$ terminations [48]. As the intensity of the CH_3 deformation bands is always higher 365 366 than CH_2 , the formation of the $CH_3(CH_2)_2CH_2^+$ species is proposed. This further supports the formation 367 of more branched products of partially cracked PP chains on EZ-ZSM-5, while on all other zeolites the 368 linear fragments dominate. Summing up, embryonic zeolites are more active in PO cracking as the 369 higher accessibility of their acid sites more than compensates their lower concentration and strength. 370 Higher bimolecular reaction rate in their supermicropores provides a distinct selectivity to branched hydrocarbons. Contrarily, in desilicated zeolites transition states are not confined and stabilized by van
 der Waals interactions in mesopores and display lower rates in acid-catalyzed PO cracking reactions.

373 The accumulation of coke precursors on 2D COS maps (Fig. 8A) appears as a negative correlation 374 between CH₃/-CH₂ deformation bands (1461/1383 cm⁻¹) and the complex C=C stretching band (1620 -1580 cm⁻¹). A sequence of catalytic events can be derived from a mutual analysis of synchronous (Fig. 375 376 8A) and asynchronous maps (Fig. 8B). The product of asynchronous and synchronous sets is one of the 377 straightforward insight into the interplay between the cracking and coking processes (Fig. 8C). The 378 analysis of the product maps is still based on the principles given by Noda [49]. In EZ-ZSM-5 the first coke precursor is identified by the $v_{(C=C)ring}$ band at 1544 cm⁻¹, typical of polyolefins and methyl-379 380 substituted benzyl cations or polycyclic aromatics characterized by the band centered at 1600-1590 381 cm^{-1} [43,44]. The differentiated intensity of the peaks in product maps related to the CH₃ and CH₂ 382 deformation region, *i.e.*, 1470-1300 cm⁻¹, indicates that PP cracking mechanism is ruled by the acidic and textural properties of the catalysts. The band near 1480-1430 cm⁻¹ is associated with an 383 asymmetric out-of-plane CH₃ deformation, while the ca. 1393-1356 cm⁻¹ represents a symmetric in-384 385 phase CH₃ deformations. When two methyls are bound to one saturated carbon in isopropyl or gem-386 dimethyl groups, two bands with nearly equal intensity appear at 1385 and 1368 cm⁻¹ [50]. T The 1330 387 cm^{-1} band belongs to a C-H bending mode (C₃CH). The most complex picture of CH₃ and CH₂ 388 vibrations is representative of EZ-ZSM-5 and the absence of tertiary C—H bending mode indicates the 389 preservation of longer chains of PP on the EZ-ZSM-5 surface. From the sequential order of events, it 390 can be anticipated that the coke precursors formations (1620 - 1580 cm⁻¹) are continuously integrated 391 with polymer cracking on EZ-ZSM-5. In contrast, H-ZSM-5 and deSi-0.5-ZSM-5 with the same number 392 of Brønsted acid sites activate the cyclization and aromatization processes which precede the cracking 393 of PP; the dominant coke precursors bands are gathered in the 1650-1580 cm⁻¹ spectral region. In deSi-0.2-ZSM-5, the ultimate processing of PP is coking of the catalyst, as identified by the formation of 394 395 trisubstituted aromatics and/or polycyclic aromatics to a significant extent (1625-1600 cm⁻¹). The 396 catalyst-coking susceptibility is discussed further later.

397

398

399

400



402 Figure 7. Top-projection of 3-D maps (bottom row) of the evolution of C–H stretching band intensity within 15
 403 min of PP cracking. The white curve (top row) represents changes in the CH₃/CH₂ bands area ratio.



Figure 8. 2D COS IR synchronous (A), asynchronous (B) maps and their product (C) illustrating coke formation
408 during PP cracking. The colour coding (inset) represents correlation levels between the respective bands.

412 3.4 Coke burn-off: thermogravimetry and operando FT IR-TPO-MS

413 As coke deactivation of a catalyst changes its activity and selectivity, understanding the related 414 hydrogen transfer processes is important. An earlier scheme [51] describes successive oligomerization, 415 cyclization, and dehydrogenation of small molecules on active sites located in zeolite pores: alkanes alkenes - oligomers - naphthenes - aromatics - coke. The time evolution of the $Av(-CH_3)/Av(-CH_2)$ in 416 417 Fig. 7, indicates that hierarchical zeolites (deSi-0.5-ZSM-5 and deSi-0.2-ZSM-5) exhibit lower coke 418 formation and slower deactivation. This is due to an easier transport of reactants in the zeolites as well 419 as a lowering of diffusional restrictions on secondary products. The FT-IR 2D COS maps of the PP 420 cracking (Fig. 8) indicate a correlation between polymer chains cracking and the simultaneous 421 formation of unsaturated non-volatile high-carbon species identified by the cross peaks in the 422 $1650-1570 \text{ cm}^{-1}$ region (maximum at ca. 1605 cm⁻¹). This implies that in H-ZSM-5 and deSi-ZSM-5 423 zeolites, coke consists of both methyl-substituted cycloalkenyl carbenium ions species, methyl-424 substituted benzene cations or polycyclic aromatic compounds. Thus a high number of strong BAS 425 promotes condensations and aromatizations [43,52,53]. On EZ-ZSM-5, coke species are more diverse, as in addition to the 1605 cm⁻¹ species, bands in the 1565–1525 cm⁻¹ region attest the presence of 426 427 alkyl aromatics (alkylbenzenes) and conjugated olefinic species (C_nH_{2n+1})⁺ [54,55]. The microporous 428 structure of EZ-ZSM-5 reduces the heavy coke fractions.

429 Coke combustion under air is a common procedure to evaluate its nature and of course to regenerate 430 an industrial catalyst. The amount of coke estimated from TGA is higher on EZ-ZSM-5 (5.5%) than on 431 H-ZSM-5 (1.4%), and the hierarchical deSi-0.2-ZSM-5 (2.1%) and deSi-0.5-ZSM-5 (1.15%). It is related 432 to the coking rates observed on the time evolution of the $Av(-CH_3)/Av(-CH_2)$ ratio (Fig. 7), where EZ-433 ZSM-5 is the highest. Coke oxidation starts on molecules located on the catalyst external surface and 434 then progresses inside the micropores, where oxygen availability becomes key. So, coke on EZ-ZSM-5 435 burns more rapidly than on H-ZSM-5 and deSi-ZSM-5. As the 2D COS IR analysis already showed that 436 coke species on EZ-ZSM-5 are more diverse, this accounts for the three steps (450-555 °C) observed in 437 its light-off curve (Fig. 8). Magnoux and Guisnet [56] already concluded that both coking and coke 438 oxidation are shape-selective reactions. It is commonly agreed that in MFI-type zeolite, carbonaceous compounds formed at channel intersections totally block oxygen diffusion during regeneration. On 439 440 large pore zeolites such as FAU and MOR, oxygen can still diffuse in their micropores. So, despite 441 extensive coking on EZ-ZSM-5, an efficient contact between reactants (coke and oxygen) facilitates 442 regeneration. In deSi-0.2-ZM-5, the denser coke located on its external surface is removed at higher 443 temperatures. The internal coke on deSi-0.2-ZSM-5 burns at still higher temperatures pointing to slow 444 oxygen diffusion in micropores blocked by carbonaceous residues at channel intersections. This result 445 confirms the high toxicity of coke on desilicated zeolites compared to embryonic ones. The high

- 446 micropore volume of EZ-ZSM-5 combined with a low Brønsted acidity prevents coke precursors to
- 447 evolve into heavy toxic coke as found on the crystalline zeolites.



449 *Figure 9.* Coke light-off curves and their derivatives (inset).

450

On deSi-0.2-ZSM-5, stronger retention of coke and its precursors is favored by the presence of stronger 451 452 acid sites. Carbenium ions adsorbed in zeolite micropores are stabilized by framework oxygens, acting 453 as weak bases conjugated with the strong acid sites. Such carbenium ions are less susceptible to 454 desorption as this requires a proton abstraction the carbenium ion, impossible on a weak base. The 455 long residence time of carbenium ions in deSi-0.2-ZSM-5 contributes to coke formation by oligomerization, elimination, and ion-ion disproportionation. On deSi-0.5-ZSM-5, a lower Si/Al 456 457 produces framework oxygen of higher basicity, reducing the rate of bimolecular reactions between 458 adjacent ions by enhancing proton abstraction from the carbenium ion and hence a desorption of 459 olefins (cf. selectivities on Fig. 6). This effect is more significant than faster diffusion resulting from the 460 greater mesoporosity of deSi-0.5-ZSM-5. In the case of EZ-ZSM-5 more coking and significantly higher 461 production of *iso*-C₄ and *iso*-C₅ paraffins indicate faster hydrogen, not due to a higher BAS strength but 462 by the more open voids in EZ-ZSM-5, akin to those found in extra-large microporous materials. This 463 nature of coke in EZ-ZSM-5 is detailed in their TGA profiles, and IR explains its removal by combustion.

Silanols also impact catalyst deactivation, as observed on EZ-ZSM-5 and deSi-0.2-ZSM-5, the two materials with the highest population. The highest level of coke observed is on EZ-ZSM-5 where internal silanols are predominant, while on deSi-0.2-ZSM-5 with external silanols, coke and deactivation are lower. It highlights further that different types of silanols have a direct influence on coke formation and its preferential location on the most acidic silanols, as observed elsewhere [37]. While in mildly hierarchical deSi-0.2-ZSM-5 coking is driven by strong BAS located in the native 470 microporosity, in X-ray amorphous EZ-ZSM-5, acidic internal silanols and a higher microporosity471 promote a higher degree of coking.

472 Further information on the coke nature is provided during an operando IR-TPO-MS monitoring of coke 473 removal (Fig. 10). CO_2 and H_2O formed during the temperature-programmed oxidation (TPO, 5% of O_2 474 in N_2) of carbonaceous species are monitored by mass spectrometry. TPO is performed at 300, 350, 475 400, 450, 500, and 550 °C; at each temperature, a 10 min isotherm step is maintained before increasing 476 the temperature further at a rate of 10 °C/min. Only the corresponding 2D COS IR maps highlighting 477 changes in spectral features during regeneration at 300 °C and 500 °C are discussed further (Figure 10). 478 In the case of catalysts with high microporosity, H-ZSM-5 and EZ-ZSM-5, H_2O (m/z = 18) production is 479 maintained throughout the process and greatly exceeds CO₂ production. On the hierarchical zeolites, 480 deSi-0.2-ZSM-5 and deSi-0.5-ZSM-5, less H₂O is produced at a slightly higher level than CO₂. The high 481 level of water production in the first stages of the TPO is associated with the burning of unreacted PP 482 (conversion under isothermal operando conditions at 250 °C does not reach 100%). This is illustrated on 2D COS IR maps of coke combustion at 300 °C. The observed correlations between the C=C 483 484 stretching modes (1605 cm⁻¹) and asymmetric (1425 cm⁻¹) or symmetric modes of alkyl groups (1340 485 cm⁻¹) in aliphatics and alkyl aromatics indicates the presence of hydrocarbons with high H/C on the 486 external surface of H-ZSM-5 and EZ-ZSM-5. For deSi-0.5-ZSM-5 and deSi-0.2-ZSM-5, with added 487 intracrystalline mesoporosity, a much lower H₂O/CO₂ ratio is observed during the entire TPO, 488 indicating coke with lower H/C is combusted. The 2D COS IR maps of desi-0.5-ZSM-5 and desi-0.2-ZSM-489 5 do not show any significant correlation between C=C and alkyl vibration during combustion at 300 490 °C. The CO₂ and H₂O production in the final stages of coke combustion is constant on all the catalysts, 491 albeit significantly higher for EZ-ZSM-5 and H-ZSM-5. This also appears in the 2D COS IR maps during 492 coke oxidation at 500 °C (Fig. 10). The patterns in the synchronous spectrum of the CH_3 and CH_2 493 deformation modes (1380–1340 cm⁻¹) are referred to as "angel" patterns with cross peak wings. They 494 appear when bands shift to higher frequencies together with some intensity increase, usually the result 495 of recording spectra at increasing temperatures. In our case, since temperature remains constant, 496 temperature-induced shift of the CH₃ band can be excluded. Such angel patterns are thus not artifacts 497 but reflect complex spectral changes in position and line shape of IR bands related to coke species. All 498 changes are, therefore, due to the interaction of oxygen with the carbonaceous species. The angel 499 pattern involves terminal CH₃ symmetric mode (1383 cm⁻¹) and branched $-CH(CH_3)_2$ and $-C(CH_3)_3$ 500 terminations (1360 and 1345 cm⁻¹, resp.). A longer contact time between the spent catalyst and oxygen 501 increases the conversion of -CH₃ from branched ramifications to terminal isolated methyl groups. 502 Independently from the catalyst, coke oxidation is therefore initiated on methyl groups forming 503 oxygenated intermediates further decomposed into CO₂.

504 Correlation peaks are observed between polyaromatics (the C=C stretching modes at 1605 cm⁻¹) and 505 methyl groups (1400–1325 cm⁻¹) in H-ZSM-5 and hierarchical materials, while no such correlation 506 appear in the with EZ-ZSM-5; only very weak correlations between aliphatics and conjugated olefins 507 (1525–1480 cm⁻¹) appear. While in H-ZSM-5 and mesoporous deSi-0.2-ZSM-5 and deSi-0.5-ZSM-5 coke 508 oxidation are initiated on the –CH(CH₃)₂ and –C(CH₃)₃ groups on aromatic rings, on EZ-ZSM-5 oxidation 509 starts on alkyl species, as the aliphatics decrease independently of the coke.

510



Figure 10. TPO of coked catalysts illustrated as the mass signal intensity of the CO_2 (m/z = 44) and H_2O (m/z = 18)

evolved gases at increasing temperatures (A). 2D COS IR synchronous maps of correlated events during coke oxidation at 300 °C (B) and 500 °C (C). The colour coding represents the correlation between the respective bands

- (insets).

519 CONCLUSIONS

520 This study highlights the complexity of a model polyolefin (PO), pure polypropylene, cracking on 521 various forms of the H-ZSM-5 zeolite, namely an embryonic, a purely microporous, and hierarchical 522 ones. Two zeolite parameters play complementary roles, namely porosity, and acid site strength 523 related to confinement. Our paper shows that FCC type of catalysts are a good basis to design a PO 524 depolymerization process. Highly accessible acid sites in EZ-ZSM-5 are required to attack the bulky 525 polymer and protons confined in micropores take advantage to bimolecular reactions to fine-tune 526 selectivity towards final products. Therefore, we need to work with well-defined and controlled 527 catalysts to understand the mode of action of poorly described FCC catalysts (the patented preparations are never mentioned in the open literature when commercial FCC catalysts are used to 528 529 crack PO).

530 The complexity is also a source of opportunities to design catalysts dedicated to the chemical recycling 531 of polyolefins in an FCC type of process. The rapid but reversible catalyst deactivation followed by its 532 regeneration makes PP chemical recycling to fuel or petrochemical possible in existing and already 533 optimized FCC units.

534 The overall methodology sheds light on the chemistry of the process, including catalyst regeneration. 535 The relative role of the microporous and mesoporous surfaces of zeolites are highlighted and the 536 operando FT-IR study can be used at two levels: 1) understanding the fundamentals of the intricate 537 catalyst reactants/products interactions during the reaction, and 2) fingerprinting the catalyst behavior 538 to better optimize its design. The evaluation of the processing of PO in FCC should not be limited to 539 MFI type zeolites, but others like FAU (used in current FCC catalysts), BEA... should be considered or 540 mixtures thereof. It is probable that if such catalytic PO recycling takes place in existing or grass-root 541 FCC units, many options exist to fine-tune the design of drop-in catalysts by combining the presence 542 of various zeolites or amorphous components, as already practiced in the processing of heavy and 543 highly polluted oil fractions [4]. As in the current FCC operations, the heat requirements of the 544 (endothermic) cracking can be met by the (exothermic) coke combustion with the catalyst 545 microspheres playing the role of the heat transfer fluid.

546

547 ACKNOWLEDGEMENTS

This research was funded in whole or in part by National Science Centre, Poland [the Grant No 2021/43/B/ST4/00307]. For the purpose of Open Access, the author has applied a CC-BY public copyright licence to any Author Accepted Manuscript (AAM) version arising from this submission. The

- study was carried out using research infrastructure purchased with the funds of the European Union
- 552 in the framework of the Smart Growth Operational Programme, Measure 4.2; Grant No.
- 553 POIR.04.02.00-00-D001/20, "ATOMIN 2.0 ATOMic scale science for the INnovative economy". The

554 open-access publication of this article has been supported by a grant from the Faculty of Chemistry

under the Strategic Programme Excellence Initiative at Jagiellonian University.

556 References

- T. Hundertmark, C. McNally, T.J. Simons, H. Vanthournout, No time to waste: What plastics recycling
 could offer, McKinsey Chem. (2018).
 https://doi.org/https://www.mckinsey.com/industries/chemicals/our-insights/no-time-to-waste-what plastics-recycling-could-offer.
- 561 [2] Y. Wang, Y. Zhang, H. Fan, P. Wu, M. Liu, X. Li, J. Yang, C. Liu, P. Bai, Z. Yan, Elucidating the structure562 performance relationship of typical commercial zeolites in catalytic cracking of low-density
 563 polyethylene, Catal. Today. 405–406 (2022) 135–143. https://doi.org/10.1016/J.CATTOD.2022.06.024.
- 564 [3] Y.H. Seo, K.H. Lee, D.H. Shin, Investigation of catalytic degradation of high-density polyethylene by
 565 hydrocarbon group type analysis, J. Anal. Appl. Pyrolysis. 70 (2003) 383–398.
 566 https://doi.org/10.1016/S0165-2370(02)00186-9.
- 567 [4]W. Vermeiren, J.-P. Gilson, Impact of Zeolites on the Petroleum and Petrochemical Industry, Top. Catal.56852 (2009) 1131–1161. https://doi.org/10.1007/s11244-009-9271-8.
- 569 [5] S. Mintova, J.-P. Gilson, V. Valtchev, Advances in nanosized zeolites, Nanoscale. 5 (2013) 6693–6703.
 570 https://doi.org/10.1039/C3NR01629C.
- 571 [6] K.-G. Haw, J.-M. Goupil, J.-P. Gilson, N. Nesterenko, D. Minoux, J.-P. Dath, V. Valtchev, Embryonic ZSM572 5 zeolites: zeolitic materials with superior catalytic activity in 1,3,5-triisopropylbenzene dealkylation,
 573 New J. Chem. 40 (2016) 4307–4313. https://doi.org/10.1039/C5NJ03310A.
- 574 [7] K.-G. Haw, J.-P. Gilson, N. Nesterenko, M. Akouche, H. El Siblani, J.-M. Goupil, B. Rigaud, D. Minoux, J.575 P. Dath, V. Valtchev, Supported Embryonic Zeolites and their Use to Process Bulky Molecules, ACS
 576 Catal. 8 (2018) 8199–8212. https://doi.org/10.1021/acscatal.8b01936.
- 577 [8] M. Akouche, J.-P. Gilson, N. Nesterenko, S. Moldovan, D. Chateigner, H. El Siblani, D. Minoux, J.-P. Dath,
 578 V. Valtchev, Synthesis of Embryonic Zeolites with Controlled Physicochemical Properties, Chem. Mater.
 579 32 (2020) 2123–2132. https://doi.org/10.1021/acs.chemmater.9b05258.
- 580 [9] A. Palčić, S.N. Jaén, D. Wu, M. Cai, C. Liu, E.A. Pidko, A.Y. Khodakov, V. Ordomsky, V. Valtchev,
 581 Embryonic zeolites for highly efficient synthesis of dimethyl ether from syngas, Microporous
 582 Mesoporous Mater. 322 (2021) 111138. https://doi.org/10.1016/J.MICROMESO.2021.11138.
- [10] D. Verboekend, S. Mitchell, M. Milina, J.C. Groen, J. Pérez-Ramírez, Full Compositional Flexibility in the
 Preparation of Mesoporous MFI Zeolites by Desilication, J. Phys. Chem. C. 115 (2011) 14193–14203.
 https://doi.org/10.1021/jp201671s.
- [11] K. Sadowska, K. Góra-Marek, J. Datka, Hierarchic zeolites studied by IR spectroscopy: Acid properties of
 zeolite ZSM-5 desilicated with NaOH and NaOH/tetrabutylamine hydroxide, Vib. Spectrosc. 63 (2012)
 418–425. https://doi.org/10.1016/J.VIBSPEC.2012.09.007.
- [12] K. Góra-Marek, K. Tarach, M. Choi, 2,6-Di-tert-butylpyridine Sorption Approach to Quantify the External
 Acidity in Hierarchical Zeolites, J. Phys. Chem. C. 118 (2014) 12266–12274.
 https://doi.org/10.1021/jp501928k.
- [13] M. Thommes, K. Kaneko, A. V Neimark, J.P. Olivier, F. Rodriguez-Reinoso, J. Rouquerol, K.S.W. Sing,
 Physisorption of gases, with special reference to the evaluation of surface area and pore size
 distribution (IUPAC Technical Report), Pure Appl. Chem. 87 (2015) 1051–1069.

- 595 https://doi.org/doi:10.1515/pac-2014-1117.
- [14] C. Schlumberger, M. Thommes, Characterization of Hierarchically Ordered Porous Materials by
 Physisorption and Mercury Porosimetry—A Tutorial Review, Adv. Mater. Interfaces. 8 (2021) 2002181.
 https://doi.org/10.1002/admi.202002181.
- 599 [15] K.A. Tarach, K. Góra-Marek, J. Martinez-Triguero, I. Melián-Cabrera, Acidity and accessibility studies of
 600 desilicated ZSM-5 zeolites in terms of their effectiveness as catalysts in acid-catalyzed cracking
 601 processes, Catal. Sci. Technol. 7 (2017) 858–873. https://doi.org/10.1039/C6CY02609E.
- K. Góra-Marek, M. Derewiński, P. Sarv, J. Datka, IR and NMR studies of mesoporous alumina and
 related aluminosilicates, Catal. Today. 101 (2005) 131–138.
 https://doi.org/10.1016/J.CATTOD.2005.01.010.
- I.C. Medeiros-Costa, E. Dib, N. Nesterenko, J.-P. Dath, J.-P. Gilson, S. Mintova, Silanol defect engineering
 and healing in zeolites: opportunities to fine-tune their properties and performances, Chem. Soc. Rev.
 50 (2021) 11156–11179. https://doi.org/10.1039/D1CS00395J.
- L. Lakiss, C. Kouvatas, J.-P. Gilson, V. Valtchev, S. Mintova, C. Fernandez, R. Bedard, S. Abdo, J. Bricker,
 Atomic-Insight into Zeolite Catalyst Forming—an Advanced NMR Study, J. Phys. Chem. C. 125 (2021)
 20028–20034. https://doi.org/10.1021/acs.jpcc.1c05501.
- 611 [19] K.A. Tarach, K. Pyra, K. Góra-Marek, Opening up ZSM-5 Hierarchical Zeolite's Porosity through
 612 Sequential Treatments for Improved Low-Density Polyethylene Cracking, Molecules. 25 (2020).
 613 https://doi.org/10.3390/molecules25122878.
- K. Khivantsev, N.R. Jaegers, L. Kovarik, M.A. Derewinski, J.-H. Kwak, J. Szanyi, On the Nature of ExtraFramework Aluminum Species and Improved Catalytic Properties in Steamed Zeolites, Molecules. 27
 (2022). https://doi.org/10.3390/molecules27072352.
- 617 [21] N.S. Nesterenko, F. Thibault-Starzyk, V. Montouilliout, V. V Yushchenko, C. Fernandez, J.-P. Gilson, F.
 618 Fajula, I.I. Ivanova, The use of the consecutive adsorption of pyridine bases and carbon monoxide in the
 619 IR spectroscopic study of the accessibility of acid sites in microporous/mesoporous materials, Kinet.
 620 Catal. 47 (2006) 40–48. https://doi.org/10.1134/S0023158406010071.
- K. Tarach, K. Góra-Marek, J. Tekla, K. Brylewska, J. Datka, K. Mlekodaj, W. Makowski, M.C. Igualada
 López, J. Martínez Triguero, F. Rey, Catalytic cracking performance of alkaline-treated zeolite Beta in
 the terms of acid sites properties and their accessibility, J. Catal. 312 (2014) 46–57.
 https://doi.org/10.1016/J.JCAT.2014.01.009.
- 625 [23] M. Boronat, A. Corma, What is measured when measuring acidity in zeolites with probe molecules?,
 626 ACS Catal. 9 (2019) 1539–1548. https://doi.org/10.1021/acscatal.8b04317.
- 627 [24] A. Primo, H. Garcia, Zeolites as catalysts in oil refining, Chem. Soc. Rev. 43 (2014) 7548–7561.
 628 https://doi.org/10.1039/C3CS60394F.
- [25] J. Dwyer, F.R. Fitch, E.E. Nkang, Dependence of zeolite properties on composition. Unifying concepts, J.
 Phys. Chem. 87 (1983) 5402–5404. https://doi.org/10.1021/j150644a019.
- 631 [26] K. Góra-Marek, I. Melián-Cabrera, A note on the acid strength of porous materials assessed by thermal
 632 methods, Microporous Mesoporous Mater. 310 (2021) 110638.
 633 https://doi.org/10.1016/j.micromeso.2020.110638.
- I.C. Medeiros-Costa, E. Dib, F. Dubray, S. Moldovan, J.-P. Gilson, J.-P. Dath, N. Nesterenko, H.A.
 Aleksandrov, G.N. Vayssilov, S. Mintova, Unraveling the Effect of Silanol Defects on the Insertion of
 Single-Site Mo in the MFI Zeolite Framework, Inorg. Chem. 61 (2022) 1418–1425.
 https://doi.org/10.1021/acs.inorgchem.1c03076.
- 638 [28] A.B. Fernández, I. Lezcano-Gonzalez, M. Boronat, T. Blasco, A. Corma, NMR spectroscopy and
 639 theoretical calculations demonstrate the nature and location of active sites for the Beckmann
 640 rearrangement reaction in microporous materials, J. Catal. 249 (2007) 116–119.
 641 https://doi.org/10.1016/J.JCAT.2007.03.030.

- L. Dalstein, E. Potapova, E. Tyrode, The elusive silica/water interface: isolated silanols under water as
 revealed by vibrational sum frequency spectroscopy, Phys. Chem. Chem. Phys. 19 (2017) 10343–10349.
 https://doi.org/10.1039/C7CP01507K.
- E. Dib, I.M. Costa, G.N. Vayssilov, H.A. Aleksandrov, S. Mintova, Complex H-bonded silanol network in zeolites revealed by IR and NMR spectroscopy combined with DFT calculations, J. Mater. Chem. A. 9
 (2021) 27347–27352. https://doi.org/10.1039/D1TA06908J.
- 648 [31] D. Verboekend, J.C. Groen, J. Pérez-Ramírez, Interplay of Properties and Functions upon Introduction of
 649 Mesoporosity in ITQ-4 Zeolite, Adv. Funct. Mater. 20 (2010) 1441–1450.
 650 https://doi.org/10.1002/adfm.200902205.
- [32] K. Pyra, K.A. Tarach, E. Janiszewska, D. Majda, K. Góra-Marek, Evaluation of the Textural Parameters of
 Zeolite Beta in LDPE Catalytic Degradation: Thermogravimetric Analysis Coupled with FTIR Operando
 Studies, Molecules. 25 (2020). https://doi.org/10.3390/molecules25040926.
- K. Pyra, K.A. Tarach, D. Majda, K. Góra-Marek, Desilicated zeolite BEA for the catalytic cracking of LDPE:
 the interplay between acidic sites' strength and accessibility, Catal. Sci. Technol. 9 (2019) 1794–1801.
 https://doi.org/10.1039/C9CY00326F.
- 657[34]G. Manos, A. Garforth, J. Dwyer, Catalytic Degradation of High-Density Polyethylene over Different658Zeolitic Structures, Ind. Eng. Chem. Res. 39 (2000) 1198–1202. https://doi.org/10.1021/ie990512q.
- [35] Q. Zhou, L. Zheng, Y.Z. Wang, G.M. Zhao, B. Wang, Catalytic degradation of low-density polyethylene
 and polypropylene using modified ZSM-5 zeolites, Polym. Degrad. Stab. 84 (2004) 493–497.
 https://doi.org/10.1016/J.POLYMDEGRADSTAB.2004.01.007.
- 662 [36] K. Pyra, K.A. Tarach, K. Góra-Marek, Towards a greater olefin share in polypropylene cracking –
 663 Amorphous mesoporous aluminosilicate competes with zeolites, Appl. Catal. B Environ. 297 (2021)
 664 120408. https://doi.org/10.1016/J.APCATB.2021.120408.
- 665 [37] B. Reiprich, K.A. Tarach, K. Pyra, G. Grzybek, K. Góra-Marek, High-Silica Layer-like Zeolites Y from
 666 Seeding-Free Synthesis and Their Catalytic Performance in Low-Density Polyethylene Cracking, ACS
 667 Appl. Mater. Interfaces. 14 (2022) 6667–6679. https://doi.org/10.1021/acsami.1c21471.
- K.A. Cumming, B.W. Wojciechowski, Hydrogen Transfer, Coke Formation, and Catalyst Decay and Their
 Role in the Chain Mechanism of Catalytic Cracking, Catal. Rev. 38 (1996) 101–157.
 https://doi.org/10.1080/01614949608006455.
- 671 [39] S. Li, A. Zheng, Y. Su, H. Zhang, L. Chen, J. Yang, C. Ye, F. Deng, Brønsted/Lewis Acid Synergy in
 672 Dealuminated HY Zeolite: A Combined Solid-State NMR and Theoretical Calculation Study, J. Am.
 673 Chem. Soc. 129 (2007) 11161–11171. https://doi.org/10.1021/ja072767y.
- 674 [40] M. Derewiński, K. Góra-Marek, K. Lázár, J. Datka, Nature of active sites in the Fe-TON Zeolites:
 675 Mössbauer and IR studies, Stud. Surf. Sci. Catal. 174 (2008) 865–868. https://doi.org/10.1016/S0167676 2991(08)80025-0.
- 677 [41] A. Corma, P.J. Miguel, A. V. Orchillés, The Role of Reaction Temperature and Cracking Catalyst
 678 Characteristics in Determining the Relative Rates of Protolytic Cracking, Chain Propagation, and
 679 Hydrogen Transfer, J. Catal. 145 (1994) 171–180. https://doi.org/10.1006/JCAT.1994.1020.
- 680 [42] J. Abbot, B.W. Wojciechowski, Catalytic reactions of branched paraffins on HY zeolite, J. Catal. 113
 681 (1988) 353–366. https://doi.org/10.1016/0021-9517(88)90264-3.
- K. Gołąbek, K.A. Tarach, K. Góra-Marek, Standard and rapid scan infrared spectroscopic studies of o xylene transformations in terms of pore arrangement of 10-ring zeolites 2D COS analysis, Dalt. Trans.
 46 (2017) 9934–9950. https://doi.org/10.1039/C7DT00644F.
- K.A. Tarach, K. Gołąbek, M. Choi, K. Góra-Marek, Quantitative infrared spectroscopic studies and 2D
 COS analysis of xylenes isomerization over hierarchical zeolites, Catal. Today. 283 (2017) 158–171.
 https://doi.org/10.1016/J.CATTOD.2016.02.035.

- [45] P. Painter, M. Starsinic, M. Coleman, DETERMINATION OF FUNCTIONAL GROUPS IN COAL BY FOURIER
 689 TRANSFORM INTERFEROMETRY, in: J.R. FERRARO, L.J. BASILE (Eds.), Fourier Transform Infrared Spectra,
 690 Academic Press, San Diego, 1985: pp. 169–241. https://doi.org/https://doi.org/10.1016/B978-0-12691 254104-9.50011-0.
- 692 [46] D.P. Serrano, J. Aguado, J.M. Escola, J.M. Rodriguez, A. Peral, Catalytic properties in polyolefin cracking
 693 of hierarchical nanocrystalline HZSM-5 samples prepared according to different strategies, J. Catal. 276
 694 (2010) 152–160. https://doi.org/10.1016/j.jcat.2010.09.008.
- K.A. Tarach, K. Pyra, S. Siles, I. Melián-Cabrera, K. Góra-Marek, Operando Study Reveals the Superior
 Cracking Activity and Stability of Hierarchical ZSM-5 Catalyst for the Cracking of Low-Density
 Polyethylene, ChemSusChem. 12 (2019) 633–638. https://doi.org/10.1002/cssc.201802190.
- 698[48]C. Lamberti, E. Groppo, G. Spoto, S. Bordiga, A. Zecchina, Infrared Spectroscopy of Transient Surface699Species, Adv. Catal. 51 (2007) 1–74. https://doi.org/10.1016/S0360-0564(06)51001-6.
- [49] I. Noda, Y. Ozaki, Two-Dimensional Correlation Spectroscopy: Applications in Vibrational and Optical
 Spectroscopy, Wiley, 2004. https://doi.org/10.1002/0470012404.
- N.B. Colthup, L.H. Daly, S.E. Wiberley, CHAPTER 3 MOLECULAR SYMMETRY, in: N.B. Colthup, L.H. Daly,
 S.E. Wiberley (Eds.), Introd. to Infrared Raman Spectrosc. (Second Ed., Second Edi, Academic Press,
 1975: pp. 119–178. https://doi.org/10.1016/B978-0-12-182552-2.50006-1.
- 705[51]E.G. Derouane, Factors Affecting The Deactivation Of Zeolites By Coking, Stud. Surf. Sci. Catal. 20 (1985)706221–240. https://doi.org/10.1016/S0167-2991(09)60173-7.
- J.F. Haw, J.B. Nicholas, W. Song, F. Deng, Z. Wang, T. Xu, C.S. Heneghan, Roles for Cyclopentenyl Cations in the Synthesis of Hydrocarbons from Methanol on Zeolite Catalyst HZSM-5, J. Am. Chem. Soc. 122
 (2000) 4763–4775. https://doi.org/10.1021/ja994103x.
- 710 [53] K. Gołąbek, K.A. Tarach, K. Góra-Marek, 2D COS analysis of m-xylene transformation over medium-pore
 711 zeolites, Microporous Mesoporous Mater. 266 (2018) 90–101.
 712 https://doi.org/10.1016/J.MICROMESO.2018.02.028.
- 713 [54] Y. Ganjkhanlou, E. Groppo, S. Bordiga, M.A. Volkova, G. Berlier, Incorporation of Ni into HZSM-5
 714 zeolites: Effects of zeolite morphology and incorporation procedure, Microporous Mesoporous Mater.
 715 229 (2016) 76–82. https://doi.org/10.1016/J.MICROMESO.2016.04.002.
- [55] K. Pyra, K.A. Tarach, A. Śrębowata, I. Melián-Cabrera, K. Góra-Marek, Pd-modified beta zeolite for
 modulated hydro-cracking of low-density polyethylene into a paraffinic-rich hydrocarbon fuel, Appl.
 Catal. B Environ. 277 (2020) 119070. https://doi.org/10.1016/J.APCATB.2020.119070.
- P. Magnoux, C. Canaff, F. Machado, M. Guisnet, Coking, aging, and regeneration of zeolites XIII.
 Composition of the carbonaceous compounds responsible for the deactivation of a USHY zeolite during
 toluene disproportionation, J. Catal. 134 (1992) 286–298. https://doi.org/10.1016/00219517(92)90228-A.
- 723