



Cylindrical SDBD of well-defined expansion area for standardised studies

Konstantinos Giotis, Panagiotis Svarnas, Maria Mitrou, Kristaq Gazeli,
Guillaume Lombardi, Stéphane Béchu

► To cite this version:

Konstantinos Giotis, Panagiotis Svarnas, Maria Mitrou, Kristaq Gazeli, Guillaume Lombardi, et al.. Cylindrical SDBD of well-defined expansion area for standardised studies. International Conference on Phenomena in Ionized Gases (XXXV ICPIG), Jul 2023, Egmond aan Zee, Netherlands. hal-04285292

HAL Id: hal-04285292

<https://hal.science/hal-04285292>

Submitted on 14 Nov 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Cylindrical SDBD of well-defined expansion area for standardized studies

ICPIG XXXVth edition 9 – 14 July 2023
Egmond aan Zee, The Netherlands



K. Giotis^{1,2}, P. Svarnas¹, M. Mitrou^{1,3}, K. Gazeli², G. Lombardi² and S. Béchu³



¹University of Patras, Electrical & Computer Eng. Dept., High Voltage Lab., 26 504 Rion, Patras, Greece

²Université Sorbonne Paris Nord, LSPM, CNRS, 8 UPR 3407, F-93430 Villetaneuse, France

³Université Grenoble Alpes, Grenoble INP (Institute of Engineering), LPSC-IN2P3, 38000 Grenoble, France




The present work lies in the field of atmospheric-pressure surface dielectric-barrier discharges (SDBDs).

A tailored experimental cylindrical setup is presented, by which the SDBD expansion area is well defined, avoiding any underside discharge. Preliminary electrical and optical emission results are reported.


Experimental Setup

- SDBD reactor designed in a cylindrical configuration.
- The use of oil with high dielectric strength fully encapsulates the grounded electrode and an underside-discharge-free SDBD is considered.
- Appropriate for fundamental and standardized studies.
- Power measurements based on the mean value of current and voltage product.
- Relative calibrated UV-NIR optical emission spectroscopy (OES) for species investigation.




Results


- The mean power increases non-linearly as a function of the voltage level.
- Wider gap weakens the discharge for a given applied voltage, and lower power is thus consumed.
- Detected emissive species: N₂ second positive system (SPS) and N₂⁺ first negative system (FNS).



Ongoing Research






AC Sinusoidal; 10 kHz



Positive Squared Pulsed; 10 kHz; 1 μs

AC vs Pulsed

- Air
- Fused Quartz
- Stainless Steel
- Synthetic Ester Fluid
- Teflon



References:

- [1] Leonov S. B. et al. Plasma Sources Sci. Technol. **25**, 063001 (2016).
- [2] Laurentie J.-C. et al. J. Electrostat. **67**, 93 (2009).
- [3] Giotis K. et al. Plasma Sci. Technol. In press (2023).
- [4] Gazeli K. et al. Plasma **4(1)**, 145-171 (2021).

