



**HAL**  
open science

## Simulation and measurements of ozone production in a multi pins to plane corona discharge reactor

Valentin Ferrer, Gaëtan Wattieaux, Olivier Ducasse, Olivier Eichwald,  
Jean-Philippe Sarrette

► **To cite this version:**

Valentin Ferrer, Gaëtan Wattieaux, Olivier Ducasse, Olivier Eichwald, Jean-Philippe Sarrette. Simulation and measurements of ozone production in a multi pins to plane corona discharge reactor. International Conference on Plasma and Energy Materials (ICPEM 2023), Feb 2023, Agadir, Morocco. hal-04288755

**HAL Id: hal-04288755**

**<https://hal.science/hal-04288755>**

Submitted on 16 Nov 2023

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

## Simulation and measurements of ozone production in a multi pins to plane corona discharge reactor

V. Ferrer<sup>1</sup>, G. Wattieaux<sup>1</sup>, O. Ducasse<sup>1</sup>, O. Eichwald<sup>1\*</sup> and J.P. Sarrette<sup>1\*</sup>

<sup>1</sup>LAPLACE, Université de Toulouse, CNRS, INPT, UPS, 118 route de Narbonne, Toulouse, France

\* Email: sarrette@laplace.univ-tlse.fr

**Key words:** corona discharges, ozone, electro-hydrodynamics, atmospheric-pressure plasma, absorption measurements

This work presents a simulation of ozone production in a multi pins to plane atmospheric pressure corona reactor. When a positive DC voltage is applied to the pins, mono-filamentary discharges are generated between each pin and the common grounded plane electrode, with a mean natural repetition frequency of 10 kHz in ambient air.

The simulation of this reactor is particularly tricky, due to large differences:

- in the temporal scales, as each discharge phase lasts typically 150 ns and is followed by a long post discharge phase of about 0.1 ms during which convection and diffusion processes begin to operate, coupled with chemistry;
- in the spatial scales, the discharge diameter being typically of 50  $\mu\text{m}$  while the reactor length is 8 cm.

A 2D model taking into account the spatio-temporal generation of primary radicals (N and O atoms) and the heat deposition in each discharge channel is presented and the behavior of the whole reactor described. In previous publications [1-2], the results corresponding to the first 0.1 s of simulation were presented. Parallelization of the code allowed us to here extend the simulation up to 30 s of activation of the pins, corresponding to  $3 \cdot 10^5$  discharge / post discharge successive cycles. Calculated ozone densities are also compared with measured concentrations obtained by UV-C absorption, showing only a qualitative agreement.




Figure 1 : Spatio-temporal distribution of ozone concentration in the corona reactor (3 pins activated).

Air flows in the reactor from left to right at 15 cm/s.

### References

- [1] Meziane M., Eichwald O., Sarrette J.P., Ducasse O., Yousfi M., Marchal F, J. Appl. Phys. (2013), **113**, 153302.
- [2] Sarrette J.P., Eichwald O., Marchal F., Ducasse O., Yousfi M., Plasma Sci. Technol. (2016), **18**, 469.

### Acknowledgments

This work was performed using HPC resources from the CALMIP supercomputing center under the allocation 2022-[P1053]