



3D-AFM imaging of the liquid-solid interface at the nanometric scale

Dahlia Saad, Frédéric Dubreuil, Magali Phaner-Goutorbe

► To cite this version:

Dahlia Saad, Frédéric Dubreuil, Magali Phaner-Goutorbe. 3D-AFM imaging of the liquid-solid interface at the nanometric scale. Trends in Nanotechnology International Conference (TNT2023 Lyon), Aug 2023, Lyon, France. . hal-04294765

HAL Id: hal-04294765

<https://hal.science/hal-04294765>

Submitted on 20 Nov 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

3D-AFM imaging of the liquid-solid interface at the nanometric scale


Characterization of gold/thiol layer/liquid interfaces by 1D-AFM, force spectroscopy, and 3D-AFM, a newly developed technique for interfacial characterization at the nanometric scale, in different liquid environments

Dahlia SAAD^{1,2}, Frédéric DUBREUIL¹, Magali PHANER-GOUTORBE²

¹ Univ Lyon, Ecole Centrale de Lyon, LTDS, UMR5513, 69134 Ecully Cedex, France

² Univ Lyon, Ecole Centrale de Lyon, CNRS, INSA Lyon, Université Claude Bernard Lyon 1, CPE Lyon, INL, UMR5270, 69134 Ecully Cedex, France
(dahlia.saad@ec-lyon.fr, magali.phaner@ec-lyon.fr, frederic.dubreuil@ec-lyon.fr)


Solid/Organic layer/liquid Interfaces



M. Ralph Uhlig (Thesis, Instituto de Ciencia de Materiales de Madrid, 2019) Page 18


- “Grafted onto” Organic layers
 - Sensing layers in biosensors
 - Protective layers for tribology applications

- Polymers dissolved in distilled water ($C = 1,5 \text{ g/L}$)
- 4 hours deposition on gold wafers




Sample preparation

Poly (acrylic acid) PAA



- Protein adsorption and trapping
 - Biocompatible, non-toxic, biodegradable
 - Interesting swelling properties


Poly (ethylene oxide) PEO



- Protein repulsion and friction decrease
 - Non-toxic
 - Interesting repulsion properties

Principle of 3D-AFM

Combination between 1D-AFM and 2D-AFM




T. Fukuma, Y. Ueda, S. Yoshioka, H. Asakawa, Phys. Rev. Lett. 104 (2010) 016101

- Technique for high resolution interfacial characterization
- Implementation in a conventional 2D-AFM
- Additional sine wave signal to the z-piezo (Lock-in amplifier)
- Image of the first liquid layers above the surface

1D-AFM



Force curves in pure water



Different adhesion forces:


- adhesion on gold: 1 – 1.5nN
- adhesion on PAA: 0.7 – 1nN
- adhesion on PEO: 0.1 – 0.5nN
- both PAA and PEO behaviors on PAA/PEO

3D-AFM implementation



2D (xy) cross section representation of the interface

2D (xz) cross-section images



- Successfully implemented 3D-AFM
- Successfully generated 2D vertical images representing the interface
- Result analysis still in process

This 3D-AFM method is appropriate to visualize the interface between solid/polymer chains/liquid. It is promising to interpret the difference in behavior depending on the polymers' headgroups and the nature of the liquid. Our future work consists in improving the technique (vertical resolution, surface roughness,...) and calculating the force between the tip and the samples' surfaces and then generating a 3D force map of the interfaces. Furthermore, we are going to develop new interfaces by functionalizing silicon wafers with silane and then analyzing them using the improved version of 3D-AFM.

Funding: FRAMA2023