

Thermal effects on the kinetics of gas dissolution in brine: A case study of CO2 storage in salt caverns (a non-dimensional model)

Murad S. Abuaisha, Ahmed Rouabhi, Faouzi Hadj Hassen, David W Eaton, Firas Tayeb, Alain Valtz

▶ To cite this version:

Murad S. Abuaisha, Ahmed Rouabhi, Faouzi Hadj Hassen, David W Eaton, Firas Tayeb, et al.. Thermal effects on the kinetics of gas dissolution in brine: A case study of CO2 storage in salt caverns (a non-dimensional model). DECOVALEX 2023, Nov 2023, Troyes, France. hal-04297315

HAL Id: hal-04297315 https://hal.science/hal-04297315

Submitted on 21 Nov 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.





Thermal effects on the kinetics of gas dissolution in brine: A case study of CO₂ storage in salt caverns (a non-dimensional model)

Abstract

Understanding the dissolution kinetics of CO₂ in brine is important for efficient management of cycled CO₂ in underground salt caverns.

The kinetics is strongly influenced by natural convection, which is caused by density changes related to the concentration of dissolved gas as well as thermal changes driven by CO₂ cycling and the effects of the geothermal gradient. Based on a novel non-dimensional model that couples cavern thermodynamics with the dissolution mechanisms, this study investigates how the natural convection related to mass and thermal changes impacts dissolution kinetics. The numerical model is validated using laboratory measurements, and thereupon upscaled to typical dimensions of a salt cavern. Although our simulations show that the total dissolved mass is relatively minor compared to the initial stored mass/cycled mass, it is nevertheless important to quantify other loss phenomena, particularly gas permeation into the host rock salt. The developed model can also be adapted easily to study the kinetics of dissolution of other gases, such as hydrogen and methane.

Introduction and Methodology

One promising clean energy resource is methanation, a technique used to convert carbon dioxide to methane using hydrogen. Methanation is supposed to reply to the energy fluctuating demand, which necessitates large storage of its production elements (H₂ and CO_2). This study focuses on CO_2 storage and cycling in salt caverns in the context of clean energy transition [1].

The underground storage system can be divided into three domains: (1) the well which extends from the ground surface to the cavern; (2) **the cavern** itself; and (3) the **rock mass** that surrounds the cavern and the well (Fig.1).

The cavern brine has initially low concentration of CO₂. As CO_2 is injected into the concentration cavern, а gradient develops at the brine interface. This concentration gradient forms the driving Fickian the for force diffusion.



Fig. 1. Schematic representation of CO₂ storage in salt caverns and its transport mechanisms between the cavern phases

Consequently, convection is created in the brine due to changes in the density field. A thermal convection is further developed due to cycling temperature changes at the brine interface, which interacts with the geothermal gradient of the brine. The velocity field that emerges due to both types of convection is expected to enhance the dissolution of CO_2 in the brine.

This research introduces a non-dimensional model that couples cavern thermodynamics [2] with the dissolution mechanisms in the brine. Since the model is non-dimensional, once validated by the laboratory measurements, it can be applied to other scales. This model can also be adapted to study the dissolution of other gases. Experimental work is required, some of it considered in this study, in order to establish the key model parameters.

Murad AbuAisha (*murad.abuaisha@minesparis.psl.eu*)^a, Ahmed Rouabhi^a, Faouzi Hadj-Hassen^a, David W. Eaton^b, Firas Tayeb^a, and Alain Valtz^c ^a Mines Paris, PSL University, Centre de Géosciences, 77300 Fontainebleau, France ^b Department of Geoscience, University of Calgary, Calgary, AB, Canada ^c Mines Paris, PSL University, Centre CTP, 77300 Fontainebleau, France

Methodology and Laboratory Work



Fig. 2. The workflow of this study

Before applying the non-dimensional model on the cavern scale, experimental validation is needed. Laboratory experiments are performed based on a pressure decay test using a PVT (Pressure-Volume-Temperature) cell. In this setup, the CO_2 gas is injected from a tank into the cell that is partially filled with saturated brine. The cell temperature is controlled by placing it into a temperature-controlled basin (Fig. 3). Once gas is injected, it starts dissolving in the liquid phase.



Fig. 3. Schematic representation of the pressure decay PVT cell used to study the CO₂ dissolution in the brine and to validate the mathematical model

Validation – Laboratory Scale



Fig. 4. A comparison between the numerical and the experimental pressure histories for the two laboratory tests: (a) $p_{\gamma 0}$ = 12.9 MPa and (b) $p_{\gamma 0}$ = 16.87 MPa. The black curves represent the numerical solutions while considering only pure diffusion ($D_{app} = 8.6 \times 10^{-8} \text{ m2/s}$)

The results of the numerical model correlate well to the experimental data. The black curves represent the numerical solutions while considering only the diffusion phenomenon. For these solutions to correlate to the experimental data, the diffusion coefficient needs to be enhanced

Thermal Effects Thermal effects are quantified numerically. Fig. 5 shows the numerical model that is used for this purpose. This model represents a cylinder with a radius that is 3 times the radius of the laboratory cell. Nevertheless, the same height-radius ratio is adopted. In the first scenario, a temperature difference of 3 °C is applied over the model height. In the second scenario, the difference is reduced to 0.1 °C.

gradients accelerate the dissolution process. Fig. 5 shows how even a small temperature difference of 0.1 °C accelerates the dissolution process.

Simulations – Cavern Scale I To consider the full cavern scale, the numerical model represents a cylindrical volume ~42412 m³ in an infinite rock salt domain (Fig. 6). The cavern brine occupies almost 11% of the volume over a height of 1.5 m.

The cycling program envisaged for this research: a weekly utilization of the cavern with four cycles spreading over ~28 days. Cycling leads to reasonable mass variations where the cycled CO₂ stays always in its supercritical state.

References Schaaf, T., Grunig, J., Schuster, M. R., Rothenfluh, T., Andreas, O., 2014. Methanation of CO₂-storage of renewable energy in a gas distribution system. Energy, Sustainability, and Society, 4, 2. AbuAisha, M., Rouabhi, A., 2019. On the validity of the uniform thermodynamic state approach for underground caverns during fast and slow cycling. International Journal of Heat and Mass Transfer, 142, 118424.



Fig. 5. Schematic representation of the numerical model. Evolution of the volume averaged CO₂ concentration. The figure shows how the thermal effects due to different temperature



Fig. 6. Schematic diagram of the boundary value problem: it represents a cylindrical cavern created at a depth of 600 m in a surrounding rock salt domain





Fig. 8. Cavern CO₂ pressure (a) and temperature (b) as function of the relative mass variations during 6.5 months Fig. 9(a) shows how the brine volume averaged temperature is impacted by cycling. Fig. 9(b) shows the brine CO2 concentration averaged over its surface and the volume.

Fig. 9. The evolution of the brine average temperature during the CO₂ cycling. (b) The brine CO_2 concentration averaged over its surface and volume. The surface averaged concentration shows clearly the effects of cycling

Fig. 10 shows the contours velocity, the of the concentration difference, the and temperature, the pressure fields at 10 days of the cycling. It is observed z_{-410} that even-though the velocity field is generated by convection (mass and thermal), it has values that \tilde{z}_{-410}^{-409} are not far from ~ 1 cm/s. The concentration, temperature, and pressure fields follow the trends of \tilde{z}^{-409} the velocity evolution.





Simulations – Cavern Scale II

Fig. 8 shows the cavern thermodynamics as well as the brine CO_2 volume averaged concentration as function of cycling. Fig. 8(c) shows how the brine CO_2 concentration increases linearly due to cycling.







Conclusion

The novelty of this research stems from the fact that it presents and quantifies the effects of thermal convection on the gas-liquid dissolution process.

Simulations demonstrate that the ultimate total dissolved mass is approximately 0.32% of the initial stored mass. Although this loss may seem insignificant, the quantification of this loss, during cycling becomes important when other loss mechanisms are studied, particularly the permeation of gas into the rock domain.

Acknowledgements

Authors would like to thank the French Association Nationale de Recherche (ANR) for their financial support via the project HyTrend.