



Urea oxidation by electromediation of Ni(II)/Ni(III) system in alkaline media with simultaneous H₂ production

Guillaume Hopsort, Laure Latapie, Karine Groenen Serrano, Karine Loubière,
Theodore Tzedakis

► To cite this version:

Guillaume Hopsort, Laure Latapie, Karine Groenen Serrano, Karine Loubière, Theodore Tzedakis. Urea oxidation by electromediation of Ni(II)/Ni(III) system in alkaline media with simultaneous H₂ production. 9th European Summer School of Electrochemical Engineering (ESSEE), Oct 2022, Southampton, United Kingdom. hal-04302385

HAL Id: hal-04302385

<https://hal.science/hal-04302385>



Submitted on 23 Nov 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.


L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Contact: guillaume.hopsort@univ-tlse3.fr


BACKGROUND




At the anode:



Anodic overall:



At the cathode:



METHODOLOGY




①/② Electrochemical study at lab scale


Electrolysis at lab-scale

Investigations of (electro)oxidation kinetic and mechanisms
Effect of electrode, electrolyte, temperature,
pH, i = f(Sélectrode, E, [CO(NH₂)₂], [KOH])


③ Structural characterizations (XRD, SEM)



④ Analytical tools (ionic chromatography, mass spectroscopy)



⑤ Kinetic rate law determination



⑥ Pilote-lab scale


5 L. day. m⁻² electrode capacity



ANALYSIS - RESULTS


Influence of urea concentration

Voltammograms obtained on nickel electrode (4 cm²) in 3 M KOH solution at 50 mV.s⁻¹





Influence of temperature

Voltammograms obtained on nickel electrode (4 cm²) in 3 M KOH / 0.33 M urea solution at 50 mV.s⁻¹



Mass balances of urea/byproducts (in the liquid phase) as well as current temporal evolution during potentiostatic electrolysis

at 0.5 V vs. Hg/HgO / 3 M KOH solution containing initial urea at 0.33 M / nickel anode (31 cm²) / undivided H-shaped reactor



CONCLUSIONS

Parametric study
Kinetics rate law obtained and validated by modeling
Design and building of a pilot scale

Pilot scale experiments
Modeling & Simulation
Real human effluents
Photo-assistance integration