



On-chip temporal pulse pattern generation and fiber propagation: Multidimensional wave-packet control and characterization

Van-Thuy Hoang, Bruno Chaves, Yassin Boussafa, Lynn Sader, Alexis Bougaud, Bennet Fischer, Mario Chemnitz, Piotr Roztocki, Benjamin Maclellan, Christian Reimer, et al.

► To cite this version:

Van-Thuy Hoang, Bruno Chaves, Yassin Boussafa, Lynn Sader, Alexis Bougaud, et al.. On-chip temporal pulse pattern generation and fiber propagation: Multidimensional wave-packet control and characterization. 2023 IEEE Photonics Society Summer Topicals Meeting Series (SUM), Jul 2023, Palerme, Italy. pp.1-2, 10.1109/SUM57928.2023.10224416 . hal-04307453

HAL Id: hal-04307453

<https://hal.science/hal-04307453v1>

Submitted on 26 Nov 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

On-chip temporal pulse pattern generation and fiber propagation: Multidimensional wave-packet control and characterization

Van-Thuy Hoang

*XLIM - CNRS UMR7252
Université de Limoges
Limoges, France*

Alexis Bougaud

*XLIM - CNRS UMR7252
Université de Limoges
Limoges, France*

Benjamin MacLellan

*Institut National de la Recherche
Scientifique – Centre EMT
Varennes, Canada*

Marco Peccianti

*Emergent Photonics Research
Centre, Loughborough University
Loughborough, UK*

Sai T. Chu

*City University of Hong Kong
Hong Kong, China*

Bruno P. Chaves

*XLIM - CNRS UMR7252
Université de Limoges
Limoges, France*

Bennet Fischer

*Institut National de la Recherche
Scientifique – Centre EMT
Varennes, Canada*

Christian Reimer

*HyperLight Corporation
Massachusetts, USA*

Sébastien Février

*XLIM - CNRS UMR7252
Université de Limoges
Limoges, France*

David J. Moss

*Swinburne University of
Technology
Hawthorn, Australia*

Benjamin Wetzel

*XLIM - CNRS UMR7252
Université de Limoges
Limoges, France*

benjamin.wetzel@xlim.fr

Yassin Boussafa

*XLIM - CNRS UMR7252
Université de Limoges
Limoges, France*

Mario Chemnitz

*Institut National de la Recherche
Scientifique – Centre EMT
Varennes, Canada*

Michael Kues

*Institute of Photonics,
Leibniz University Hannover
Hannover, Germany*

Vincent Couderc

*XLIM - CNRS UMR7252
Université de Limoges
Limoges, France*

Jose Azaña

*Institut National de la Recherche
Scientifique – Centre EMT
Varennes, Canada*

Lynn Sader

*XLIM - CNRS UMR7252
Université de Limoges
Limoges, France*

Piotr Roztocki

*Institut National de la Recherche
Scientifique – Centre EMT
Varennes, Canada*

Alessia Pasquazi

*Emergent Photonics Research
Centre, Loughborough University
Loughborough, UK*

Brent E. Little

*QXP Technologies Inc.
Xi'an, China*

Roberto Morandotti

*Institut National de la Recherche
Scientifique – Centre EMT
Varennes, Canada*

Abstract— We review recent work using integrated and fibered platforms for advanced optical processing. We show that machine learning in photonics systems can be leveraged to generate custom optical wave-packets relevant for targeted applications and further discuss the extension of this approach within multimode fibers.

Keywords—*nonlinear optics, fiber optics, integrated photonics, supercontinuum, pulse shaping, machine learning, multimode fiber*

I. INTRODUCTION

The fields of ultrafast and nonlinear photonics have brought about several recent research breakthroughs, for which machine learning (ML) has been a driving force at the core of numerous research efforts [1]. Among others, advances in so-called “smart” photonics have been enabled by photonic integrated circuits (PICs), which provide customizable and scalable functionalities highly sought-after for a wide variety of machine learning architectures [2]. In particular, systems based on cascaded interferometers allow to boost the accessible parameter space of optical systems required for multiple applications.

Fairly simple architectures can thus be leveraged for generating customized optical wave-packets, eventually taking advantage of hybrid platforms encompassing nonlinear fiber propagation for optimized spectral broadening [3]. Here, we provide a succinct overview of our recent results in this research area.

II. RESULTS

A. Supercontinuum optimization

Our implementations rely on a PIC, playing the role of an integrated pulse splitter, by means of concatenated balanced and unbalanced Mach-Zehnder interferometers [4,5]. The high-index glass platform of the chip exhibits low linear (< 0.06 dB/cm) and negligible nonlinear losses. The eight unbalanced interferometer structures of the chip feature bit-wise increasing delays (from 1 to 255 ps), which are readily adjusted by a micro-controller driving the pulse splitting via on-chip electric heaters. Fully fiber-coupled, the PIC can be effectively reconfigured with a > 20 Hz refresh rate, offering a good approach for versatile ML-based optical processing. For

instance, the short delays and weak dispersion of the PIC sample can be used to tailor femtosecond pulse patterns and subsequent nonlinear guided-propagation for optimized spectral broadening. This approach was demonstrated to drive conjoint broadening processes in highly-nonlinear fibers and yield spectrally-optimized supercontinuum (SC) generation [3], as illustrated in Fig. 1.




Fig. 1. Supercontinuum spectral optimization: (a) Experimental setup. (b-c) Example of optimized supercontinua (red) with spectral intensities enhanced at selected target wavelengths (blue shading).

B. Pulse shaping

Similar optical processing, paired with ML optimization, can yield autonomous picosecond pulse generation with arbitrary and reconfigurable shapes following the approach displayed in Fig. 2. In this case, the picosecond pulses are experimentally measured via asynchronous optical sampling based on fibered four-wave mixing [5]. Using the previously-demonstrated PIC femtosecond pulse pattern shaping [4], we numerically studied and showed that the spectrally-optimized SCs could be further tuned in the temporal domain [6], as to iteratively enhance multiphoton absorption relevant for various modalities of nonlinear microscopy [7].




Fig. 2. Experimental setup used for autonomous picosecond pulse shaping.

III. DISCUSSION

More recently, we experimentally implemented a similar approach using (asynchronous) cross-correlated frequency-resolved optical gating (X-FROG) based on sum-frequency generation [8]. Experimental results, shown in Fig.3, illustrate how spectrograms obtained after nonlinear broadening can be

reconfigured to gain complete control for customizing the spectro-temporal properties of the SC, thus yielding optical signals directly relevant for applications such as multiphoton microscopy and spectroscopy [7].




Fig. 3. (a,b) Experimental spectrograms retrieved from X-FROG measurements, illustrating the spectro-temporal reconfigurability of the SC. The different output spectrograms are obtained by adjusting the pulse patterns at the fiber input (via on-chip temporal reshaping).

In this paper, we review these numerical and experimental results while discussing the potential of such processing techniques in the framework of multidimensional wave-packet optimization. We also discuss the viability and the impact of these advanced characterization tools for tailoring pulse propagation dynamics in multimode fibers [9].

REFERENCES

- [1] G. Genty, et al., “Machine learning and applications in ultrafast photonics,” *Nat. Photon.* **15**, 91–101 (2021).
- [2] W. Bogaerts, et al., “Programmable photonic circuits,” *Nature* **586**, 207–216 (2020).
- [3] J. M. Dudley and J. R. Taylor, *Supercontinuum Generation in Optical Fibers* (Cambridge University Press, 2010).
- [4] B. Wetzel, et al., “Customizing supercontinuum generation via on-chip adaptive temporal pulse-splitting,” *Nat. Commun.* **9**, 4884 (2018).
- [5] B. Fischer, et al., “Autonomous on-chip interferometry for reconfigurable optical waveform generation,” *Optica* **8**, 1268 (2021).
- [6] V. T. Hoang, Y. Boussafa, L. Sader, S. Février, V. Couderc, B. Wetzel, “Optimizing supercontinuum spectro-temporal properties by leveraging machine learning towards multi-photon microscopy,” *Front. Photon.* **3**, 940902 (2022).
- [7] E. Hoover and J. Squier, “Advances in multiphoton microscopy technology,” *Nat. Photon.* **7**, 93–101 (2013).
- [8] A. M. Weiner, *Ultrafast Optics* (John Wiley & Sons, 2008)
- [9] K. Krupa et al. “Multimode nonlinear fiber optics, a spatiotemporal avenue,” *APL Photonics* **4**, 110901 (2019).