



Enhanced LATIN-PGD in a multi-query framework

Alexandre Daby-Seesaram, Amélie Fau, Pierre-Étienne Charbonnel, David Néron

► To cite this version:

Alexandre Daby-Seesaram, Amélie Fau, Pierre-Étienne Charbonnel, David Néron. Enhanced LATIN-PGD in a multi-query framework. MORTech 2023 – 6th International Workshop on Model Reduction Techniques, Nov 2023, Gif Sur Yvette, France. . hal-04332069

HAL Id: hal-04332069

<https://hal.science/hal-04332069>

Submitted on 10 Jul 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Enhanced LATIN-PGD in a multi-query framework

A. Daby-Seesaram^{†,‡}, A. Fau[†], P.-É. Charbonnel[‡], D.Néron[†]


[†] Université Paris-Saclay, CentraleSupélec, ENS Paris-Saclay, CNRS, LMPS - Laboratoire de Mécanique Paris-Saclay, 91190, Gif-sur-Yvette, France

[‡]DES - Service d'Études Mécaniques et Thermiques (SEMT), CEA, Université Paris-Saclay

Keywords: Nonlinear, Dynamics, Reduced-order model, LATIN-PGD

✉ alexandre.daby-seesaram@ens-paris-saclay.fr

Seismic hazard assessment



- Efficient solver
 - ▶ Reduced-order modelling
- Multi-query capability
 - ▶ Exploits redundancy

Proper Generalised Decomposition (PGD)

- $\mathbf{u}(\mathbf{x}, \omega) = \sum_{i=1}^m \bar{\mathbf{u}}^i(\mathbf{x}) \lambda_\omega^i(\omega)$
 - ▶ Spatial modes $\bar{\mathbf{u}}^i(\mathbf{x})$
 - ▶ Frequency modes $\lambda_\omega^i(\omega)$
- For a given basis $\{\bar{\mathbf{u}}^i(\mathbf{x})\}_{i \in [1, m]}$
 - ▶ Galerkin projection
- Add new modes on the fly
 - ▶ Greedy algorithm
 - ▶ Generate modes targeted for the current problem

$$\begin{matrix} N \\ \downarrow \\ \text{Requirements} \end{matrix} = \begin{matrix} \text{Spatial modes } \bar{\mathbf{u}}^i(\mathbf{x}) \\ \times \\ \text{Frequency modes } \lambda_\omega^i(\omega) \\ + \cdots + \\ \times \end{matrix}$$

Requirements


- Linear equations
- Global equations
- Non-incremental scheme

Methods

Admissibility - \mathcal{A}_d

$$\nabla \cdot \boldsymbol{\sigma} + \mathbf{f}_d = \rho \ddot{\mathbf{u}}$$

Best solved in the frequency domain



Nonlinear behaviour - Γ

$$\tilde{\boldsymbol{\sigma}} = \frac{\boldsymbol{\sigma}_D}{1-D} + \frac{\langle \sigma_H \rangle}{1-D} \mathbf{1} - \langle -\sigma_H \rangle \mathbf{1}$$

Temporal description


LATIN Method:

- Non-incremental scheme
- Separation of the difficulties
- 2-alternated search directions


Iterative scheme

- LATIN paradigm allows for the hybrid scheme
- Non-linear temporal computations
- Linear reduced-order model frequency computations

Reduced-order model hybrid scheme



Numerical results




Performances

PGD well suited to localised corrections


Multi-query framework

Two computations




- 💡 Wise initialisation of the iterative scheme
- ✓ Initial solution
- ✓ Reduced-order basis


Many-query context



- 💡 Robust choice of the parent-simulation
- 💡 Well-suited distance indicator (Weighted Grassmann distance)



3x fewer iterations



20x fewer modes

Conclusion

- ✓ Great reducibility with PGD
- ✓ Enhanced multi-query framework
- ✓ Robust & automatic strategy

