

Modelling the influence of clustered defects on HCF properties of Nibased superalloys

Arjun Kalkur Matpadi Raghavendra, Lionel Marcin, Vincent Maurel, Henry

Proudhon

► To cite this version:

Arjun Kalkur Matpadi Raghavendra, Lionel Marcin, Vincent Maurel, Henry Proudhon. Modelling the influence of clustered defects on HCF properties of Nibased superalloys. 13th International Fatigue Congress, Nov 2023, Hiroshima, Japan. hal-04346313

HAL Id: hal-04346313 https://hal.science/hal-04346313

Submitted on 15 Dec 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Modelling the influence of clustered defects on HCF properties of Nibased superalloys

A. K. Matpadi Raghavendra^{a,b,*}, L. Marcin^b, V. Maurel^a, H. Proudhon^a

^a Centre des materiaux, Mines Paris, FRANCE

^b Safran Aircraft Engines, FRANCE

* Corresponding author: arjun-kalkur.matpadi_raghavendra@minesparis.psl.eu

ABSTRACT:

Casting defects like shrinkages and pores are very detrimental for material's High Cycle Fatigue (HCF) performance. It is known that defect's size and their location from free surface are the most important parameters to take into account regarding HCF properties. However, this conclusion is questionable in the case of clustered defects: specimen lifetime seems to also depend on other characteristics of the defect cluster. The distribution of defect size in an individual cluster is found to be dependent on clustered defects volume and thus influencing the ASTM grades of the material. The gradient associated to the same isolated defect is modified in the presence of cluster further modifying the fatigue predictions via non-local approaches like volumetric homogenization.

However, this type of analysis requires a very large number of three-dimensional observations of casting defects dataset which is impractical and very expensive. Therefore, in this work, a Generative Adversarial Network (GAN) is integrated with Convolutional Neural Network (CNN) to generate synthetic defects (see figure 1.a) and are distributed in material space with the aid of spatial point pattern analysis of defects to generate synthetic microstructures that mirrors real specimens as shown in figure 1.b. Four Inconel 100 and nine Rene 125 specimens tomographed via X-Ray Computed Tomography have been used to study the spatial point pattern of defects and to train Deep Neural Networks (DNN). Spatial point pattern analysis helps to understand how the defects are distributed in material space whilst GANs generate synthetic defects which can be placed randomly respecting the statistics of real specimens.

These N synthetic samples are submitted to numerical simulations to exploit the fatigue behavior via non-local approaches, see figure 2. Furthermore, some of the important features of defect clusters such as, defect volumes, cluster thickness, density of defects in a cluster etc., are controlled to analyze the influence on stress gradients in the synthetic microstructures.

KEYWORDS:

Ni-based Superalloys; HCF; Deep learning; X-ray Tomography; Casting defect





synthetic microstructures



Figure 2. Wohler curves of synthetic microstructures