

## Source-free seismic imaging with reciprocity-gap misfit criterion

Florian Faucher

## ► To cite this version:

Florian Faucher. Source-free seismic imaging with reciprocity-gap misfit criterion. Applied Inverse Problems 2023, Sep 2023, Göttingen, Germany. hal-04355838

## HAL Id: hal-04355838 https://hal.science/hal-04355838v1

Submitted on 17 Jan2024

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

## Source-free seismic imaging with reciprocity-gap misfit criterion.

Florian Faucher<sup>1</sup>

<sup>1</sup> Team Makutu, Inria Bordeaux, University of Pau and Pays de l'Adour, France.

We consider the quantitative inverse problem of recovering sub-surface Earth's parameters from measurements obtained near surface. The reconstruction procedure uses the iterative minimization of a misfit criterion that evaluates the discrepancy between the observed and simulated signals, following the principles of Full Waveform Inversion. In the context of passive imaging, the position and characterization of the source signature are unknown, hence increasing the difficulty of inversion. In this work, we propose a new misfit criterion based upon reciprocity formulas, and that allows for source-free inversion, such that no information regarding the probing sources is required, making it an interesting candidate for ambient noise imaging. Our misfit criterion relies on the deployment of new sensing devices such as dual-sensors and distributed acoustic sensing technology, that offer the perspective of measuring different wave fields. It is the combination of these wave fields that makes the essence of our Full Reciprocity-gap Waveform Inversion method, [1, 2]. with two and three-dimensional reconstructions of acoustic and elastic media.

[1] F. Faucher, G. Alessandrini, H. Barucq, M. V. de Hoop, R. Gaburro and E. Sincich. Full Reciprocity-Gap Waveform Inversion, enabling sparse-source acquisition, Geophysics, 85 (6), 2020, <u>http://dx.doi.org/10.1190/geo2019-0527.1</u>.

[2] F. Faucher, M. V. de Hoop and O. Scherzer. Reciprocity-gap misfit functional for Distributed Acoustic Sensing, combining data from active and passive sources , Geophysics, 86 (2), 2021, <u>https://doi.org/10.1190/geo2020-0305.1</u>.