



HAL
open science

Effect of Pore Size Polydispersity on Acoustic Properties of High-Porosity Solid Foams

C T Nguyen, Vincent Langlois, Johann Guilleminot, Arnaud Duval, Camille Perrot

► **To cite this version:**

C T Nguyen, Vincent Langlois, Johann Guilleminot, Arnaud Duval, Camille Perrot. Effect of Pore Size Polydispersity on Acoustic Properties of High-Porosity Solid Foams. Symposium on the Acoustics of Poro-Elastic Materials, Nov 2023, SORRENTO, Italy. hal-04382858

HAL Id: hal-04382858

<https://hal.science/hal-04382858v1>

Submitted on 9 Jan 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Effect of Pore Size Polydispersity on Acoustic Properties of High-Porosity Solid Foams

C. T. Nguyen^{1,2}, V. Langlois³, J. Guillemot⁴, A. Duval², C. Perrot¹

¹ MSME, Univ Gustave Eiffel, CNRS UMR 8208, Univ Paris Est Creteil, F-77454 Marne-la-Vallée, France

² Trèves products, services and innovation, 2-4 rue Emile Arquès, CS 70017, 51686 Reims Cedex 2, France

³ Navier, Univ Gustave Eiffel, ENPC, CNRS, F-77447 Marne-la-Vallée, France

⁴ Department of Civil and Environmental Engineering, Pratt School of Engineering, Duke University, P.O. Box 90287, 121 Hudson Hall, Durham, North Carolina 27708-0287, USA

This work numerically investigates the influence of pore size polydispersity on the acoustic behavior of high-porosity open-cell solid foams, using proxy geometries defined by Laguerre tessellations [1]. The polydispersity degree of a random foam is characterized by the coefficient of variation of the pore size, $C_d = \sigma_d/d$, where d is the number-weighted size average of pores and σ_d is the corresponding standard deviation. All windows are opened with an identical aperture ratio denoted by τ_o and defined as $\tau_o = \sqrt{S_o/S_w}$, where S_o is the area of the window aperture and S_w is the total area of the window (see Fig. 1). The main results are as follows. First, the effect of the size of the periodic unit cell (PUC) or domain size L on transport parameters was examined. It was found that the size of the PUC required for simulating acoustic properties of random foams is parameter-dependent and depends on the polydispersity degree. Specifically, the results indicate that the viscous permeability k_0 predominantly controls convergence for the acoustic properties, and that foams exhibiting high polydispersity require a large number of pores to achieve proper convergence in terms of morphological characteristics and acoustic properties (see Fig. 2a). Indeed, it is seen that reaching convergence for the other transport parameters (namely, the thermal permeability k'_0 , the viscous Λ and thermal Λ' characteristic lengths, and the tortuosity α_∞) requires a smaller domain size L/d . Second, the influence of polydispersity on the dimensionless transport parameters \mathcal{TP}^* was analyzed. It was found that the high-frequency tortuosity α_∞ is almost independent of the polydispersity degree C_d , while increasing C_d leads to a systematic increase of the remaining macroscopic parameters (when compared to the monodisperse case); See Fig. 2b. The simulations also revealed that the ratio of the dimensionless transport parameters does not depend on the membrane aperture ratio. These important observations imply that the main curves shown in Fig. 2b can be used to predict the transport and sound absorbing properties of random polydisperse foams, based on a limited number of parameters—namely, C_d , τ_o , and d . Third, the proposed method was employed to identify the pore size average d and polydispersity degree C_d in real foam samples (with or without membranes), solving an inverse problem with transport parameters determined through direct characterization (see Tab. 1).




Figure 1: Illustration of the numerically generated foam structures, corresponding to an increase of the polydispersity degree. In this example, the coefficient of variation of the pore size is respectively equal to 3.0%, 44% and 73% (from left to right). Periodic conditions are imposed during the generation process. The size of the domain L corresponds to $L/d = 10$, d being the average pore diameter.




Figure 2: a) Convergence of transport parameters for Cd10. b) Simulation results ($\beta = 1$ for Λ , Λ' and α_∞ ; $\beta = 2$ for k_0 and k'_0). The error bars correspond to standard deviations.

Foam	d (μm)	C_d (-)	τ_o (-)	ϕ (-)	k_0 ($\times 10^{-10} \text{m}^2$)	α_∞ (-)	Λ (μm)	Λ' (μm)
<u>Melamine</u>								
Direct Charac.	—	—	—	0.99 ± 0.002	16.71 ± 1.78	1.02 ± 0.01	100 ± 10	190 ± 15
Refs. [2, 3]	232	—	—	0.986	9.69	1.03	144	250
Ref. [4]	305	—	—	0.986	16.71	1.03	190	329
Our model	118	0.51	—	≈ 1	16.71	1.03	100	185
<u>Polyurethane</u>								
Direct Charac.	—	—	—	0.96 ± 0.020	14.49 ± 2.20	1.79 ± 0.03	66 ± 4	286 ± 59
Refs. [2, 3]	220	—	—	0.986	8.71	1.03	137	237
Ref. [4]	284	—	—	0.986	14.49	1.03	177	306
Ref. [5]	1092	0	0.35	0.986	14.49	1.79	101	358
Our model	593	0.38	0.35	≈ 1	14.49	1.79	66	244

Table 1: Macroscopic parameters of the studied foam samples. "Direct charac." corresponds to the values given in Foam-X user's guide available for benchmark purposes. The other estimates are obtained by means of previously published models (Refs. [2, 3, 4, 5]) of the literature and the proposed approach ("Our model").

References

- [1] C. T. Nguyen, V. Langlois, J. Guilleminot, F. Detrez, A. Duval, M. Bornert, P. Aïmediu and C. Perrot, *Polydisperse solid foams: Multiscale modeling and simulations of elasto-acoustic properties including thin membrane effects*, Int. J. Solids Struct. **249**, pp. 111684, 2022.
- [2] K. V. Horoshenkov, K. Attenborough and S.N Chandler-Wilde *Padé approximants for the acoustical properties of rigid frame porous media with pore size distributions*, J. Acoust. Soc. Am., **104**, pp. 1198-1209, 1998.
- [3] K. V. Horoshenkov, *A review of acoustical methods for porous material characterisation*, Int. J. Acoust. Vib. **1**, pp. 99-103, 2017.
- [4] C. Perrot, F. Chevillotte, M. T. Hoang, G. Bonnet, F. X. Bécot, L. Gautron and A. Duval, *Microstructure, transport, and acoustic properties of open-cell foam samples: Experiments and three-dimensional numerical simulations*, J. Appl. Phys. **111**, pp. 014911, 2012.
- [5] M. T. Hoang and C. Perrot, *Solid films and transports in cellular foams*, J. Appl. Phys. **112**, pp. 054911, 2012.