



## APOLLON: a multi-PW laser facility

Sylvie Jacquemot, Philippe Zeitoun

### ► To cite this version:

Sylvie Jacquemot, Philippe Zeitoun. APOLLON: a multi-PW laser facility: on behalf of the APOLLON project team and of the CILEX consortium. X-Ray Lasers and Coherent X-Ray Sources: Development and Applications XIII, Aug 2019, San Diego, United States. pp.18, 10.1117/12.2531949 . hal-04386078

HAL Id: hal-04386078

<https://hal.science/hal-04386078>

Submitted on 10 Jan 2024

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.


L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# **APOLLON**


## **a multi-PW laser facility**

**S. Jacquemot (LULI)**  
on behalf of the APOLLON project team  
and of the CILEX consortium

- a Research Infrastructure included in the 2018 French roadmap and operated by the LULI laboratory
- a **user-oriented multi-PW multi-beam laser facility** designed to:
  - reach extreme laser powers (**10PW**) & intensities
  - produce energetic & ultra-short particle beams and x-rays with unique characteristics



- push forward the limits of fundamental research



- *quantum effects in laser-plasma interaction*
- *high-energy  $\gamma$  production and positron generation*


# The APOLLON targeted performances



- 4 independent laser beams delivering 1 shot per minute
  - F1                    15fs / 150J max (10PW)
  - F2                    15 fs / 15J max (1PW)
  - F3 (creation)      uncompressed (ns) remaining energy
  - F4 (probe)          < 20 fs / 0.2J (10 TW)
- 2 independent radio-protected experimental areas: SFA & LFA
  - SFA (Short Focal Area: f=1m) - intensities  $> 2 \cdot 10^{22} \text{ W/cm}^2$   
for ion acceleration & strong field physics
  - LFA (Long Focal Area: f=8-32m) - for electron acceleration

## ➤ *unique features*


- hybrid architecture: OPCPA + Ti:Sapphire  
➔ contrast + bandwidth + energy
- extreme materials: Φ10-200mm crystals, meter-size low-TWE gratings, state-of-the-art optics



# The APOLLON laser architecture & layout


Apollon

*laser hall*  
**700 m<sup>2</sup> / ISO7-8**




# The APOLLON building

Apollon






# The APOLLON front-end architecture


Apollon




# Commissioning of the APOLLON front-end



- ✓ **Reliable operation & fast start-up (<30min)**
- ✓ **Stable operation:  $\delta\lambda < 2 \text{ nm/hour}$  spectral thermal drift**
- ✓ **1 mJ / 100 Hz with excellent beam quality**
- ✓ **Optimized injection spectrum: 720-920nm > sub-10 fs**
- ✓ **High contrast pulses  $CR > 10^{12}$**







# The APOLLON amplification architecture



- 5x “low-gain” / image-relayed multipass amplifiers  
 $\Phi 6\text{-}\Phi 140 \text{ mm} \Rightarrow 0.01\text{-}300 \text{ J / 1 shot min, 1 ns @ 820 nm}$
- pump energies @ 527 nm : 300 J available (3-4PW), +300 J budgeted (9PW)  
+100 J technically possible (11PW)
- AMP300 not yet operational (bypassed)



# Commissioning of the APOLLON AMP30 section



**AMP-30**  
 $E_{ave} = 30.5\text{J}$  / 1.6% rms / 7.8% PtP

> **38 J** for a pump energy of **82 J** ⇔ ~44% efficiency into an uniform flat-top like beam  
reliable energy delivery over > 4000 shots (2 weeks, 6-7 h/day) & stable operation  
over > 7h (1 day)

# *APOLLON spectral performances at max. energy*




**~50 nm at FWHM and ~130 nm at 1% → 21 fs FTL** → **>1 PW expected**

**15 fs possible once spectral filtering optimized (2020)**



# The APOLLON compression zone & beam transport




## Compression zone



## Beam transport




# The APOLLON pulse compressors



6x LLNL Au gratings  
910 x 455 mm<sup>2</sup>  
 $\lambda/6 - \lambda/8$

10 PW compressor ( $\Phi 400$ )




gold gratings 530 x 380mm<sup>2</sup>,  $\lambda/33$

1 PW compressor ( $\Phi 140$ )

fully operational  
67% full aperture efficiency



# APOLLON pulse duration




**21.5 fs measured (FTL=21.3 fs) for an energy of 22.6 J (AMP30)**


**over more than 1 hour of shots:  $\Delta t=21.7\pm 0.6$  fs for  $E=36.1\pm 1.2$  J**

=> 1 PW on "target"

# *The APOLLON Short Focal Area*




# *The APOLLON Long Focal Area*




# The APOLLON performances on LFA TCC




- *single AO loop installed in the amplification zone, before compression, ~60 m away from the target, using an **ILAO STAR** deformable mirror*
- *satisfactory correction efficiency:  $\sim\lambda/10$  rms residual error / **Strehl > 50%***




*at the exit of AMP30*




*in LFA before correction*



*in LFA after correction*




$\Phi 45-50\mu\text{m}$



- *good stability: practically no pointing drift over ~3 hours, ~1 focal spot PtV shot-to-shot instability*

## ❖ single-stage electron acceleration (PI: C. Thaury LOA, A. Speck LLR)

- “bubble” regime
- gas: He+1%N<sub>2</sub>
- nozzle: 10x0.3 mm<sup>2</sup>
- stable acceleration without laser guiding
- peak e energy:~2.7 GeV




## ❖ 2-stage electron acceleration (PI: B. Cros LPGP)

context: development of future high-energy physics accelerators

1<sup>st</sup> step: prepare the seeding source

- dedicated gas cell (ELISA)
- gas: H<sub>2</sub>+1%N<sub>2</sub>
- high charge ( $nC$ ) @ 450 MeV




# Commissioning experiments @ 1PW : SFA



## ❖ proton acceleration (PI: J. Fuchs LULI)


- thin (5nm) to thick ( $\mu\text{m}$ ) solid targets
- peak  $p$  energy:  $\sim 20 \text{ MeV}$



## ❖ high-order harmonics generation from solids (PI: F. Quéré LIDyL)

- $\text{SiO}_2$  thick (0.5cm) targets

both strongly binding in terms of contrast



- ❖ facility opened to national & international users (with a fraction of the beam time allocated to the CILEX consortium)
- ❖ experimental programs decided on an annual basis following recommendations of an independent Program Committee
- ❖ once facility completed, 20 experimental projects per year (10 per area)
  - 60 days / year for maintenance & configuration changes
  - 50 days / year for laser development
- ❖ fixed duration of the experimental campaigns: 6 days (1800 shots) + 9 days for setting up (incl. 7 without laser) + 2 days for dismantling
- ❖ laser sequences on demand (from 1 to 100 shots) over 5 hours per day
- ❖ operation teams to change configurations & laser parameters

- ❖ July 2020 – June 2021
  - ✓ first user experiments
    - 4 experiments @ 1PW (2 SFA, 2 LFA)
    - call for proposal to be launched next December
- have a look to the LULI website or contact me to be included in the mailing list*

<https://portail.polytechnique.edu/luli/fr>
- ✓ pump energy ramping up & MPW demonstration
- ❖ July 2021 – June 2022
  - ✓ continuation of the user experiments @ 1PW
  - ✓ commissioning experiments with the MPW beam
- ❖ July 2022 – June 2023
  - ✓ user experiments combining the MPW & the 1PW beams

# *Conclusion*

---



- ❖ **1 PW peak power demonstrated**
  - ✓ > 38 J pulses with sub-22 fs pulses delivered on “target”
  - ✓ contrast ratio >  $10^{12}$
- ❖ **1<sup>st</sup> PW commissioning experiments this autumn**
- ❖ **1<sup>st</sup> call of proposals to be launched end of the year**
- ❖ **MPW operation in 2020**

*Thanks for your attention*

