



HAL
open science

APOLLON: a multi-PW laser facility

Sylvie Jacquemot, Philippe Zeitoun

► **To cite this version:**

Sylvie Jacquemot, Philippe Zeitoun. APOLLON: a multi-PW laser facility. X-Ray Lasers and Coherent X-Ray Sources: Development and Applications XIII, Aug 2019, San Diego, United States. pp.18, 10.1117/12.2531949 . hal-04386078

HAL Id: hal-04386078

<https://hal.science/hal-04386078v1>

Submitted on 10 Jan 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.


L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

APOLLON


a multi-PW laser facility

S. Jacquemot (LULI)
on behalf of the APOLLON project team
and of the CILEX consortium

- a Research Infrastructure included in the 2018 French roadmap and operated by the LULI laboratory
- a **user-oriented multi-PW multi-beam laser facility** designed to:
 - reach extreme laser powers (10PW) & intensities
 - produce energetic & ultra-short particle beams and x-rays with unique characteristics



- push forward the limits of fundamental research



- quantum effects in laser-plasma interaction
- high-energy γ production and positron generation


The APOLLON targeted performances



- 4 independent laser beams delivering 1 shot per minute
 - F1 15fs / 150J max (10PW) ↑ contrast: $< 10^9$ W/cm² for pre-pulses
 - F2 15 fs / 15J max (1PW) ↓ $< 10^{10}$ W/cm² at -100 ps
 - F3 (creation) uncompressed (ns) remaining energy
 - F4 (probe) < 20 fs / 0.2J (10 TW)
- 2 independent radio-protected experimental areas: SFA & LFA
 - SFA (Short Focal Area: f=1m) - intensities $> 2 \cdot 10^{22}$ W/cm²
for ion acceleration & strong field physics
 - LFA (Long Focal Area: f=8-32m) - for electron acceleration

➤ *unique features*


- hybrid architecture: OPCPA + Ti:Sapphire
➔ contrast + bandwidth + energy
- extreme materials: Φ 10-200mm crystals, meter-size low-TWE gratings, state-of-the-art optics



The APOLLON laser architecture & layout



laser hall
700 m² / ISO7-8




LFA
300m²

SFA
130m²

The APOLLON building



The APOLLON front-end architecture






commissioned June 2017




...to Ti:Sapphire based amplifiers (5x)

D. Papadopoulos et al., Optics Lett. 42, 3530 (2017)
L. Ramirez et al., J.O.S.A. B 30, 2607 (2013)


Commissioning of the APOLLON front-end




OPCPA spectral evolution with time: $\sim 100 \text{ min}$



- ✓ **Reliable operation & fast start-up ($< 30 \text{ min}$)**
- ✓ **Stable operation: $\delta\lambda < 2 \text{ nm/hour}$ spectral thermal drift**
- ✓ **$1 \text{ mJ} / 100 \text{ Hz}$ with excellent beam quality**
- ✓ **Optimized injection spectrum: $720\text{-}920 \text{ nm}$ > $\text{sub-}10 \text{ fs}$**
- ✓ **High contrast pulses $\text{CR} > 10^{12}$**






The APOLLON amplification architecture



- 5x “low-gain” / image-relayed multipass amplifiers
 $\Phi 6\text{-}\Phi 140\text{ mm} \Rightarrow 0.01\text{-}300\text{ J} / 1\text{ shot min, } 1\text{ ns @ } 820\text{ nm}$
- pump energies @ 527 nm : 300 J available (3-4PW), +300 J budgeted (9PW)
+100 J technically possible (11PW)
- AMP300 not yet operational (bypassed)



Commissioning of the APOLLON AMP30 section



AMP-30
 $E_{ave} = 30.5\text{ J} / 1.6\% \text{ rms} / 7.8\% \text{ PtP}$

> **38 J** for a pump energy of **82 J** \Leftrightarrow ~44% efficiency into an uniform flat-top like beam
reliable energy delivery over > 4000 shots (2 weeks, 6-7 h/day) & stable operation
over > 7h (1 day)

APOLLON spectral performances at max. energy




~50 nm at FWHM and ~130 nm at 1% → 21 fs FTL → >1 PW expected
15 fs possible once spectral filtering optimized (2020)



The APOLLON compression zone & beam transport




Compression zone



Beam transport




The APOLLON pulse compressors



*6x LLNL Au gratings
910 x 455 mm²
 $\lambda/6$ - $\lambda/8$*

10 PW compressor ($\Phi 400$)



HORIBA JOBIN YVON

gold gratings 530 x 380mm², $\lambda/33$


1 PW compressor ($\Phi 140$)

fully operational

67% full aperture efficiency



APOLLON pulse duration




21.5 fs measured (FTL=21.3 fs) for an energy of 22.6 J (AMP30)


over more than 1 hour of shots: $\Delta t = 21.7 \pm 0.6$ fs for $E = 36.1 \pm 1.2$ J

=> 1 PW on "target"

The APOLLON Short Focal Area




The APOLLON Long Focal Area




The APOLLON performances on LFA TCC




- single AO loop installed in the amplification zone, before compression, ~60 m away from the target, using an **ILAO STAR** deformable mirror
- satisfactory correction efficiency: $\sim \lambda/10$ rms residual error / **Strehl > 50%**




at the exit of AMP30




in LFA before correction



in LFA after correction



$\Phi 45-50\mu\text{m}$




- **good stability:** practically no pointing drift over ~ 3 hours, ~ 1 focal spot PtV shot-to-shot instability

Commissioning experiments @ 1PW (f: 3m) : LFA



❖ single-stage electron acceleration (PI: C. Thaury LOA, A. Specka LLR)

- “bubble” regime
- gas: $\text{He}+1\%\text{N}_2$
- nozzle: $10 \times 0.3 \text{ mm}^2$
- stable acceleration without laser guiding
- peak e energy: $\sim 2.7 \text{ GeV}$




❖ 2-stage electron acceleration (PI: B. Cros LPGP)

context: development of future high-energy physics accelerators


1st step: prepare the seeding source

- dedicated gas cell (ELISA)
- gas: $\text{H}_2+1\%\text{N}_2$
- high charge (nC) @ 450 MeV




❖ proton acceleration (PI: J. Fuchs LULI)

- *thin (5nm) to thick (μm) solid targets*
- *peak p energy: ~ 20 MeV*



❖ high-order harmonics generation from solids (PI: F. Quéré LIDyL)

- *SiO_2 thick (0.5cm) targets*



both strongly binding in terms of contrast

- ❖ **facility opened to national & international users (with a fraction of the beam time allocated to the CILEX consortium)**
- ❖ **experimental programs decided on an annual basis following recommendations of an independent Program Committee**
- ❖ **once facility completed, 20 experimental projects per year (10 per area)**
 - **60 days / year for maintenance & configuration changes**
 - **50 days / year for laser development**
- ❖ **fixed duration of the experimental campaigns: 6 days (1800 shots) + 9 days for setting up (incl. 7 without laser) + 2 days for dismantling**
- ❖ **laser sequences on demand (from 1 to 100 shots) over 5 hours per day**
- ❖ **operation teams to change configurations & laser parameters**

❖ July 2020 – June 2021

- ✓ first user experiments
 - 4 experiments @ 1PW (2 SFA, 2 LFA)
 - call for proposal to be launched next December

have a look to the LULI website or contact me to be included in the mailing list

<https://portail.polytechnique.edu/luli/fr>

- ✓ pump energy ramping up & MPW demonstration

❖ July 2021 – June 2022

- ✓ continuation of the user experiments @ 1PW
- ✓ commissioning experiments with the MPW beam

❖ July 2022 – June 2023

- ✓ user experiments combining the MPW & the 1PW beams

- ❖ **1 PW peak power demonstrated**
 - ✓ **> 38 J pulses with sub-22 fs pulses delivered on “target”**
 - ✓ **contrast ratio > 10^{12}**
- ❖ **1st PW commissioning experiments this autumn**
- ❖ **1st call of proposals to be launched end of the year**
- ❖ **MPW operation in 2020**

Thanks for your attention

