

Identification of microstructural descriptors characterizing the macro-behavior of polydisperse random fibrous media

Quang Vu Tran, Camille Perrot, Raymond Panneton, Minh Tan Hoang, Ludovic Dejaeger, Valérie Marcel, Mathieu Jouve

▶ To cite this version:

Quang Vu Tran, Camille Perrot, Raymond Panneton, Minh Tan Hoang, Ludovic Dejaeger, et al.. Identification of microstructural descriptors characterizing the macro-behavior of polydisperse random fibrous media. Symposium on the Acoustics of Poro-Elastic Materials (SAPEM'23), Nov 2023, Sorrento (Naples), Italy, Italy. hal-04393690

HAL Id: hal-04393690 https://hal.science/hal-04393690

Submitted on 14 Jan 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Identification of microstructural descriptors characterizing the macrobehavior of polydisperse random fibrous media

Q.V. Tran^{1,2,3}, C. Perrot¹, R. Panneton², M. T. Hoang³, L. Dejaeger³, V. Marcel³, M. Jouve³

¹Univ Gustave Eiffel, Univ Paris Est Creteil, CNRS, UMR 8208, MSME, F-77454 Marne-la-Vallée, France

² Département de Génie Mécanique, Université de Sherbrooke, Québec J1K 2R1,

Canada

³Adler Pelzer Group, Acoustic TechCenter R&D, Z.I. François Sommer – BP13,

08210 Mouzon, France

Fine predictions of the transport and acoustical properties of composite felts can now be obtained in principle using sophisticated fiber scale numerical approaches. However, there is still a need, in particular for polydisperse random fibrous media, to identify the appropriate microstructural descriptors of the models that enable an accurate prediction of the transport coefficients of these nonwovens from the knowledge of various distributions about their fiber orientations and fiber diameters. For that purpose, polydisperse composite felts were manufactured with transversely isotropic random fibrous structures, and oriented fibrous microstructures corresponding to different compression rates before thermobonding. The fibrous microstructures of these composite felts were characterized using scanning electron microscope images taken on orthogonal sections of the studied specimens. The corresponding images revealed a wide distribution of fiber diameters and a standard deviation of the azimuthal angle of fibers decreasing with increasing compression rate. Furthermore, the evolution of their transport properties with compression rate, when normalized by the average fiber diameter as microstructural descriptor, were not captured by the current models or required prior knowledge of all the transport properties from measurements in the initial state. In light of these experimental data, we developed a fiber network model for the through-plane transport processes of transversely isotropic random fibrous media in which the main visco-thermal dissipation mechanisms of the polydisperse fibrous structure are related to the largest channels within the fluid phase, whereas the smallest channels were considered as leading the inertial behaviors. The viscous and thermal permeabilities of composite felts were then estimated numerically from a representative elementary volume (REV) with a volume weighted average diameter, and the viscous and thermal characteristic lengths from a REV with inverse volume weighted average diameter (Figure 1). A unified empirical model was proposed. The model predictions agree with the experimental results, without adjusting any microstructural parameter.




Figure 1: Illustration of the proposed methodology used to identify the microstructural descriptors D_v and D_{iv} enabling to predict the transport and sound absorbing properties of a polydisperse random fibrous media. Note that D_v is the volume weighted average diameter, D_{iv} is the inverse volume weighted average diameter, whereas D_m is the average diameter; V_i is the volume of the *i*th fiber and N_f corresponds to the number of fibers.