



HAL
open science

Hierarchical materials based on nanocellulose and poly(lactic acid)

Manon Guivier, Giana Almeida, Sandra Domenek, Chloé Chevigny

► To cite this version:

Manon Guivier, Giana Almeida, Sandra Domenek, Chloé Chevigny. Hierarchical materials based on nanocellulose and poly(lactic acid). ACS Spring Meeting, American Chemical Society, Mar 2023, Indianapolis, United States. ⟨hal-04395571⟩

HAL Id: hal-04395571

<https://hal.science/hal-04395571v1>

Submitted on 15 Jan 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



HAL Authorization

Hierarchical materials based on nanocellulose and poly(lactic acid)

Manon Guivier*, Giana Almeida*, Sandra Domenek*, Chloé Chevigny*
*Université Paris-Saclay, INRAE, AgroParisTech, UMR SayFood, Palaiseau, France

Nanocelluloses, i.e. cellulose nanocrystals (CNC) and cellulose nanofibrils (CNF), have shown excellent gas barrier properties which makes them of the highest interest for food packaging applications¹. However, the nanocelluloses swelling, in presence of water vapor, thwarts their good gas barrier properties². Consequently, the use of nanocelluloses in food packaging, while extremely promising, is still a challenge. A multilayer architecture starting with an hydrophobic layer of poly(lactic acid) (PLA) could be a solution to protect nanocelluloses. Different studies have been devoted to the use of nanocelluloses as fillers in a PLA matrix³, but here, a new architecture was developed by depositing layers of nanocelluloses on PLA. The effect of nanocelluloses coating on O₂ barrier properties and water vapor barrier properties was studied, as well as the organization of the nanocellulose layers (Fig.1). Very promising results were obtained, with O₂ permeation several orders of magnitude lower than PLA, thus validating this innovative process.




Figure 1: Oxygen permeabilities of uncoated and coated-PLA (a) and the AFM images of the sample surfaces coated with 10 deposits of CNC (b), CNF (c) and CNF TEMPO (d).

- (1) Belbekhouche, S. et al. Water Sorption Behavior and Gas Barrier Properties of Cellulose Whiskers and Microfibrils Films. *Carbohydr. Polym.* **2011**, 83 (4), 1740–1748.
- (2) Liu, A. et al. Clay Nanopaper with Tough Cellulose Nanofiber Matrix for Fire Retardancy and Gas Barrier Functions. **2011**, 9.
- (3) Espino-Pérez, E. et al. Designed Cellulose Nanocrystal Surface Properties for Improving Barrier Properties in Poly(lactide) Nanocomposites. *Carbohydr. Polym.* **2018**, 183, 267–277.

