# A Decision Support Assistant to Operate a Power Grids with Zonal Automatons



Eva Boguslawski, Alessandro Leite, Marc Schoenauer, Matthieu Dussartre, Benjamin Donnot RTE, TAU, INRIA, Université Paris-Saclay eva.boguslawski@rte-france.com

#### 1. Context


Renewable energy sources are forcing power grid operators to review their grid management strategies

Réseau de Transport d'Électricité (RTE) is developing new adaptive zonal automatons

- Each automaton monitors a zone of the power grid (up to 40 lines) thanks to an optimization algorithm.
- An automaton can act on the power grid configuration and on the electricity production.
- -Each automaton can receive a target path or additional information from operators to decide the appropriate actions to be done. Examples of target path include (un)desirable configurations in future hours or information about other zones.

## 2. Objective

Design a decision support assistant for the supervision of zonal automatons able to recommend relevant target paths/information for automatons based on the power grid's configuration and constraints




Example of a simulated power grid

## 3. Considered method

### Reinforcement learning (RL)

RL approaches are particularly efficient for sequential problems because:


- RL is able to **anticipate** future events
- RL can take into account uncertainties



The principle of Reinforcement Learning

# Multi-Agent Reinforcement Learning

**Several agents cooperate** to ensure the safety of the power grid. We think a decentralized approach could greatly **improve** scalability compared to traditional deep learning methods [1].



Decentralized multi-agent reinforcement learning

For example, each agent can be associated with a subset of automatons and their zones. In this context, at each time-step t:

- $\rightarrow$  Each **agent** i chooses an **action** according to its observation.
- → The **actions** are combined and executed
- $\rightarrow$  A **reward** representing the safety of the hole grid is returned.

#### 4. How to emulate a zonal automaton?

To obtain **reasonable computation times** during training, we need a trade-off between speed and realism.

Emulate an automaton through a reinforcement learning agent to:

- $\rightarrow$  Operate the grid
- $\rightarrow$  Follow a target setpoint

We designed an agent able to operate a 14-nodes power grid by controlling storage power


	Do Nothing Agent	RL Agent
Average number of survived	206/288	279/288
time steps per episode	200/200	213/200

Performances of our agent on a 14-nodes simulated grid

### We designed an agent able to follow a storage charge setpoint

We got interesting results about:

- how to penalize deviations from the setpoint.
- the impact of hyperparameters.
- -the ability to **generalize to other shapes of setpoint** which is great as illustrated in the figures below.



Comparison of observed charge with a smooth setpoint or a step function setpoint

### References

[1] Karl Johan Åström. Optimal control of markov processes with incomplete state information. *Journal of mathematical analysis and applications*, 10(1):174–205, 1965.