

Turbulent plumes in asymmetric rough Rayleigh-Bénard cell

Guillaume de Romemont, Simon Rozenkranz, Anne Sergent, Yann Fraigneau

▶ To cite this version:

Guillaume de Romemont, Simon Rozenkranz, Anne Sergent, Yann Fraigneau. Turbulent plumes in asymmetric rough Rayleigh-Bénard cell. 14th european fluid mechanics conference, Euromech, Sep 2022, Athens, Greece. hal-04400868

HAL Id: hal-04400868 https://hal.science/hal-04400868

Submitted on 17 Jan2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Turbulent plumes in asymmetric rough Rayleigh-Bénard cell

G. de Romemont^a, S. Rosenkranz^a, Y. Fraigneau^a and <u>A. Sergent^{a,b}</u>

In a real thermal system, the underlying surfaces involve specific topographies or smallscale roughness which have a significant impact on the heat transfer. Particularly, in the case of turbulent convection, the addition of wall roughness results in a global heat transfer enhancement and even in an increase of the exponent of the heat transfer scaling law [1, 2]. It is commonly admitted that the heat transfer enhancement originates from an intensification of the thermal plume emission. In the present study, we consider convection over a regularly roughened plate in a Rayleigh-Bénard cell. The objective of this work is to identify how roughness changes the plume features and their dynamics, depending on the regime. Three-dimensional direct numerical simulations have been performed for Rayleigh numbers covering five decades up to Ra=10¹⁰ and for two roughness sizes. As expected, the three heat transfer regimes have been obtained [3]. Taking advantage of the cavity asymmetry, we conduct a comparative study of the plume dynamics near the rough and smooth horizontal plates within the same set-up. Based on thermal and velocity fluctuations, thermal plumes are extracted from the turbulent background. Temporal and spatial statistical properties of the plumes are analysed in the mixing layer of both cavity sides in terms of fluctuations or energy content. Interactions between roughness, plumes, large scale circulation and turbulent background are also investigated.

³ Belkadi et al. J. Fluid Mech. 923, A6 (2021).



Figure 1: Thermal plumes in a water-filled cell at $Ra=10^{10}$ with several hundred blocks roughened on the bottom plate.

^a Université Paris-Saclay, CNRS, Laboratoire Interdisciplinaire des Sciences du Numérique (LISN), F-91405 Orsay, France

^b Sorbonne Université, Faculté des Sciences et Ingénierie, UFR Ingénierie, F-75005 Paris, France

¹ Xie and Xia. J. Fluid Mech. 825, 573 (2017).

² Rusaouën et al., J. Fluid Mech. 837, 443 (2018).