

# A new reactive absorption model using extents of reaction and activities. II. Application to CO 2 absorption into aqueous MDEA solutions

Serena Delgado, Alain Gaunand, Christophe Coquelet, Renaud Cadours,

Céline Volpi

### ▶ To cite this version:

Serena Delgado, Alain Gaunand, Christophe Coquelet, Renaud Cadours, Céline Volpi. A new reactive absorption model using extents of reaction and activities. II. Application to CO 2 absorption into aqueous MDEA solutions. Chemical Engineering Science, 2024, 287, pp.119759. 10.1016/j.ces.2024.119759. hal-04402486

## HAL Id: hal-04402486 https://hal.science/hal-04402486

Submitted on 18 Jan2024

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

1 2	A new reactive absorption model using extents of reaction and activities. II. Application to $CO_2$ absorption into aqueous MDEA solutions							
3	Serena Delgado <sup>a</sup> , Alain Gaunand <sup>a</sup> *, Christophe Coquelet <sup>a,c</sup> *, Renaud Cadours <sup>a,b</sup> and Céline Volpi <sup>b</sup>							
4	<sup>a</sup> Mines Paris, PSL University, CTP (Centre of Thermodynamics of Processes) 35 Rue Saint Honoré							
5	77305 Fontainebleau Cedex, France							
6	<sup>b</sup> TotalEnergies SE, Tour Coupole, 2 place Jean Millier, 92078 Paris La Défense Cedex, France							
7	<sup>c</sup> Université de Toulouse, IMT Mines Albi, CNRS UMR 5302, Centre Rapsodee Campus Jarlard, 81013							
8	Albi CT Cedex 9, France							
9 10	*Corresponding authors e-mail addresses: <u>alain.gaunand@minesparis.psl.eu</u> , <u>christophe.coquelet@mines-albi.fr</u> .							
11	Keywords							
12	Gas-liquid absorption, Kinetic model, Non ideality, MDEA solution, $CO_2$ absorption							
13	Abstract							
14	Absorption into basic aqueous solutions is widely used for $CO_2$ separation from raw natural gas or							
15	from flue gases. This study implements a general steady-state model for reactive gas-liquid							
16	absorption. This work expands upon a first case study where the model was applied with the							
17	stagnant film theory (Whitman, 1923) to alkaline salts-water-CO <sub>2</sub> systems. This second case study							
18	uses the resulting Arrhenius expression to examine published $CO_2$ absorption and desorption flux							
19 20	data in MDEA-water-CO <sub>2</sub> system. Arrhenius parameters are optimised for the reaction CO <sub>2</sub> + MDEA + $H_2O \leftrightarrow HCO_3^-$ + MDEAH <sup>+</sup> with lnk (m <sup>3</sup> .mol <sup>-1</sup> .s <sup>-1</sup> ) = 16.69 - 6385/T (K). Results emphasise the role of							
20 21	$H_2O \leftrightarrow HCO_3 + MDEAH$ with lnk (m .mol .s ) = 16.69 – 6385/1 (k). Results emphasise the role of $CO_2$ physical solubility representation in reactive absorption model overall performance. Global							
<b>~</b> 1	co <sub>2</sub> physical solubility representation in reactive absorption model overall performance. Global							

22 modelling is needed: kinetic parameters should be used together with all underlying parameters with

which they were obtained. The relevance of activity-based modelling is shown, especially at high CO<sub>2</sub>

24 absorption/desorption driving force.

26	<u>Nome</u>	<u>nclature</u>
27	А	Logarithm of Arrhenius pre-exponential factor
28	Ci	Molar concentration of species i (mol.m <sup>-3</sup> )
29	C <sub>1,0</sub>	Concentration of absorbed gas at gas-liquid interface (mol.m <sup>-3</sup> )
30	C <sub>abs,tot</sub>	Total absorptive species concentration (mol.m <sup>-3</sup> )
31	Ci	Normalised concentration of species i (-)
32	E <sub>A</sub>	Activation energy (J.mol <sup>-1</sup> )
33	E'	Flux density (-)
34	$f_{obj}$	Optimisation objective function (-)
35	$H_1$	Henry's constant of absorbed gas at infinite dilution (Pa)
36	<b>j</b> i	Flux of species i through liquid film (mol.m <sup>-2</sup> .s <sup>-1</sup> )
37	$\mathbf{k}_{j}$	Reaction j kinetic constant
38	Kj	Reaction j equilibrium constant
39	k <sub>L,1</sub>	Liquid-side mass transfer coefficient regarding the absorbed gas (m.s <sup>-1</sup> )
40	n <sub>c</sub>	Number of solute constituents in liquid phase
41	n <sub>R,kin</sub>	Number of finite-rate reactions in the reaction mechanism
42	n <sub>R,eq</sub>	Number of reactions at equilibrium in the reaction mechanism
43	Р	Pressure (Pa)
44	Re	Reynolds number
45	r <sub>j</sub>	Reaction rate of reaction j (mol.m <sup>-3</sup> .s <sup>-1</sup> )
46	Sc	Schmidt number
47	Sh	Sherwood number
48	Т	Temperature (K)
49	Consta	ants
50	R	Ideal gas constant (J.mol <sup>-1</sup> .K <sup>-1</sup> )
51	Greek	letters
52	α	$CO_2$ loading in solution (mol.mol MDEA <sup>-1</sup> )
53	γι	Activity coefficient of species i (-)
54	$\mu_{s}$	Solution viscosity (Pa.s)
55	ξj	Extent of reaction j (-)
56	ρs	Solution density (kg.m <sup>-3</sup> )
57	$\omega_{i}$	Mass fraction of species i (-)
58	$\omega_{MDEA,i}$	
59	at zero	o CO <sub>2</sub> loading)
60	Subscr	ripts and superscripts
61	арр	Apparent (=in equivalent unloaded solution)
62	calc	Calculated
63	eq	At equilibrium
64	exp	Experimental
65	0	At interface
66	1	Absorbed gas
67	~c	Molar concentration-based symmetric thermodynamic convention

#### 68 1. Introduction

- 69 Chemical absorption of  $CO_2$  into basic solutions has been in use since the 1930s for its separation 70 from raw natural gas of from flue gases (Bottoms 1931). Solvent screening and design are at the 71 heart of the research effort to increase both  $CO_2$  absorption rate and capacity, and to decrease 72 solvent regeneration duty (e.g., aqueous amine blends). Kinetic parameters are typically obtained 73 from absorption or desorption flux measurements in laboratory gas-liquid contactors of known mass
- 74 transfer coefficient and interfacial area.
- Experiments should be carried out as close to industrial conditions as possible (amine content, CO<sub>2</sub> partial pressure and loading, temperature). Yet, most kinetic studies deal with absorption experiments into unloaded basic solutions. Only one irreversible reaction is considered between absorbed gas and amine (e.g., (Pohorecki et Moniuk 1988), (Pani, et al. 1997), (Derks, et al. 2006)). Moreover, rate expressions are based on molarities. However, when CO<sub>2</sub> is absorbed, bicarbonate, carbonate and carbamate ions are formed. This increases ionic strength, and solution non ideality as well. Therefore, absorption models based on activities rather than molarities should lead to more
- 82 relevant process simulation.
- 83  $CO_2$  reaction with hydroxide ion HO<sup>-</sup> takes place in all aqueous systems with  $CO_2$ . In amine-based 84 solutions, its rate cannot always be disregarded compared to that of CO<sub>2</sub> reaction with the amine 85 species. Furthermore, through molecular simulation, (Rozanska, Wimmer et de Meyer 2021) show 86 that  $CO_2$  kinetics in aqueous tertiary amine solutions can be written as a function of  $CO_2$  and HO<sup>-</sup> 87 concentrations only. For pilot effective mass transfer area measurement by CO<sub>2</sub> absorption into 88 NaOH solutions, (Sheng, et al. 2019) obtain large deviations in estimated area based on five literature 89 kinetic constants. They additionally conclude that inconsistencies between kinetic and physical 90 parameter sources should be avoided. The need for global modelling is emphasised.

91 For these reasons, part I of the present work focused on CO<sub>2</sub> absorption kinetics into alkaline salts 92 solutions (Delgado, et al. 2023). It introduced a reactive absorption model where equilibrium 93 relations, Nernst-Planck diffusion fluxes and reaction rates are written based on activities. This model 94 can be applied in any chemical system and to validate any reaction mechanism. For steady-state 95 mass transfer representations, local fluxes are related by stochiometric constraints through extents 96 of reactions and ensure mass conservation. This significantly reduces the number of differential 97 equations to solve. This model with the stagnant film theory (Whitman, 1923) was then applied to 98 alkaline salts-water-CO<sub>2</sub> systems for validation. Arrhenius parameters of the direct kinetic constant of 99 reaction  $CO_2 + HO^- \leftrightarrow HCO_3^-$  were obtained in the 298-338 K temperature range. Resulting values 100 were coherent with previous works.

Following this first case study, the purpose of this article is to apply the developed general reactive absorption model to  $CO_2$  absorption and desorption in aqueous N-methyldiethanolamine (MDEA) solutions. Both  $CO_2$  reactions with MDEA and with hydroxide ion are considered, so that their individual contribution to absorption can be quantified. Most available literature datasets are included, covering broad experimental condition ranges (see Table 1). The last column indicates the number of available  $CO_2$  absorption and/or desorption flux measurements.

Ref, apparatus	$\omega_{MDEA,app}$	α (mol.mol MDEA <sup>-1</sup> )	Т (К)	P <sub>CO2</sub> (kPa)	n <sub>data</sub>
(Rinker, Sami et Sandall 1995), SC	0.1-0.3	0	293-342	72-100	21
(Pani, et al. 1997), LC	0.1-0.52	0	295-344	100-196	34
(Cadours 1998), LC	0.25-0.5	0.02-0.85	312-383	2.3-1757	114
(Ko et Li 2000), WWC	0.12-0.29	0.01-0.03	303-313	37-98	12
(Pacheco et Kaganoi 2000), WWC	0.35-0.5	0.03-0.32	298-373	67-748	9
(Benamor et Aroua 2007), LC	0.12-0.46	0-0.17	293-323	9.1-59	99
(Camacho, et al. 2009), LC	0.009-0.38	0	288-313	88-95	42
(Qian et Guo 2009), WWC	0.1-0.3	0.01-0.04	300-313	94-98	12
(Kierzkowska-Pawlak et Chacuk 2010), LC	0.1-0.2	0	293-333	26-108	30
(Hamborg et Versteeg 2012), LC	0.23	0-0.8	298-333	1.7-136	21
(Costa, et al. 2019), MC	0.12-0.35	0	298	14	3

108 **Table 1** Summary of lab-scale CO<sub>2</sub> absorption studies in aqueous MDEA solutions


HSC: "Hemispherical Contactor", LC: "Lewis Cell", MC: "Membrane Contactor", SC: "Spherical Wetted-Wall Contactor", WWC: "Wetted-Wall Column"

109

110 Firstly, a data coherence analysis over available absorption and desorption flux measurements is carried out (section 2). It consists in a graphical analysis of flux density E' (see eq. 1) as a function of 111 temperature and CO<sub>2</sub> loading. Outlier points are identified and filtered out. Over the consolidated 112 dataset, the model is then applied to  $CO_2$  absorption and desorption in aqueous MDEA solutions with 113 114 a complete reaction mechanism considering four reversible reactions (two finite rate reactions and two acid-base equilibria). This third section aims at fitting the parameters of an Arrhenius-type 115 116 expression for the direct kinetic constant of reaction  $CO_2 + MDEA + H_2O \leftrightarrow MDEAH^+ + HCO_3^-$ . 117 Optimisation is carried out in both concentration- and activity-based modelling frameworks. Kinetic 118 parameters of CO<sub>2</sub> reaction with hydroxide ion from (Delgado, et al. 2023) are reused here. An 119 overall average absolute deviation (AAD) of calculated to experimental fluxes of 12% was obtained in 120 (Delgado, et al. 2023), with slightly better performance than (Gondal, Svendsen et Knuutila 2016).

121

#### 122 2. Data coherence analysis



$$E' = \frac{j_{\rm CO_2,exp}}{\frac{k_{\rm L,CO_2}}{H_{\rm CO_2,app}}} \left( p_{\rm CO_2,0} - p_{\rm CO_2,eq} \right)$$
(1)


Where, for a given data point, flux density E' is a normalised flux considering proximity to equilibrium.  $j_{CO2,exp}$ , the algebraic experimental CO<sub>2</sub> absorption (>0) or desorption (<0) flux,  $k_{L,CO2}$ , the liquid-side CO<sub>2</sub> mass transfer coefficient, and  $p_{CO2,O}$ , the CO<sub>2</sub> partial pressure at gas-liquid interface are provided by literature sources.  $H_{CO2,app}$ , the apparent Henry's constant of CO<sub>2</sub>, is calculated with the correlation by (Vinel et Bouallou 2004), and  $p_{CO2,eq}$ , the equilibrium CO<sub>2</sub> partial pressure, is 129 calculated as a function of experimental conditions with the thermodynamic model described in the130 Supplementary Material.

131 This variable can be read as a comparison of chemical absorption or desorption flux  $j_{CO_2,exp}$  to a 132 physical absorption flux in an equivalent non-reactive system  $\frac{k_{L,CO_2}}{H_{CO_2,app}}(p_{CO_2,0} - p_{CO_2,eq})$ . Moreover, 133 flux density is always positive. Therefore, CO<sub>2</sub> absorption and desorption data can be represented

and compared on one diagram.

135 E' is plotted as a function of  $CO_2$  loading and at different MDEA concentration levels in Figure 1. 136 Datasets are sorted according to five rounded apparent MDEA mass fraction. Colours reflect four

137 different temperature intervals.




138


**Figure 1** Graphical coherence analysis of available  $CO_2$  absorption and desorption flux data in aqueous MDEA solutions as a function of  $CO_2$  loading and apparent MDEA mass fraction  $\omega_{MDEA,app}$ 

Figure 1 shows a decreasing trend of flux density with increasing  $CO_2$  loading at 0.2 and 0.5 MDEA mass fractions. Data are mostly available in unloaded solutions, where flux density spans a wide

- interval. This can stem from variability between data sources and visualising all temperatures in thesame plot. The choice of thermodynamic representation could also play a role in this result.
- Outlier points are mainly from two references. On the one hand, flux density of (Benamor et Aroua 2007) data is systematically above that of other data sources in unloaded solutions and remains constant or increases slightly with increasing CO<sub>2</sub> loading. This behaviour is incompatible with other data sources. Therefore, absorption flux measurements by (Benamor et Aroua 2007) are not selected in the following section.
- On the other hand, outlier points from (Pacheco et Kaganoi 2000) data at 0.4 MDEA mass fraction 150 have flux densities close to 1.10<sup>4</sup> whereas flux densities from other sources are not over 1.10<sup>2</sup>. At 0.5 151 152 MDEA mass fraction, another of their points stands out with a flux density around 0.1 at low CO<sub>2</sub> 153 loading whereas it is not below 1 in other sources. Three more points stand out from the trend 154 outlined by the data from (Cadours 1998) and (Hamborg et Versteeg 2012) with a higher flux density of around 10 that remains constant regardless of temperature or CO<sub>2</sub> loading. Considering outliers 155 represent more than half of the data from (Pacheco et Kaganoi 2000), their absorption flux 156 157 measurements are not selected either in section 3.
- Figure 2 focuses on calculated flux density from (Cadours 1998) and (Hamborg et Versteeg 2012) data as a function of  $CO_2$  loading at  $\omega_{MDEA,app} = 0.23-0.25$ . Activity-based model trend is also represented with the kinetic parameters determined in section 3. Flux density tends to decrease with growing  $CO_2$  loading, as in Figure 1. However, data from (Hamborg et Versteeg 2012) systematically display lower densities than the trend of (Cadours 1998). Selected data sources for  $CO_2$ -loaded solutions appear incompatible. Both were kept in section 3 because of missing discrimination method, such as a third data source with  $CO_2$ -loaded solutions.



165



#### 169 3. Application to MDEA-water-CO<sub>2</sub> system

- 170 The mass transfer modelling framework is described in part I of the present work (Delgado, et al. 2023). Therefore, only MDEA-specific parameters are specified in the following section (see 171 172 Supplementary Material section 1 and (Delgado, et al. 2023) for modelling framework description).
- In this system, six species are considered:  $CO_2$ ,  $HCO_3^{-2}$ ,  $CO_3^{-2}$ , MDEA, MDEAH<sup>+</sup> and HO<sup>-</sup> (n<sub>c</sub>=6). The 173 mechanism consists in four reversible reactions  $(n_R=4)$ : 174

$$CO_2 + MDEA + H_2O \leftrightarrow MDEAH^+ + HCO_3^-$$
 (R-I)

 $CO_2 + HO^2 \leftrightarrow HCO_3^2$  $HCO_3^2 + HO^2 = CO_2^{2^2} + HO^2$ (R-II)

$$HCO_3 + HO = CO_3^2 + H_2O$$
 (R-III)

$$MDEAH^{+} + HO^{-} = MDEA + H_2O$$
 (R-IV)

175

Reactions R-I and R-II are reversible and with finite rate  $(n_{R,kin}=2)$ . As in most studies, a direct CO<sub>2</sub> 176 reaction with MDEA is considered according to the mechanism proposed by (Donaldson et Nguyen 177 178 1980).

$$r_{I} = r_{(CO_{2},MDEA)} = \tilde{k}_{(CO_{2},MDEA)}^{c} \left( \tilde{\gamma}_{CO_{2}} \tilde{\gamma}_{MDEA} c_{CO_{2}} c_{MDEA} - \frac{\tilde{\gamma}_{(MDEAH^{+})} c_{(MDEAH^{+})} \tilde{\gamma}_{(HCO_{3}^{-})} c_{(HCO_{3}^{-})}}{\tilde{K}_{(CO_{2},MDEA)}^{c}} \right)$$
(2)

$$r_{II} = r_{(CO_2,HO^-)} = \tilde{k}_{(CO_2,HO^-)}^c \left( \tilde{\gamma}_{CO_2} \tilde{\gamma}_{(HO^-)} c_{CO_2} c_{(HO^-)} - \frac{\tilde{\gamma}_{(HCO_3)} c_{(HCO_3)}}{\tilde{k}_{(CO_2,HO^-)}^c} \right)$$
(3)

Where  $\tilde{k}^{c}_{(CO_2,MDEA)}$  and  $\tilde{k}^{c}_{(CO_2,HO^{-})}$  (m<sup>3</sup>.mol<sup>-1</sup>.s<sup>-1</sup>) are the forward kinetic constants of reactions R-I and 179 R-II, and  $\widetilde{K}^{c}_{(CO_2,MDEA)}$  (dimensionless) and  $\widetilde{K}^{c}_{(CO_2,HO^-)}$  (m<sup>3</sup>.mol<sup>-1</sup>) are their equilibrium constants. 180  $ilde{k}^c_{(CO_2,MDEA)}$  is the constant to determine. ~c refers to the molar concentration-based symmetric 181 thermodynamic convention (see eq. SM24 and following in Supplementary Material). 182

In addition, acid-base equilibria between  $HCO_3^{-1}$  and  $CO_3^{-2-1}$  (reaction R-III) and  $MDEAH^+$  and MDEA183 184 (reaction R-IV) are considered (n<sub>R,eq</sub>=2). Equilibrium constant parameters of reactions R-II and R-III 185 are taken from (Kamps, Balaban, et al. 2001). (Kamps et Maurer, 1996) provides equilibrium constant 186 parameters of reactions R-I and R-IV.

187 New correlations have been developed for density and viscosity of both CO<sub>2</sub>-unloaded and -loaded 188 solutions. CO<sub>2</sub> and MDEA liquid phase diffusion coefficients are calculated using modified Stokes-189 Einstein relations (Versteeg et Van Swaaij, Solubility and diffusivity of acid gases (carbon dioxide, 190 nitrous oxide) in aqueous alkanolamine solutions 1988). All ionic species are assumed to have the 191 same diffusivity as MDEA (see Supplementary Material section 1 for detailed correlations). As stated 192 in part I of the present work, the necessary data to implement a distinction in ionic diffusivities is not 193 available. Ionic diffusivities are primarily measured at infinite dilution. However, they are expected to 194 depend on the composition of the solution, but these effects have not been measured in ionic 195 systems. The current assumption is a result of the lack of data. Moreover, this effect is expected to 196 be small compared to the uncertainty of CO<sub>2</sub> absorption and desorption flux measurements and of 197 relevant physico-chemical parameters like viscosity.

As a base case, the mass transfer model is tested with no deviation from ideality. This modelling framework is denoted "concentration-based model". N<sub>2</sub>O physical solubility in aqueous MDEA solutions is calculated with the correlation of (Vinel et Bouallou 2004). CO<sub>2</sub> Henry's constant is calculated with the so-called CO<sub>2</sub>-N<sub>2</sub>O analogy. Since the physical solubility correlation only considers unloaded solutions, this base case is applied to low-loading flux data ( $\alpha \le 0.05$  mol.mol MDEA<sup>-1</sup>).

Secondly, the activity-based model is implemented. Equilibria and solution non-ideality are represented with one thermodynamic model, described in the Supplementary Material. Thus, all selected datapoints in CO<sub>2</sub>-unloaded and -loaded solutions are considered. Several hundred CO<sub>2</sub> absorption and desorption flux measurements are available in the literature, from a variety of gasliquid contactors over broad ranges of operating conditions (293-383 K, 0.009-0.52 apparent MDEA mass fraction, 0-0.85 mol.mol MDEA<sup>-1</sup> CO<sub>2</sub> loading and 0.2-1757 kPa CO<sub>2</sub> partial pressure).

The pre-exponential factor A and the temperature of activation  $E_A/R$  of reaction R-I direct kinetic constant are fitted. The Arrhenius equation is shown in eq. (4) and the objective function is specified in eq. (5).

$$\ln k_{(\rm CO_2, MDEA)} = A - \frac{E_A}{RT}$$
<sup>(4)</sup>

$$f_{\rm obj} = \sum_{i \text{ points}} \frac{1}{2} \left( \left( \frac{j_i^{\rm calc} - j_i^{\rm exp}}{j_i^{\rm exp} + s\varepsilon} \right)^2 + \left( \frac{j_i^{\rm calc} - j_i^{\rm exp}}{j_i^{\rm calc} + s\varepsilon} \right)^2 \right)$$
(5)

212 Where j is the CO<sub>2</sub> absorption flux and  $\varepsilon$  is a constant set to  $1.10^{-4}$  to mitigate error value for very 213 small absorption fluxes. Because both absorption and desorption fluxes are available in this system, a 214 factor s represents the experimental flux sign (s=1 if  $j_i^{exp} > 0$ , -1 otherwise). As indicated in (Delgado, 215 et al. 2023), the two terms give this objective function a symmetric behaviour regarding flux 216 underestimation and overestimation. Optimisation function fminsearch in Matlab R2013a is used to 217 adjust Arrhenius parameters of the kinetic constant. This function implements the simplex algorithm 218 by (Lagarias, et al. 1998).

219 Model application to selected flux measurements aims at optimising Arrhenius parameters of the 220 direct kinetic constant of reaction R-I to minimise  $f_{obj}$ . Arrhenius parameters obtained in (Delgado, et 221 al. 2023) are used for the direct kinetic constant of reaction R-II.

223 Table 2 and Figure 3 compare adjusted Arrhenius parameters in each modelling approach to previous 224 studies. The concentration-based model leads to similar Arrhenius parameters to (Littel, Van Swaaij 225 et Versteeg 1990), (Rangwala, et al. 1992), (Pani, et al. 1997), (Kierzkowska-Pawlak et Chacuk 2010) 226 and (Jamal, Meisen et Lim 2006). On the other hand, the activity-based model leads to higher values 227 for A and  $E_A/R$  compared to Arrhenius parameters of previous studies. For instance, the resulting 228 kinetic constant is 1.8 times higher than that of (Jamal, Meisen et Lim 2006) over the entire 229 temperature interval. The higher activity-based model kinetic constant can be caused by a product of 230 CO<sub>2</sub> and MDEA activity coefficients lower than one. It can also stem from the different representation 231 of equilibria, with lower calculated absorption/desorption driving force in the activity-based model 232 compared to the concentration-based model. As will be seen in Figure 7 and Figure 8, driving force is 233 indeed lower according to the activity-based model. Among the listed studies, the activity-based 234 model in the present work is the only modelling framework considering system deviation from 235 ideality through the liquid film. Only in (Cadours 1998) and (Hamborg et Versteeg 2012) is  $CO_2$ 236 loading factored in CO<sub>2</sub> Henry's constant, by an ionic-strength-dependent correction factor or an 237 experimental assessment with the  $N_2O-CO_2$  analogy (see Table 2).

239 **Table 2** Resulting Arrhenius parameters for the direct kinetic constant of reaction R-I and comparison to previous studies

Reference	А	$E_A/R$ (K)	Т (К)	Transfert model	Non-ideality representation	Reactions
Activity-based model	16.69	6385	293-383	Film	Deshmukh-Mather	I-IV
Concentration-based model	13.60	5567	293-383	Film	Ideal solution	I-IV
(Versteeg et van Swaaij 1988)	11.69	5103	293-333	Penetration	Ideal solution	I, II, V
(Tomcej et Otto 1989)	11.99	5134	298-348	Film (pfo)	Ideal solution	I, II, V
(Littel, Van Swaaij et Versteeg 1990)	14.11	5771	293-333	Penetration	Ideal solution	I, II
(Rangwala, et al. 1992)	13.96	5770	298-333	Film (pfo)	Ideal solution	I
(Rinker, Sami et Sandall 1995)	10.28	4579	293-343	Penetration	Ideal solution	I-IV, VI
(Pani, et al. 1997)	13.06	5461	296-343	Film	Ideal solution	I
(Cadours 1998)	12.60	5333	296-343	Film	$H_{CO2} = f(I)$	I
(Ko et Li 2000)	12.90	5400	303-313	Film	Ideal solution	I, II
(Jamal, Meisen et Lim 2006)	14.51	5798	303-353	Penetration	Ideal solution	I-IV, VI
(Camacho, et al. 2009)	15.49	6244	288-313	Film	Ideal solution	1,11
(Qian et Guo 2009)	12.28	5190	300-313	Penetration	Ideal solution	I-VI
(Kierzkowska-Pawlak et Chacuk 2010)	14.54	5913	293-333	Film	Ideal solution	I
(Hamborg et Versteeg 2012)	9.72	4504	298-333	Penetration	Ideal solution*	I-IV, VI

pfo: "pseudo-first order", H<sub>CO2</sub>: CO<sub>2</sub> Henry's constant, I: ionic strength

\* (Hamborg et Versteeg 2012) experimentally assess  $H_{N20}$  in  $CO_2$ -loaded solution and use the  $N_2O-CO_2$  analogy to calculate  $H_{CO2}$ Reactions: (V)  $CO_2 + H_2O \leftrightarrow HCO_3^- + H^+$ , (VI)  $2H_2O = HO^- + H_3O^+$ 




Figure 3 Arrhenius plots obtained in concentration-based and activity-based modelling frameworksand in previous studies for the direct kinetic constant of reaction R-I

245 Model performance criteria are presented in Table 3, including average absolute deviation (AAD, eq.

246 (6)) and bias (eq. (7)).

242

$$AAD = \frac{1}{n_{data}} \sum_{i \text{ data}} \left| \frac{j_i^{\text{calc}} - j_i^{\text{exp}}}{j_i^{\text{exp}}} \right| \times 100$$
(6)


bias = 
$$\frac{1}{n_{\text{data}}} \sum_{i \text{ data}} \frac{j_i^{\text{calc}} - j_i^{\text{exp}}}{j_i^{\text{exp}}} \times 100$$
 (7)

#### 247 Table 3 Mass-transfer modelling performance for MDEA-water-CO<sub>2</sub> system


(%)	Model	Concentratio		Activity-based	
(,,,,	model	(α ≤ 0.0	15)	(all selected	data)
Reference		AAD	Bias	AAD	Bias
(Rinker, Sami et	Sandall 1995)	9	-9	11	-5
(Pani, et al. 1997	')	11	-10	17	-17
(Cadours 1998)		29	29	17	0.8
(Ko et Li 2000)		15	-15	17	-17
(Camacho, et al.	2009)	17	16	20	20
(Qian et Guo 200	)9)	11	-11	13	-13
(Kierzkowska-Pa	(Kierzkowska-Pawlak et Chacuk		2	10	9
2010)					
(Hamborg et Versteeg 2012)		20	20	42	42
(Costa, et al. 201	.9)	24	-24	35	-35
Overall	<b>α</b> ≤ 0.05	12	-0.6	16	-0.2
Overall	All selected data	-	-	18	3


248


Parity and deviation plots are shown in Figure 4, Figure 5 and Figure 6.



**Figure 4** Reactive absorption model parity plot for MDEA-water-CO<sub>2</sub> system. Concentration-based model:  $\alpha \le 0.05$ , activity-based model: all selected data.








**Figure 6** Reactive activity-based absorption model deviations for MDEA solutions at high CO<sub>2</sub> loading  $(\alpha > 0.05)$ 


- 258 Both approaches give reliable representation of selected data at low CO<sub>2</sub> loading (AAD 12% vs. 16%).
- 259 Figure 5 shows (Camacho, et al. 2009) data is better represented by activity-based model when
- amine mass fraction increases, whereas (Pani, et al. 1997) data is increasingly underestimated with
- this model. The concentration-based model results in slightly better performance at low CO<sub>2</sub> loading,
- but the activity-based model considers non-ideality with a unique thermodynamic model: (1) in diffusion via Nernst-Planck equation, (2) in kinetics via activity-based rates of reactions and (3) in
- equilibria as part of the selected thermodynamic representation. Moreover, the use of  $CO_2$  solubility
- 265 correlations based on  $N_2O-CO_2$  analogy is avoided. This is a major advantage for model generality.
- The main area for improvement of the activity-based model concerns the thermodynamic representation of the system, specifically that of  $CO_2$  physical solubility in solution. Indeed, Henry's constant in solution is calculated based on  $CO_2$  Henry's constant in pure water (see Supplementary Material). It might be beneficial to consider amine concentration as well instead of simply correcting Henry's constant in pure water by the  $CO_2$  activity coefficient factor. (Zhang et Chen 2011) achieve this by introducing a mixing rule for  $CO_2$  Henry's constant normalised by solute activity coefficient at infinite dilution in each component of the solvent.
- At high CO<sub>2</sub> loading (see Figure 6), (Cadours 1998) data is well represented by the activity-based model. Absorption and desorption flux measurements by (Hamborg et Versteeg 2012) are systematically overestimated by the activity-based model (bias=AAD=42%). This is coherent with previous observations of the incompatibility of the two datasets in the data coherence analysis (see Figure 2). Optimisation currently favours (Cadours 1998) data representation because of the difference in data point numbers between the two sources (114 vs. 21).
- 279 Activity-based model results at specific conditions are then examined (Figure 7 to Figure 10, 280 conditions listed in Table 4). The four selected points cover the examined data experimental 281 conditions (MDEA concentration, temperature, CO2 partial pressure and loading, absorption and desorption experiments). For each point, normalised concentration, extent of reaction and activity 282 283 coefficient profiles obtained with the activity-based model are plotted. In unloaded solutions, 284 concentration-based model normalised concentration and extent of reaction profiles are also plotted 285 in dashed lines. As a reminder,  $CO_2$  concentration is normalised by  $c_{1,0}$ , its interfacial concentration, while all other concentrations are normalised by  $c_{abs,tot} = c_{MDEA,app}$ . 286
- Table 4 Conditions of selected points for concentration, extent of reaction and activity coefficientprofile simulation

Figure	Reference	$\omega_{\text{MDEA,app}}$	α	Т (К)	P <sub>co2</sub> (kPa)	k <sub>L,1</sub> (m.s <sup>-1</sup> )	c <sub>1,0</sub> (mol.m <sup>-3</sup> )*
Figure 7	(Qian et Guo 2009)	0.10	0.03	300	94.6	5.38.10 <sup>-5</sup>	24.3
Figure 8	(Pani, et al. 1997)	0.51	0	318	104.9	5.43.10 <sup>-6</sup>	6.3
Figure 9	(Cadours 1998)	0.50	0.28	332	70.1	$9.44.10^{-6}$	5.1
Figure 10	(Hamborg et Versteeg 2012)	0.23	0.10	333	22.6	1.84.10 <sup>-5</sup>	2.7

\*Calculated variable (see (Delgado, et al. 2023)), in the activity-based model framework.




**Figure 7** Simulated CO<sub>2</sub> absorption in aqueous MDEA solution at  $\omega_{MDEA,app} = 0.10$  and  $\alpha = 0.03$ mol/mol MDEA, 300 K and P<sub>CO2</sub> = 94.6 kPa measured by (Qian et Guo 2009). C: normalised concentration,  $\xi$ : extent of reaction,  $\gamma$ : activity coefficient. Solid line & symbol: activity-based model, dashed line: concentration-based model (C and  $\xi$ ).




295

**Figure 8** Simulated CO<sub>2</sub> absorption in aqueous MDEA solution at  $\omega_{MDEA,app} = 0.51$  and  $\alpha = 0$  mol/mol MDEA, 318 K and P<sub>CO2</sub> = 104.9 kPa measured by (Pani, et al. 1997). C: normalised concentration,  $\xi$ : extent of reaction,  $\gamma$ : activity coefficient. Solid line & symbol: activity-based model, dashed line: concentration-based model (C and  $\xi$ ).

300 For selected points at low CO<sub>2</sub> loading, concentration and extent of reaction profiles calculated with 301 non-ideality consideration (solid lines and symbols in Figure 7 and Figure 8) or with ideal solution 302 hypothesis (dashed lines in Figure 7 and Figure 8) display similar trends. In both cases, estimated CO<sub>2</sub> 303 concentration at interface is higher in concentration-based model than in activity-based model. 304 However, the difference is way higher at  $\omega_{\text{MDEA,app}}$  = 0.51 (Figure 8: +221%) than at  $\omega_{\text{MDEA,app}}$  = 0.10 (Figure 7: +20%). This is linked to the thermodynamic representation of CO<sub>2</sub> physical solubility 305 306 discussed previously. Moreover, activity coefficients differ from unity in activity-based model and 307 significantly vary through the film, which is another difference factor with concentration-based 308 model.



- 310 Figure 9 Simulated CO<sub>2</sub> desorption from aqueous MDEA solution by the activity-based model at
- 311  $\omega_{MDEA,app} = 0.5$  and  $\alpha = 0.28$  mol/mol MDEA, 332 K and P<sub>CO2</sub> = 70.1 kPa measured by (Cadours 1998).
- 312 C: normalised concentration,  $\xi$ : extent of reaction,  $\gamma$ : activity coefficient.



**Figure 10** Simulated CO<sub>2</sub> absorption in aqueous MDEA solution by the activity-based model at  $\omega_{\text{MDEA,app}} = 0.23$  and  $\alpha = 0.1$  mol/mol MDEA, 333 K and P<sub>CO2</sub> = 22.6 kPa measured by (Hamborg et Versteeg 2012). C: normalised concentration,  $\xi$ : extent of reaction,  $\gamma$ : activity coefficient.

From all four extent of reaction plots, the reaction between  $CO_2$  and  $HO^-$  ion (R-II) appears to have no influence ( $\xi_{II} \approx 0$ ). HO<sup>-</sup> concentration is negligible, especially close to the interface.

319 Extents of acid-base reactions (R-III and R-IV) are significant in initially unloaded solutions. However,

- 320 contrary to alkaline salts systems studied in (Delgado, et al. 2023),  $CO_3^{2-}$  conversion through the film
- 321 remains marginal.  $HCO_3^-$  and  $MDEAH^+$  are the main reaction products, even at low  $CO_2$  loadings
- 322 where pH is highest.
- 323 The apparition of activity coefficient gradients seems much more influenced by 324 absorption/desorption driving force than by  $CO_2$  loading, MDEA composition or temperature. In

Figure 7 and Figure 8, absorption into initially unloaded solutions at  $\omega_{MDEA,app} = 0.10$  and 0.51 and T = 300 and 332 K, with CO<sub>2</sub> driving forces of around 100 kPa (94.6 and 104.9 kPa) shows the highest activity coefficient gradients (especially MDEAH<sup>+</sup> and CO<sub>3</sub><sup>2-</sup> activity coefficients). Additionally, at these conditions, an important drop in MDEA concentration at the interface takes place (respectively 0.10 and 0.51 of total MDEA mass fractions). Therefore, the "pseudo-first order absorption regime" assumption cannot apply.

On the other hand, profiles calculated in already loaded solutions (Figure 9 and Figure 10), with  $CO_2$ driving forces below 20 kPa, either in the positive or negative, don't display any significant activity coefficient gradient. However, activity coefficients appreciably differ from unity. Although  $CO_3^{2-}$  is never a main product of  $CO_2$  absorption or desorption,  $CO_3^{2-}$  activity coefficient is always lower than 0.5.

#### 336 4. <u>Conclusion</u>

The current two-part study implements a steady-state reactive absorption model applied to the 337 338 stagnant film theory and focusing on solution non-ideality representation in equilibrium relations, 339 Nernst-Planck diffusion fluxes and reaction rates. This approach is more complete than literature 340 models where activity coefficients are assumed constant, and most often equal to unity. Extents of 341 reactions, a new feature for reactive absorption models, reduces the number of differential problem 342 variables while maintaining a general formulation. This formulation with Nernst-Planck equation for 343 molecular diffusion and activity-based rate expressions consists in a system of  $n_c + n_{B,kin}$  first-order 344 ordinary differential equations, whereas writing local balances per species leads to a system of n<sub>c</sub> 345 second-order differential equations. The relation between fluxes and extents of reactions is dictated 346 by stochiometric constraints.

In (Delgado, et al. 2023), this model was first applied to alkaline salts-water-CO<sub>2</sub> systems and the CO<sub>2</sub>
 absorption flux data from the literature. In part II presented here, CO<sub>2</sub> absorption into aqueous
 MDEA solutions was studied. Firstly, a graphical data coherence analysis was carried out by plotting a
 flux density variable against CO<sub>2</sub> loading. Outliers from (Benamor et Aroua 2007) and (Pacheco et
 Kaganoi 2000) were then filtered out.

Then, using the selected data, Arrhenius parameters of the reaction between MDEA and  $CO_2$  were optimised in both concentration- and activity-based models. Results emphasise the role of  $CO_2$ physical solubility representation in reactive absorption model overall performance. N<sub>2</sub>O-CO<sub>2</sub> analogy and activity-coefficient-corrected  $CO_2$  Henry's constant in pure water lead to incompatible estimations of  $CO_2$  interfacial concentration at high MDEA concentrations. This supports the need for global modelling: kinetic parameters should be used with all underlying parameters with which they were obtained. This is especially true when designing industrial columns.

For aqueous MDEA solutions,  $N_2O-CO_2$  analogy is not proven theoretically. Having access to direct measurements of molecular  $CO_2$  concentration in aqueous MDEA solutions would be beneficial to kinetic modelling. Such measurements exist for reactive systems, such as  $CO_2$  in aqueous diethanolamine solutions (Diab, et al. 2012). In their absence, molecular simulation could provide estimates. Results of the present study suggest that amine concentration should be considered as well as water in  $CO_2$  Henry's constant calculation at infinite dilution. Lastly, simulated profiles through the liquid film indicate the relevance of the developed representation, especially considering the high deviation from ideality of the system and the apparition of activity coefficient gradients through the film at high absorption driving force. This implies kinetic parameters obtained at high absorption driving force with a simplified approach disregarding this effect could be incompatible with low absorption driving force experimental absorption/desorption flux data, and vice versa. This could be a factor impeding laboratory-scale data comparisons obtained at different absorption driving force conditions.

372

#### 373 Acknowledgements

Pr. Alain Gaunand and Pr. Christophe Coquelet would like to acknowledge TotalEnergies for their
research partnership and financial support, and the authors would like to acknowledge the Agence
Nationale de la Recherche et de la Technologie (ANRT) for their financial support (CIFRE 2018/1069).

377

#### 378 <u>References</u>

- Benamor, A, et M K Aroua. «An experimental investigation on the rate of CO2 absorption into
   aqueous methyldiethanolamine solutions.» Édité par Springer. *Korean Journal of Chemical Engineering* 24, n° 1 (2007): 16-23.
- Bottoms, R R. «Organic bases for gas purification.» *Industrial & Engineering Chemistry* 23, n° 5
   (1931): 501-504.
- Cadours, R. Absorption-desorption de gaz acides par des solutions aqueuses d'amines. Paris: ENSMP,
   1998.
- Camacho, F, S Sanchez, R Pacheco, M D La Rubia, et A Sanchez. «Kinetics of the reaction of pure CO2
   with N-methyldiethanolamine in aqueous solutions.» Édité par Wiley Online Library.
   *International journal of chemical kinetics* 41, n° 3 (2009): 204-214.
- Costa, C, M Demartini, R Di Felice, M Oliva, et P Pagliai. «Piperazine and methyldiethanolamine
   interrelationships in CO2 absorption by aqueous amine mixtures. Part I: Saturation rates of
   single-reagent solutions.» Édité par Wiley Online Library. *The Canadian Journal of Chemical Engineering* 97, n° 5 (2019): 1160-1171.
- Delgado, S, A Gaunand, C Coquelet, R Cadours, et C Volpi. «A new reactive absorption model using
   extents of reaction and activities. I. Application to Alkaline-salts-CO2 systems.» *Chemical Engineering Science* 270 (2023): 118522.
- Derks, P. W. J, T Kleingeld, C Van Aken, J A Hogendoorn, et G F Versteeg. «Kinetics of absorption of
   carbon dioxide in aqueous piperazine solutions.» *Chemical Engineering Science* 61, n° 20
   (2006): 6837-6854.

- Diab, F, et al. «Quantitative analysis of the liquid phase by FT-IR spectroscopy in the system
   CO2/diethanolamine (DEA)/H2O.» *Fluid Phase Equilibria* 325 (2012): 90-99.
- 401 Donaldson, T, et Y Nguyen. «Carbon dioxide reaction kinetics and transport in aqueous amine
   402 membranes.» *Industrial & Engineering Chemistry Fundamentals* 19, n° 3 (1980): 260-266.
- Gondal, S, H F Svendsen, et H K Knuutila. «Activity based kinetics of CO2--OH- systems with Li+, Na+
   and K+ counter ions.» Édité par Elsevier. *Chemical Engineering Science* 151 (2016): 1-6.
- Hamborg, E S, et G F Versteeg. «Absorption and desorption mass transfer rates in chemically
  enhanced reactive systems. Part I: Chemical enhancement factors.» Édité par Elsevier. *Chemical engineering journal* 198 (2012): 555-560.
- Jamal, A, A Meisen, et C J Lim. «Kinetics of carbon dioxide absorption and desorption in aqueous
  alkanolamine solutions using a novel hemispherical contactor—I. Experimental apparatus
  and mathematical modeling.» Édité par Elsevier. *Chemical engineering science* 61, n° 19
  (2006): 6571-6589.
- Kamps, A P-S, A Balaban, M Jödecke, N A S Kuranov, et G Maurer. «Solubility of single gases carbon dioxide and hydrogen sulfide in aqueous solutions of N-methyldiethanolamine at temperatures from 313 to 393 K and pressures up to 7.6 MPa: New experimental data and model extension.» *Industrial & Engineering Chemistry Research* 40, n° 2 (2001): 696-706.
- Kamps, A P-S, et G Maurer. «Dissociation constant of N-methyldiethanolamine in aqueous solution at
  temperatures from 278 K to 368 K.» *Journal of Chemical & Engineering Data* 41, n° 6 (1996):
  1505-1513.
- 419 Kierzkowska-Pawlak, H, et A Chacuk. «Kinetics of carbon dioxide absorption into aqueous MDEA
  420 solutions.» *Ecol. Chem. Eng. S* 17, n° 4 (2010): 463-475.
- 421 Ko, J-J, et M-H Li. «Kinetics of absorption of carbon dioxide into solutions of N422 methyldiethanolamine+ water.» Édité par Elsevier. *Chemical engineering science* 55, n° 19
  423 (2000): 4139-4147.
- Lagarias, J C, J A Reeds, M H Wright, et P E Wright. «Convergence properties of the Nelder-Mead
  simplex method in low dimensions.» *SIAM Journal on Optimization* 9, n° 1 (1998): 112-147.
- Littel, R J, W P M Van Swaaij, et Geert F Versteeg. «Kinetics of carbon dioxide with tertiary amines in
   aqueous solution.» Édité par Wiley Online Library. *AIChE Journal* 36, n° 11 (1990): 1633-1640.
- 428 Pacheco, M A, et S Kaganoi. «CO2 absorption into aqueous mixtures of diglycolamine and
  429 methyldiethanolamine.» Édité par Elsevier. *Chemical engineering science* 55, n° 21 (2000):
  430 5125-5140.
- Pani, F, A Gaunand, R Cadours, C Bouallou, et D Richon. «Kinetics of absorption of CO2 in
   concentrated aqueous methyldiethanolamine solutions in the range 296 K to 343 K.» Édité
   par ACS Publications. *Journal of Chemical & Engineering Data* 42, n° 2 (1997): 353-359.

- Pohorecki, R, et W Moniuk. «Kinetics of reaction between carbon dioxide and hydroxyl ions in
   aqueous electrolyte solutions.» *Chemical Engineering Science* 43, n° 7 (1988): 1677-1684.
- Qian, Z, et K Guo. «Modeling and kinetic study on absorption of CO2 by aqueous solutions of Nmethyldiethanolamine in a modified wetted wall column.» (Elsevier) 17, n° 4 (2009): 571579.
- Rangwala, H A, B R Morrell, A E Mather, et F D Otto. «Absorption of CO2 into aqueous tertiary
  amine/MEA solutions.» Édité par Wiley Online Library. *The Canadian journal of chemical engineering* 70, n° 3 (1992): 482-490.
- 442 Rinker, E B, S A Sami, et O C Sandall. «Kinetics and modelling of carbon dioxide absorption into
  443 aqueous solutions of N-methyldiethanolamine.» Édité par Elsevier. *Chemical Engineering*444 *Science* 50, n° 5 (1995): 755-768.
- Rozanska, X, E Wimmer, et F de Meyer. «Quantitative kinetic model of CO2 absorption in aqueous
  tertiary amine solvents.» *Journal of Chemical Information and Modeling* 61, n° 4 (2021):
  1814-1824.
- Sheng, M, et al. «Effective Mass Transfer Area Measurement Using a CO2–NaOH System: Impact of
   Different Sources of Kinetics Models and Physical Properties.» *Industrial & Engineering Chemistry Research* 58, n° 25 (2019): 11082-11092.
- Tomcej, R A, et F D Otto. «Absorption of CO2 and N2O into aqueous solutions of
   methyldiethanolamine.» Édité par Wiley Online Library. *AIChE journal* 35, n° 5 (1989): 861 864.
- 454 Versteeg, G F, et W PM van Swaaij. «On the kinetics between CO2 and alkanolamines both in
  455 aqueous and non-aqueous solutions—II. Tertiary amines.» Édité par Elsevier. *Chemical*456 *Engineering Science* 43, n° 3 (1988): 587-591.
- 457 Versteeg, G F, et W PM Van Swaaij. «Solubility and diffusivity of acid gases (carbon dioxide, nitrous
  458 oxide) in aqueous alkanolamine solutions.» Édité par ACS Publications. *Journal of Chemical &*459 *Engineering Data* 33, n° 1 (1988): 29-34.
- Vinel, D J, et C Bouallou. «Propriétés physico-chimiques des solutions aqueuses d'alcanolamines
   utilisées dans le traitement du gaz.» *Scientific Study & Research* 1 (2004): 2.
- Whitman, W G. «The two-film theory of gas absorption.» *Chemical & Mellaurgy Engineering* 29
  (1923): 146-148.
- Zhang, Y, et C-C Chen. «Thermodynamic Modeling for CO2 Absorption in Aqueous MDEA Solution
  with Electrolyte NRTL Model.» *Industrial & Engineering Chemistry Research* (American
  Chemical Society) 50, n° 1 (2011): 0888-5885.
- 467
- 468