



Entropy Computation in Partially Observed Markov Chains

François Desbouvries

► To cite this version:

François Desbouvries. Entropy Computation in Partially Observed Markov Chains. Bayesian Inference and Maximum Entropy Methods In Science and Engineering, MaxEnt, Jul 2006, Paris, France. pp.355-357, 10.1063/1.2423294 . hal-04415402

HAL Id: hal-04415402

<https://hal.science/hal-04415402v1>

Submitted on 24 Jan 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

ENTROPY COMPUTATION IN PARTIALLY OBSERVED MARKOV CHAINS

François Desbouvries

Institut National des Télécommunications, Evry, France

Abstract. Let $X = \{X_n\}_{n \in \mathbb{N}}$ be a hidden process and $Y = \{Y_n\}_{n \in \mathbb{N}}$ be an observed process. We assume that (X, Y) is a (pairwise) Markov Chain (PMC). PMC are more general than Hidden Markov Chains (HMC) and yet enable the development of efficient parameter estimation and Bayesian restoration algorithms. In this paper we propose a fast (i.e., $O(N)$) algorithm for computing the entropy of $\{X_n\}_{n=0}^N$ given an observation sequence $\{y_n\}_{n=0}^N$.

Keywords: Entropy, Hidden Markov Models, Partially observed Markov Chains

PACS: 05.70.-a, 65.40.Gr, 02.50.-r, 02.50.Ga.

INTRODUCTION

Let $(X, Y) = \{X_n, Y_n\}_{n \in \mathbb{N}}$ be a joint process in which X is unobserved and Y is observed. We assume that X and Y are both discrete with $X_n \in \{1, \dots, K\}$ and $Y_n \in \{1, \dots, M\}$ for all $n \in \mathbb{N}$. Let $X_{i:j} = \{X_n\}_{i \leq n \leq j}$, $Y_{i:j} = \{Y_n\}_{i \leq n \leq j}$, $x_{i:j} = \{x_n\}_{i \leq n \leq j}$ and $y_{i:j} = \{y_n\}_{i \leq n \leq j}$ (upper case letters denote random variables (r.v.) and lower case letters their realizations). Let also $p(x_{i:j}|y_{i:j})$, say, denote the conditional probability that $X_{i:j} = x_{i:j}$ given $Y_{i:j} = y_{i:j}$. In some applications it is relevant to compute the entropy of $X_{0:N} = \{X_n\}_{n=0}^N$ given an observation $y_{0:N} = \{y_n\}_{n=0}^N$, i.e. we want to compute

$$H(X_{0:N}|y_{0:N}) = - \sum_{x_{0:N}} p(x_{0:N}|y_{0:N}) \log p(x_{0:N}|y_{0:N}). \quad (1)$$

The brute force computation of (1) requires $O(K^N)$ elementary operations. However, a fast (i.e., $O(K^2 N)$) algorithm for computing (1) has been proposed recently [1] in the framework of Hidden Markov Chains (HMC) (see e. g. the recent tutorials [2] [3]), i.e. of processes (X, Y) satisfying

$$p(x_{n+1}|x_{0:n}) = p(x_{n+1}|x_n); \quad (2)$$

$$p(y_{0:N}|x_{0:N}) = \prod_{n=0}^N p(y_n|x_{0:N}); \quad (3)$$

$$p(y_n|x_{0:N}) = p(y_n|x_n) \text{ for all } n, 0 \leq n \leq N. \quad (4)$$

Now, HMC have been generalized recently to Pairwise Markov Chains (PMC) [4], i.e. to joint processes (X, Y) which satisfy

$$p(x_n, y_n|x_{0:n-1}, y_{0:n-1}) = p(x_n, y_n|x_{n-1}, y_{n-1}). \quad (5)$$

As we see from the definition, a PMC can be seen as a (vector) Markov chain in which one component is observed and the other one is hidden. Now, (2)-(4) imply (5), so any HMC is a PMC. The converse is not true, as can be seen at the local level, since in a PMC the transition probability reads

$$p(x_n, y_n | x_{n-1}, y_{n-1}) = p(x_n | x_{n-1}, y_{n-1})p(y_n | x_n, x_{n-1}, y_{n-1}); \quad (6)$$

so an HMC is indeed a PMC in which $p(x_n | x_{n-1}, y_{n-1})$ reduces to $p(x_n | x_{n-1})$ and $p(y_n | x_n, x_{n-1}, y_{n-1})$ reduces to $p(y_n | x_n)$. In other words, making use of PMC enables to model rather complex physical situations, since at time n , conditionally on the previous state x_{n-1} , the probability of the current state x_n may still depend on the previous observation y_{n-1} ; and conditionally on x_n , the probability of observation y_n may still depend on the previous state x_{n-1} and on the previous observation y_{n-1} .

It happens that it is possible to extend from HMC to PMC [4] the existing efficient Bayesian restoration or parameter estimation algorithms. As we shall see in this paper, it is also possible in the context of PMC to compute $H(X_{0:N} | y_{0:N})$ efficiently. More precisely, our aim here is to extend to PMC the algorithm of [1]; the algorithm we obtain remains $O(K^2N)$.

EFFICIENT ENTROPY COMPUTATION IN PMC

From now on we assume that (X, Y) is a PMC, i.e. that (5) holds. Let us first recall [5] the following basic properties of entropy :

$$h(U, V / w) = h(U / w) + h(V / U, w), \quad (7)$$

$$h(V / U, w) = \sum_u h(V / u, w)p(u | w). \quad (8)$$

Let us now address the computation of $H(X_{0:N} | y_{0:N})$. Let $0 \leq n \leq N$. From (7), (8) we get

$$\begin{aligned} H(X_{0:n} | y_{0:n}) &= H(X_n | y_{0:n}) + H(X_{0:n-1} | X_n, y_{0:n}) \\ &= H(X_n | y_{0:n}) + \sum_{x_n} H(X_{0:n-1} | x_n, y_{0:n})p(x_n | y_{0:n}). \end{aligned} \quad (9)$$

On the other hand, from (5) we get

$$p(x_{0:n-2} | x_{n-1}, x_n, y_{0:n}) = p(x_{0:n-2} | x_{n-1}, y_{0:n-1}), \quad (10)$$

so $H(X_{0:n-1} | x_n, y_{0:n})$ in (9) can be computed recursively by

$$\begin{aligned} H(X_{0:n-1} | x_n, y_{0:n}) &= H(X_{n-1} | x_n, y_{0:n}) + H(X_{0:n-2} | X_{n-1}, x_n, y_{0:n}) \\ &= H(X_{n-1} | x_n, y_{0:n}) + \sum_{x_{n-1}} H(X_{0:n-2} | x_{n-1}, x_n, y_{0:n})p(x_{n-1} | x_n, y_{0:n}) \\ &\stackrel{(10)}{=} H(X_{n-1} | x_n, y_{0:n}) + \sum_{x_{n-1}} H(X_{0:n-2} | x_{n-1}, y_{0:n-1})p(x_{n-1} | x_n, y_{0:n}) \end{aligned} \quad (11)$$

It remains to compute $p(x_n|y_{0:n})$ and $p(x_{n-1}|x_n, y_{0:n})$ efficiently. This can be performed by an algorithm which extends to PMC [4] the (forward pass of) the Forward-Backward algorithm [6] [7] [8] [9], and which we now recall

$$\begin{aligned} p(x_{n-1}, x_n|y_{0:n}) &= \frac{p(x_{n-1}, x_n, y_{0:n})}{\sum_{x_{n-1}, x_n} p(x_{n-1}, x_n, y_{0:n})} \\ &\stackrel{(5)}{=} \frac{p(x_n, y_n|x_{n-1}, y_{n-1})p(x_{n-1}|y_{0:n-1})p(y_{0:n-1})}{\sum_{x_{n-1}, x_n} p(x_n, y_n|x_{n-1}, y_{n-1})p(x_{n-1}|y_{0:n-1})p(y_{0:n-1})} \\ &= \frac{p(x_n, y_n|x_{n-1}, y_{n-1})p(x_{n-1}|y_{0:n-1})}{\sum_{x_{n-1}, x_n} p(x_n, y_n|x_{n-1}, y_{n-1})p(x_{n-1}|y_{0:n-1})}, \end{aligned} \quad (12)$$

$$p(x_n|y_{0:n}) = \sum_{x_{n-1}} p(x_{n-1}, x_n|y_{0:n}), \quad (13)$$

$$p(x_{n-1}|x_n, y_{0:n}) = \frac{p(x_{n-1}, x_n|y_{0:n})}{p(x_n|y_{0:n})}. \quad (14)$$

Let us summarize the discussion. We got the following algorithm :

Fast algorithm for computing $H(X_{0:N}|y_{0:N})$.

- At time $n - 1$:
 - assume that we have $\{H(X_{0:n-2}|x_{n-1}, y_{0:n-1})\}_{x_{n-1}=1}^K$, $\{p(x_{n-1}|y_{0:n-1})\}_{x_{n-1}=1}^K$.
- Iteration $n - 1 \rightarrow n$:
 - compute $\{p(x_n|y_{0:n})\}_{x_n=1}^K$ and $\{p(x_{n-1}|x_n, y_{0:n})\}_{x_{n-1}, x_n=1}^K$ via (12), (13) and (14);
 - compute $\{H(X_{n-1}|x_n, y_{0:n}) = -\sum_{x_{n-1}} p(x_{n-1}|x_n, y_{0:n}) \log p(x_{n-1}|x_n, y_{0:n})\}_{x_n=1}^K$;
 - compute $\{H(X_{0:n-1}|x_n, y_{0:n})\}_{x_n=1}^K$ via (11);
 - compute $H(X_n|y_{0:n}) = -\sum_{x_n} p(x_n|y_{0:n}) \log p(x_n|y_{0:n})$;
 - compute $H(X_{0:n}|y_{0:n})$ via (9).

Note that the algorithm is $O(K^2N)$, as was the original algorithm of [1]. Finally, we assumed that Y_n is a discrete r.v., but the extension to continuous emission probability densities is straightforward.

REFERENCES

1. D. Hernando, V. Crespi, and G. Cybenko, *IEEE Transactions on Information Theory* **51**, 2681–85 (2005).
2. Y. Ephraim, and N. Merhav, *IEEE Transactions on Information Theory* **48**, 1518–69 (2002).
3. O. Cappé, E. Moulines, and T. Rydén, *Inference in Hidden Markov Models*, Springer-Verlag, 2005.
4. W. Pieczynski, *IEEE Transactions on Pattern Analysis and Machine Intelligence* **25**, 634–39 (2003).
5. T. M. Cover, and J. A. Thomas, *Elements of Information Theory*, Wiley series in Telecommunications, Wiley Interscience, 1991.
6. L. E. Baum, and T. Petrie, *Ann. Math. Stat.* **37**, 1554–63 (1966).
7. L. E. Baum, and J. A. Eagon, *Bull. Amer. Meteorol. Soc.* **73**, 360–63 (1967).
8. L. R. Rabiner, *Proceedings of the IEEE* **77**, 257–286 (1989).
9. L. R. Bahl, J. Cocke, F. Jelinek, and J. Raviv, *IEEE Transactions on Information Theory* **20**, 284–87 (1974).