

Lattice Boltzmann simulations of contact angle hysteresis on chemically square patterned surfaces of large wettability contrast

Magali Dupuy, Alexey Koltsov, Marie-Laurence Giorgi, Hervé Duval

► To cite this version:

Magali Dupuy, Alexey Koltsov, Marie-Laurence Giorgi, Hervé Duval. Lattice Boltzmann simulations of contact angle hysteresis on chemically square patterned surfaces of large wettability contrast. Particles 2021, Oct 2021, Hamburg, Germany. hal-04431936

HAL Id: hal-04431936 https://hal.science/hal-04431936

Submitted on 1 Feb2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Lattice Boltzmann simulations of contact angle hysteresis on chemically square patterned surfaces of large wettability contrast

M. Dupuy*[†], A. Koltsov[‡], M.L. Giorgi[†] and H. Duval[†]

 [†] Laboratoire de Génie des Procédés et Matériaux (LGPM) CentraleSupélec, Université Paris-Saclay
3 rue Joliot-Curie, 91190 Gif sur Yvette, France web page: http://lgpm.centralesupelec.fr/

[‡] ArcelorMittal Global Research & Development Voir Romaine, 57280 Maizières-les-Metz, France

ABSTRACT

The contact angle hysteresis on flat and chemically patterned surfaces with large wettability contrast of 86° is studied numerically using an in-house lattice Boltzmann (LB) code. The two-dimensional phase-field-based multiple relaxation time LB model of Liang et al.¹ has been extended to three dimensions. The D3Q19 model is used for both the Cahn-Hilliard equation and the Navier-Stokes equations. The wetting properties of the wall are specified using the contact angle geometric scheme of Ding and Spelt² while the approach of Iliev et al.³ is used to estimate the contact angle.

The code has first been validated by successfully simulating a 3D droplet resting on a chemically homogeneous surface for both acute and obtuse equilibrium contact angles. Then, contact angle hysteresis on chemically patterned surfaces has been investigated. To that end, the intrusion (resp. extrusion) of a liquid phase into (resp. from) a channel has been simulated. The channel is formed by two similarly patterned walls. The pattern consists of non-wetted squares regularly distributed on a wetted surface. The intruding fluid is compelled to move quasi-statically by a body force.

Simulations have been computed with different values of the square size and inter-square distance and their influence on the advancing and receding contact angles has been studied. By rotating the square around its centre the influence of its orientation on the hysteresis has also been investigated. The numerical results proved to be in good agreement with Raj's model⁴. A key parameter to estimate the contact angle hysteresis for such patterned surfaces independently of the square positioning has been identified.

REFERENCES

- [1] H. Liang, B. C. Shi, Z. L. Guo and Z. H. Chai, "Phase-field-based multiple-relaxation-time lattice Boltzmann model for incompressible multiphase flows", *Physical Review E* **89**, 053320 (2014).
- [2] H. Ding and P. D. M. Spelt, "Wetting condition in diffuse interface simulations of contact line motion", *Physical Review E* **75**, 046708 (2007).
- [3] S. Iliev, N. Pesheva and V. S. Nikolayev, "Contact angle hysteresis and pinning at periodic defects in statics", *Physical Review E* **90**, 012406 (2014).
- [4] R. Raj, R. Enright, Y. Zhu, S. Adera and E. N. Wang, "Unified Model for Contact Angle Hysteresis on Heterogeneous and Superhydrophobic Surfaces", *Langmuir*, 28, 45, 15777-15788 (2012).