



HAL
open science

TIPTOP: cone effect for single laser adaptive optics systems

Guido Agapito, Cedric Plantet, Fabio Rossi, Giulia Carlà, Anne-Laure Cheffot, Daniele Vassallo, Arseniy Kuznetsov, Simon Conseil, Benoit Neichel

► **To cite this version:**

Guido Agapito, Cedric Plantet, Fabio Rossi, Giulia Carlà, Anne-Laure Cheffot, et al.. TIPTOP: cone effect for single laser adaptive optics systems. Adaptive Optics for Extremely Large Telescopes 7th Edition, Jun 2023, Avignon, France. 10.13009/AO4ELT7-2023-012 . hal-04440482

HAL Id: hal-04440482

<https://hal.science/hal-04440482>

Submitted on 6 Feb 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



TIPTOP: cone effect for single laser adaptive optics systems

Guido Agapito^{a,e}, Cédric Plantet^{a,e}, Fabio Rossi^{a,e}, Giulia Carlà^{a,e}, Anne-Laure Cheffot^{a,e}, Daniele Vassallo^{b,e}, Arseniy Kuznetsov^c, Simon Conseil^d, and Benoit Neichel^d

^aINAF – Osservatorio Astrofisico di Arcetri, Largo E. Fermi 5, 50125, Firenze, Italy

^bINAF – Osservatorio Astronomico di Padova, Vicolo dell'Osservatorio, 5, 35122, Padova, Italy

^cEuropean Southern Observatory, Karl-Schwarzschild-str-2, D-85748 Garching, Germany

^dAix Marseille University, CNRS, CNES, LAM, Marseille, France

^eADaptive Optics National laboratory in Italy (ADONI)

ABSTRACT

TIPTOP is a python library that is able to quickly compute Point Spread Functions (PSF) of any kind of Adaptive Optics systems. This library has multiple objectives: support the exposure time calculators of future VLT and ELT instruments, support adaptive optics systems design activities, be part of PSF reconstruction pipelines and support the selection of the best asterism of natural guide stars for observation preparation. Here we report one of the last improvements of TIPTOP: the introduction of the error given by a single conjugated laser, commonly known as the cone effect. The Cone effect was not introduced before because it is challenging due to the non-stationarity of the phase. Laser guide stars are at a finite distance with respect to the telescope and probe beam accepted by the wavefront sensor has the shape of a cone. Given a single spatial frequency in an atmospheric layer, the cone effect arises from the apparent magnification or stretching of this frequency when it reaches the wavefront sensor. The magnification effect leads to an incorrect estimation of the spatial frequency. Therefore, we estimate the residual power by calculating the difference between two sinusoids with different periods: the nominal one and the magnified one. Replicating this for each spatial frequency we obtain the power spectrum associated with the cone effect. We compare this estimation with the one given by end-to-end simulation and we present how we plan to validate this with on-sky data.

Keywords: simulations, single conjugate adaptive optics, laser, cone effect

Further author information: (Send correspondence to G.A.)

G.A.: E-mail: guido.agapito@inaf.it

1. INTRODUCTION

Adaptive Optics (AO) is a technique used to compensate the effects of atmospheric turbulence and it is becoming increasingly popular among current and future astronomical instruments of large ground based telescopes (a non exhaustive list is [1], [2], [3], [4], [5], [6], [7] and [8]).

Numerical simulations are playing an important role in the sizing, development, and analysis of AO systems and several libraries are used to numerically simulate AO systems, like Refs. [9], [10], [11], [12] and [13]. TIPTOP [14] is one of these libraries: it is an analytical simulator developed in Python that works in the Fourier domain that can quickly* produce the AO Point Spread Function (PSF) of several kind of systems. It is available on github at <https://github.com/astro-tiptop/TIPTOP> and on pypi at <https://pypi.org/project/astro-tiptop/>. The goals of TIPTOP are many: from supporting AO system design and observation preparation, estimating the PSF for exposure time calculation, to being part of the PSF reconstruction activity (it is also part of the tools developed in the context of the ESO ELT working groups, see Ref. [15]).

In this work we focused on a new feature of TIPTOP[†], the ability to simulate the cone effect of a Single Laser guide star Adaptive Optics (SLAO) system like ERIS [16] and KECK Laser Guide Star (LGS) AO system [17, 18].

In the past, attempts have been made to find a solution to introduce the cone effect into Fourier simulation (for example in Ref. [19] and [20]). As described in Ref. [21], in the case of the classical AO, modeling the cone effect using a filter on the PSD is not feasible due to the non-stationarity of the residual phase. In the case of tomographic AO, the situation is different, as information from several stars is used for volume estimation. The residual phase is no longer given by the simple difference of a plane wave and a spherical wave, but from the result of turbulent volume estimation by several spherical waves and the plane wave. The residual phase thus regains a certain stationary character.

In this work we followed a different approach based on sinusoids and on the magnification effect seen by the wavefront sensor and given by the spherical wave propagation. This method is described in Sec. 2 and it is combined with the other error sources of TIPTOP and the tilt filter (tilt filter is presented in Sec. 3) to produce the so called high orders PSF, that is the PSF generated by the LGS correction without the tip and tilt errors associated with the sensing and correction of the natural guide star. We compared the results from TIPTOP with the one of end-to-end simulation in Sec. 4. Finally, we conclude the paper with a few comments in Sec. 5 and we present a possible alternative approach in Appendix A.

2. CONE EFFECT IN THE SPATIAL FREQUENCY DOMAIN


In this section we present the method to compute the error associated with the so called focal anisoplanatism or cone effect for a SLAO system. Let's consider a single spatial frequency $f < f_c^{DM}$ (DM is deformable mirror, and f_c^{DM} the DM's maximum correction frequency linked to the actuator pitch). The correction of f in a system with the source at infinity is perfect, if we exclude aliasing, measurement errors, and reconstruction errors. However, in a system with a source at finite distance, the wavefront sensor can be tricked by a magnification effect due to the systems geometry. As shown in Fig. 1(a), only the central part of the wavefront is measured by the sensor. This measurement is then used to control the DM on the full pupil. This leads to a mismatch between the wavefront seen by the observed star and the corrected wavefront. The magnification of the wavefront at a distance h from the entrance pupil is equal to

$$m = \frac{h_{Na}}{h_{Na} - h}. \quad (1)$$


With h_{Na} the altitude of the LGS and h the altitude of the atmospheric layer observed. If x is the pupil position going from $-r$ to r (r is pupil radius) and considering a sinusoidal signal with unitary amplitude,

*especially when GPU/CUDA acceleration is available.

[†]available from version 1.1.



(a) Scheme of the geometry. Black curve is the input signal on the right.



(b) Input signal (wavefront to be corrected), reconstructed signal (wavefront seen) and error, 0 phase shift case. X-axis units are radius units.

FIGURE 1: Example of the magnification given by the cone effect on a spatial frequency with 1.5 period in the diameter at a distance from the entrance pupil that is half the distance between the source and the entrance pupil. The sensed signal has a spatial frequency that is half the one of the input.

$s(f, x) = \sin(2\pi fx)$, the reconstructed signal, s_{rec} , is:

$$s_{rec}(f, x, m, \phi) = A(f, m) \sin\left(2\pi \frac{f}{m} x + \phi\right) \quad (2)$$

where ϕ is the phase shift and $A(f, m)$ is approximated as:

$$A(f, m, \phi) = \arg \min_A \left(\sqrt{\int_{-r}^r \left(\sin(2\pi fx + \phi) - A \sin\left(2\pi \frac{f}{m} x + \phi\right) \right)^2 x^2 dx} \right). \quad (3)$$

The minimization found in equation 3 is an approximation of the closed loop behaviour. The AO closed loop is able to minimize the measurement of the phase seen by the WFS but on $x = [-r/m, r/m]$ instead of $x = [-r, r]$. Additionally there are some cross-talks between spatial frequencies. Note that in open loop A is 1 if $f/m > 0.25/r$ and $A = \frac{\sin(2\pi \frac{f}{m} r)}{\sin(2\pi fr)}$ otherwise.

The error, $e(f, x, m)$, is:

$$e(f, m, x, \phi) = s(f, x, \phi) - s_{rec}(f, x, m, \phi) = \sin(2\pi fx + \phi) - A(f, m, \phi) \sin\left(2\pi \frac{f}{m} x + \phi\right) \quad (4)$$

An example of this error for $\phi=0$ is shown in Fig. 1(b), and this error can be used to derive the filtering function. We approximate that the spatial frequencies found in the error signal are the same as the one seen at the wavefront sensor. This approximation is negligible when the magnification is close to 1, but can introduce large errors when the magnification is much greater than 1. Fortunately, the maximum value of m is around 1.3 when considering sodium laser ($h_{Na} \simeq 90$ km) and standard C_n^2 profile ($\max(h) \simeq 20$ km). The filter coefficient, $k(f, m)$, is described as:

$$k(f, m) = \sum_{j=0}^{N_\phi-1} \frac{1}{N_\phi} \frac{\sigma_e(f, m, \frac{2\pi j}{N_\phi})}{\sigma_s(f, m, \frac{2\pi j}{N_\phi})} \quad (5)$$




FIGURE 2: Single dimension filter values from the brute force approach for an 8 m telescope with source at 90 km, zenith angle of 30 deg and a C_n^2 profile with altitudes of [30, 140, 281, 562, 1125, 2250, 4500, 7750, 11000, 14000] m.




FIGURE 3: 2D filter values from the brute force approach for an 8 m telescope with source at 90 km, zenith angle of 30 deg and a C_n^2 profile with altitudes of [30, 140, 281, 562, 1125, 2250, 4500, 7750, 11000, 14000] m (the first 5 values correspond to the first row of images, the last 5 values to the second row). Spatial frequencies range from -5 to 5 m^{-1} , with a cut at 2.5 m^{-1} due to the DM pitch of 0.2 m.

where σ_e is the standard deviation of e , the error, σ_s is the standard deviation of s , the signal and N_ϕ is the phase shift. An example of the filter coefficients, k , for an 8m telescope is shown in Fig. 2.

As depicted in Figure 3, the cone effect in the spatial frequency domain has circular symmetry and depends only on the norm of the frequency vector $\mathbf{f} = (f_x, f_y)$. This simplifies the computation of $k(f_x, f_y)$. Using a PSD the cone effect can be described as:

$$W_{cone}(\mathbf{f}) = \sum_{i=1}^{N_{layer}} C_n^2(i) k^2(\mathbf{f}, m_i) W_{turb}(\mathbf{f}) \quad (6)$$

where $0 < C_n^2(i) \leq 1$ is the fraction of C_n^2 associated to the layer i and W_{turb} is the PSD of the turbulence. An




FIGURE 4: Comparison of estimated PSFs considering a $r_0(500\text{ nm})=0.14\text{ m}$ on the line of sight. Left, seeing limited, center, fitting error only (pitch=0.2m), right, fitting error and cone effect. The SR in K band (2200nm) is 0.92 in case of fitting error only and 0.76 in case of fitting error and cone effect for a source at 90 km (based on the brute force computations).

example of the PSFs produced with this estimation is reported in Fig. 4.

3. TILT FILTER




FIGURE 5: Example of the tilt estimated on a sinusoidal with a period twice the pupil size. (a), 0deg phase shift, (b), 108deg of phase shift.

As an approximation in laser-based AO systems, the computation of the high-order PSF was performed using only a piston filter in TIPTOP. The calculation of the high order PSF should exclude any errors related to the tilt as they have already been accounted for in the low-order calculation. To achieve this, a tilt filter is required for the high order PSD. In this section, we present this tilt filter and follow the same method as the one in Section 2 for the cone effect. The base idea is to compute what should be the tilt contribution to the high order depending on the atmospheric layer we are looking at, and use that information to remove the tilt from the PSD.

Let's consider a single spatial frequency $f < f_c^{DM}$, impacted by a tilt offset. The tilt filter coefficient for this frequency will be given by:

$$k(f) = \sum_{j=0}^{N_\phi-1} \frac{1}{N_\phi} \frac{\sigma_e(f, 2\pi i/N_\phi)}{\sigma_s(f, 2\pi i/N_\phi)} \quad (7)$$

where σ is the standard deviation, $e(f, x, \phi) = s(f, x, \phi) - s_{lin}(f, x, \phi)$, $s(f, x, \phi) = \sin(2\pi f x + \phi)$ and s_{lin} is the linear fitting of s . An example of these signals is shown in Fig. 5, and the filter coefficients, k , for an 8m telescope is show in Fig. 6. As for the cone effect, the tilt filter in the spatial frequency plane has a circular symmetry, so we can compute the filter map, $k(f_x, f_y)$, deduce a PSD from it, and remove that PSD from the high-order PSD. An example of the PSFs produced with this estimation is reported in Fig. 7.




FIGURE 6: Single dimension tilt filter values.





FIGURE 7: Comparison of estimated PSFs considering a $r_0(500\text{nm})=0.14\text{m}$ on the line of sight. Left, seeing limited, center, fitting error only (pitch=0.2m), right seeing limited without tilt. SR in K band (2200nm) is 0.92 in case of fitting error only and 0.03 in case of seeing limited without tilt.


Finally, we compared TIPTOP with the end-to-end simulator PASSATA [12]. We compute the amount of power associated with tip and tilt in the case of a line-of-sight seeing of 0.87 arcsec. During the 5-second simulation performed using PASSATA, it was observed that the quadratic sum of the two tilt axis exhibits 900nm Root Mean Square (RMS). By comparison, using TIPTOP resulted in an 850nm RMS. TIPTOP's value is lower, yet the agreement remains satisfactory and suitable for a single occurrence of relatively brief turbulence in PASSATA. Additionally, the total turbulence RMS of TIPTOP for this situation is 1240 nm and of PASSATA 1230 nm.

4. RESULTS

In this section we present the results of a simulation of a single LGS AO system like ERIS [16]. We compared TIPTOP with an end-to-end simulator, PASSATA [12]. We consider an atmosphere with a seeing of 0.87 arcsec at the zenith and an average wind speed of 11m/s. The laser sensing is given by a 40×40 Shack-Hartmann sensor while the visible WFS of the natural guide star is a 4×4 Shack-Hartmann sensor. The correction is given by a deformable mirror with 1156 actuators [22]. The comparison is shown in Fig. 8(a) considering a zenith angle of 0 deg and a laser spot at 90km. An additional test with a LGS source at 45km is reported in Fig. 8(b). As can be seen in these two figures the agreement of TIPTOP with an end-to-end simulation is good with a difference of a few percents.



(a) LGS source altitude is 90km ($z=0\text{deg}$). The ratio of the K band SR (TIPTOP over PASSATA) is 0.97.



(b) LGS source altitude is 45km ($z=0\text{deg}$). The ratio of the K band SR (TIPTOP over PASSATA) is 0.93.

FIGURE 8: Comparison of estimated PSFs in K band (2200nm) for the ERIS LGS mode. Left PASSATA, center TIPTOP and right absolute value of the difference.

5. CONCLUSION

We presented a new feature of TIPTOP, the ability to simulate the error associated to the so called focal anisoplanatism, or cone effect. This feature enables TIPTOP to estimate the PSF of AO systems like ERIS, KECK LGS AO system or the future GRAVITY+ systems [23]. We show that this new feature gives results consistent with the end-to-end simulation PASSATA [12] of the aforementioned systems. TIPTOP is a python library under development. We heavily rely on user feedback to improve the library and provide new functionality. The aim for the future of TIPTOP is to provide a library that is both stable and accurate, with ample examples and improved documentation that can be utilised by the entire AO community.

APPENDIX A. A POSSIBLE ALTERNATIVE APPROACH

In this section we present a possible alternative approach for computing the cone effect error (in addition to the one presented in Ref. [19] and [20]) in TIPTOP. This approach is based on the statistics of the turbulent phase: starting from eq. 24. of Ref. [24] and considering that $R = R_1 = R_2$, $A_{1l} = 0$ and $A = A_{2l}$ we can write:

$$W_{cone}^i(\mathbf{f}) = W_{\phi_l}(\mathbf{f}) \left[\frac{J_1(2\pi R(K-1)f)}{\pi R(K-1)f} - \frac{J_1(2\pi Rf)}{\pi Rf} \frac{J_1(2\pi R(1-A)f)}{\pi R(1-A)f} \right] \quad (8)$$

where $W_{cone}^i(\mathbf{f})$ is the PSD related to cone effect for the layer i . Then if we make the difference with the classical filter function for piston removal we get:

$$W_{cone}^i(\mathbf{f}) = W_{\phi_l}(\mathbf{f}) \left[1 - \left(\frac{J_1(2\pi Rf)}{\pi Rf} \right)^2 - \frac{J_1(2\pi R(K-1)f)}{\pi R(K-1)f} + \frac{J_1(2\pi Rf)}{\pi Rf} \frac{J_1(2\pi R(1-A)f)}{\pi R(1-A)f} \right] \quad (9)$$

that can be written as:

$$W_{cone}^i(\mathbf{f}) = W_{\phi_i}(\mathbf{f}) \left[1 - \frac{J_1(2\pi RAf)}{\pi RAf} + \frac{J_1(2\pi Rf)}{\pi Rf} \left(\frac{J_1(2\pi R(1-A)f)}{\pi R(1-A)f} - \frac{J_1(2\pi Rf)}{\pi Rf} \right) \right] \quad (10)$$

This equation gives the power spectral density (PSD) of the error associated with the cone effect. Please note that:

- A is the ratio h/h_{Na} , where h_{Na} is the distance between the pupil to the laser guide star and h is the distance between the the pupil and the observed atmospheric layer. A is therefore the description of how the atmospheric layer is stretched because of the cone effect.
- $K = 1 - A$

References

- [1] J. -L. Beuzit et al. “SPHERE: the exoplanet imager for the Very Large Telescope”. In: *A&A* 631, A155 (Nov. 2019), A155. DOI: [10.1051/0004-6361/201935251](https://doi.org/10.1051/0004-6361/201935251). arXiv: [1902.04080](https://arxiv.org/abs/1902.04080) [[astro-ph.IM](#)].
- [2] Bruce Macintosh et al. “First light of the Gemini Planet Imager”. In: *Proceedings of the National Academy of Sciences* 111.35 (2014), pp. 12661–12666. ISSN: 0027-8424. DOI: [10.1073/pnas.1304215111](https://doi.org/10.1073/pnas.1304215111). eprint: <https://www.pnas.org/content/111/35/12661.full.pdf>. URL: <https://www.pnas.org/content/111/35/12661>.
- [3] Jeffrey Chilcote et al. “GPI 2.0: upgrading the Gemini Planet Imager”. In: *Ground-based and Airborne Instrumentation for Astronomy VIII*. Ed. by Christopher J. Evans, Julia J. Bryant, and Kentaro Motohara. Vol. 11447. Society of Photo-Optical Instrumentation Engineers (SPIE) Conference Series. Dec. 2020, 114471S, 114471S. DOI: [10.1117/12.2562578](https://doi.org/10.1117/12.2562578).
- [4] Enrico Pinna et al. “Bringing SOUL on sky”. In: *arXiv e-prints*, arXiv:2101.07091 (Jan. 2021), arXiv:2101.07091. DOI: [10.48550/arXiv.2101.07091](https://doi.org/10.48550/arXiv.2101.07091). arXiv: [2101.07091](https://arxiv.org/abs/2101.07091) [[astro-ph.IM](#)].
- [5] P. Ciliegi et al. “MAORY: A Multi-conjugate Adaptive Optics Relay for ELT”. In: *The Messenger* 182 (Mar. 2021), pp. 13–16. DOI: [10.18727/0722-6691/5216](https://doi.org/10.18727/0722-6691/5216). arXiv: [2103.11219](https://arxiv.org/abs/2103.11219) [[astro-ph.IM](#)].
- [6] A. Marconi et al. “HIRES, the High-resolution Spectrograph for the ELT”. In: *The Messenger* 182 (Mar. 2021), pp. 27–32. DOI: [10.18727/0722-6691/5219](https://doi.org/10.18727/0722-6691/5219). arXiv: [2011.12317](https://arxiv.org/abs/2011.12317) [[astro-ph.IM](#)].
- [7] N. Thatte et al. “HARMONI: the ELT’s First-Light Near-infrared and Visible Integral Field Spectrograph”. In: *The Messenger* 182 (Mar. 2021), pp. 7–12. DOI: [10.18727/0722-6691/5215](https://doi.org/10.18727/0722-6691/5215). arXiv: [2103.11215](https://arxiv.org/abs/2103.11215) [[astro-ph.IM](#)].
- [8] A. Riccardi et al. “The ERIS Adaptive Optics System: first on-sky results of the ongoing commissioning at the VLT-UT4”. In: *Adaptive Optics Systems VIII*. Ed. by Laura Schreiber, Dirk Schmidt, and Elise Vernet. Vol. 12185. Society of Photo-Optical Instrumentation Engineers (SPIE) Conference Series. Aug. 2022, 1218508, p. 1218508. DOI: [10.1117/12.2629425](https://doi.org/10.1117/12.2629425).
- [9] Laurent Jolissaint. “Synthetic modeling of astronomical closed loop adaptive optics”. In: *Journal of the European Optical Society* 5, 10055 (Nov. 2010), p. 10055. DOI: [10.2971/jeos.2010.10055](https://doi.org/10.2971/jeos.2010.10055). arXiv: [1009.1581](https://arxiv.org/abs/1009.1581) [[astro-ph.IM](#)].
- [10] R. Conan and C. Correia. “Object-oriented Matlab adaptive optics toolbox”. In: *Adaptive Optics Systems IV*. Ed. by Enrico Marchetti, Laird M. Close, and Jean-Pierre Vran. Vol. 9148. Society of Photo-Optical Instrumentation Engineers (SPIE) Conference Series. Aug. 2014, 91486C, p. 91486C. DOI: [10.1117/12.2054470](https://doi.org/10.1117/12.2054470).
- [11] Marcel Carbillet et al. “The software package CAOS 7.0: enhanced numerical modelling of astronomical adaptive optics systems”. In: *Adaptive Optics Systems V*. Ed. by Enrico Marchetti, Laird M. Close, and Jean-Pierre Véran. Vol. 9909. Society of Photo-Optical Instrumentation Engineers (SPIE) Conference Series. July 2016, 99097J, 99097J. DOI: [10.1117/12.2234280](https://doi.org/10.1117/12.2234280).

- [12] G. Agapito, A. Puglisi, and S. Esposito. “PASSATA: object oriented numerical simulation software for adaptive optics”. In: *Adaptive Optics Systems V*. Ed. by Enrico Marchetti, Laird M. Close, and Jean-Pierre Véran. Vol. 9909. Society of Photo-Optical Instrumentation Engineers (SPIE) Conference Series. July 2016, 99097E, 99097E. DOI: [10.1117/12.2233963](https://doi.org/10.1117/12.2233963). arXiv: [1607.07624](https://arxiv.org/abs/1607.07624) [[astro-ph.IM](#)].
- [13] Andrew Reeves. “Soapy: an adaptive optics simulation written purely in Python for rapid concept development”. In: *Adaptive Optics Systems V*. Ed. by Enrico Marchetti, Laird M. Close, and Jean-Pierre Véran. Vol. 9909. Society of Photo-Optical Instrumentation Engineers (SPIE) Conference Series. July 2016, 99097F, 99097F. DOI: [10.1117/12.2232438](https://doi.org/10.1117/12.2232438).
- [14] Benoit Neichel et al. “TIPTOP: a new tool to efficiently predict your favorite AO PSF”. In: *Adaptive Optics Systems VII*. Ed. by Laura Schreiber, Dirk Schmidt, and Elise Vernet. Vol. 11448. Society of Photo-Optical Instrumentation Engineers (SPIE) Conference Series. Dec. 2020, 114482T, 114482T. DOI: [10.1117/12.2561533](https://doi.org/10.1117/12.2561533). arXiv: [2101.06486](https://arxiv.org/abs/2101.06486) [[astro-ph.IM](#)].
- [15] P. Padovani et al. “The ESO’s Extremely Large Telescope Working Groups”. In: *The Messenger* 189 (Dec. 2022), pp. 23–30. DOI: [10.18727/0722-6691/5286](https://doi.org/10.18727/0722-6691/5286). arXiv: [2302.14375](https://arxiv.org/abs/2302.14375) [[astro-ph.IM](#)].
- [16] R. Davies et al. “The Enhanced Resolution Imager and Spectrograph for the VLT”. In: *A&A* 674, A207 (June 2023), A207. DOI: [10.1051/0004-6361/202346559](https://doi.org/10.1051/0004-6361/202346559). arXiv: [2304.02343](https://arxiv.org/abs/2304.02343) [[astro-ph.IM](#)].
- [17] Herbert W. Friedman et al. “Design and performance of a laser guide star system for the Keck II telescope”. In: *Adaptive Optical System Technologies*. Ed. by Domenico Bonaccini and Robert K. Tyson. Vol. 3353. Society of Photo-Optical Instrumentation Engineers (SPIE) Conference Series. Sept. 1998, pp. 260–276. DOI: [10.1117/12.321681](https://doi.org/10.1117/12.321681).
- [18] Jason C. Y. Chin et al. “Keck II laser guide star AO system and performance with the TOPTICA/MPBC laser”. In: *Adaptive Optics Systems V*. Ed. by Enrico Marchetti, Laird M. Close, and Jean-Pierre Véran. Vol. 9909. Society of Photo-Optical Instrumentation Engineers (SPIE) Conference Series. July 2016, 99090S, 99090S. DOI: [10.1117/12.2233138](https://doi.org/10.1117/12.2233138).
- [19] Donald T. Gavel. “Tomography for multiconjugate adaptive optics systems using laser guide stars”. In: *Advancements in Adaptive Optics*. Ed. by Domenico Bonaccini Calia, Brent L. Ellerbroek, and Roberto Ragazzoni. Vol. 5490. Society of Photo-Optical Instrumentation Engineers (SPIE) Conference Series. Oct. 2004, pp. 1356–1373. DOI: [10.1117/12.552402](https://doi.org/10.1117/12.552402).
- [20] François Assémat et al. “Numerical Fourier simulations of tip-tilt LGS indetermination for the EAGLE instrument of the European ELT”. In: *Adaptive Optics Systems*. Ed. by Norbert Hubin, Claire E. Max, and Peter L. Wizinowich. Vol. 7015. Society of Photo-Optical Instrumentation Engineers (SPIE) Conference Series. July 2008, 70154A, 70154A. DOI: [10.1117/12.787779](https://doi.org/10.1117/12.787779).
- [21] Benoît Neichel. “Etude des galaxies lointaines et optiques adaptatives tomographiques pour ELTs”. 2008PA077206. PhD thesis. 2008, 1 vol. (331 p.) URL: <http://www.theses.fr/2008PA077206>.
- [22] R. Arsenault et al. “The Adaptive Optics Facility: Commissioning Progress and Results”. In: *The Messenger* 168 (June 2017), pp. 8–14. DOI: [10.18727/0722-6691/5019](https://doi.org/10.18727/0722-6691/5019).
- [23] Gravity+ Collaboration et al. “The GRAVITY+ Project: Towards All-sky, Faint-Science, High-Contrast Near-Infrared Interferometry at the VLTI”. In: *The Messenger* 189 (Dec. 2022), pp. 17–22. DOI: [10.18727/0722-6691/5285](https://doi.org/10.18727/0722-6691/5285). arXiv: [2301.08071](https://arxiv.org/abs/2301.08071) [[astro-ph.IM](#)].
- [24] Cédric Plantet et al. “Spatiotemporal statistics of the turbulent piston-removed phase and Zernike coefficients for two distinct beams”. In: *Journal of the Optical Society of America A* 39.1 (Jan. 2022), p. 17. DOI: [10.1364/JOSAA.431520](https://doi.org/10.1364/JOSAA.431520). arXiv: [2209.00931](https://arxiv.org/abs/2209.00931) [[astro-ph.IM](#)].